Hook Carabiner 1.97"

Part #: C134

Yellow chromate finish, forged steel twist lock gate , 1-15/16" gate opening. Gate Strength 3600 lbs. Min breaking strength 5000 lbs. Meets or Exceeds ANSI Z359.12-2009.

Hook Rebar Scaffold

Part#: S00140

Rebar scaffold hook. Alloy Steel. Min breaking strength 5000 lbs. Meets or Exceeds ANSI Z359.12-2009.

Rope Grab 5/8" Diameter

Part #: C0850

5/8" Large Bail Yellow Chromate Finish Rope Grab. Meets or Exceeds ANSI Z359.15-2014.

Vertical Co-Polymer Rope Lifeline

Part#: V1003202 50' 100'

Variable Length Lifeline 5/8" co-polymer rope, 3/4" hook on one end. Meets or Exceeds ANSI Z359.15-2014.

Termination Plate

Part#: RETP

This termination plate can be used with both Kernmantle rope between 7/16"and 3/4" 11mm-19mm) and 5/8" to 3/4" (16mm-19mm) three strand rope.

Anchor Sliding Beamer

Part #: A3145000

This anchor connector is designed to easily glide along the beam while trailing the worker. Adjustable from 3"-12" with a minimum flange thickness of 1/4". Meets or Exceeds ANSI Z359.18-2017, OSHA 1926.502.

Anchor Sliding Super Beamer

Part #: A12305000

Super Sliding Beam Anchor, 12" – 30" flange adjustable. Min breaking strength 5000 lbs. Meets or Exceeds ANSI Z359.18-2017.

Parapet Anchor

Part #: A00002

Parapet Anchor. Galvanized Steel. 2.36" – 14.17" parapet range. Min breaking strength 5000 lbs. Meets or Exceeds ANSI Z359.18-2017.

Anchor Door Jamb

Part #: A00003

Door Jamb Anchor, Aluminum construction. Min breaking strength 5000 lbs. Meets or Exceeds ANSI Z359.18-2017.