Simpson Strong-Tie® Anchoring, Fastening, Restoration and Strengthening Systems for Concrete and Masonry

SIMPSON Strong-Tie®

Titen HD® Heavy-Duty Screw Anchor

Titen HD Anchor Product Data — Zinc Plated

Size (in.)	Model No.	Thread Length (in.)	Drill Bit Diameter (in.)	Wrench Size (in.)	Quantity	
					Box	Carton
¼ x 1⅞	THDB25178H	1½	¼	⅜	100	500
¼ x 2¾	THDB25234H	2⅜	¼	⅜	50	250
¼ x 3	THDB25300H	2⅝	¼	⅜	50	250
¼ x 3½	THDB25312H	3⅛	¼	⅜	50	250
¼ x 4	THDB25400H	3⅝	¼	⅜	50	250
⅜ x 1¾	THD37134H†	1¼	⅜	9⁄16	50	250
⅜ x 2½	THD37212H†	2	⅜	9⁄16	50	200
⅜ x 3	THD37300H	2½	⅜	9⁄16	50	200
⅜ x 4	THD37400H	3½	⅜	9⁄16	50	200
⅜ x 5	THD37500H	4½	⅜	9⁄16	50	100
⅜ x 6	THD37600H	5½	⅜	9⁄16	50	100
½ x 3	THD50300H	2½	½	¾	25	100
½ x 4	THD50400H	3½	½	¾	20	80
½ x 5	THD50500H	4½	½	¾	20	80
½ x 6	THD50600H	5½	½	¾	20	80
½ x 6½	THD50612H	5½	½	¾	20	40
½ x 8	THD50800H	5½	½	¾	20	40
½ x 12	THD501200H	5½	½	¾	5	25
½ x 13	THD501300H	5½	½	¾	5	25
½ x 14	THD501400H	5½	½	¾	5	25
½ x 15	THD501500H	5½	½	¾	5	25
⅝ x 4	THDB62400H	3½	⅝	15⁄16	10	40
⅝ x 5	THDB62500H	4½	⅝	15⁄16	10	40
⅝ x 6	THDB62600H	5½	⅝	15⁄16	10	40
⅝ x 6½	THDB62612H	5½	⅝	15⁄16	10	40
⅝ x 8	THDB62800H	5½	⅝	15⁄16	10	20
⅝ x 10	THDB62100H	5½	⅝	15⁄16	10	20
¾ x 4	THD75400H	3½	¾	1⅛	10	40
¾ x 5	THD75500H	4½	¾	1⅛	5	20
¾ x 6	THDT75600H	4½	¾	1⅛	5	20
¾ x 7	THD75700H	5½	¾	1⅛	5	10
¾ x 8½	THD75812H	5½	¾	1⅛	5	10
¾ x 10	THD75100H	5½	¾	1⅛	5	10

† These models do not meet minimum embedment depth requirements for strength design and require maximum installation torque of 25 ft. – lb. using a torque wrench, driver drill or cordless ¼" impact driver with a maximum permitted torque rating of 100 ft. – lb.

1. Length of anchor is measured from underside of head to end of anchor.