MADE IN THE USA WITH GLOBAL MATERIALS

Tap-Flex™ Thread-Forming Structural Screws

Increased thread engagement with strength and ductility

Feature a unique thread profile to ease installation and increase performance.

Specifications

- Diameters: 3/8", 1/2", and 5/8"
- Head Style: Hex washer
- Threads: E-Form® five-lobe thread forming
- Material: Alloy steel,Finish: Silver Stalgard® SUB coating
- Heat Treat: Grade 5; meets ASTM A449 specifications (120 KSI strength)

Features and Benefits

- E-Form thread overcomes friction build-up and reduces drive torque
- Roll forms own work-hardened thread to resist loosening and provide enhanced pull-out values
- Virtually immune to delayed embrittlement failures
- Stalgard SUB coating provides 2000 hours of salt spray resistance (per ASTM B117)

Cat #	Size	Finish	Seating Torque	Drill Bit Size	Load-Bearing Length	Qty	Wt
3/8" Diameter, Hex Washer Head							
ESU310	3/8-16 x 1-1/2	Stalgard SUB	31 ft.lb.	11/32	1.00"	500	34
ESU320	3/8-16 x 2	Stalgard SUB	31 ft.lb.	11/32	1.49"	500	40
ESU330	3/8-16 x 2-1/2	Stalgard SUB	31 ft.lb.	11/32	1.99"	500	46
ESU340	3/8-16 x 3	Stalgard SUB	31 ft.lb.	11/32	2.49"	250	26
ESU350	3/8-16 x 4	Stalgard SUB	31 ft.lb.	11/32	3.49"	250	32
ESU360	3/8-16 x 5	Stalgard SUB	31 ft.lb.	11/32	4.49"	150	23

1/2" Diameter, Hex Washer Head							
ESU410	1/2-13 x 1-1/2	Stalgard SUB	75 ft.lb.	15/32	0.875"	250	36
ESU420	1/2-13 x 2	Stalgard SUB	75 ft.lb.	15/32	1.365"	250	41
ESU430	1/2-13 x 2-1/2	Stalgard SUB	75 ft.lb.	15/32	1.865"	250	47
ESU440	1/2-13 x 3	Stalgard SUB	75 ft.lb.	15/32	2.37"	150	32
ESU450	1/2-13 x 4	Stalgard SUB	75 ft.lb.	15/32	3.37"	100	26
ESU460	1/2-13 x 5	Stalgard SUB	75 ft.lb.	15/32	4.37"	100	30
5/8" Diameter, Hex Washer Head							
ESU510	5/8-11 x 1-1/2	Stalgard SUB	150 ft.lb.	19/32	0.800"	250	46
ESU520	5/8-11 x 2	Stalgard SUB	150 ft.lb.	19/32	1.24"	150	33
ESU530	5/8-11 x 2-1/2	Stalgard SUB	150 ft.lb.	19/32	1.74"	150	38
ESU540	5/8-11 x 3	Stalgard SUB	150 ft.lb.	19/32	2.24"	100	29
ESU550	5/8-11 x 4	Stalgard SUB	150 ft.lb.	19/32	3.24"	50	18
ESU560	5/8-11 x 5	Stalgard SUB	150 ft.lb.	19/32	4.24"	50	22

Identification

E-Form® Profile

Alumi-Flex™ 302 (18-8) Stainless Steel Drill Screws

For fastening to aluminum when corrosion and galvanic reaction are a primary concern

Stainless steel drill screws provide strength and corrosion resistance in a variety of aluminum applications.

Specifications

- Diameters: #10 to 1/4"
- Lengths: 1/2" to 1-1/2"
- Head Style: Hex washer
- Drive System: Hex
- Point Types: #3 and #4
- Material: 302 stainless steel
- Finish: Stalgard® GB (Galvanic Barrier) coating

Features & Benefits

- Provides a very high level of corrosion resistance
- Coating allows greater galvanic compatibility in dissimilar metal applications involving aluminum
- Head marked with a "3" for easy identification

Cat #	Description	Finish	Ctn Qty	Ctn Wt
#10 Diameter Hex Washer Head				
EAH430-I	10-16 x 1/2"	Stalgard GB	8,000	41
EAH445-I	10-16 x 3/4"	Stalgard GB	6,000	39
EAH460-I	10-16 x 1"	Stalgard GB	5,000	45
#10 Diameter, Undercut Flat Head				
EBM160-I	10-16 x 3/4"	Stalgard GB	10,000	44