HEX WASHER HEAD SELF-DRILL

Attaches back up plates, fixtures, door frames, and lathers channel to structural studs, and metal decks up to 12 gauge. Zinc finish.

Screw Diameter	Min. Tension	Min. Tortional	Avg. Shear	Avg. Pull out
6	1150	25	840	670
8 10	1575 2100 2350	42 61 65	1055 1496	705 786
12	2800 3250	92 100	2015	842
14	3850 4275	150 168	2585	910

Specifications apply to most STAR and POSI-GRIP screws. Tested in .16 metal.

Size	Part No.	Qty/ Box	Approx. Wt/Box	Point No.	Max. Drill Cap.
6 x 1/2"	HD6012	15m	36 lbs	2	0.104
6 x 3/4"	HD6034	10m	31 lbs	2	0.104
8 x 1/2"	HD8012	10m	29 lbs	2	0.104
8 x 5/8"	HD8058	10m	37 lbs	2	0.104
8 x 3/4"	HD8034	10m	40 lbs	2	0.104
8 x 1"	HD8100	7.5m	37 lbs	2	0.104
8 x 1-1/4"	HD8114	5m	32 lbs	2	0.104
8 x 1-1/2"	HD8112	5m	35 lbs	2	0.104
8 x 2"	HD8200	3m	28 lbs	2	0.104
10 x 1/2"	HD10012	10m	46 lbs	2	0.110
10 x 5/8"	HD10058	7.5m	41 lbs	3	0.179
10 x 3/4"	HD10034	7m	41 lbs	3	0.179
10 x 3/4"	HD10034S	5m	36 lbs	3	0.179
10 x 1"	HD10100	5m	35 lbs	3	0.179
10 x 1-1/4"	HD10114	3.5m	31 lbs	3	0.179
10 x 1-1/2"	HD10112	3m	29 lbs	3	0.179
10 x 1-1/2"	HD10112BT	3m	28 lbs	3	0.179
10 x 2"	HD10200	2m	24 lbs	3	0.179
10 x 3"	HD10300	1.5m	23 lbs	3	0.179
12 x 3/4"	HD12034	5m	37 lbs	3	0.220
12 x 1"	HD12100	3.5m	32 lbs	3	0.220
12 x 1-1/4"	HD12114	3.5m	38 lbs	3	0.220
12 x 1-1/2"	HD12112	2.5m	32 lbs	3	0.220
12 x 2"	HD12200	2m	33 lbs	3	0.220
12 x 2-1/2"	HD12212	1m	18 lbs	3	0.220
12 x 3"	HD12300	1m	23 lbs	3	0.220
14 x 3/4"	HD14034	3.5m	40 lbs	3	0.250
14 x 1"	HD14100	2.5m	35 lbs	3	0.250
14 x 1-1/4"	HD14114	2m	33 lbs	3	0.250
14 x 1-1/2"	HD14112	2m	38 lbs	3	0.250
14 x 2"	HD14200	1.5m	33 lbs	3	0.250
14 x 2-1/2"	HD14212	1m	28 lbs	3	0.250
14 x 3"	HD14300	1m	33 lbs	3	0.250
14 x 4"	HD14400	0.5m	19 lbs	3	0.250
14 x 5"	HD14500	0.5m	27 lbs	3	0.250

SELF-PIERCING SLOTTED HEX WASHER HEAD NEEDLE POINT

Used in light metal assembly such as electrical outlets, framing, and various other sheet metal applications. Slotted head. Zinc plated.

- Extra sharp point for faster penetration

Size	Part No.	Qty/Box	Approx. Wt/Box
8 x 1/2"	HSS8012	10m	28 lbs
8 x 3/4"	HSS8034	10m	41 lbs
8 x 1"	HSS8100	8m	37 lbs
8 x 1-1/4"	HSS8114	6m	34 lbs
8 x 1-1/2"	HSS8112	5m	33 lbs
8 x 2"	HSS8200	3m	25 lbs
10 x 1/2"	HSS10012	10m	44 lbs
10 x 3/4"	HSS10034	6m	32 lbs
10 x 1"	HSS10100	5m	34 lbs
10 x 1-1/2"	HSS10112	3m	26 lbs
10 x 2"	HSS10200	2m	24 lbs

PAN HEAD SELF-DRILL

Attaching steel strapping (bridging) or furring channel to steel joist.

- Zinc finish. Phillips recess.

Size	Part No.	Qty/ Box	Approx. Wt/Box	Point No.	Max. Drill Cap.
6 x 3/8"	PD6038	10m	16 lbs	2	0.104
6 x 1/2"	PD6012	15m	31 lbs	2	0.104
6 x 5/8"	PD6058	10m	24 lbs	2	0.104
6 x 3/4"	PD6034	10m	29 lbs	2	0.104
6 x 1"	PD6100	10m	35 lbs	2	0.104
8 x 1/2"	PD8012	10m	31 lbs	2	0.104
8 x 5/8"	PD8058	10m	39 lbs	2	0.104
8 x 3/4"	PD8034	10m	40 lbs	2	0.104
8 x 1"	PD8100	7.5m	37 lbs	2	0.104
8 x 1-1/4"	PD8114	5m	33 lbs	2	0.104
8 x 1-1/2"	PD8112	5m	36 lbs	2	0.104
8 x 2"	PD8200	3m	28 lbs	2	0.104
10 x 1/2"	PD10012	10m	47 lbs	2	0.110
10 x 5/8"	PD10058	8m	39 lbs	3	0.179
10 x 5/8"	PD10058FH	7.5m	39 lbs	3	0.179
10 x 3/4"	PD10034	7.5m	44 lbs	3	0.179
10 x 1"	PD10100	5m	38 lbs	3	0.179
10 x 1-1/4"	PD10114	3.5m	32 lbs	3	0.179
10 x 1-1/2"	PD10112	3m	29 lbs	3	0.179