A325 Structural Bolts

Available in Metric (A325M), M20, M22 & M25 diameters up to 170 mm in length. Plain, Hot Dip Galvanized & Mechanical Galvanized Finishes.



PLAIN LENGTH	HOT DIP	MECHANICAL NIZED LENGTH
1-1/4		2
1-1/2		2-1/4
1-3/4		2-1/2
2		2-3/4
2-1/4		3
2-1/2		3-1/4
2-3/4		3-1/2
3		3-3/4
3-1/4		4
3-1/2		4-1/2
3-3/4		5
4		5-1/2
5/8 - 11		6
1-1/2		6-1/2
1-3/4		7
2		7-1/2
2-1/4		**1 - 8 NC**
2-1/2		2
2-3/4		2-1/4
3		2-1/2
3-1/4		2-3/4
3-1/2		3
3-3/4		3-1/4
4		3-1/2
4-1/2		3-3/4
5		4
5-1/2		4-1/2
3/4 - 10		5
1-1/2		5-1/2
1-3/4		6
2		6-1/2
2-1/4		7
2-1/2		7-1/2
2-3/4		**1 - 1/8 - 7**
3		2-1/4
3-1/4		2-1/2
3-1/2		2-3/4
3-3/4		3
4		3-1/4
4-1/2		3-1/2
5		3-3/4
5-1/2		4
6		4-1/2
6-1/2		5
7		6
7-1/2		6-1/2
8		7
9		7-1/2
9-1/2		
10		
7/8 - 9 I		
1-3/4		

Structural Bolt Dimensions

BOLT DIA.	THREAD LEN.	BOLT DIA.	THREAD LEN.
1/2"	1.00	1-1/8"	2.00
5/8"	1.25	1-1/4"	2.00
3/4"	1.38	1-3/8"	2.25
7/8"	1.50	1-1/2"	2.25
1"	1.75		

A490 Structural Bolts

- Plain
- ***SPECIAL COATINGS AVAILABLE***

LENGTH (INCH)	DIAMETER 5/8" - 11	3/4" - 10	7/8" - 9	1" - 8	1-1/8" - 7	1-1/4" - 7
	–	–	–	–	–	–
	1-1/2	1-1/2	–	–	–	–
	1-3/4	1-3/4	1-3/4	–	–	–
	2	2	2	2	–	–
	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4	2-1/4
	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2	2-1/2
	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4	2-3/4
	3	3	3	3	3	3
	3-1/4	3-1/4	3-1/4	3-1/4	3-1/4	3-1/4
	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2	3-1/2
	3-3/4	3-3/4	3-3/4	3-3/4	3-3/4	3-3/4
	4	4	4	4	4	4
	4-1/2	4-1/2	4-1/2	4-1/2	4-1/2	4-1/2
	5	5	5	5	5	5
	5-1/2	5-1/2	5-1/2	5-1/2	5-1/2	5-1/2
	–	6	6	6	6	6

Beveled Square Washers

NOMINAL ID
1/4
5/16
3/8
1/2
5/8
3/4
7/8
1



A563 Grade DH & DH3 Structural Nuts

Grade DH -Plain, mechanical & hot dipped galvanized

Grade DH3 - Black Type III weathering steel

SIZE	DH	DH 3 TYPE III
1/2-13		
5/8-11		
3/4-10	ASTM A563 Grade C	ASTM A563 Grade C3
7/8-9		
1-8		
1-1/8-7	ASTM A563 Grade C	ASTM A563 Grade C3
1-1/4-7		



PLAIN HOT DIP GALVANIZED

A325 Flat Washers (AS™ F436)



- Plain or Hot Dip Galvanized Finish

SIZE	PLAIN	HDG
1/2		
5/8		
3/4		
7/8		
1		
1-1/8		
1-1/4		

Squirter® DTI's

- Flexible silicone embedded in depressions under bumps
- Tighten bolt until calibrated amount of orange silicone appears under the squirt locations

SIZE
3/4
7/8
1

Heavy Hex Nuts Mechanical Properties

HEAVY HEX NUT TYPE	ROCKWELL HARDNESS	PROOF LOAD STRESS PLAIN	GALV.
C & C3	B78 - C38	144,000 psi	–
DH & DH3	C24 - C38	175,000 psi	150,000 psi
2H	C24 - C38	175,000 psi	–
Class 10S	C26 - C38	1245 mpa	1245 mpa

Grade C & C3 Nuts - Recommended for plain (non-galvanized) ASTM A325 High Strength Structural Bolts.

Grade DH & DH3 Nuts - Recommended for ASTM A490 & ASTM A325 Structural Bolts.

Grade A194 2H Nuts - Designed to be used with bolts in high-pressure & high temperature service.

Class A563M10S Nuts - Recommended for zinc-coated ASTM A32M high strength structural bolts. May be substituted for Class 8S nuts with approval