SPIRA-LOK® THE ORIGINAL HELICIAL WALL TIE SYSTEM

A one-piece, flexible stainless steel wall tie for pinning masonry to new or existing walls. Also suitable for temporary support for lintel and shelf angle replacement. The dry-set technique may involve various tie diameters, drill bits and installation tools.

AVAILABLE: 8 mm or 10 mm diameter x 6-1/8" (155 mm) up to 24" (600 mm) long in Stainless Steel Type 304. (316 available by special order).

SPECIAL FEATURES:

- Only a small diameter pilot hole required
- No toxic adhesives or expansion devices
- Functional in a wide variety of building materials
- Able to withstand cyclic loading
- Accommodates differential movement between materials
- Does not stress or fracture fragile substrates

NOTE: An on-site survey should be carried out prior to project tendering to determine material strength, tie diameter & length, pilot hole size and appropriate drilling technique

DIMENSIONAL STONE
(to concrete or masonry)

INTERIOR: STEEL OR WOOD STUD

BRICK TO CONCRETE
(mortar joint or solid brick)

BRICK TO CONCRETE BLOCK

MULTI-WYTHE BRICK

BRICK TO WOOD STUD
(mortar joint or solid brick)

TERRA COTTA TO MASONRY

BRICK TO CLAY TILE