STEPLADDERS

LOUISVILLE.

FS1500 Series Fiberglass Step Ladder

Type 1A

- Non-conductive ladder designed for everyday use by contractors and industry
- Molded top with tool slots
- Wide back braces
- Full channel fiberglass rail
- Double-rivet step construction
- Inside spreader braces
- Slip-resistant rubber feet

PART NO.	SIZE	STEP SIZE	BOTTOM WIDTH	SPREAD	WEIGHT
FS1504	4'	3"	19-9/16"	28-15/16"	14 lb.
FS1506	6'	3"	22-9/16"	40-7/8"	20 lb.
FS1508	8'	3"	25-9/16"	52-3/4"	26 lb.
FS1510	10'	3"	28-9/16"	64-11/16"	34 lb.
FS1512	12'	3"	31-9/16"	76-1/16"	47 lb.

WERNER

Fiberglass Step Ladder

- Holster top with lock-in system secures tools to increase productivity
- Shoulder bolt and nut on top hinge
- 4-rivets attach top to each front rail
- Double riveted slip-resistant traction-tred steps
- 300 lb. rated

PART NO.	SIZE	MAX. STANDING HEIGHT	WIDTH	SPREAD
6204	4'	1' 11"	19-7/8"	29"
6205	5'	2' 10"	21-5/8"	35-1/8"
6206	6'	3' 10"	23-3/8"	41-1/4"
6208	8'	5' 9"	26-7/8"	53-5/8"
6210	10'	7' 8"	30-3/8"	65-7/8"
6212	12'	9' 7"	33-7/8"	78-1/4"

LOUISVILLE.

Fiberglass Cross Step Ladder

Type 1A

- Converts from a step ladder into a shelf ladder for a 2-in-1 combination
- Shape ProTop allows the ladder to lean against walls buildings and poles
- ProTop with multiple tool slots and magnet
- Innovative lock latch to secure rear section
- Step ladder angles allows you to get closer to work area
- Shox Impact absorption system
- Raptor boot with slip-resistant non-marring bonded tread
- Inside spreader braces
- Double-rivet step construction
- Double heavy-duty reinforcements

PART NO.	SIZE
FXS1504	4'
FXS1506	6'
FXS1508	8'
FXS1510	10'
FXS1512	12'

STANLEY_SUPPLY.indd 132-133

PODIUM/PLATFORM LADDERS

PLEASE NOTE: Platform Ladders are measured DIFFERENTLY than regular stepladders. Platform Ladders are measured to PLATFORM (Standing) height. Stepladder heights are the OVERALL height of ladder

WERNER

Fiberglass Podium Platform

Type 1A

- LOCKTOP extended guard rail securely wraps around work zone and holds an arsenal of tools
- 4X work zone allows work facing any direction
- Extra-large standing platform for comfort
- Customize ladder top with Lock-In Accessories System
- EDGE360™ gives protection from every angle with integrated rail sheild, EDGE bracing and over-sized foot pad
- Double riveted slip-resistant TRACTION-TRED® steps
- Back-up plates reinforce all top connectors
- All steps and two rear horizontals are knee-braced

TYPE 1A 300 LOAD CAP.

PD6203-4C

PD6203

PART NO.	PLATFORM HEIGHT	EQUAL STEP LADDER HT	WEIGHT	WIDTH
PD6203	3"	5'	22.4 lb.	26-3/8"
PD6204	4'	6'	27.7 lb.	27-1/2'
PD6206	6'	8'	33.6 lb.	31-1/4'
PD6208	8'	10'	45.9 lb.	34-3/4'
PD6210	10'	12'	57 lb.	38-3/8"

PART NO.	PLATFORM HEIGHT
FIBERGLASS PODIUM PLATFORM LADDER WITH CASTERS	
PD6203-4C	3'
PD6204-4C	4'

LOUISVILLE.

FXP1700 Series Fiberglass Pro Platform Ladder

Type 1A

- ProTop with multiple tool slots and magnet
- Extended handrail from top to platform
- Shox impact absorption system
- DaBoot slip-resistant boot
- Double-rivet step construction
- Wide back braces

TYPE IA 300 lbs LOAD CAPACITY

PART NO.	PLATFORM HEIGHT
FXP1704	4'
FXP1706	6'
FXP1708	8'

PART NO.	PLATFORM HEIGHT
FXP1710	10'
FXP1712	12'

TYPE IA 300 lbs LOAD CAPACITY

LOUISVILLE.

FP1500 Series Fiberglass Platform Ladder

Type 1A

- Large standing surface for worker safety and comfort
- Ability to safely turn from side to side while standing on platform
- Reduces fatigue compared to traditional stepladders
- Improved design allows for easier storage and shipping
- SHOX bracing to safeguard ladder from side impacts
- Gapless slip-resistant platform
- Top rail guard
- Double-rivet step construction

PART NO.	PLATFORM HEIGHT	EQUAL STEP LADDER HEIGHT	BOTTOM WIDTH	SPRD	WT.
FP1504	4'	6'	25"	45-1/2"	24 lb.
FP1506	6'	8'	28"	56-1/2"	29 lb.
FP1508	8'	10'	31"	67-1/2"	43 lb.
FP1510	10'	12'	34"	78-1/2"	55 lb.
FP1512	12'	14'	37"	89-1/2"	66 lb.

6/15/24 12:51 PM

EXTENSION LADDERS

LOUISVILLE.

FE3200 Series Fiberglass Channel Extension Ladder

Type 1A

- The extra heavy duty, channel extension ladder for lighter industrial use
- Full channel non-conductive side rails
- Designed for 300 lb. workload when set at the proper working angle
- D-shaped rungs
- Swivel safety shoes
- Outside slide guides
- Mar-resistant rail end caps
- Quicklatch™

SPECIFICATIONS						
SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE BASE	WIDTH FLY	OUTSIDE BASE	WIDTH FLY
16' - 28'	3-1/4"	5-3/4"	14-11/16"	13-11/16"	17-1/16"	16-1/16"
32 - 40'	3-15/16"	6-1/8"	15-5/16"	14-5/16"	17-11/16	16-11/16"

PART NO.	SIZE	STEP SIZE	BOTTOM WIDTH	SPREAD
FE3220	20'	10"	17"	42"
FE3224	24'	12"	21"	52"
FE3228	28'	14"	25"	58"
FE3232	32'	16"	29"	70"
FE3236	36'	18"	32"	79"
FE3240	40'	20''	35"	93"

LOUISVILLE.

FE7000 Series Fiberglass Plate Connect Extension Ladder

Type 1A

- For all industrial needs
- Full channel non-conductive side rails
- Designed for a 300 lb. workload when set at the proper working angle
- Full metal Boot™
- D-shaped rungs
- Swivel safety shoes
- Outside slide guides
- Mar-resistant rail end caps
- Aluminum plate coonection rungs
- Quicklatch™

SPECIFICATIONS						
SIZES	RAIL DEPTH	STACK HEIGHT	INSIDE BASE	WIDTH FLY	OUTSIDE BASE	WIDTH FLY
16' - 28'	3-1/4"	5-3/4"	14-11/16"	13-11/16"	17-1/16"	16-1/16"
32 - 40'	3-15/16"	6-1/8"	15-5/16"	14-5/16"	17-11/16	16-11/16"

PART NO.	SIZE	STEP SIZE	BOTTOM WIDTH	SPREAD
FE7216	20'	10'	17"	42"
FE7220	24'	12"	21"	52"
FE7224	28'	14"	25"	58"
FE7240	32'	16"	29"	70"

WERNER

Fiberglass D-Rung Extension Ladder

- Exclusive ALFLO® rung joint means TWIST-PROOF® performance
- 1-5/8" slip-resistant TRACTION-TRED® D-rungs
- Smooth operating pulley with polypropylene rope
- Interlocking side rails with internal rail guides on bottom of fly section securely connect rails

PART NO.	SIZE	REACH HEIGHT	MAX. WORKING LENGTH	WEIGHT
D6220-2	20''	19'	17'	44.5 lb.
D6224-2	24'	23'	21'	52 lb.
D6228-2	28'	27'	25'	59.5 lb.
D6232-2	32'	31'	29'	71.5 lb.
D6240-2	40'	37'	35'	195.1 lb.