DUCT ACCESS DOORS

RD-5090 Round Duct / Galvanized Steel

- Pull and catch lock system
- Gasketing on the door assures a tight seal without obstruction in the air system
- **Applications:** Economical access to round ducts

SPECIFICATIONS	
Door / Door Frame:	16 gauge galvanized steel
Finish:	Mill Finish
Gasketing:	1/8" thick by 1" wide closed cell neoprene
Hinge:	Continuous aluminum piano hinge
Standard Latch:	Plated steel pull and catch

SIZE	OPENING	WEIGHT
6" x 4"	5"	1 lb.
7" x 5"	6"	1.25 lb.
8" x 6"	7"	1.5 lb.
9" x 8"	8"	1.75 lb.
10" x 8"	9"	2 lb.
11" x 9"	10"	3 lb.

SIZE	OPENING	WEIGHT
13" x 10"	12"	3.5 lb.
15" x 13"	14"	4 lb.
17" x 13"	16"	5.5 lb.
19" x 15"	18"	6 lb.
19" x 17"	20"	6.75 lb.
20" x 17"	24"	7.25 lb.

Note: Duct opening is normal door size plus 3/8"

PLASTIC ACCESS DOORS

PA-3000

- High impact styrene plastic with U.V. stabilizers
- Hinged with a removable feature
- **Applications:** Easy access to walls and ceilings

SPECIFICATIONS	
Door / Door Frame:	1/8" high impact styrene plastic with U.V. stabilizers. Flush to frame — rounded safety corners, one piece outside flange with 3/4" deep mounting frame
Finish:	White, with textured exposed surfaces
Hinge:	Concealed
Latch:	Snap latches allow door to fit tightly within frame door

STANDARD DOOR SIZE	WEIGHT
4" x 6"	.5 lb.
6" x 9"	.5 lb.
8" x 8"	1 lb.
12" x 12"	.5 lb.
14" x 14"	.75 lb.
14" x 29"	4 lb.
18" x 18"	2.25 lb.
22" x 22"	4 lb.
24" x 24"	4.75 lb.

Note: Wall opening is width + 3/8"

Contour Cam Latch Access Door

- Hidden magnetic closing mechanism
- **Material:** 16 gauge steel frame and door
- **Hinge:** Concealed double arm pantograph system
- **Lock / Latch:** Concealed magnets for locking mechanism
- **Finish:** High quality white powder coat finish

PART NO.	SIZE
CTR16X30	16" x 30"

STANLEY_SUPPLY.indd 178-179