PFN

FIRE RATED UNINSULATED ACCESS DOOR
FOR WALLS ONLY

Intertek

The **PFN** is **not insulated** and can **only be used on fire rated walls**. It comes with a 1" flange for an easy flush installation on any type of surface material. As per **UL** and NFPA 80 standards, once the installation is complete and the provided springs installed, this door will be self closing and self locking. It should not be used in situations where protection against temperature elevation is required. The largest fire rated PFN door available is: (36" x 36" or 1296 sq. in.).

Fire rated by

Intertek

FIRE RATED UNINSULATED DOOR
WITH DRYWALL FLANGE

DESCRIPTION

FIRE RATING: For vertical wall assemblies only:
CERTIFIED TO STANDARDS: UL 10C, UL 10B (2009), NFPA 252 (2012), CAN/ULC S104 (R1985), CAN/ULC S104 (2010).
RATING ACHIEVED: 1-1/2 hours
MAXIMUM SIZE: 36" wide x 36" high (914 mm x 914 mm). Maximum area of 1296 in². Tolerance on height and width limitation is ± 3" (76 mm) as long as the area does not exceed 1296 in².
TEMPERATURE RISE: No rating achieved.

Material: 16 gauge cold rolled steel
Hinge: continuous piano hinge
Lock / latch: self latching tool-key operated latch and/or ring operated latch, both included
Inside panel release: standard on all doors over 12" x 12"
Automatic panel closer: standard on all doors
Finish: high quality white powder coat primer
Packaging: individually wrapped, 1 per box

POPULAR **OPTIONS**

Material: stainless steel #4 (brushed finish),
Lock / latch: Key operated slam latch, handle operated slam latch, mortise preparation for cylinder (cylinder optional), hex head slam latch , mortise deadbolt lock
Masonery anchor: available on all sizes

PFN-HS SECURITY for high security PFN-HS: optional 16 gauge cold rolled steel frame and 14 gauge galvanneal steel door

LEED ready: This product contributes to LEED® credits. Visit **www.cendrex.com** for more information.

Table of standard sizes
[other sizes available upon request]

DOOR SIZE - W x H INCHES (MM)	NUMBER OF LOCKS	SHIPPING WEIGHT LBS	KG
8 x 8 (203 x 203)	1	5	2.3
10 x 10 (254 x 254)	1	7	3.2
12 x 12 (304 x 304)	1	8	3.6
14 x 14 (355 x 355)	1	10	4.5
16 x 16 (406 x 406)	1	12	5.5
18 x 18 (457 x 457)	1	14	6.4
22 x 22 (558 x 558)	1	18	8.2
22 x 30 (558 x 762)	1	22	10.0
22 x 36 (558 x 914)	2	27	12.2
24 x 24 (609 x 609)	1	22	10.0
24 x 36 (609 x 914)	2	29	13.2
30 x 30 (762 x 762)	1	30	13.6
32 x 32 (812 x 812)	2	33	15
36 x 36 (914 x 914)	2	39	17.7

Rough wall opening = door size + 1/4" or + 6mm

Authorities Having Jurisdiction (AHJ) should be consulted in all cases as to the particular requirements covering the installation and use of fire rated access doors.

Your odd sizes: Made in 5 days

www.**cendrex**.com

BUILDING MATERIALS

6/15/24 12:51 PM