

AUDITORIA DE PANTALLAS (APLICACION CON LLAMADAS A FUNCIONES BD)

A) Resumen numérico

- N° total de usos `.from(: 31`
- N° total de usos `.rpc(: 9`
- N° total de usos `.functions.invoke(: 9`

B) Tabla de “Accesos directos a tablas”

Archivo	Línea	Función o componente	Tabla afectada	Fragmento
auditExport.ts (line 41)	41	<code>uploadToAuditExportsBucket</code>	<code>bucket system-exports</code>	<code>.from(bucket)</code>
auditExport.ts (line 95)	95	<code>insertAuditExportRow</code>	<code>audit_exports</code>	<code>.from("audit_exports")</code>
SubscriptionManager2.tsx (line 214)	214	<code>SubscriptionManager2 · load effect</code>	<code>customers</code>	<code>.from("customers")</code>
SubscriptionManager2.tsx (line 223)	223	<code>SubscriptionManager2 · load effect</code>	<code>debacu_eval_invoices</code>	<code>.from("debacu_eval_invoices")</code>
SubscriptionManager2.tsx (line 242)	242	<code>SubscriptionManager2 · load effect</code>	<code>plans</code>	<code>.from("plans")</code>
SubscriptionManager2.tsx (line 355)	355	<code>SubscriptionManager2 · handleSaveProfile</code>	<code>customers</code>	<code>.from("customers")</code>
SubscriptionManager2.tsx (line 384)	384	<code>SubscriptionManager2 · handleSaveBankData</code>	<code>customers</code>	<code>.from("customers")</code>
evaluationService.ts (line 128)	128	<code>getGlobalSummary</code>	<code>debacu_eval_platform_</code>	<code>.from("debacu_eval_platform_</code>

Archivo	Línea	Función o componente	Tabla afectada	Fragmento
128)			<code>summary</code>	<code>summary")</code>
evaluationService.ts (line 134)	134	<code>getGlobalSummary</code>	<code>debacu_eval_country_summary</code>	<code>.from("debacu_eval_country_summary")</code>
evaluationService.ts (line 317)	317	<code>searchMyRatingsInSupabase</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
evaluationService.ts (line 365)	365	<code>searchRatingsInSupabase</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
evaluationService.ts (line 410)	410	<code>searchEvaluations</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
evaluationService.ts (line 476)	476	<code>getClientHistoryByDocument</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
debacu_eval_subscription_state.service.ts (line 25)	25	<code>get_plan_by_id</code>	<code>plans</code>	<code>.from("plans")</code>
debacu_eval_subscription_state.service.ts (line 43)	43	<code>get_current_subscription</code>	<code>subscriptions</code>	<code>.from("subscriptions")</code>
authService.ts (line 41)	41	<code>validateUserAccess</code>	<code>customers</code>	<code>.from("customers")</code>
authService.ts (line 64)	64	<code>validateUserAccess</code>	<code>subscriptions</code>	<code>.from("subscriptions")</code>
authService.ts (line 90)	90	<code>validateUserAccess</code>	<code>plans</code>	<code>.from("plans")</code>
accountService.ts (line 95)	95	<code>getMyEvalAccount</code>	<code>customers</code>	<code>.from('customers')</code>

Archivo	Línea	Función o componente	Tabla afectada	Fragmento
accountService.ts (line 106)	106	<code>getMyEvalAccount</code>	<code>subscriptions</code>	<code>.from('subscriptions')</code>
accountService.ts (line 124)	124	<code>getMyEvalAccount</code>	<code>plans</code>	<code>.from('plans')</code>
accountService.ts (line 139)	139	<code>getMyEvalAccount</code>	<code>receipts</code>	<code>.from('receipts')</code>
DashboardHome.tsx (line 133)	133	<code>DashboardHome · load</code>	<code>subscriptions</code>	<code>.from("subscriptions")</code>
DashboardHome.tsx (line 173)	173	<code>DashboardHome · load</code>	<code>debacu_eval_audit_log</code>	<code>.from("debacu_eval_audit_log")</code>
DashboardHome.tsx (line 186)	186	<code>DashboardHome · load</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
DashboardHome.tsx (line 200)	200	<code>DashboardHome · load</code>	<code>debacu_eval_audit_log</code>	<code>.from("debacu_eval_audit_log")</code>
DashboardHome.tsx (line 249)	249	<code>DashboardHome · load fallback</code>	<code>debacu_evaluations</code>	<code>.from("debacu_evaluations")</code>
AdminChangesPage.tsx (line 344)	344	<code>AdminChangesPage · load</code>	<code>abuse_settings_audit_grouped</code>	<code>.from("abuse_settings_audit_grouped")</code>
AdminClientsPage.tsx (line 195)	195	<code>AdminClientsPage · openPdf</code>	storage bucket (req.accepted_terms_pdf_bucket)	<code>supabase.storage.from(bucket).getPublicUrl(path);</code>

Archivo	Línea	Función o componente	Tabla afectada	Fragmento
AdminClientsPage.tsx (line 203)	203	<code>AdminClientsPage · openPdf</code>	storage bucket (req.accepted_terms_pdf_bucket)	<code>supabase.storage.from(bucket).createSignedUrl(path, 60 * 15);</code>
adminService.ts (line 451)	451	<code>listAbuseSettingsAudit</code>	<code>abuse_settings_audit</code>	<code>.from("abuse_settings_audit")</code>

C) Tabla de “Llamadas directas a RPC”

Archivo	Línea	Nombre del RPC	Fragmento
AdminChangesPage.tsx (line 395)	395	<code>admin_rollback_abuse_settings</code>	<code>const { error } = await (supabase as any).rpc("admin_rollback_abuse_settings", {</code>
rpcUntyped.ts (line 8)	8	<code>fn (dinámico en rpcUntyped)</code>	<code>const { data, error } = await (supabase as any).rpc(fn, args ?? {});</code>
adminService.ts (line 88)	88	<code>admin_list_customers</code>	<code>const { data, error } = await sb.rpc("admin_list_customers", {</code>
adminService.ts (line 194)	194	<code>admin_list_audit_exports</code>	<code>const { data, error } = await sb.rpc("admin_list_audit_exports", {</code>
adminService.ts (line 227)	227	<code>admin_list_audit_exports_v2</code>	<code>const { data, error } = await sb.rpc("admin_list_audit_exports_v2", {</code>
adminService.ts (line 245)	245	<code>admin_list_audit_export_downloads</code>	<code>const { data, error } = await sb.rpc("admin_list_audit_export_downloads", {</code>

Archivo	Línea	Nombre del RPC	Fragmento
adminService.ts (line 274)	274	admin_list_audit_exports_v2 (full params)	const { data, error } = await (supabase as any).rpc("admin_list_audit_exports_v2", {
adminService.ts (line 452)	452	admin_audit_export_download_stats	const { data, error } = await (supabase as any).rpc("admin_audit_export_download_stats", {
evaluationService.ts (line 642)	642	global_risk_snapshot_public	const { data, error } = await supabase.rpc<any>("global_risk_snapshot_public");

D) Tabla de “Uso de Edge Functions”

Archivo	Línea	Nombre de la función invocada	Wrapper usado	Fragmento
edge.ts (line 15)	15	fn (parámetro)	edgeCall (helper)	const { data, error } = await supabase.functions.invoke(fn, {
adminService.ts (line 24)	24	fn (parámetro)	invokeAuthed (helper)	const { data, error } = await supabase.functions.invoke(fn, {
adminService.ts (line 62)	62	admin_dashboard_metrics	edgeCall	return edgeCall<{ ... }>("admin_dashboard_metrics", {});
adminService.ts (line 79)	79	admin_list_customers	invokeAuthed	return invokeAuthed<any[]>("admin_list_customers", { q, limit, offset });
adminService.ts (line 100)	100	admin_list_	edgeCall	const res = await edgeCall<{ rows: any[];

Archivo	Línea	Nombre de la función invocada	Wrapper usado	Fragmento
		<code>plans</code>		<code>count: number; limit: number; offset: number }>("admin_list_plans", { app_id: "DEBACU_EVAL", q, limit, offset }));</code>
adminService.ts (line 111)	111	<code>admin_list_invoices</code>	<code>edgeCall</code>	<code>const res = await edgeCall<{ rows: any[]; count: number; limit: number; offset: number }>("admin_list_invoices", { app_id: "DEBACU_EVAL", limit, offset }));</code>
adminService.ts (line 299)	299	<code>admin_abuse_api . list_alerts</code>	<code>edgeCall</code>	<code>return edgeCall<any[]>("admin_abuse_api", { action: "list_alerts", payload: { status: params?.status ?? "OPEN", limit: params?.limit ?? 200, offset: params?.offset ?? 0 }, });</code>
adminService.ts (line 306)	306	<code>admin_abuse_api . get_alert</code>	<code>edgeCall</code>	<code>return edgeCall<any>("admin_abuse_api", { action: "get_alert", payload: { id } }));</code>
adminService.ts (line 310)	310	<code>admin_abuse_api . list_actions</code>	<code>edgeCall</code>	<code>return edgeCall<any[]>("admin_abuse_api", { action: "list_actions", payload: { id, limit, offset } }));</code>
adminService.ts (line 314)	314	<code>admin_abuse_api . ack</code>	<code>edgeCall</code>	<code>return edgeCall<boolean>("admin_abuse_api",</code>

Archivo	Línea	Nombre de la función invocada	Wrapper usado	Fragmento
				<code>{ action: "ack", payload: { id, note: note ?? null } }));</code>
adminService.ts (line 318)	318	<code>admin_abuse_api · resolve</code>	<code>edgeCall</code>	<code>return edgeCall<boolean>("admin_abuse_api", { action: "resolve", payload: { id, note: note ?? null } }));</code>
adminService.ts (line 322)	322	<code>admin_abuse_api · reopen</code>	<code>edgeCall</code>	<code>return edgeCall<boolean>("admin_abuse_api", { action: "reopen", payload: { id, note: note ?? null } }));</code>
adminService.ts (line 326)	326	<code>admin_abuse_api · add_note</code>	<code>edgeCall</code>	<code>return edgeCall<boolean>("admin_abuse_api", { action: "add_note", payload: { id, note } }));</code>
adminService.ts (line 330)	330	<code>admin_abuse_api · metrics</code>	<code>edgeCall</code>	<code>return edgeCall<any>("admin_abuse_api", { action: "metrics", payload: { from: fromISO, to: toISO } }));</code>
adminService.ts (line 334)	334	<code>admin_abuse_api · get_setting s</code>	<code>edgeCall</code>	<code>return edgeCall<any>("admin_abuse_api", { action: "get_settings", payload: {} }));</code>

Archivo	Línea	Nombre de la función invocada	Wrapper usado	Fragmento
adminService.ts (line 343)	343	admin_abuse_api · update_settings	edgeCall	return edgeCall<any>("admin_abuse_api", { action: "update_settings", payload: input });
adminService.ts (line 424)	424	admin_whoami	invokeAuthed	return invokeAuthed<AdminWhoAmI>("admin_whoami", {});
adminService.ts (line 431)	431	admin_get_signed_audit_export_url_v2	invokeAuthed	const data = await invokeAuthed<{ signed_url: string; expires_in: number }>("admin_get_signed_audit_export_url_v2", { export_id: exportId, expires_in: 300 });
adminService.ts (line 455)	455	admin_get_signed_export_url	invokeAuthed	const data = await invokeAuthed<{ signed_url: string; expires_in: number }>("admin_get_signed_audit_export_url_v2", { export_id: exportId, expires_in: expiresIn });
adminService.ts (line 208)	208	debacu_eval_audit_export_sign	Directa (supabase.functions.invoke)	const { data, error } = await supabase.functions.invoke("debacu_eval_audit_export_sign", {

Archivo	Línea	Nombre de la función invocada	Wrapper usado	Fragmento
adminService.ts (line 377)	377	audit_export	Directa (supabase.functions.invoke)	<pre>const { data, error } = await supabase.functions.invoke("audit_export", {</pre>
debacu_eval_accessRequests.service.ts (line 68)	68	debacu_eval_access_request_create_draft	Directa (supabase.functions.invoke)	<pre>const { data, error } = await supabase.functions.invoke("debacu_eval_access_request_create_draft", { body: input });</pre>
debacu_eval_accessRequests.service.ts (line 90)	90	debacu_eval_generate_terms_acceptance	Directa (supabase.functions.invoke)	<pre>const { data, error } = await supabase.functions.invoke("debacu_eval_generate_terms_acceptance", { body: input });</pre>
debacu_eval_accessRequests.service.ts (line 123)	123	debacu_eval_access_request_finalize	Directa (supabase.functions.invoke)	<pre>const { data, error } = await supabase.functions.invoke("debacu_eval_access_request_finalize", { body: input });</pre>
debacu_eval_adminAccess.service.ts (line 16)	16	debacu_eval_admin_access	Directa (supabase.functions.invoke)	<pre>const { data: res, error } = await supabase.functions.invoke("debacu_eval_admin_access", {</pre>

E) “Top 10 archivos a tocar”

1. [adminService.ts](#) — 7 usos combinados (.from + .rpc).
2. [evaluationService.ts](#) — 7 usos combinados.
3. [SubscriptionManager2.tsx](#) — 5 .from direct.

4. `DashboardHome.tsx` — 5 `.from` direct.
5. `accountService.ts` — 4 `.from` direct.
6. `authService.ts` — 3 `.from` direct.
7. `debacu_eval_subscription_state.service.ts` — 2 `.from` direct.
8. `AdminClientsPage.tsx` — 2 `.from` direct (storage).
9. `auditExport.ts` — 2 `.from` (storage + audit row).
10. `AdminChangesPage.tsx` — 1 `.from` + 1 `.rpc`.

F) Recomendación de migración (sin tocar código)

- Crear una Edge function consolidada para “panel de suscripciones” (recupera `customers`, `subscriptions`, `debacu_eval_audit_log` y `debacu_eval_evaluations`) y reemplazar las consultas directas desde `SubscriptionManager2` y `DashboardHome` por ese endpoint.
- Llevar los `search*InSupabase` y `getClientHistoryByDocument` a una Edge function o RPC que devuelva únicamente los campos necesarios de `debacu_evaluations`; así se evita exponer directamente esa tabla en el cliente global RGPD-safe.
- En `AdminClientsPage`, usar una Edge function que genere las URLs públicas/signed del bucket en lugar de invocar `supabase.storage.from(...)` desde el navegador; así se limita la superficie de credenciales y permisos.
- Reutilizar el frontend de audit (como `listAbuseSettingsAudit`) para invocar las ya existentes Edge functions `admin_abuse_api` en vez de `.from("abuse_settings_audit")`, manteniendo toda la lógica de filtrado en el backend.

No he modificado ningún archivo. Auditoría solo lectura.