
Functions

Adapted from materials by Dr. Carrier



Homa Appliances - Unsplash

CIS 162/163 Recap

CIS 162/163 Recap

What is a function?

CIS 162/163 Recap

What is a function?

- Blocks of code that can be called from elsewhere
- Usually accomplish one specific task

CIS 162/163 Recap

What is a function?

- Blocks of code that can be called from elsewhere
- Usually accomplish one specific task

Why would we use them?

CIS 162/163 Recap

What is a function?

- Blocks of code that can be called from elsewhere
- Usually accomplish one specific task

Why would we use them?

- Save time writing code
- Improves readability
- Modularity

Comparing to Python

```
def get_smaller(a, b):
   if a < b:
      return a
   return b;
```

Comparing to Python

```
def get_smaller(a, b):
   if a < b:
      return a
   return b;
```

Roughly the same function in C:

Comparing to Python

```
def get_smaller(a, b):
   if a < b:
      return a
   return b;
```

Roughly the same function in C:

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Comparing to Python

```
def get_smaller(a, b):
   if a < b:
      return a
   return b;
```

Roughly the same function in C:

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Calling a function:

```
int res = GetSmaller(7, x);
```

Terminology

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Calling a function:

```
int res = GetSmaller(7, x);
```

Terminology

Function name




```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Calling a function:

```
int res = GetSmaller(7, x);
```

Terminology





```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Calling a function:

```
int res = GetSmaller(7, x);
```


Terminology




Calling a function:

```
int res = GetSmaller(7, x);
```

Terminology



Calling a function:



Little more terminology

Function prototype:

```
int GetSmaller(int a, int b);
   or
int GetSmaller(int, int);
```

Little more terminology

Function prototype:

```
int GetSmaller(int a, int b);
   or
int GetSmaller(int, int);
```

Function definition:

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Little more terminology

Function prototype:

```
int GetSmaller(int a, int b);
   or
int GetSmaller(int, int);
```

Function definition:

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Key: Definition can come before or after main

If definition is after main, you *must* have prototype before main

Returning

```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Returning




```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

Returning




```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

All functions must have a return type

Returning




```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

All functions must have a return type

If you don't return anything, return type is `void`

Returning




```
int GetSmaller(int a, int b){
   if(a < b) return a;
   return b;
}
```

All functions must have a return type

If you don't return anything, return type is `void`

```
void Example(int a, int b){
   // Do something
   // No need to return
}
```

Arguments

```
int Increment(int x){
   x++;
   return x;
}

int main(){
   int i = 0;
   printf(“i = %d\n”, i);
   int res = Increment(i);
   printf(“res = %d\n”, res);
   printf(“i = %d\n”, i);
}
```

What does this output?

Arguments

```
int Increment(int x){
   x++;
   return x;
}

int main(){
   int i = 0;
   printf(“i = %d\n”, i);      // 0
   int res = Increment(i);
   printf(“res = %d\n”, res); // 1
   printf(“i = %d\n”, i);      // 0
}
```

What does this output?

Arguments

C is always **pass-by-value**

- Not pass-by-reference

Arguments

C is always **pass-by-value**

Not pass-by-reference

WAIT!

This is only half true!
We'll come back to this after we've talked about pointers!

Arguments

```
int Increment(int* p){
   (*p)++;
   return *p;
}

int main(){
   int i = 0;
   printf(“i = %d\n”, i);
   int res = Increment(&i);
   printf(“res = %d\n”, res);
   printf(“i = %d\n”, i);
}
```

What does this output?

Arguments

```
int Increment(int* p){
   (*p)++;
   return *p;
}

int main(){
   int i = 0;
   printf(“i = %d\n”, i);      // 0
   int res = Increment(&i);
   printf(“res = %d\n”, res); // 1
   printf(“i = %d\n”, i);      // 1
}
```

What does this output?

Arguments

What about passing an array?

How can we write a function to print an array in a nice way?

Scope

What is the output of this code?

```
void DoStuff(){
   int x = 10;
   printf("In func: x = %d\n", x);
   ...
}

int main(){
   int x = 0;
   printf("x = %d\n", x);
   DoStuff();
   printf("x = %d\n", x);
}
```

Scope

What is the output of this code?

```
void DoStuff(){
   int x = 10;            //v x = 10
   printf("In func: x = %d\n", x);
   ...
}

int main(){
   int x = 0;
   printf("x = %d\n", x); // x = 0
   DoStuff();
   printf("x = %d\n", x); // x = 0
}
```

Scope

Functions have their own scope

Scope

Functions have their own scope

- Variables in function don’t exist outside it
- Functions can’t access variables in main


STOP
And come back
after pointers

Arguments

C is always **pass-by-value**

Not pass-by-reference

How can we change arguments?

Arguments

C is always **pass-by-value**

Not pass-by-reference

How can we change arguments?

Pass a pointer!

Arguments

What about passing an array?

How can we write a function to print an array in a nice way?

```
void PrintArray(int* arr, int len){
  printf("[");
  int i = 0;
  for(i = 0; i < len; i++){
    printf(" %d", arr[i]);
  }
  printf(" ]\n");
}
```

Arguments

What about passing an array?

How can we write a function to print an array in a nice way?

```
void PrintArray(int* arr, int len){
  printf("[");
  int i = 0;
  for(i = 0; i < len; i++){
    printf(" %d", arr[i]);
  }
  printf(" ]\n");
}
```

Notice we also have to pass the length!

Scope

Functions have their own scope

- Variables in function don’t exist outside it
- Functions can’t access variables in main

Is this code valid?

```
int* MakeInt(){
   int x = 10;
   return &x;
}
```

Scope

Functions have their own scope

- Variables in function don’t exist outside it
- Functions can’t access variables in main

Is this code valid?

```
int* MakeInt(){
  int x = 10;
  return &x;
}
```

Nope! x falls out of scope when we return

- Memory address is then pointing at nothing :(