

# File I/O in C

Adapted from materials by Dr. Carrier



# Overview

Files are treated like streams

# Overview

Files are treated like streams

Files are managed via **file pointers**

# Overview

Files are treated like streams

Files are managed via **file pointers**

All file functions are in `<stdio.h>`

# Overview

Files are treated like streams

Files are managed via **file pointers**

All file functions are in `<stdio.h>`

Generally, the process looks like this:

1. Create file pointer

# Overview

Files are treated like streams

Files are managed via **file pointers**

All file functions are in `<stdio.h>`

Generally, the process looks like this:

1. Create file pointer
2. Open file in the correct mode

# Overview

Files are treated like streams

Files are managed via **file pointers**

All file functions are in `<stdio.h>`

Generally, the process looks like this:

1. Create file pointer
2. Open file in the correct mode
3. Read and/or edit the file

# Overview

Files are treated like streams

Files are managed via **file pointers**

All file functions are in `<stdio.h>`

Generally, the process looks like this:

1. Create file pointer
2. Open file in the correct mode
3. Read and/or edit the file
4. Close the file



# Opening a file

```
FILE* fp_in;  
fp_in fopen("in_filename", "r");  
// Read file  
fclose(fp_in);
```

# Opening a file

```
FILE* fp_in;  
fp_in = fopen("in_filename", "r");  
// Read file  
fclose(fp_in);  
  
FILE* fp_out;  
fp_out = fopen("out_filename", "w");  
// Write to file  
fclose(fp_out);
```

# fopen

```
FILE* fp = fopen(filename, mode);
```

# fopen

```
FILE* fp = fopen(filename, mode);
```

Modes:

- “r” to read
- “w” to write (discards old contents)
- “a” to append

# fopen

```
FILE* fp = fopen(filename, mode);
```

Modes:

- “r” to read
- “w” to write (discards old contents)
- “a” to append

Can also add “+” to both read/write [\(docs\)](#)

# fopen

```
FILE* fp = fopen(filename, mode);
```

Modes:

- “r” to read
- “w” to write (discards old contents)
- “a” to append

Can also add “+” to both read/write [\(docs\)](#)

You *can* add “b” to the end for binary mode

This does not matter on Unix systems

# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

fopen returns NULL on failure, good to check!



# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

fopen returns NULL on failure, good to check!

When can it fail?

# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

fopen returns NULL on failure, good to check!

When can it fail?

- Reading a file that doesn't exist

# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

fopen returns NULL on failure, good to check!

When can it fail?

- Reading a file that doesn't exist
- Incorrect permissions

# fopen

Mode	File exists?	File doesn't exist?
read	Open to read	Error
write	Overwrite it	Create it
append	Append to it	Create it

fopen returns NULL on failure, good to check!

When can it fail?

- Reading a file that doesn't exist
- Incorrect permissions

```
FILE* fp = fopen("file.txt", "r");
if(fp == NULL){
    printf("Error! Could not open file\n");
    return 1;
}
```

# fclose

```
fclose(file_pointer);
```

# fclose

```
fclose(file_pointer);
```

Closing your files is important!

File output is often buffered – changes are only written to file when its closed!

# fclose

```
fclose(file_pointer);
```

Closing your files is important!

File output is often buffered – changes are only written to file when its closed!

Even if your system doesn't buffer, we want to close files to make our code portable!

# Reading from a file

*Very* similar to reading input from stdin!



# Reading from a file

*Very* similar to reading input from stdin!

scanf switches to fscanf

fgets and getline work out of the box!

# Reading from a file

*Very* similar to reading input from stdin!

scanf switches to fscanf

fgets and getline work out of the box!

```
fscanf(fileptr, formatstr, memaddr1, ...);
```

# Reading from a file

*Very* similar to reading input from stdin!

scanf switches to fscanf

fgets and getline work out of the box!

```
fscanf(fileptr, formatstr, memaddr1, ...);
```

```
fgets(char* s, int size, FILE* stream);
```

# Reading from a file

*Very* similar to reading input from stdin!

scanf switches to fscanf

fgets and getline work out of the box!

```
fscanf(fileptr, formatstr, memaddr1, ...);
```

```
fgets(char* s, int size, FILE* stream);
```

```
getline(char ** lineptr, size_t n,  
        FILE* stream);
```

# Writing to a file

```
fprintf(FILE* fp, format_str, args...);
```

Identical to printf, but writes to a file, not stdout

Don't forget the first f!

# Writing to a file

```
fprintf(FILE* fp, format_str, args...);
```

Identical to printf, but writes to a file, not stdout

Don't forget the first f!

```
fputc(int c, FILE* fp);
```

Writes a single character to file

there's also a fgetc)

# Writing to a file

```
fprintf(FILE* fp, format_str, args...);
```

Identical to printf, but writes to a file, not stdout

Don't forget the first f!

```
fputc(int c, FILE* fp);
```

Writes a single character to file

there's also a fgetc)

```
fputs(char* s, FILE* fp);
```

Writes the string to file

# Working with bytes

```
fread(void* buffer, size_t size,  
      size_t n, FILE* fp);
```

- Reads n objects (which are size bytes each) from file and stores data in buffer.



# Working with bytes

```
fread(void* buffer, size_t size,  
      size_t n, FILE* fp);
```

- Reads n objects (which are size bytes each) from file and stores data in buffer.

```
fwrite(void* buffer, size_t size,  
       size_t n, FILE* fp);
```

- Writes n objects (which are size bytes each) from buffer to fp

# Working with bytes

```
fseek(FILE* fp, long offset,  
      int origin);
```

- Think of your cursor in a text file, next read/write will occur here

# Working with bytes

```
fseek(FILE* fp, long offset,  
      int origin);
```

- Think of your cursor in a text file, next read/write will occur here
- This also applies to reading/writing files in C
- `fseek` will move this cursor (position indicator)

# Working with bytes

```
fseek(FILE* fp, long offset,  
      int origin);
```

- Think of your cursor in a text file, next read/write will occur here
- This also applies to reading/writing files in C
- `fseek` will move this cursor (position indicator)

Options for origin:

- `SEEK_SET` - start of file
- `SEEK_CUR` - current position
- `SEEK_END` - end of file

# Final thoughts

Pay attention to return values!!

e.g., input functions will treat errors and  
EOF differently

This will save you future headaches

# Final thoughts

Pay attention to return values!!

e.g., input functions will treat errors and  
EOF differently

This will save you future headaches

If you are switch between reading and writing in the  
same file pointer

Use `fseek()` or `fflush()` before switching

This forces buffer to be flushed