

EFS

EKS



EC2 > Security Groups > Create security group

Basic details

Security group name [Info](#)

Name cannot be edited after creation.

Description [Info](#)

VPC [Info](#)

EC2 > Security Groups > Create security group

Inbound rules

Type	Protocol	Port range	Source	Description - optional
NFS	TCP	2049	An... 0.0.0.0/0	

[Add rule](#)

Rules with source of 0.0.0.0/0 or ::/0 allow all IP addresses to access your instance. We recommend setting security group rules to allow access from known IP addresses only.

Outbound rules

Type	Protocol	Port range	Destination	Description - optional
All traffic	All	All	Cu... 0.0.0.0/0	

Creación de un grupo de seguridad con una regla de entrada para poder acceder al EFS que crearemos a continuación

EKS

Create file system

×

Create an EFS file system with recommended settings. [Learn more](#)

Name - *optional*

Name your file system.

efs-eks

Name can include letters, numbers, and +-=._:/ symbols, up to 256 characters.

Virtual Private Cloud (VPC)

Choose the VPC where you want EC2 instances to connect to your file system.

vpc-0a9517b3c09f63c6b

default

Cancel

Customize

Create

EKS

Elastic File System X

- File systems
- Access points
- AWS Backup [↗](#)
- AWS DataSync [↗](#)
- AWS Transfer [↗](#)
- Documentation [↗](#)

Mount targets

A mount target provides an NFSv4 endpoint at which you can mount an Amazon EFS file system. We recommend creating one mount target per Availability Zone. [Learn more](#) [↗](#)

Availability zone	Subnet ID	IP address	Security groups	
us-east-1a	subnet-0bd70a5251	172.31.23.32	Choose securl... ▼ sg-037b790c5 X 99c354f0 EKS-SG_EFS	Remove
us-east-1b	subnet-0bac3d76ae	172.31.35.246	Choose securl... ▼ sg-037b790c5 X 99c354f0 EKS-SG_EFS	Remove
us-east-1c	subnet-0a86eea9aa	172.31.7.0	Choose securl... ▼ sg-037b790c5 X 99c354f0 EKS-SG_EFS	Remove
us-east-1d	subnet-02251cf85e	172.31.93.205	Choose securl... ▼ sg-037b790c5 X 99c354f0 EKS-SG_EFS	Remove

EKS

```
susana@minikube2025:~$ kubectl apply -k "github.com/kubernetes-sigs/aws-efs-csi-driver/deploy/kubernetes/overlays/stable/ecr/?ref=release-7"
```

Esta forma esta deprecated, ahora se hace con kustomize

The screenshot shows the AWS EKS console interface for configuring add-ons. The breadcrumb navigation at the top reads: [EKS](#) > [Clusters](#) > [liberis](#) > [Add-ons](#) > [Add add-ons](#). On the left sidebar, the steps are: **Select add-ons**, **Step 2**, **Configure selected add-ons settings** (highlighted), and **Step 3** Review and add.

The main section is titled **Configure selected add-ons settings** with the instruction: "Configure the add-ons for your cluster by selecting settings." It features a card for the **Amazon EFS CSI Driver** (Info).

Key details for the Amazon EFS CSI Driver:

- Listed by:** (Icon of a hexagon with a 'K')
- Category:** storage
- Status:** ✓ Ready to install (with a **Remove add-on** button)
- Version:** Select the version for this add-on. The dropdown menu shows **v2.1.4-eksbuild.1**.
- Add-on access:** Two radio buttons are present: **EKS Pod Identity** (selected) and **IAM roles for service accounts (IRSA)**.
- Pod Identity IAM role for service account: efs-csi-controller-sa**: Select an IAM role to use with this add-on. This dropdown only contains IAM roles with the pods.eks.amazonaws.com service principal in the trust policy of the IAM role. The dropdown shows **Not set**, with a **Create recommended role** button.

The footer contains: [CloudShell](#), [Feedback](#), © 2025, Amazon Web Services, Inc. or its affiliates., [Privacy](#), [Terms](#), and [Cookie preferences](#).

EKS

```
susana@minikube2025:~$ kubectl get pods -n kube-system
```

NAME	READY	STATUS	RESTARTS	AGE
aws-node-9zwdl	2/2	Running	0	5h25m
aws-node-glxdj	2/2	Running	0	5h23m
coredns-789f8477df-cj2kj	1/1	Running	0	5h19m
coredns-789f8477df-gqtg6	1/1	Running	0	5h19m
ebs-csi-controller-ffcdd857f-5ndlb	6/6	Running	0	5h19m
ebs-csi-controller-ffcdd857f-g86r8	6/6	Running	0	5h19m
ebs-csi-node-99mtk	3/3	Running	0	5h23m
ebs-csi-node-dgqhj	3/3	Running	0	5h25m
efs-csi-controller-755f9d7cfc-ldlvp	3/3	Running	0	5h24m
efs-csi-controller-755f9d7cfc-t2k2p	3/3	Running	0	5h26m
efs-csi-node-dqdxk	3/3	Running	0	5h23m
efs-csi-node-gc9c5	3/3	Running	0	5h25m
eks-node-monitoring-agent-bx2cr	1/1	Running	0	5h25m
eks-node-monitoring-agent-mlzfc	1/1	Running	0	5h23m
eks-pod-identity-agent-whgr7	1/1	Running	0	5h25m
eks-pod-identity-agent-xmmlf	1/1	Running	0	5h23m
kube-proxy-sdcs8	1/1	Running	0	5h23m
kube-proxy-xx26h	1/1	Running	0	5h25m
metrics-server-67cd494699-sp7dl	1/1	Running	0	5h19m
metrics-server-67cd494699-zjlvv	1/1	Running	0	5h19m

```
susana@minikube2025:~$
```

EKS

Ejemplo de uso del volumen EFS. Writer-Reader

EKS

Instalo el cliente nfs

```
 _ | _ | _ )  
 _ | ( _ /  Amazon Linux 2 AMI  
 _ | \ _ | _ |
```

```
https://aws.amazon.com/amazon-linux-2/
```

```
[ec2-user@ip-172-31-9-204 ~]$ sudo yum install -y amazon-efs-utils
```

Creo el directorio en el que monto el sistema de ficheros.

```
[ec2-user@ip-172-31-9-204 ~]$ pwd
```

```
/home/ec2-user
```

```
[ec2-user@ip-172-31-9-204 ~]$ mkdir efs
```

```
[ec2-user@ip-172-31-9-204 ~]$
```


EKS

 s3

Elas

File

Acco

AWS

AWS

AWS

Doc

Attach

×

Mount your Amazon EFS file system on a Linux instance. [Learn more](#) 

☒ Mount via DNS

☐ Mount via IP

Using the EFS mount helper:

```
 sudo mount -t efs -o tls fs-01dbb71c40cf7339b:/ efs
```

Using the NFS client:

```
 sudo mount -t nfs4 -o nfsvers=4.1,rsize=1048576,wsiz=1048576,hard,timeo=600,retrans=2,noresvport fs-01dbb71c40cf7339b.efs.us-east-1.amazonaws.com:/ efs
```

See our user guide for more information. [Learn more](#) 

Close

 © 2017 Amazon

EKS

```
[ec2-user@ip-172-31-9-204 ~]$ df -h
Filesystem      Size  Used Avail Use% Mounted on
devtmpfs        474M   0    474M   0% /dev
tmpfs           483M   0    483M   0% /dev/shm
tmpfs           483M 472K   482M   1% /run
tmpfs           483M   0    483M   0% /sys/fs/cgroup
/dev/xvda1      8.0G 1.8G   6.3G  22% /
tmpfs           97M   0     97M   0% /run/user/1000
127.0.0.1:/     8.0E   0    8.0E   0% /home/ec2-user/efs
[ec2-user@ip-172-31-9-204 ~]$ cd efs
[ec2-user@ip-172-31-9-204 efs]$ ls
out.txt
[ec2-user@ip-172-31-9-204 efs]$ cat out.txt
```