

List of figures

Figure 1.1	NASA spacecraft. From upper left, clockwise. GGS Wind, Cassini, Mars Observer, TDRS H, New Horizons, and Europa Clipper. The author worked on GGS Polar, Mars Observer, and TDRS H, I, J. All images are courtesy of NASA.	4
Figure 1.2	European Space Agency BepiColombo Mercury Planetary Orbiter. Copyright: spacecraft: ESA/ATG medialab; Mercury: NASA/Johns Hopkins University Applied Physics Laboratory/Carnegie Institution of Washington.	5
Figure 1.3	European Space Agency BepiColombo Mercury Magnetospheric Orbiter. Copyright: spacecraft: ESA/ATG medialab; Mercury: NASA/Johns Hopkins University Applied Physics Laboratory/Carnegie Institution of Washington.	5
Figure 2.1	Hubble Space Telescope. Image courtesy of NASA.	17
Figure 2.2	Four ISS Control-Moment Gyros. Image courtesy of NASA.	18
Figure 2.3	The International Space Station. Image courtesy of NASA.	19
Figure 2.4	Japanese H-II transfer vehicle. The use of space robot arms was pioneered by NASA and the Canadian Space Agency for the Shuttle. Image courtesy of NASA.	20
Figure 2.5	Pluto orbiter. DFD stands for Direct Fusion Drive.	21
Figure 3.1	Single-axis control system.	24
Figure 3.2	Sine wave to illustrate sampling. If sampling was exactly half the period, the samples might all be zero.	26
Figure 4.1	Spacecraft-design flow.	34
Figure 4.2	Spacecraft control-system design flow.	36
Figure 4.3	Pivoted wheel.	42
Figure 5.1	Two-frame vector diagram.	48
Figure 5.2	Euler-angle diagram.	48
Figure 5.3	Transformation matrix from two vectors.	50
Figure 5.4	Quaternion diagram.	52
Figure 5.5	Coordinate transformations from LVLH to body with small angles. This diagram shows the roll angle, α . The body axes are in red.	62
Figure 6.1	A satellite represented by three boxes.	68
Figure 6.2	Rotating coordinate frame.	74
Figure 6.3	The planar slosh system.	82
Figure 6.4	Dynamical model with two one-degree-of-freedom hinges for the momentum wheel and the telescope. Unlike a gyrostat, these are not necessarily rotating about their center-of-mass.	86
Figure 6.5	James Webb Space Telescope dynamical model. There is the core body, six reaction wheels assumed to be perfectly symmetric, and two fuel tanks.	92
Figure 6.6	Single-gimbal control-moment gyro (CMG). The momentum wheel spins at a constant angular rate.	95

Figure 6.7	Flexible structure schematic.	99
Figure 7.1	Lambertian reflector.	104
Figure 7.2	Atmospheric properties for Titan and Neptune.	108
Figure 7.3	Coordinates for a nonhomogeneous planet.	109
Figure 7.4	Earth 68-by-68 spherical-harmonic gravity model.	110
Figure 7.5	150-by-150 spherical-harmonic lunar gravity model. The plot shows magnitude variations.	111
Figure 7.6	The Earth's dipole field in a 55-degree inclined orbit.	112
Figure 7.7	The Earth's Van Allen radiation belts. Image Source: http://www.nasa.gov/mission_pages/rbsp/multimedia/20130228_briefing_materials.html .	114
Figure 7.8	Another view showing the inner and outer belts. An inclined orbit is shown for reference.	114
Figure 8.1	Disturbance analysis fits into the spacecraft-design process in several places.	119
Figure 8.2	Torque production. Some disturbances produce torques without a force.	122
Figure 8.3	Normals can be used to select surfaces in some cases.	123
Figure 8.4	Free molecular flow.	125
Figure 8.5	Lift and drag on a plate.	126
Figure 8.6	LVLH frame for the gravity-gradient analysis.	130
Figure 8.7	Earth albedo and radiosity.	135
Figure 8.8	Adaptive subdivision.	136
Figure 8.9	Diffuse surface radiation.	137
Figure 8.10	Plume-geometry diagram.	138
Figure 8.11	Scan-line algorithm. The red rectangles are the included areas. The picture on the right shows the view down the flux vector.	142
Figure 10.1	Reaction wheel.	156
Figure 10.2	Anatomy of an axial-flux motor reaction wheel. Clockwise from left: side view showing the stator coils, the Halbach rotor magnet array, the complete wheel in operation, view from the top and bottom view showing the optical angle encoder.	156
Figure 10.3	DC motor model.	157
Figure 10.4	Response to a doublet with and without current feedback. The plot on the right shows current feedback.	159
Figure 10.5	Response to commutation.	162
Figure 10.6	Hubble Space Telescope suspension [2]. Image courtesy of NASA.	163
Figure 10.7	Impulse bit vs. pulsewidth.	167
Figure 10.8	Tank geometry.	168
Figure 10.9	Dual-coil solenoid.	173
Figure 10.10	Contours for integrating the magnetic field.	173
Figure 10.11	Single-coil solenoid.	176
Figure 10.12	Contours for integrating the magnetic field.	177
Figure 10.13	Valve driver.	178
Figure 11.1	Horizon sensor measurement geometry and pulse.	183

Figure 11.2	Static Earth sensor, left, and conical scanning Earth sensor on the right.	185
Figure 11.3	Diagram of the Earth-sensor scanning and chordwidth geometry.	187
Figure 11.4	Nomenclature for measured chord parts.	188
Figure 11.5	Sun-sensor geometry.	188
Figure 11.6	Simple one-dimensional Sun sensor.	189
Figure 11.7	Allan Deviation and noise. τ is the averaging bin size.	191
Figure 11.8	Proof-mass accelerometer.	196
Figure 11.9	Pinhole camera.	197
Figure 11.10	Star-camera errors.	199
Figure 12.1	Attitude control system hierarchy. This diagram shows various types of attitude control systems.	204
Figure 12.2	Attitude control phases.	205
Figure 12.3	Attitude control system architecture.	207
Figure 12.4	Control system.	207
Figure 12.5	Attitude control system flow.	210
Figure 12.6	Friction-torque diagram.	219
Figure 12.7	Low-bandwidth control system.	224
Figure 12.8	Coordinate transformations from LVLH to body with small angles. This diagram shows the roll angle, α . The body axes are in red.	225
Figure 12.9	Hill's frame of reference for relative orbital motion.	235
Figure 12.10	The Soyuz spacecraft with thruster locations.	238
Figure 12.11	Rotation about an axis to align two vectors.	244
Figure 13.1	Four thrusters on for a velocity-change maneuver. The arrows show the plume direction.	257
Figure 13.2	Aerodynamics geometry.	264
Figure 13.3	Simplified aerodynamics geometry.	265
Figure 13.4	Coordinate transformations from LVLH to body with small angles. This diagram shows the roll angle, α . The body axes are in red.	266
Figure 13.5	Solar-pressure unloading geometry.	268
Figure 14.1	Star-camera geometry. The diagram on the left shows the pinhole camera. The image on the right shows a focal plane.	272
Figure 14.2	Earth sensor at zero roll and 0.6 deg roll.	273
Figure 14.3	Simple one-dimensional Sun sensor.	275
Figure 14.4	Two-axis analog Sun sensor. The supporting structure is 3D printed. The windows are visible on the top.	276
Figure 14.5	ECI magnetic-field computation.	277
Figure 14.6	GPS attitude geometry. The range signals will be a function of the attitude. Multiple GPS satellites are used.	278
Figure 14.7	Vector geometry for Earth/Sun/magnetic-field-attitude estimation.	280
Figure 14.8	The closed-loop system block diagram.	282
Figure 14.9	Butterworth fourth-order filter with $\omega_C = 0.5$.	283
Figure 15.1	Small angles.	287

Figure 15.2	Flow of the quaternion through the Kalman filter.	295
Figure 15.3	Two-sensor, single-axis sensing.	296
Figure 15.4	Stellar attitude determination system.	298
Figure 16.1	Operational amplifier configured as an integrator.	306
Figure 16.2	Analog computer.	307
Figure 16.3	One-axis simulation. Two disks are aligned on the same shaft. The dotted line surrounds the entire system.	309
Figure 16.4	Simulation sequence for ACS development. The attitude control block evolves and gains complexity during the design process.	312
Figure 16.5	End-to-end testing involves the entire operational chain.	314
Figure 16.6	Hardware interfaces showing interface types. Direct memory access (DMA) is typically used for cameras although modern (terrestrial) serial interfaces are very fast.	320
Figure 17.1	Bathtub curve. The end-of-life curve is shaped differently from the beginning-of-life curve.	324
Figure 17.2	Typical requirements flow for an attitude control system.	326
Figure 17.3	Testing lifecycle from algorithm design through flight.	327
Figure 18.1	Rehearsal schedule for a satellite launch.	334
Figure 18.2	Satellite-launch team.	334
Figure 18.3	Mission-operations elements and timeline.	335
Figure 18.4	Entities involved in mission operations.	337
Figure 18.5	Mission-operations organization.	338
Figure 18.6	Mission operations.	340
Figure 19.1	CubeSat model.	347
Figure 19.2	CubeSat prior to deployment. The box at the top is the folded boom with the tip mass.	347
Figure 19.3	CubeSat attitude control components.	348
Figure 20.1	Spin-axis attitude determination diagram.	356
Figure 20.2	Great-circle precession diagram.	356
Figure 20.3	Rhumb-line precession diagram.	357
Figure 20.4	Thruster geometry for spin-precession maneuvers.	359
Figure 20.5	Attitude determination geometry diagram.	361
Figure 21.1	Orbital geometry.	367
Figure 21.2	Spacecraft-configuration diagrams.	368
Figure 21.3	Close-up of spacecraft showing the Sun geometry.	369
Figure 21.4	Thruster layout diagram.	372
Figure 21.5	Dual-spin turn.	373
Figure 21.6	Station-keeping geometry.	377
Figure 22.1	Orbit-geometry diagram.	394
Figure 22.2	Solar-array frame.	394
Figure 22.3	Sun-nadir yaw trajectory for a GPS orbit. The noon–midnight flips are evident.	396

Figure 22.4	Sun-sensor geometry. These sensors are used to determine yaw. γ is along the solar-array rotation axis. $+z$ is normal to the cell face.	398
Figure 22.5	Earth-sensor geometry diagram.	398
Figure 23.1	Surveyor (on the left) and Lunar Module landing trajectories (on the right). Images courtesy of NASA.	409
Figure 23.2	NASA JPL Mars lander. Image courtesy of NASA.	410
Figure 23.3	Lunar-landing concept of operations.	411
Figure 23.4	Selenographic frame.	412
Figure 23.5	Selenographic to ECI frame.	412
Figure 23.6	Proposed landers. The upper left is a lander with a high-gain antenna. The next three are a proposed commercial lunar helium-3 return vehicle. The reentry vehicle would be reusable. All of the avionics are in the reentry vehicle, include all RCS thrusters. Images courtesy of Princeton Satellite Systems.	417
Figure 23.7	Aligning two vectors with ECI vectors. The acceleration vector is aligned exactly, the other as close as possible.	418
Figure 24.1	James Webb Space Telescope. Image courtesy of NASA.	425
Figure 24.2	The James Webb Space Telescope ACS system designed in this chapter. FGS is a fine guidance sensor.	426
Figure 24.3	The James Webb Space Telescope CAD model. The surfaces are divided into triangles.	428
Figure 24.4	Propulsion system [5].	430
Figure 24.5	James Webb Space Telescope 2D drawing showing the approximate center-of-mass.	431
Figure 24.6	The James Webb Space Telescope sunshield. Image courtesy of NASA.	431
Figure 24.7	Disturbance model with three plates.	432
Figure 24.8	Thruster layout. There are eight thruster pairs in four locations at the bottom edge of the bus. The thrust vectors are all at 45 degrees with respect to the sunshade.	434
Figure 24.9	Attitude determination using an unscented Kalman filter (UKF).	435
Figure 25.1	Student-built magnetic torquers and field-measurement app on an iPhone.	441
Figure 25.2	A solar cell and simulator and reaction-wheel hardware connected to a simulation.	442
Figure 25.3	CubeSat concept of operations. Damping of rates is done at separation. The spacecraft deploys its solar wings, then reorients.	443
Figure 25.4	3U CubeSat with deployable solar wings. The wings are fixed. The orthogonal torquers and Earth sensor are on the nadir deck. The magnetometer is on the zenith deck.	444
Figure 25.5	The CubeSat control system. It has a magnetometer, Earth sensor, reaction wheels, and magnetic torquers.	445
Figure 26.1	The Microwave Anisotropy Probe. Image courtesy of NASA.	450
Figure 26.2	Control-system block diagram.	452

Figure 27.1	The NEA Scout solar-sail spacecraft is shown during integration and test. Image courtesy of NASA.	457
Figure 27.2	Four solar-sail types.	458
Figure 27.3	Moving-mass geometry.	461
Figure 27.4	Flux balance on the solar-sail surface.	463
Figure 27.5	Sail with vanes. c is the vector from the geometric center to the center-of-mass. u_i is the rotation axis for the vanes.	467
Figure 27.6	GN&C system. The black boxes are included ACS software. IMU stands for inertial measurement unit.	469
Figure 27.7	Attitude control simulation with vanes enabled for momentum control. The large angles necessitate the use of a numerical method to solve for the angles.	471
Figure A.1	Linearization of the function $y = x^3$ around $x = 1$.	478
Figure A.2	Unit sphere and unit vectors.	484
Figure D.1	Coordinate frames.	503
Figure D.2	Local vertical/local horizontal (LVLH) frame.	505
Figure D.3	International Space Station frame. Image Courtesy of NASA.	506
Figure D.4	The selenographic reference frame.	507
Figure D.5	Selenographic to ECI frame.	507
Figure D.6	Areocentric frame.	508
Figure E.1	ECI and Earth-fixed coordinate frames. In many applications, only the rotation angle needs be considered. The green arrows are the Earth-fixed frame.	511
Figure G.1	Rate-control block diagram.	521
Figure G.2	General control-system block diagram.	523
Figure G.3	Control-system block diagram.	529
Figure G.4	Standard representation of uncertainty.	531
Figure G.5	Compensated plant.	533
Figure G.6	Standard plant model.	536
Figure G.7	Unity-feedback block diagram.	541
Figure G.8	Computer-controlled system.	545
Figure G.9	Two inertias coupled by a spring and a damper.	557
Figure G.10	Model-following controller.	567
Figure G.11	Feedback controller.	567
Figure G.12	Block diagram of the closed-loop control system.	570
Figure H.1	The Kalman-filter family tree. All are derived from a Bayesian filter. This book covers those in colored boxes.	587
Figure H.2	Mass with a 3rd-order spring in parallel with a damper and linear spring.	597
Figure I.1	Elliptical orbit.	604
Figure I.2	Orbital elements.	606
Figure I.3	Equinoctial acceleration frame.	609
Figure I.4	Position vectors in the n -body system.	613
Figure I.5	Coordinates for a nonhomogeneous planet.	613

Figure J.1	Telescope taxonomy shows the variety of telescopes that could be used as part of a spacecraft optical system.	619
Figure J.2	Telescope optical geometry. The gray rectangle is the imaging chip.	620
Figure J.3	Geometry of imaging for a simple lens.	621
Figure J.4	Mirror optical geometry.	622
Figure J.5	Snell's law.	622
Figure J.6	A negative lens is on the left and a positive lens is on the right.	623
Figure J.7	Pinhole camera.	627
Figure J.8	Vision system.	629
Figure J.9	Basic radiometry.	630
Figure K.1	Coarse centroiding steps.	640
Figure K.2	Pixel histogram. b is the mean background level.	641
Figure K.3	Effect of thresholding a simulated image. Thresholding, on the right, removes the noise.	642
Figure K.4	Blobify routine results. Seven blobs, which are potential stars, are identified.	643
Figure K.5	Region of interest with border.	643
Figure K.6	Star-catalog processing. This reduces the catalog to a manageable size and makes star identification easier.	645
Figure K.7	Reduced star catalog. The field-of-view is used to reduce the catalog size. Only the brightest stars in a given region are kept.	646
Figure K.8	K-vector example in MATLAB. The plot on the left shows the steps in k . The right plot shows the data display against a straight-line fit.	648
Figure K.9	Center-of-mass centroiding compared against Gaussian fitting to the marginal distribution when the centroid moves throughout the pixel. The scales of the color bars in both images are the same.	649
Figure K.10	Digital centering example.	650
Figure L.1	Hysteresis for Permalloy C. The dotted lines are minor loops.	653
Figure M.1	Taxonomy of machine learning.	659
Figure M.2	The Deep Space 1 spacecraft. Image courtesy of NASA.	661
Figure M.3	Deep Space 1 autonomous flight system [2].	662
Figure M.4	A two-input neuron.	663
Figure M.5	A neuron connected to a second neuron. A real neuron can have 10 000 inputs!	664
Figure M.6	Four activation functions.	664
Figure M.7	A one-input neural net. The weight w is 2 and the bias b is 3. An artificial neuron consists of, at a minimum, the weight, and activation function. The bias is optional.	665
Figure M.8	The "linear" neuron compared to other activation functions from LinearNeuron.	666
Figure M.9	Exclusive-Or (XOR) truth table and possible solution networks.	667
Figure M.10	Attitude geometry showing roll and pitch.	672

Figure M.11	Static Earth-sensor operation. The circles represent the sensor elements. The left shows the geometry with zero roll and pitch. The right shows the geometry with roll-and-pitch angles.	674
Figure M.12	The Earth sensor.	674
Figure M.13	The training GUI.	675
Figure M.14	Reinforcement-learning architecture.	679
Figure M.15	Reinforcement-learning training window. The agent converges after 1500 episodes. The light blue line is the episode reward, the dark blue is the average reward since the start of training.	685