CISCO SECURE ACCESS

SCENE 01 | 0:00 - 0:14

The 9:00 AM Data Leak

Well-intentioned developer pastes 200 lines of proprietary code into a public AI assistant

auth_token_service.py (PROPRIETARY)

```
104 class InternalTokenSigner:
105     SECRET_SALT = 'c1sc0-pr0d-9981'
106     def sign_payload(self, tenant):
107         # Confidential routing logic
108         digest = self.compute(tenant)
109         return f'{tenant}.{digest}'
110
111 # [200 lines copied to clipboard...]
```

Public AI Assistant (Unsanctioned Cloud)

Prompt sent over HTTPS (TLS):

"Can you fix the bug in this auth service? Here is our internal code..."

[+ 200 lines of proprietary source code]

EXPOSURE IMPACT:

- Stored on external vendor servers
- Outside corporate visibility & control

ALERT **"DATA JUST LEFT THE BUILDING."**

No bad intent - but proprietary intellectual property just exited your organization.

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 02 | 0:14 - 0:32

Why Traditional Controls Fail on Shadow AI

Employees using unapproved GenAI apps create blind spots that legacy security cannot stop

1. Blanket Category Blocking

PUSHES USERS TO PERSONAL DEVICES

Blocking all 'AI / ML' domains disrupts legitimate engineering workflows and drives developers to personal laptops or mobile hotspots.

2. Legacy Pattern-Only DLP

MISSES SOURCE CODE & CONTEXT

Traditional regex-based DLP looks for credit cards or SSNs - it fails to recognize proprietary source code, logic, or conversational prompts.

3. Uninspected TLS / HTTPS Traffic

COMPLETE BLINDNESS TO PROMPTS

Every GenAI prompt travels inside an encrypted HTTPS session. Without TLS decryption, your DLP engine cannot see a single word.

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 03 | 0:32 - 0:38

Cisco Secure Access: 5-Step GenAI Governance

Turning Shadow AI exposure into a structured, repeatable security architecture

STEP 1

DISCOVER

AI Access Visibility &

App Risk Scoring

▶

STEP 2

DECRYPT

HTTPS Inspection

on Access Policy

▶

STEP 3

CLASSIFY

DLP AI Guardrails

Source Code & PII

▶

STEP 4

ENFORCE

Monitor or Block

Prompts & Uploads

▶

STEP 5

REFINE

Baseline in Monitor

Then Move to Block

SINGLE CONVERGED SSE WORKFLOW

```
Discover  -->  Decrypt  -->  Classify  -->  Enforce  -->  Refine
```

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 04 | 0:38 - 0:50

Step 1 - Discover with AI Access

Identify every GenAI application in use across your organization and evaluate its risk profile

Cisco Secure Access > Experience Insights > AI Access Dashboard

APPLICATION NAME	RISK SCORE	DATA RETENTION POLICY	GOVERNANCE
CodeHelper-FreeAI	CRITICAL (92/100)	Trains on user prompts	UNSANCTIONED
PublicChat-LLM	HIGH (78/100)	Retains logs 30 days	UNSANCTIONED
DocSummarize-Cloud	HIGH (74/100)	No enterprise DPA	UNSANCTIONED
EnterpriseCopilot-Pro	LOW (12/100)	Zero data retention	SANCTIONED

KEY PRINCIPLE: "You can't govern what you can't see."

AI Access baselines Shadow AI adoption and ranks applications by data-exposure risk.

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 05 | 0:50 - 1:05

Step 2 - Decrypt: The Mandatory Prerequisite

Prompt inspection requires HTTPS Inspection enabled on the matching Access Policy rule

[MISCONFIGURATION] HTTPS Inspection OFF -> DLP Sees Only Encrypted TLS

Developer Prompt
TLS 1.3 Encrypted

→

Access Policy Rule
Decrypt: [DISABLED]

→

DLP AI Guardrails
Result: 0 HITS (Blind)

[CORRECT ARCHITECTURE] HTTPS Inspection ON -> Full Prompt Visibility

Developer Prompt
Source Code Payload

→

Access Policy Rule
HTTPS Decrypt: [ON]

→

DLP AI Guardrails
Prompt Inspected!

FIELD TIP: If an AI Guardrails rule shows 0 hits, verify HTTPS Inspection on the Access Policy first.

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 06 | 1:05 - 1:20

Steps 3 & 4 - Classify and Enforce with AI Guardrails

Configure a DLP AI Guardrails rule to inspect prompts, responses, and file uploads in real time

Cisco Secure Access > Data Loss Prevention Policy > Add AI Guardrails Rule

1. INSPECTION SCOPE (INLINE CONTENT):

- [ON] User Prompts
- [ON] AI Model Responses
- [ON] File Uploads

2. SENSITIVE DATA & AI CLASSIFIERS:

- Source Code & Proprietary Algorithms
- API Keys, Tokens & Cloud Credentials
- PII, Customer Records & Financial Data
- Intellectual Property & Internal Docs

3. ENFORCEMENT ACTION:

ACTION: MONITOR (Baseline Phase)

Logs full event & matched snippet without blocking user

ACTION: BLOCK (Enforcement Phase)

Intercepts prompt/upload & displays policy notification

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 07 | 1:20 - 1:30

Step 5 - Refine: Safe Enterprise Rollout Strategy

Avoid operational friction by baselining in Monitor mode before enforcing Block

PHASE 1: WEEKS 1-2

Start in MONITOR Mode

- Deploy AI Guardrails rule in Monitor
- Capture real prompt & upload telemetry
- Zero disruption to engineering sprints

PHASE 2: TUNING

Tune Out False Positives

- Review matched snippets in DLP logs
- Whitelist sanctioned coding assistants
- Refine source-code classifier thresholds

PHASE 3: PRODUCTION

Enforce BLOCK Mode

- Switch high-risk Shadow AI apps to Block
- Prevent real-time source code exfiltration
- Maintain high developer trust & velocity

RESULT: High-precision data protection with near-zero false positives.

COLOSSYAN AVATAR ZONE

CISCO SECURE ACCESS

SCENE 08 | 1:30 - 1:35

Govern AI - Don't Just Block It

Summary & Transition to the Interactive Branching Scenario Assessment

SHADOW AI IS A DATA-EXPOSURE PROBLEM

[1] DISCOVER: Use AI Access to uncover unsanctioned GenAI apps and risk scores.

[2] DECRYPT: Enable HTTPS Inspection on the Access Policy so DLP can read prompts.

[3] CLASSIFY & ENFORCE: Apply DLP AI Guardrails to prompts, responses, and uploads.

[4] REFINE: Baseline in Monitor mode first, tune false positives, then enforce Block.

NEXT UP: HANDS-ON SCENARIO CHALLENGE (ANDES FREIGHT)

Put this architecture into practice: Diagnose a 0-hit DLP policy and design a safe Monitor-to-Block rollout to earn the 'Leak Stopper' badge.

COLOSSYAN AVATAR ZONE