

Package ‘SEMgraph’

March 15, 2021

Type Package

Title Network Analysis and Causal Inference Through Structural Equation Modeling

Version 1.0.2

Date 2020-10-08

Author Mario Grassi [aut], Fernando Palluzzi [aut, cre], Daniele Pepe [ctb]

Maintainer Fernando Palluzzi <fernando.palluzzi@gmail.com>

Description This is the SEMgraph package for network analysis and causal inference through Structural Equation Modeling (SEM). It includes functions to import, weight, manipulate, and fit biological network models using the SEM framework.

License GPL-3

Encoding UTF-8

LazyData TRUE

Depends igraph (>= 1.2.1), lavaan (>= 0.5-23), R (>= 4.0)

Imports boot (>= 1.3-25), cate (>= 1.0.4), corpcor (>= 1.6.9), dagitty (>= 0.3-0),
diffusr (>= 0.1.4), flip (>= 2.5.0), gdata (>= 2.18.0), ggm (>= 2.3),
GGMncv (>= 2.0.0), glmnet (>= 2.0-18), graph (>= 1.56.0),
Matrix (>= 1.3-2), pbapply (>= 1.4-3), pcalg (>= 2.6-5),
protoclust (>= 1.6.3), RcppEigen (>= 0.3.3.4.0), Rgraphviz (>= 2.22.0)

Suggests BiocStyle, knitr, rmarkdown, SEMdata, huge, graphite,
org.Hs.eg.db

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

R topics documented:

activeModule	2
ancestry	5
clusterGraph	6
clusterScore	7

colorGraph	9
corr2graph	11
cplot	13
extendGraph	14
extractClusters	16
gplot	17
graph2dag	18
graph2lavaan	20
lavaan2graph	21
mergeNodes	22
modelSearch	23
orientEdges	26
pairwiseMatrix	27
pathFinder	28
properties	30
sachs	31
SEMace	32
SEMbap	33
SEMdag	35
SEMgsa	37
SEMrpath	39
SEMrun	40
Shiple.test	44
summary.GGM	45
summary.RICF	46
weightGraph	47

Index 50

activeModule	<i>Active module identification</i>
--------------	-------------------------------------

Description

Uses different information flow and tree-based strategies for identifying active modules (e.g., disease modules), showing a perturbed subset of nodes and edges. Function scalability enables graph reduction at both pathway and entire interactome scales.

Usage

```
activeModule(
  graph,
  type,
  seed,
  eweight = "none",
  alpha = 0.05,
  q = 0.5,
  limit = NULL,
```

```
    ...
  )
```

Arguments

graph	An igraph object.
type	Module identification method. If type = "kou", the Steiner tree algorithm will be applied. If type = "usp", the resulting graph will be the union of all significant shortest paths. If type = "rwr", the random walk with restart algorithm will be enabled. Finally, if type = "hdi", the heat diffusion algorithm is used.
seed	Either a user-defined vector containing seed node names or one among: "pvlm", "proto", or "qi", corresponding to the seed name attribute yielded by weightGraph .
eweight	Edge weight type derived from weightGraph or from user-defined distances. This option determines the weight-to-distance transform. If set to "none" (default), edge weights will be set to 1. If eweight = "kegg", repressing interactions (-1) will be set to 1 (maximum distance), neutral interactions (0) will be set to 0.5, and activating interactions (+1) will be set to 0 (minimum distance). If eweight = "zsign", all significant interactions will be set to 0 (minimum distance), while non-significant ones will be set to 1. If eweight = "pvalue", weights (p-values) will be transformed to the inverse of negative base-10 logarithm. If eweight = "custom", the algorithm will use the distance measure specified by the user as "weight" edge attribute.
alpha	Significance level to assess shortest paths significance, when type is "usp". By default, alpha is set to 0.05.
q	Inclusion quantile for the "rwr" and "hdi" algorithms. The higher the q, the closer the nodes to the input seeds, the smaller the output graph induced by the q-top ranking nodes. By default, q = 0.5 (i.e., the top 50% of nodes are selected).
limit	An integer value corresponding to the number of graph edges. If type = "usp", beyond this limit, multicore computation is enabled to reduce the computational burden. By default, limit = NULL (i.e., multicore disabled).
...	Currently ignored.

Details

Graph filtering algorithms include:

1. "kou", the Steiner tree connecting a set of seed nodes, using the algorithm from Kou et al. (1981);
2. "usp", generates a subnetwork as the union of the significant (P-value < alpha) shortest paths between the seeds set;
3. "rwr", Random Walk with Restart; wrapper for random.walk of the R package diffusr;
4. "hdi", Heat Diffusion algorithm; wrapper for heat.diffusion of the R package diffusr.

Value

An active module of class [igraph](#).

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx* x(x): xxxxx. <https://doi.org/xxxxx>

Kou L, Markowsky G, Berman L (1981). A fast algorithm for Steiner trees. *Acta Informatica*, 15(2): 141-145. <https://doi.org/10.1007/BF00288961>

Simon Dirmeier (2018). diffusr: Network Diffusion Algorithms. R package version 0.1.4. <https://CRAN.R-project.org/package=diffusr>

Examples

```
# Graph weighting
G <- weightGraph(graph = sachs$graph, data = sachs$pkc, group = sachs$group,
                 method = "r2z",
                 seed = c(0.05, 0.5, 0.5))

# RWR algorithm, seeds and edge P-values as weights
R1 <- activeModule(graph = G, type = "kou", seed = "pv1m", eweight = "pvalue")
R2 <- activeModule(graph = G, type = "kou", seed = "proto", eweight = "pvalue")
R3 <- activeModule(graph = G, type = "kou", seed = "qi", eweight = "pvalue")

# Graphs
par(mfrow=c(2,2), mar=rep(2, 4))
plot(G, layout = layout.circle, main = "input graph")
box(col = "gray")
plot(R1, layout = layout.circle, main = "1m P-value (alpha = 0.05)")
box(col = "gray")
plot(R2, layout = layout.circle, main = "prototype (h = 0.5)")
box(col = "gray")
plot(R3, layout = layout.circle, main = "closeness (q = 0.5)")
box(col = "gray")

## Not run:

# Weight and reduce the whole KEGG interactome, using RWR

kegg1 <- weightGraph(kegg, alsData$exprs, alsData$group,
                    method = "r2z",
                    seed = c(5E-8, 0.5, 0.5))

# Set quantile value, based on the top k nodes
k <- sum(V(kegg1)$pv1m)
q <- 1 - k/vcount(kegg1)

ig1 <- activeModule(graph = kegg1, type = "rwr", seed = "pv1m",
                   eweight = "pvalue",
                   q = q)
ig1 <- graph2dag(ig1, alsData$exprs)
```

```

ig1 <- properties(ig1)[[1]]

# Fitting
sem1 <- SEMrun(ig1, alsData$exprs, alsData$group, fit = 1, algo = "ricf")
summary(sem1$gest)
gplot(sem1$graph)

## End(Not run)

```

ancestry

Node ancestry utilities

Description

Get ancestry for a collection of nodes in a graph. These functions are wrappers for the original SEMID R package.

Usage

```

ancestors(g, nodes)

descendants(g, nodes)

parents(g, nodes)

siblings(g, nodes)

```

Arguments

<code>g</code>	An igraph object.
<code>nodes</code>	the nodes in the graph of which to get the ancestry.

Value

a sorted vector of nodes.

References

Rina Foygel Barber, Mathias Drton and Luca Weihs (2019). SEMID: Identifiability of Linear Structural Equation Models. R package version 0.3.2. <https://CRAN.R-project.org/package=SEMID>

Examples

```
# Get all ancestors
an <- V(sachs$graph)[ancestors(sachs$graph, "Erk")]

# Get parents
pa <- V(sachs$graph)[parents(sachs$graph, "PKC")]

# Get descendants
de <- V(sachs$graph)[descendants(sachs$graph, "PKA")]

# Get siblings
sib <- V(sachs$graph)[siblings(sachs$graph, "PIP3")]
```

clusterGraph	<i>Topological graph clustering</i>
--------------	-------------------------------------

Description

Topological graph clustering methods.

Usage

```
clusterGraph(graph, type = "wtc", HM = "none", size = 5, verbose = FALSE, ...)
```

Arguments

graph	An igraph object.
type	Topological clustering methods. If type = "tahc", network modules are generated using the tree agglomerative hierarchical clustering method (Yu et al., 2015). Other non-tree clustering methods from igraph package include: "wtc" (default value; walktrap community structure with short random walks), "ebc" (edge betweenness clustering), "fgc" (fast greedy method), "lbc" (label propagation method), "lec" (leading eigenvector method), "loc" (multi-level optimization), "opc" (optimal community structure), "sgc" (springlass statistical mechanics).
HM	Hidden model type. Enables the visualization of the hidden model. If set to "none" (default), no HM is visualized. For each defined hidden module: (i) if HM = "LV", a latent variable (LV) will be defined as common unknown cause acting on cluster nodes; (ii) if HM = "CV", cluster nodes will be considered as regressors of a latent composite variable (CV); (iii) if HM = "UV", an unmeasured variable (UV) is defined, where source nodes of the module (i.e., in-degree = 0) act as common regressors influencing the other nodes via an unmeasured variable (see also clusterScore).
size	Minimum number of nodes per module. By default, a minimum number of 5 nodes is required.

verbose	A logical value. If FALSE (default), the processed graphs will not be plotted to screen, saving execution time (they will be returned in output anyway).
...	Currently ignored.

Value

If HM is not "none" a list of 3 objects is returned:

1. "gHM", subgraph containing hidden modules as an igraph object;
2. "membership", cluster membership vector for each node;
3. "gHC", the list of modules as igraph objects.

If HM is "none", only the cluster membership vector is returned.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Fortunato S, Hric D. Community detection in networks: A user guide (2016). Phys Rep; 659: 1-44. <http://dx.doi.org/10.1016/j.physrep.2016.09.002>

Yu M, Hillebrand A, Tewarie P, Meier J, van Dijk B, Van Mieghem P, Stam CJ (2015). Hierarchical clustering in minimum spanning trees. Chaos 25(2): 023107. <https://doi.org/10.1063/1.4908014>

See Also

[clusterScore](#), [cplot](#)

Examples

```
library(SEMdata)
G <- kegg.pathways$"Amyotrophic lateral sclerosis (ALS)"
# Largest connected component
G <- properties(G)[[1]]
membership <- clusterGraph(graph = G, type = "wtc", HM = "LV", verbose = TRUE)
```

clusterScore

Module scoring

Description

Generate factor scores, principal component scores, or projection scores of latent, composite, and unmeasured variable modules, respectively, and fit them in a SEM with exogenous group effect.

Usage

```
clusterScore(
  graph,
  data,
  group,
  HM = "LV",
  type = "wtc",
  size = 5,
  verbose = FALSE,
  ...
)
```

Arguments

graph	An igraph object.
data	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes.
group	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects.
HM	Hidden model type. For each defined hidden module: (i) if HM = "LV", a latent variable (LV) will be defined as common unknown cause acting on cluster nodes; (ii) if HM = "CV", cluster nodes will be considered as regressors of a latent composite variable (CV); (iii) if HM = "UV", an unmeasured variable (UV) model will be generated for each module, where source nodes (i.e., in-degree = 0) act as common regressors influencing the other nodes via an unmeasured variable.
type	Graph clustering method. If type = "talc", network modules are generated using the tree agglomerative hierarchical clustering method (Yu et al., 2015). Other non-tree clustering methods from igraph package include: "wtc" (default value; walktrap community structure with short random walks), "ebc" (edge betweenness clustering), "fgc" (fast greedy method), "lbc" (label propagation method), "lec" (leading eigenvector method), "loc" (multi-level optimization), "opc" (optimal community structure), "sgc" (springlass statistical mechanics). By default, the "wtc" method is used.
size	Minimum number of nodes per hidden module. By default, a minimum number of 5 nodes is required. By default, HM is set to "LV" (i.e., the latent variable model).
verbose	A logical value. If TRUE, intermediate graphs will be displayed during the execution. In addition, a condensed graph with clusters as nodes will be fitted and showed to screen (see also mergeNodes). By default, verbose = FALSE.
...	Currently ignored.

Value

A list of 3 objects:

1. "fit", hidden module fitting as a lavaan object;

2. "membership", hidden module nodes membership; [clusterGraph](#) function;
3. "dataHM", hidden module data matrix with cluster scores.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx x(x): xxxxx*. <https://doi.org/xxxxx>

See Also

See [clusterGraph](#) and [cplot](#) for graph clustering, and [factor.analysis](#) for factor analysis.

Examples

```
library(SEMdata)
library(huge)

als.npn <- huge.npn(alsData$exprs)

C <- clusterScore(graph = alsData$graph, data = als.npn,
                  group = alsData$group,
                  HM = "LV",
                  type = "wtc",
                  verbose = TRUE)

summary(C$fit)
head(C$dataHM)
table(C$membership)
```

colorGraph

Vertex and edge graph coloring on the base of fitting

Description

Add vertex and edge color attributes to an igraph object, based on a fitting results data.frame generated by [SEMrun](#).

Usage

```
colorGraph(
  est,
  graph,
  group,
  method = "none",
  alpha = 0.05,
```

```

vcolor = c("lightblue", "white", "pink"),
ecolor = c("royalblue3", "gray50", "red2"),
ewidth = c(1, 2),
...
)

```

Arguments

<code>est</code>	A data.frame of estimated parameters and p-values, derived from the <code>fit</code> object returned by SEMrun . As an alternative, the user may provide a "gest" or "dest" data.frame generated by SEMrun .
<code>graph</code>	An igraph object.
<code>group</code>	group A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects.
<code>method</code>	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "none" (i.e., no multiple test correction).
<code>alpha</code>	Significance level for node and edge coloring (by default, $\alpha = 0.05$).
<code>vcolor</code>	A vector of three color names. The first color is given to nodes with P-value < α and $\beta < 0$, the third color is given to nodes with P-value < α and $\beta > 0$, and the second is given to nodes with P-value > α . By default, <code>vcolor = c("lightblue", "white", "pink")</code> .
<code>ecolor</code>	A vector of three color names. The first color is given to edges with P-value < α and regression coefficient < 0, the third color is given to edges with P-value < α and regression coefficient > 0, and the second is given to edges with P-value > α . By default, <code>vcolor = c("blue", "gray50", "red2")</code> .
<code>ewidth</code>	A vector of two values. The first value refers to the basic edge width (i.e., edges with P-value > α), while the second is given to edges with P-value < α . By default <code>ewidth = c(1, 2)</code> .
<code>...</code>	Currently ignored.

Value

An igraph object with vertex and edge color and width attributes.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```

library(SEMdata)

# Model fitting: node perturbation
sem1 <- SEMrun(graph = alsData$graph, data = alsData$exprs,
               group = alsData$group,
               fit = 1)
est1 <- parameterEstimates(sem1$fit)

```

```

# Model fitting: edge perturbation
sem2 <- SEMrun(graph = alsData$graph, data = alsData$exprs,
               group = alsData$group,
               fit = 2)
est20 <- subset(parameterEstimates(sem2$fit), group = 1)[, -c(4, 5)]
est21 <- subset(parameterEstimates(sem2$fit), group = 2)[, -c(4, 5)]

# Graphs
par(mfrow=c(2,2), mar=rep(1,4))
g <- alsData$graph
x <- alsData$group
gplot(colorGraph(est = est1, g, group = x, method = "BH"),
      main = "vertex differences")
gplot(colorGraph(est = sem2$dest, g, group = NULL),
      main = "edge differences")
gplot(colorGraph(est = est20, g, group = NULL),
      main = "edges for group = 0")
gplot(colorGraph(est = est21, g, group = NULL),
      main = "edges for group = 1")

```

corr2graph

Correlation matrix to graph

Description

Convert a correlation matrix to an igraph object.

Usage

```

corr2graph(
  R,
  n,
  graph = NULL,
  type = "marg",
  method = "none",
  alpha = 0.05,
  ...
)

```

Arguments

R	Correlation matrix.
n	Sample size (i.e., the number of subjects).
graph	Reference graph used for filtering the correlation matrix. By default, graph is set to NULL.

type	Graph building method. If type is either "marg" or "cond", marginal or conditional correlation tests will be used, respectively. If type = "mst", input correlations are converted to distances and a minimum spanning tree is generated from the distance matrix, using Prim's algorithm (Prim, 1957). If type = "tmfg", a triangulate maximally graph is generated from the given correlation matrix (Massara et al., 2016).
method	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "none" (i.e., no multiple test correction). See p.adjust for other correction methods.
alpha	Significance level used to compute the correlation threshold. By default, alpha = 0.05.
...	Currently ignored.

Value

An igraph object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

- Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx x(x): xxxxx*. <https://doi.org/xxxxx>
- Massara GP, Di Matteo T and Aste T (2009). Network Filtering for Big Data: Triangulated Maximally Filtered Graph. *Journal of complex Networks*, 5(2): 161–178. <https://doi.org/10.1093/comnet/cnw015>
- Prim RC (1957). Shortest connection networks and some generalizations. *Bell System Technical Journal*, 36(6):1389–1401. <https://doi.org/10.1002/j.1538-7305.1957.tb01515.x>

Examples

```
# Graphs creation
C1 <- corr2graph(R = cor(log(sachs$pkc)), n = nrow(sachs$pkc),
                 type = "marg",
                 method = "BH")
C2 <- corr2graph(R = cor(log(sachs$pkc)), n = nrow(sachs$pkc),
                 type = "cond",
                 method = "BH")
C3 <- corr2graph(R = cor(log(sachs$pkc)), n = nrow(sachs$pkc),
                 type = "mst",
                 method = "BH")
C4 <- corr2graph(R = cor(log(sachs$pkc)), n = nrow(sachs$pkc),
                 type = "tmfg",
                 method = "BH")

# Graphs plots
par(mfrow=c(2,2), mar= rep(2, 4))
plot(C1, layout=layout.circle, main= "marg"); box(col="gray")
```

```
plot(C2, layout=layout.circle, main= "cond"); box(col="gray")
plot(C3, layout=layout.circle, main= "mst"); box(col="gray")
plot(C4, layout=layout.circle, main= "tmfg"); box(col="gray")
```

cplot

Subgraph mapping

Description

Map groups of nodes onto an input graph, based on a membership vector.

Usage

```
cplot(graph, membership, l = layout.auto, map = FALSE, verbose = FALSE, ...)
```

Arguments

graph	An igraph object.
membership	Cluster membership vector for each node.
l	graph layout. One of the igraph layouts. If this argument is ignored, an automatic layout will be applied.
map	A logical value. Visualize cluster mapping over the input graph. If FALSE (default), visualization will be disabled. For large graphs, visualization may take long.
verbose	A logical value. If FALSE (default), the processed graphs will not be plotted to screen, saving execution time (they will be returned in output anyway).
...	Currently ignored.

Value

The list of clusters and cluster mapping as igraph objects.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

See Also

[clusterGraph](#), [clusterScore](#)

Examples

```
library(SEMdata)
G <- kegg.pathways$"Amyotrophic lateral sclerosis (ALS)"
# Largest connected component
G <- properties(G)[[1]]
membership <- clusterGraph(graph = G, type = "wtc")
cplot(G, membership, map = TRUE)

## Not run:
cplot(G, membership, map = FALSE, verbose = TRUE)

## End(Not run)
```

extendGraph	<i>Interactome-assisted graph extension</i>
-------------	---------------------------------------------

Description

Extend an input directed graph, importing new interactions from a second graph. Added interactions will be chosen among those available in a given reference interactome.

Usage

```
extendGraph(g = list(), data, gnet, verbose = FALSE, ...)
```

Arguments

<code>g</code>	A list of two graphs as <code>igraph</code> objects.
<code>data</code>	A matrix with rows corresponding to subjects, and columns to graph nodes.
<code>gnet</code>	External interaction network as an <code>igraph</code> object. Interaction data from this network will be used to integrate additional interaction information inside the graph.
<code>verbose</code>	A logical value. If <code>FALSE</code> (default), the processed graphs will not be plotted to screen, saving execution time (they will be returned anyway).
<code>...</code>	Currently ignored.

Details

This function takes two input graphs: the first is the input causal model (i.e., a directed graph), and the second can be either a directed or undirected graph, providing a set of connections to be checked against the reference network and imported to the first graph. Typically, the second graph is the output of either [SEMdag](#) or [SEMbap](#). In the former we use the new inferred causal structure stored in the `dag.red` object. In the latter, we use the new inferred covariance structure stored in the `guu` object. In both cases, new hidden directed paths and new nodes (i.e., new mediators) can be revealed.

Value

A list of 2 objects:

1. "Ug", the extended graph (union of the input graph and guv);
2. "guv", the directed subgraph added to the input graph.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx x(x): xxxxx*. <https://doi.org/xxxxx>

Examples

```
library(SEMdata)
G <- kegg.pathways$"Steroid biosynthesis"
G <- properties(G)[[1]]

# Extend a graph using new inferred DAG edges

library(SEMdata)
library(huge)
als.npn <- huge.npn(alsData$exprs)

dag <- SEMdag(graph = G, data = als.npn, beta = 0.1)
ext <- extendGraph(list(dag$dag, dag$dag.red), data = als.npn, gnet = kegg)
gplot(ext$Ug)

# Extend a graph using the inferred bow-free path diagram

bap <- SEMbap(graph = G, data = als.npn, gnet = kegg, d = 1, alpha = 0.05)
ext <- extendGraph(list(bap$bap, bap$guu), data = als.npn, gnet = kegg)
gplot(ext$Ug)

# Create a graph from correlation matrix, using KEGG as reference

v <- which(colnames(als.npn) %in% V(G)$name)
selectedData <- als.npn[, v]
G0 <- make_empty_graph(n = ncol(selectedData))
V(G0)$name <- colnames(selectedData)

G1 <- corr2graph(R = cor(selectedData), n = nrow(selectedData),
                type = "tmfg")
ext <- extendGraph(list(G0, G1), data = selectedData, gnet = kegg)
par(mfrow=c(1,2), mar=rep(1,4))
plot(G1, layout = layout.circle)
plot(ext$Ug, layout = layout.circle)
```

extractClusters	<i>Cluster extraction utility</i>
-----------------	-----------------------------------

Description

Extract and fit clusters from an input graph.

Usage

```
extractClusters(
  graph,
  data,
  group = NULL,
  membership = NULL,
  map = FALSE,
  verbose = FALSE,
  ...
)
```

Arguments

graph	Input network as an igraph object.
data	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
group	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. Group specification enables node perturbation testing. By default, group = NULL.
membership	A vector of cluster membership IDs. If NULL, clusters will be automatically generated with clusterGraph using the edge betweenness clustering ("ebc") algorithm.
map	Logical value. If TRUE, the plot of the input graph (coloured by cluster membership) will be generated along with independent module plots. If the input graph is very large, plotting could be computationally intensive (by default, map = FALSE).
verbose	Logical value. If TRUE, a plot will be showed for each cluster.
...	Currently ignored.

Value

List of clusters as igraph objects and fitting results for each cluster as a lavaan object.

Author(s)

Fernando Palluzzi <fernando.palluzzi@gmail.com>

Examples

```

library(SEMdata)
library(huge)

als.npn <- huge.npn(alsData$exprs)

adjdata <- SEMbap(alsData$graph, als.npn)$data

# Clusters creation
clusters <- extractClusters(graph = alsData$graph, data = adjdata)
head(parameterEstimates(clusters$fit$HM1))
head(parameterEstimates(clusters$fit$HM2))
head(parameterEstimates(clusters$fit$HM4))
gplot(clusters$clusters$HM2)

# Map cluster on the input graph
g <- alsData$graph
c <- clusters$clusters$HM2
V(g)$color <- ifelse(V(g)$name %in% V(c)$name, "gold", "white")
gplot(g)

```

gplot

*Graph plotting with renderGraph***Description**

Wrapper for function `renderGraph` of the R package `Rgraphviz`.

Usage

```

gplot(
  graph,
  l = "dot",
  main = "",
  cex.main = 1,
  font.main = 1,
  color.txt = "black",
  fontsize = 16,
  cex = 0.6,
  shape = "circle",
  color = "gray70",
  lty = 1,
  lwd = 1,
  w = "auto",
  h = "auto",
  psize = 80,
  ...
)

```

Arguments

<code>graph</code>	An igraph or graphNEL object.
<code>l</code>	any layout supported by Rgraphviz. It can be one among: "dot" (default), "neato", "circo", "fdp", "osage", "twopi".
<code>main</code>	Plot main title (by default, no title is added).
<code>cex.main</code>	Main title size (default = 1).
<code>font.main</code>	Main title font (default = 1). Available options are: 1 for plain text, 2 for bold, 3 for italics, 4 for bold italics, and 5 for symbol.
<code>color.txt</code>	Node text color (default = "black").
<code>fontsize</code>	Node text size (default = 16).
<code>cex</code>	Another argument to control node text size (default = 0.6).
<code>shape</code>	Node shape (default = "circle").
<code>color</code>	Node border color (default = "gray70").
<code>lty</code>	Node border outline (default = 1). Available options include: 0 for blank, 1 for solid line, 2 for dashed, 3 for dotted, 4 for dotdash, 5 for longdash, and 6 for twodash.
<code>lwd</code>	Node border thickness (default = 1).
<code>w</code>	Manual node width (default = "auto").
<code>h</code>	Manual node height (default = "auto").
<code>psize</code>	Automatic node size (default = 80).
<code>...</code>	Currently ignored.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
gplot(sachs$graph, main = "input graph")

sem <- SEMrun(sachs$graph, sachs$pkc)
gplot(sem$graph, main = "output graph")
```

graph2dag

Convert directed graphs to directed acyclic graphs (DAGs)

Description

Remove cycles and bidirected edges from a directed graph.

Usage

```
graph2dag(graph, data, bap = FALSE, time.limit = Inf, ...)
```

Arguments

<code>graph</code>	A directed graph as an igraph object.
<code>data</code>	A data matrix with subjects as rows and variables as columns.
<code>bap</code>	If TRUE, a bow-free acyclic path (BAP) is returned (default = FALSE).
<code>time.limit</code>	CPU time for the computation, in seconds (defaults = Inf).
<code>...</code>	Currently ignored.

Details

The conversion is performed firstly by removing bidirected edges and then the data matrix is used to compute edge P-values, through marginal correlation testing (see [weightGraph](#), r-to-z method). When a cycle is detected, the edge with highest P-value is removed, breaking the cycle. If the bap argument is TRUE, a BAP is generated merging the output DAG and the bidirected edges from the input graph.

Value

A DAG as an igraph object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
dag <- graph2dag(graph = sachs$graph, data = log(sachs$pkc))
par(mfrow=c(1,2), mar=rep(1, 4))
gplot(sachs$graph, main = "Input graph")
gplot(dag, main = "Output DAG")

## Not run:

# Convert every KEGG pathway into a DAG

# Node count for each pathway
ngs <- unlist(lapply(1:length(kegg.pathways),
                    function(x) vcount(kegg.pathways[[x]])))
head(ngs)

# Remove pathways with less than 5 nodes and more than 500 nodes
Blacklist <- which(ngs < 5 | ngs > 500)
length(Blacklist)
KEGG <- kegg.pathways[-Blacklist]

# DAG conversion
library(SEMdata)
```

```

library(huge)
als.npn <- huge.npn(alsData$exprs)
dag <- lapply(KEGG, function(x) graph2dag(x, data = als.npn))
length(dag)
head(dag)

## End(Not run)

```

graph2lavaan

Graph to lavaan model

Description

Convert an igraph object to a model, specified using lavaan syntax.

Usage

```
graph2lavaan(graph, nodes = V(graph)$name, ...)
```

Arguments

graph	An igraph object.
nodes	Subset of nodes to be included in the model. By default, all the input graph nodes will be included in the output model.
...	Currently ignored.

Value

A model in lavaan syntax.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```

model <- graph2lavaan(sachs$graph)
cat(model, "\n")

```

lavaan2graph	<i>lavaan model to graph</i>
--------------	------------------------------

Description

Convert a model, specified using lavaan syntax, to an igraph object.

Usage

```
lavaan2graph(model, directed = TRUE, psi = TRUE, verbose = FALSE, ...)
```

Arguments

model	Model using lavaan syntax.
directed	Logical value. If TRUE (default), edge directions from the model will be preserved. If FALSE, the resulting graph will be undirected.
psi	Logical value. If TRUE (default) covariances will be converted into bidirected graph edges. If FALSE, covariances will be excluded from the output graph.
verbose	Logical value. If TRUE, a plot of the output graph will be generated. For large graphs, this could significantly increase computation time. If FALSE (default), graph plotting will be disabled.
...	Currently ignored.

Value

An igraph object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
# Writing path diagram in lavaan syntax

model<-'
#path model
Jnk ~ PKA + PKC
P38 ~ PKA + PKC
Akt ~ PKA + PIP3
Erk ~ PKA + Mek
Mek ~ PKA + PKC + Raf
Raf ~ PKA + PKC
PKC ~ PIP2 + Plcg
PIP2 ~ PIP3 + Plcg
Plcg ~ PIP3
#PKA ~ 1
#PIP3 ~ 1
```

```
# (co)variances
# PIP2 ~~ PIP3
'

# Graph with covariances
G0 <- lavaan2graph(model, psi=TRUE)
gplot(G0)
plot(G0, layout=layout.circle)

# Graph without covariances
G1 <- lavaan2graph(model, psi=FALSE)
gplot(G1)
plot(G1, layout=layout.circle)
```

mergeNodes

*Graph nodes merging by a user-defined membership attribute***Description**

Merge groups of graph nodes using a custom membership attribute (e.g., cluster membership).

Usage

```
mergeNodes(graph, membership, HM, ...)
```

Arguments

graph	Network as an igraph object.
membership	Cluster membership. A vector of cluster membership identifiers, where vector names correspond to graph node names. Topological graph clustering can be done using clusterGraph .
HM	Hidden model label. If HM = "LV", a latent variable (LV) will be defined as common unknown cause acting on cluster nodes. If HM = "CV", cluster nodes will be considered as regressors of a latent composite variable (CV). Finally, if HM = "UV", an unmeasured variable (UV) is defined, where source nodes of the module (i.e., in-degree = 0) act as common regressors influencing the other nodes via an unmeasured variable.
...	Currently ignored.

Value

A network with merged nodes as an igraph object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

See Also[clusterGraph](#)**Examples**

```
library(SEMdata)
G <- kegg.pathways$"Amyotrophic lateral sclerosis (ALS)"
# Largest connected component
G <- properties(G)[[1]]
membership <- clusterGraph(graph = G, type = "wtc")
M <- mergeNodes(G, membership, HM = "LV")
gplot(M)
```

modelSearch

*Optimal model search strategies***Description**

Four model search strategies are implemented combining SEMdag(), SEMbap(), and extendGraph() functions. All strategies estimate a DAG through the adjusted (de-correlate) data matrix Z by iteratively update DAG and Z.

Usage

```
modelSearch(
  graph,
  data,
  gnet = NULL,
  d = 2,
  search = "basic",
  beta = 0,
  alpha = 0.05,
  pstop = TRUE,
  limit = NULL,
  verbose = FALSE,
  ...
)
```

Arguments

graph	Input network as an igraph object.
data	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
gnet	Reference directed network used to validate and import nodes and interactions.

d	Maximum allowed geodesic distance for directed or undirected shortest path search. A distance $d = 0$ disables shortest path search (fixed in <code>search = "basic"</code>), while $d = 1$ (fixed in <code>search = "direct"</code>) only search for directed links (i.e., no mediators are allowed). A distance $d > 1$ (defaults $d = 2$ for "outer" and "inner" strategies), will search for shortest paths with at most $d - 1$ mediators between nodes sharing a significant estimated interaction. Connectors are imported from the reference interactome, as specified by the argument <code>gnet</code> . If the edges of the reference interactome are weighted by P-value, as defined by the <code>E(graph)\$pv</code> attribute, the shortest path with the smallest sum of weights will be chosen (e.g., see weightGraph for graph weighting options).
search	Search strategy. Four model search strategies are available: <ul style="list-style-type: none"> • "outer". The estimated DAG is extended using extendGraph to find new indirect paths (i.e., inferred directed connections that may hide new mediators). New interactions and mediators will be searched and imported from the reference network (argument <code>gnet</code>, see above). Both DAG and extended graph complexity can be controlled with $\beta > 0$ and $d > 1$ arguments, respectively (see below). The term "outer" means that new model mediator variables are imported from an external resource (i.e., the reference network). • "inner". This strategy is analogous to the "outer" one, but disables external mediator search. In other words, new indirect paths are generated by adding new interactions of the input model, so that mediators will be nodes already present in the input graph. The reference network is still used to validate new model paths. Also in this case, $\beta > 0$ and $d > 1$ are used. • "direct". The input graph structure is improved through direct (i.e., adjacent) link search, followed by interaction validation and import from the reference network, with no mediators (i.e., $d = 1$). • "basic" (default). While the previous strategies rely on the input graph and the reference network to integrate knowledge to the final model, the "basic" strategy is data-driven. The input graph is needed to define the topological order. The argument <code>gnet</code> is set to <code>NULL</code> (i.e., no reference network is needed) and argument $d = 0$. Model complexity can be still controlled by setting $\beta > 0$.
beta	Numeric value. Minimum absolute LASSO beta coefficient for a new interaction to be retained in the estimated DAG backbone. Lower beta values correspond to more complex DAGs. By default, beta is set to 0 (i.e., maximum complexity).
alpha	Significance level for false discovery rate (FDR) used for either local d-separation tests (below <code>limit</code>) or conditional independence (CI) test (above <code>limit</code>). This argument is used to control data de-correlation. A higher alpha level includes more hidden covariances, thus considering more sources of confounding. If $\alpha = 0$, data de-correlation is disabled. By default, $\alpha = 0.05$.
pstop	A logical value. With the argument <code>pstop = TRUE</code> (default), the algorithm can be halted when the Shipley's global model test P-value > 0.05 . If <code>pstop = FALSE</code> , the model search algorithm stops when no additional edges can be added to the estimated DAG.
limit	An integer value corresponding to the number of missing edges of the extracted

	acyclic graph. Beyond this limit, multicore computation is enabled to reduce the computational burden.
verbose	If TRUE, it shows intermediate graphs during the execution (not recommended for large graphs).
...	Currently ignored.

Details

Search strategies can be ordered by decreasing conservativeness respect to the input graph, as: "direct", "inner", "outer", and "basic". The first three strategies are knowledge-based, since they require an input graph and a reference network, together with data, for knowledge-assisted model improvement. The last one does not require any reference and the output model structure will be completely determined by data. Output model complexity can be limited using arguments `d` and `beta`. While `d` is fixed to 0 or 1 in "basic" or "direct", respectively; we suggest starting with `d = 2` (only one mediator) for the other two strategies. For knowledge-based strategies, we suggest to start with `beta = 0.1`. Then, `beta` can be relaxed ($0 < \beta < 0.1$) to improve model fitting, if needed. Since data-driven models can be complex, we suggest starting from `beta = 0.1` when using the "basic" strategy. The `beta` value can be relaxed until a good model fit is obtained. Argument `alpha` determines the extent of data adjustment: lower `alpha` values for FDR correction correspond to a smaller number of significant confounding factors, hence a weaker correction (default `alpha = 0.05`).

Value

The output model as well as the adjusted dataset are returned as a list of 3 objects:

- "fit", the fitted output model (lavaan object);
- "graph", the output model as an igraph object;
- "data", the adjusted dataset.

Author(s)

Fernando Palluzzi <fernando.palluzzi@gmail.com>

Examples

```
## Not run:

# Comparison among different model estimation strategies

library(SEMdata)
library(huge)

als.npn <- huge.npn(alsData$exprs)

# Models estimation
m1 <- modelSearch(graph = alsData$graph, data = als.npn, gnet = kegg,
  search = "direct", beta = 0, alpha = 0.05)
m2 <- modelSearch(graph = alsData$graph, data = als.npn, gnet = kegg,
  d = 2, search = "inner", beta = 0.05, alpha = 0.05)
```

```

m3 <- modelSearch(graph = alsData$graph, data = als.npn, gnet = kegg,
  d = 2, search = "outer", beta = 0.05, alpha = 0.05)
m4 <- modelSearch(graph = alsData$graph, data = als.npn, gnet = NULL,
  search = "basic", beta = 0.05, alpha = 0.05)

# Graphs
par(mfrow=c(2,2), mar= rep(1,4))
gplot(m1$graph, main = "direct graph")
gplot(m2$graph, main = "inner graph")
gplot(m3$graph, main = "outer graph")
gplot(m4$graph, main = "basic graph")

## End(Not run)

```

orientEdges

Assign edge orientation of an undirected graph

Description

Assign edge orientation of an undirected graph either through a given reference directed interactome or using the adaptively restricted greedy equivalence search (ARGES) method, implemented in the [ges](#) function of the R package `pcalg`.

Usage

```
orientEdges(ug, dg = NULL, data = NULL, ...)
```

Arguments

<code>ug</code>	An undirected graph as an <code>igraph</code> object.
<code>dg</code>	A directed reference graph.
<code>data</code>	A matrix with rows corresponding to subjects, and columns to graph nodes (variables).
<code>...</code>	Currently ignored.

Value

A directed graph as an `igraph` object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Kalisch M, Maechler M, Colombo D, Maathuis MH, Buehlmann P (2012). Causal Inference Using Graphical Models with the R Package pcalg. *Journal of Statistical Software*, 47(11), 1-26. <http://www.jstatsoft.org/v47/i11/>.

Nandy P, Hauser A, and Maathuis MH (2018). High-dimensional consistency in score-based and hybrid structure learning. *The Annals of Statistics*, 46(6A), 3151-3183. <https://doi.org/10.1214/17-AOS1654>.

Examples

```
# Graphs definition
R <- corr2graph(R = cor(log(sachs$pkc)), n = nrow(sachs$pkc), type = "tmfg")
G0 <- sachs$graph
E(G0)$color <- "gray"

# Data-driven orientation
G1 <- orientEdges(ug = R, dg = NULL, data = log(sachs$pkc))
# Reference graph-based orientation
G2 <- orientEdges(ug = R, dg = sachs$graph, data = NULL)

# Graphs plotting
par(mfrow=c(2,2), mar=rep(2,4))
plot(R, layout=layout.circle,
     main = "Input undirected graph (TMFG)")
plot(G1, layout=layout.circle,
     main = "Output directed graph (data-driven)")
plot(G0, layout=layout.circle,
     main = "Reference graph")
plot(G2, layout=layout.circle,
     main = "Output directed graph (reference-based)")
```

pairwiseMatrix

Pairwise plotting of multivariate data

Description

Display a pairwise scatter plot of two datasets for a random selection of variables. If the second dataset is not given, the function displays a histogram with normal curve superposition.

Usage

```
pairwiseMatrix(x, y = NULL, size = nrow(x), r = 4, c = 4, ...)
```

Arguments

x	A matrix or data.frame (n x p) of continuous data.
y	A matrix or data.frame (n x q) of continuous data.
size	number of rows to be sampled (default s = nrow(z)).
r	number of rows of the plot layout (default r = 4).
c	number of columns of the plot layout (default r = 4).
...	Currently ignored.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
adjdata <- SEMbap(sachs$graph, log(sachs$pkc))$data
rawdata <- log(sachs$pkc)
pairwiseMatrix(adjdata, rawdata, size = 1000)
```

pathFinder

Perturbed path search utility

Description

This function uses [SEMace](#) to find significant causal effects between source-sink pairs and [SEMPath](#) to fit them and test their edge perturbation.

Usage

```
pathFinder(
  graph,
  data,
  group = NULL,
  ace = NULL,
  path = "directed",
  method = "none",
  alpha = 0.05,
  verbose = FALSE,
  ...
)
```

Arguments

graph	Input network as an igraph object.
data	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
group	group A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. Group specification enables edge perturbation testing. By default, group = NULL.
ace	A data.frame generated by SEMace . If NULL, SEMace will be automatically run.
path	If path = "directed", all directed paths between the two nodes will be included in the fitted model. If path = "shortest", only shortest paths will be considered.
method	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "none" (i.e., no multiple test correction).
alpha	Significance level for ACE selection (by default, alpha = 0.05).
verbose	Show the significant directed (or shortest) paths inside the input graph.
...	Currently ignored.

Value

A list of 3 objects:

- "paths", list of paths as igraph objects;
- "fit", fitting results for each path as a lavaan object;
- "dfp", a data.frame containing SEM global fitting statistics.

Author(s)

Fernando Palluzzi <fernando.palluzzi@gmail.com>

Examples

```
## Not run:

# Find and evaluate significantly perturbed paths

library(SEMdata)
library(huge)

als.npn <- huge.npn(alsData$exprs)

adjData <- SEMbap(graph = alsData$graph, data = als.npn)$data

ace <- SEMace(graph = alsData$graph, data = adjData,
              group = alsData$group)
ace <- ace[order(ace$pvalue),]
print(ace)

paths <- pathFinder(graph = alsData$graph, data = adjData,
```

```

        group = alsData$group,
        ace = ace)

head(parameterEstimates(paths$fit$P19))
gplot(paths$paths$P19)

path19 <- SEMpath(graph = alsData$graph, data = adjData,
  group = alsData$group,
  from = "7133",
  to = "4747",
  path = "directed",
  verbose = TRUE)

## End(Not run)

```

properties

Graph properties summary and graph decomposition

Description

Produces a summary of network properties and returns graph components (ordered by decreasing size), without self-loops.

Usage

```
properties(graph, data = NULL, ...)
```

Arguments

graph	Input network as an igraph object.
data	An optional data matrix with rows corresponding to subjects, and columns to graph nodes (variables). Nodes will be mapped onto variable names.
...	Currently ignored.

Value

List of graph components, ordered by decreasing size (the first component is the giant one), without self-loops.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
library(SEMdata)
G <- kegg.pathways$"Amyotrophic lateral sclerosis (ALS)"
properties(G)
```

sachs

Sachs multiparameter flow cytometry data and consensus model

Description

Flow cytometry data and causal model from Sachs et al. (2005).

Usage

sachs

Format

"sachs" is a list of 5 objects:

1. "rawdata", a list of 14 data.frames containing raw flow cytometry data (Sachs et al., 2005);
2. "graph", consensus signaling network;
3. "model", consensus model (lavaan syntax);
4. "pkc", data.frame of 1766 samples and 11 variables, containing cd3cd28 (baseline) and pma (PKC activation) data;
5. "group", a binary group vector, where 0 is for cd3cd28 samples (n = 853) and 1 is for pma samples (n = 913).
6. "details", a data.frame containing dataset information.

Source

<https://doi.org/10.1126/science.1105809>

References

Sachs K, Perez O, Pe'er D, Lauffenburger DA, Nolan GP (2019). Causal Protein-Signaling Networks Derived from Multiparameter Single-Cell Data. *Science*, 308(5721): 523-529.

Examples

```
# Dataset content
names(sachs$rawdata)
dim(sachs$pkc)
table(sachs$group)
cat(sachs$model)
gplot(sachs$graph)
```

SEMace

*Compute the Average Causal Effect (ACE) for a given source-sink pair***Description**

Compute total effects as ACEs of source variables X (i.e., incoming connectivity = 0) on sink variables Y (i.e., outgoing connectivity = 0), in a directed graph. The ACE will be estimated as the path coefficient of X (i.e., θ) in the linear equation $Y \sim X + Z$. Z is defined as the adjustment (or conditioning) set of Y over X , applying an "optimal" valid set (O-set), with the smallest asymptotic variance. Standard errors (SE), for each ACE, are computed following the lavaan standard procedure or a bootstrap-based procedure (see [boot](#) for details).

Usage

```
SEMace(
  graph,
  data,
  group = NULL,
  method = "none",
  alpha = 0.05,
  boot = NULL,
  ...
)
```

Arguments

<code>graph</code>	An igraph object.
<code>data</code>	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
<code>group</code>	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. If NULL (default), group influence will not be considered.
<code>method</code>	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "none" (i.e., no multiple test correction).
<code>alpha</code>	Significance level for ACE selection (by default, $\alpha = 0.05$).
<code>boot</code>	The number of bootstrap samplings enabling bootstrap computation of ACE standard errors. If NULL (default), the bootstrap is disabled.
<code>...</code>	Currently ignored.

Value

A data.frame of ACE estimates between network sources and sinks.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Witte J, Henckel L, Maathuis MH, Didelez V (2020). On efficient adjustment in causal graphs. arXiv:2002.06825 [math.ST]. URL: <https://arxiv.org/abs/2002.06825>

Examples

```
# ACE estimation, without group (default)
ace <- SEMace(graph = sachs$graph, data = log(sachs$pkc))
print(ace)

# ACE estimation, with group perturbation and multiple test correction
ace2 <- SEMace(graph = sachs$graph, data = log(sachs$pkc),
               group = sachs$group,
               method = "BH", alpha = 0.05)
print(ace2)
```

SEMbap

Bow-free covariance search and data de-correlation

Description

Search for new bow-free covariances and adjust the data matrix by removing latent sources of confounding encoded in them.

Usage

```
SEMbap(
  graph,
  data,
  method = "BH",
  alpha = 0.05,
  limit = NULL,
  verbose = FALSE,
  ...
)
```

Arguments

graph	An igraph object.
data	A matrix with rows corresponding to subjects, and columns to graph nodes (variables).
method	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "BH" (i.e., Benjamini-Hochberg multiple test correction).

<code>alpha</code>	Significance level for false discovery rate (FDR) used for either local d-separation tests (below <code>limit</code>) or conditional independence (CI) test (above <code>limit</code>). This argument is used to control data de-correlation. A higher alpha level includes more hidden covariances, thus considering more sources of confounding. If <code>alpha = 0</code> , data de-correlation is disabled. By default, <code>alpha = 0.05</code> .
<code>limit</code>	An integer value corresponding to the number of missing edges of the extracted acyclic graph. Beyond this limit, multicore computation is enabled to reduce the computational burden. By default, <code>limit = NULL</code> (i.e., multicore disabled).
<code>verbose</code>	A logical value. If <code>FALSE</code> (default), the processed graphs will not be plotted to screen.
<code>...</code>	Currently ignored.

Details

SEMbap algorithm makes an exhaustive search of all possible missing edges of the mixed acyclic graph (BAP or DAG) via d-separation P-value screening. The d-separation test evaluates if two variables (X, Y) in an acyclic graph are conditionally independent for a given conditioning set Z. The conditioning set Z is represented in a DAG by the union of the parent sets of X and Y (Shiple, 2000) or the minimal set consisting in the smallest conditioning set Z that makes these two variables independent. A new bow-free covariance is added if there is a significant (X, Y) association, after multiple testing correction. The selected covariance between pairs of nodes (X, Y) is interpreted as the effect of a latent variable (LV) acting on both X and Y; i.e., the LV is an unobserved confounder. These LVs are then removed by conditioning them out from the observed data.

Value

A list of 3 igraph objects:

- "bap", the output bow-free acyclic path diagram,
- "guu", the bidirected graph of significant covariances,
- "gLV", the directed graph of latent variables (LV) underlying significant covariances (i.e., the canonical graph, where bidirected $X \leftrightarrow Y$ edges are substituted by directed edges $X \leftarrow LV \rightarrow Y$),
- "data", the adjusted (de-correlated) data matrix.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

- Shiple B (2000). A new inferential test for path models based on DAGs. *Struct. Equ. Modeling*, 7(2): 206-218. https://doi.org/10.1207/S15328007SEM0702_4
- Brito C and Pearl J (2002). A New Identification Condition for Recursive Models With Correlated Errors. *Structural Equation Modeling*, 9(4): 459-474.
- Whittaker J (2009). *Graphical Models in Applied Multivariate Statistics*. ISBN:978-0-470-74366-9; Wiley Publishing.

Examples

```
# Model fitting
sem0 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc))

# BAP estimation
BAP <- SEMbap(graph = sachs$graph, data = log(sachs$pkc), verbose = TRUE)

# Model fitting (node perturbation) with adjusted data
sem1 <- SEMrun(graph = sachs$graph, data = BAP$data, group = sachs$group)
```

SEMdag

*Estimate the optimal DAG from an input graph***Description**

Extract the optimal DAG from an input graph, using the LASSO-based algorithm, implemented in [glmnet](#).

Usage

```
SEMdag(
  graph,
  data,
  gnet = NULL,
  d = 0,
  beta = 0,
  lambdas = NA,
  verbose = FALSE,
  ...
)
```

Arguments

graph	An igraph object.
data	A matrix with rows corresponding to subjects, and columns to graph nodes (variables).
gnet	Reference "global" network as an igraph object. If given, new edges will be added to the final DAG only if present in the reference network.
d	An integer value indicating the maximum length of indirect interactions between pairs of nodes. If $d = 1$, direct interactions between nodes will be searched in the reference interactome (if given). If $d > 1$, indirect interactions of length d or shorter (i.e., with at most $d - 1$ connectors) between bow-free nodes will be searched. Setting $d = 0$, is equivalent to $gnet = NULL$.
beta	Numeric value. Minimum absolute LASSO beta coefficient for a new interaction to be retained in the final model. By default, beta is set to 0.

lambdas	A vector of regularization LASSO lambda values. Cross-validation ($n > 100$) or BIC-based ($n \leq 100$) optimal lambdas for each response variable will be selected. If lambdas is NULL, the glmnet default is enabled. If lambdas is NA (default), the tuning-free scheme is enabled by fixing $\text{lambdas} = \sqrt{\log(p)/n}$, as suggested by Janková and van de Geer (2015). This will both reduce computational time and provide the same result at each run.
verbose	A logical value. If FALSE (default), the processed graphs will not be plotted to screen.
...	Currently ignored.

Details

The optimal DAG is estimated after node topological order, using successive penalized (L1) regressions. If the input graph is not acyclic, a warning message will be raised, and a cycle-breaking algorithm will be applied (see [graph2dag](#) for details). Output DAG edges will be colored in blue, if they were present in the input graph, and in red, if they are new edges generated by LASSO screening.

Value

A list of 3 igraph objects:

1. "dag", the estimated DAG;
2. "dag.red", new estimated connections;
3. "dag.blue", connections preserved from the input graph.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

- Shojaie A, Michailidis G (2010). Penalized likelihood methods for estimation of sparse high-dimensional directed acyclic graphs. *Biometrika*, 97(3): 519-538. <https://doi.org/10.1093/biomet/asq038>
- Tibshirani R, Bien J, Friedman J, Hastie T, Simon N, Taylor J, Tibshirani RJ (2012). Strong rules for discarding predictors in lasso-type problems. *Royal Statistical Society: Series B (Statistical Methodology)*, 74(2): 245-266. <https://doi.org/10.1111/j.1467-9868.2011.01004.x>
- Jana Jankova and Sara van de Geer (2015). Confidence intervals for high-dimensional inverse covariance estimation. *Electronic Journal of Statistics*, 9(1): 1205-1229. <https://doi.org/10.1214/15-EJS1031>

See Also

[modelSearch](#)

Examples

```
# DAG estimation
G <- SEMdag(graph = sachs$graph, data = log(sachs$pkc), beta = 0.05)

# Model fitting
sem <- SEMrun(graph = G$dag, data = log(sachs$pkc), group = sachs$group)

# Graphs
par(mfrow=c(2,2), mar=rep(1,4))
plot(sachs$graph, layout=layout.circle, main="input graph")
plot(G$dag, layout=layout.circle, main = "Output DAG")
plot(G$dag.blue, layout=layout.circle, main = "Inferred old edges")
plot(G$dag.red, layout=layout.circle, main = "Inferred new edges")
```

SEMgsa

SEM-based gene set analysis

Description

Gene Set Analysis (GSA) via self-contained test for group effect on signaling (directed) pathways as SEM, evaluating overall pathway perturbation, perturbation emission from source nodes, and perturbation accumulation on target nodes. Approximate randomization test P-values of specific node and aggregated group effects will be computed. For directed graphs, they include: the sum of group effects adjusted by residual variances (D), the sum of the target nodes perturbation (i.e., group effect) accumulation from source nodes (A), and the sum of the source nodes perturbation emission towards target nodes (E). For undirected graphs, the sum of group effects, adjusted by residual variances (D), will be estimated.

Usage

```
SEMgsa(g = list(), data, group, method = "BH", alpha = 0.05, n_rep = 1000, ...)
```

Arguments

<code>g</code>	A list of pathways to be tested.
<code>data</code>	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
<code>group</code>	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects.
<code>method</code>	Multiple testing correction method. One of the values available in p.adjust . By default, method is set to "BH" (i.e., Benjamini-Hochberg correction).
<code>alpha</code>	Gene set test significance level. Alpha is set to 0.05 by default.
<code>n_rep</code>	Number of randomization replicates (default = 1000).
<code>...</code>	Currently ignored.

Value

A data.frame reporting the following information for each pathway in the input list:

- "N.nodes", pathway size (number of nodes);
- "N.DRNs", number of differential expressed genes within the pathway, after multiple test correction with Benjamini-Hochberg method;
- "pD", significance of the sum of group effects, adjusted by the residual variance;
- "pA", significance of the sum of tagret nodes perturbation (i.e., group effect) accumulation from source nodes;
- "pE", significance of the sum of source nodes perturbation (i.e., group effect) emission towards target nodes;
- "pvalue", Fisher's combined P-value of pD, pA, and pE.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
library(SEMdata)
library(huge)

als.npn <- huge.npn(alsData$exprs)

pathway.names <- c("Amyotrophic lateral sclerosis (ALS)",
                  "Notch signaling pathway")
j <- which(names(kegg.pathways) %in% pathway.names)
pathways <- kegg.pathways[j]
GSA <- SEMgsa(pathways, als.npn, alsData$group, method = "BH", n_rep = 5000)
head(GSA$gsa)

## Not run:

# GSA over the entire KEGG database

# Node count for each pathway
ngs <- unlist(lapply(1:length(kegg.pathways),
                    function(x) vcount(kegg.pathways[[x]])))

# Remove pathways with less than 5 nodes and more than 500 nodes
Blacklist <- which(ngs < 5 | ngs > 500)
KEGG <- kegg.pathways[-Blacklist]

# DAG conversion
dag <- lapply(KEGG, function(x) graph2dag(x, data = als.npn))

# Gene Set Analysis
res <- SEMgsa(KEGG, als.npn, alsData$group, method = "BH", n_rep = 5000)
head(res$gsa)
dim(res$gsa)
```

```

head(res$DRN)
length(res$DRN)

## End(Not run)

```

SEMpath	<i>Search for directed or shortest paths between pairs of source-sink nodes</i>
---------	---------------------------------------------------------------------------------

Description

Find and fit all directed or shortest paths between two source-sink nodes of a graph.

Usage

```
SEMpath(graph, data, group, from, to, path, verbose = FALSE, ...)
```

Arguments

graph	An igraph object.
data	A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes (variables).
group	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. If NULL (default), group influence will not be considered.
from	Starting node name (i.e., source node).
to	Ending node name (i.e., sink node).
path	If path = "directed", all directed paths between the two nodes will be included in the fitted model. If path = "shortest", only shortest paths will be returned.
verbose	Show the directed (or shortest) path between the given source-sink pair inside the input graph.
...	Currently ignored.

Value

A list of four objects: a fitted model object of class `lavaan` ("fit"), aggregated and node-specific group effect estimates and P-values ("gest"), the extracted subnetwork as an igraph object ("graph"), and the input graph with a color attribute mapping the chosen path ("map").

Author(s)

Mario Grassi <mario.grassi@unipv.it>

Examples

```
# Directed path fitting
path <- SEMpath(graph = sachs$graph, data = log(sachs$pkc),
               group = sachs$group,
               from = "PIP3",
               to = "Erk",
               path = "directed")

# Summaries
summary(path$fit)
print(path$gest)

# Graphs
gplot(path$map, main="path from PiP2 to Erk")
plot(path$map, layout=layout.circle, main="path from PiP2 to Erk")
```

SEMrun

Fit a graph as a Structural Equation Model (SEM)

Description

SEMrun converts a (directed, undirected, or mixed) graph to a SEM and fits it. If a binary group variable (i.e., case/control) is present, node-level or edge-level perturbation is evaluated. SEMrun can handle loop-containing models, although multiple links between the same two nodes (including self-loops and mutual interactions) and bows (i.e., a directed and a bidirected link between two nodes) are not allowed.

Usage

```
SEMrun(
  graph,
  data,
  group = NULL,
  fit = 0,
  algo = "lavaan",
  start = NULL,
  limit = 100,
  ...
)
```

Arguments

graph	An igraph object.
data	A matrix with rows corresponding to subjects, and columns to graph nodes (variables).

group	A binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. If NULL (default), group influence will not be considered.
fit	A numeric value indicating the SEM fitting mode. If <code>fit = 0</code> (default), no group effect is considered. If <code>fit = 1</code> , a "common" model is used to evaluate group effects on graph nodes. If <code>fit = 2</code> , a two-group model is used to evaluate group effects on graph edges.
algo	MLE method used for SEM fitting. If <code>algo = "lavaan"</code> (default), the SEM will be fitted using the NLMINB solver from lavaan R package, with standard errors derived from the expected Fisher information matrix. If <code>algo = "ricf"</code> , the model is fitted via residual iterative conditional fitting (RICF; Drton et al. 2009). If <code>algo = "cggm"</code> , model fitting is based on constrained Gaussian Graphical Modeling (GGM) and de-sparsified glasso estimator (Williams, 2020).
start	Starting value of SEM parameters for <code>algo = "lavaan"</code> . If start is NULL (default), the algorithm will determine the starting values. If start is a numeric value, it will be used as a scaling factor for the edge weights in the graph object (graph attribute <code>E(graph)\$weight</code>). For instance, a scaling factor is useful when weights have fixed values (e.g., 1 for activated, -1 for repressed, and 0 for unchanged interaction). Fixed values may compromise model fitting, and scaling them is a safe option to avoid this problem. As a rule of thumb, to our experience, <code>start = 0.1</code> generally performs well with -1, 0, 1 weights.
limit	An integer value corresponding to the network size (i.e., number of nodes). Beyond this limit, the execution under <code>algo = "lavaan"</code> will be redirected to <code>algo = "ricf"</code> , if <code>fit</code> is either 0 or 1, or to <code>algo = "ggm"</code> , if <code>fit = 2</code> . This redirection is necessary to reduce the computational demand of standard error estimation by lavaan. Increasing this number will enforce lavaan execution when <code>algo = "lavaan"</code> .
...	Currently ignored.

Details

SEMrun maps data onto the input graph and converts it into a SEM. Directed connections ($X \rightarrow Y$) are interpreted as direct causal effects, while undirected, mutual, and bidirected connections are converted into model covariances. SEMrun output contains different sets of parameter estimates. Beta coefficients (i.e., direct effects) are estimated from directed interactions and residual covariances (psi coefficients) from bidirected, undirected, or mutual interactions. If a group variable is given, exogenous group effects on nodes (gamma coefficients) will be estimated. This will also lead to the estimation of a set of aggregated group effects, if `algo = "ricf"` (see [SEMgsa](#)). By default, maximum likelihood parameter estimates and P-values for parameter sets are computed by conventional z-test ($= \text{estimate}/\text{SE}$), and fits it through the [lavaan](#) function, via Maximum Likelihood Estimation (estimator = "ML", default estimator in [lavOptions](#)). In case of high dimensionality ($n.\text{variables} \gg n.\text{subjects}$), the covariance matrix could not be semi-definite positive and thus parameter estimates could not be done. If this happens, covariance matrix regularization is enabled using the James-Stein-type shrinkage estimator implemented in the function [pcor.shrink](#) of [corpcor](#) R package. Argument `fit` determines how group influence is evaluated in the model, as absent (`fit = 0`), node perturbation (`fit = 1`), or edge perturbation (`fit = 2`). When `fit = 1`, the group is modeled as an exogenous variable, influencing all the other graph nodes. When `fit = 2`, SEMrun estimates

the differences of the beta and/or psi coefficients (network edges) between groups. This is equivalent to fit a separate model for cases and controls, as opposed to one common model perturbed by the exogenous group effect. Once fitted, the two models are then compared to assess significant edge (i.e., direct effect) differences ($d = \beta_{11} - \beta_{01}$). P-values for parameter sets are computed by z-test ($= d/SE$), through [lavaan](#). As an alternative to standard P-value calculation, SEMrun may use either RICF (randomization P-values) or GGM (de-sparsified P-values) methods. These algorithms are much faster than [lavaan](#) in case of large input graphs.

Value

A list of 5 objects:

1. "fit", SEM fitted lavaan, ricf, or ggmncv object, depending on the MLE method specified by the algo argument;
2. "gest" or "dest", a data.frame of node-specific ("gest") or edge-specific ("dest") group effect estimates and P-values;
3. "model", SEM model as a string if algo is "lavaan", and NULL otherwise;
4. "graph", the induced subgraph of the input network mapped on data variables. Graph edges (i.e., direct effects) with P-value < 0.05 will be highlighted in red ($\beta > 0$) or blue ($\beta < 0$). If a group vector is given, nodes with significant group effect (P-value < 0.05) will be red-shaded ($\beta > 0$) or lightblue-shaded ($\beta < 0$);
5. "dataXY", input data subset mapping graph nodes, plus group at the first column (if no group is specified, this column will take NA values).

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

- Pearl J (1998). Graphs, Causality, and Structural Equation Models. *Sociological Methods & Research*, 27(2):226-284. <https://doi.org/10.1177/0049124198027002004>
- Yves Rosseel (2012). lavaan: An R Package for Structural Equation Modeling. *Journal of Statistical Software*, 48(2): 1-36. URL <http://www.jstatsoft.org/v48/i02/>
- Pepe D, Grassi M (2014). Investigating perturbed pathway modules from gene expression data via Structural Equation Models. *BMC Bioinformatics*, 15: 132. URL <https://doi.org/10.1186/1471-2105-15-132>
- Drton M, Eichler M, Richardson TS (2009). Computing Maximum Likelihood Estimated in Recursive Linear Models with Correlated Errors. *Journal of Machine Learning Research*, 10(Oct): 2329-2348. <http://www.jmlr.org/papers/volume10/drton09a/drton09a.pdf>
- Larson JL and Owen AB (2015). Moment based gene set tests. *BMC Bioinformatics*, 16: 132. <https://doi.org/10.1186/s12859-015-0571-7>
- Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx x(x): xxxxx*. <https://doi.org/xxxxx>
- Williams D (2020). GGMncv: Gaussian Graphical Models with Non-Convex Penalties. R package version 1.1.0. <https://CRAN.R-project.org/package=GGMncv>

See Also

See [fitAncestralGraph](#) for RICF algorithm details, [flip](#) for randomization P-values, and [constrained](#) for constrained GGM, and [inference](#) for de-sparsified P-values.

Examples

```
#### Model fitting (no group effect)

sem0 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc), algo = "lavaan")
summary(sem0$fit)
head(parameterEstimates(sem0$fit))

sem0 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc), algo = "ricf")
summary(sem0$fit)
head(sem0$fit$parameterEstimates)

sem0 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc), algo = "cggm")
summary(sem0$fit)
head(sem0$fit$parameterEstimates)

# Graphs
gplot(sem0$graph, main = "node differences")
plot(sem0$graph, layout = layout.circle, main = "node differences")

#### Model fitting (common model, group effect on nodes)

sem1 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc),
               group = sachs$group)

# Fitting summaries
summary(sem1$fit)
print(sem1$gest)
head(parameterEstimates(sem1$fit))

# Graphs
gplot(sem1$graph, main = "node differences")
plot(sem1$graph, layout = layout.circle, main = "node differences")

#### Two-group model fitting (group effect on edges)

sem2 <- SEMrun(graph = sachs$graph, data = log(sachs$pkc),
               group = sachs$group,
               fit = 2)

# Summaries
summary(sem2$fit) # class lavaan
print(sem2$dest)
head(parameterEstimates(sem2$fit))

# Graphs
```

```

gplot(sem2$graph, main = "Edge differences")
plot(sem2$graph, layout = layout.circle, main = "Edge differences")

## Not run:

# Fitting and visualization of a large graph

library(SEMdata)
library(huge)
library(org.Hs.eg.db)

als.npn <- huge.npn(alsData$exprs)
i <- which(names(kegg.pathways) == "MAPK signaling pathway")
graph <- properties(kegg.pathways[[i]])[[1]]

sem2 <- SEMrun(graph, als.npn, alsData$group, fit = 2, algo = "cggm")

g2 <- sem2$graph
g2 <- g2 - E(g2)[-which(E(g2)$color != "gray50")]
g <- properties(g2)[[1]]

E(g)$color<- E(g2)$color[E(g2) %in% E(g)]
V(g)$label <- mapIds(org.Hs.eg.db, V(g)$name, 'SYMBOL', 'ENTREZID')
gplot(g, l = "fdp")

## End(Not run)

```

Shipley.test

Missing edge testing implied by a graph

Description

Compute all the P-values of the d-separation tests implied by the missing edges of a given acyclic graph (DAG or BAP). The conditioning set Z is represented, in a DAG, by the union of the parent sets of X and Y (Shipley, 2000). In a BAP, Z is the minimal set consisting in the smallest conditioning set Z that makes these two variables independent. The results of every test, in a DAG, is then combined using the Fisher's statistic in an overall test of the fitted model $C = -2 \cdot \sum(\log(\text{P-value}(k)))$, where C is distributed as a chi-squared variate with $df = 2k$, as suggested by Shipley (2000). In a BAP, the P-values resulting from every test are corrected by multiple testing multiplying by the number of missing edges. The smallest one is then considered as the overall test P-value (Shipley, 2002).

Usage

```
Shipley.test(graph, data, limit = NULL, verbose = TRUE, ...)
```

Arguments

<code>graph</code>	A directed graph as an <code>igraph</code> object.
<code>data</code>	A data matrix with subjects as rows and variables as columns.
<code>limit</code>	An integer value corresponding to the number of missing edges of the extracted acyclic graph. Beyond this limit, multicore computation is enabled to reduce the computational burden. By default, <code>limit = NULL</code> (i.e., multicore disabled).
<code>verbose</code>	If TRUE, Shipley's test results will be showed to screen (default = TRUE).
<code>...</code>	Currently ignored.

Value

A list of three objects: (i) the list of all d-separation tests over missing edges in the input DAG or BAP, (ii) the DAG or BAP used to perform the Shipley test, and (iii) the overall Shipley's P-value.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Shipley B (2000). A new inferential test for path models based on DAGs. *Struct. Equ. Modeling*, 7(2): 206-218. https://doi.org/10.1207/S15328007SEM0702_4

Shipley B (2002). Start and Stop Rules for Exploratory Path Analysis. *Structural Equation Modeling A Multidisciplinary Journal*, 9(4): 554-561. https://doi.org/10.1207/S15328007SEM0904_5

Examples

```
library(SEMdata)
library(huge)
als.npn <- huge.npn(alsData$exprs)

sem <- SEMrun(alsData$graph, als.npn)
C.test0 <- Shipley.test(sem$graph, als.npn)
```

summary.GGM

GGM model summary

Description

Generate a summary for a constrained Gaussian Graphical Model (GGM) and show it to standard output.

Usage

```
## S3 method for class 'GGM'
summary(object, ...)
```

Arguments

object	A constrained GGM fitted model object.
...	Currently ignored.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

See Also

[SEMrun](#).

Examples

```
sem1 <- SEMrun(sachs$graph, log(sachs$pkc), sachs$group, algo = "cggm")
summary(sem1$fit)
```

summary.RICF

RICF model summary

Description

Generate a summary for a RICF model and show it to standard output.

Usage

```
## S3 method for class 'RICF'
summary(object, ...)
```

Arguments

object	A RICF fitted model object.
...	Currently ignored.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

See Also

[SEMrun](#).

Examples

```
sem1 <- SEMrun(sachs$graph, log(sachs$pkc), sachs$group, algo = "ricf")
summary(sem1$fit)
```

Description

Add data-driven edge and node weights to the input graph.

Usage

```
weightGraph(
  graph,
  data,
  group = NULL,
  method = "r2z",
  seed = "none",
  limit = NULL,
  ...
)
```

Arguments

- | | |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| graph | An igraph object. |
| data | A matrix or data.frame. Rows correspond to subjects, and columns to graph nodes. |
| group | Binary vector. This vector must be as long as the number of subjects. Each vector element must be 1 for cases and 0 for control subjects. By default, group = NULL. |
| method | <p>Edge weighting method. It can be one of the following:</p> <ol style="list-style-type: none"> 1. "r2z". Weight edges of a graph using Fisher's r-to-z transform to test the group difference between correlation coefficients of pairs of interacting nodes (Fisher, 1915). 2. "sem". Edge weights are defined by a SEM model that implies testing the group effect simultaneously on the j-th source node and the k-th sink node. A new parameter w is defined as the weighted sum of the total effect of the group on source and sink nodes, adjusted by node degree centrality, and edge weights correspond to the sign and P-value of the z-test = $w/SE(w)$. Not available if group == NULL. 3. "cov". Edge weights are defined by a new parameter w combining the group effect on the source node (mean group difference, adjusted by source degree centrality), the sink node (mean group difference, adjusted by sink degree centrality), and the source-sink interaction (correlation difference). Edge weights correspond to the sign and P-value of the z-test = $w/SE(w)$ of the combined difference of the group over source node, sink node, and their connection. Not available if group == NULL. |

seed	<p>A vector of three cutoffs. By default, seed = "none" and seed calculation is disabled. Suggested cutoff values are seed = c(0.05, 0.5, 0.5). If these cutoffs are defined, seed search is enabled. Nodes can be labeled as either seeds (node weight = 1) or non-seeds (node weight = 0), according to three alternative importance criteria: perturbed group effect, prototype clustering, and closeness node index. The first cutoff is the significance level of the group effect over graph nodes. The second is a threshold corresponding to the prototype clustering distance measure (= 1 - abs(correlation)) cutoff. The third one is the closeness percentile. Nodes having closeness greater than the q-th percentile are labeled as seeds. If the seed argument is enabled, the output graph will have three new binary (1: seed, 0: not-seed) vertex attributes:</p> <ol style="list-style-type: none"> 1. "pvlm", P-value of the simple linear regression $y \sim x$ (i.e., node ~ group); 2. "proto", prototype seeds derived from <code>protoclust</code>; 3. "qi", nodes with closeness greater than the q-th percentile.
limit	An integer value corresponding to the number of graph edges. Beyond this limit, multicore computation is enabled to reduce the computational burden. By default, limit = NULL (i.e., multicore disabled).
...	Currently ignored.

Value

A weighted graph, as an igraph object.

Author(s)

Mario Grassi <mario.grassi@unipv.it>

References

Grassi M, Palluzzi F (2021). SEMgraph: An R Package for Causal Network Analysis of High-Throughput Data with Structural Equation Models. *xxxxx x(x): xxxxx*. <https://doi.org/xxxxx>

Examples

```
# Graph weighting
G <- weightGraph(graph = sachs$graph,
  data = log(sachs$pkc),
  group = sachs$group,
  method = "r2z",
  seed = c(0.05, 0.5, 0.5))

# New edge attributes
E(G)$pv
E(G)$zsign

# New nodes attributes (1: seed, 0: non-seed)
V(G)$pvlm; table(V(G)$pvlm)
V(G)$proto; table(V(G)$proto)
V(G)$qi; table(V(G)$qi)
```



```
# Reduced graph (using highest closeness nodes)
R <- induced_subgraph(G, vids = V(G)$name[V(G)$qi == 1])
R <- properties(R)[[1]]
```

Index

activeModule, [2](#)
ancestors (ancestry), [5](#)
ancestry, [5](#)

boot, [32](#)

clusterGraph, [6](#), [9](#), [13](#), [16](#), [22](#), [23](#)
clusterScore, [6](#), [7](#), [13](#)
colorGraph, [9](#)
constrained, [43](#)
corr2graph, [11](#)
cplot, [7](#), [9](#), [13](#)

descendants (ancestry), [5](#)

extendGraph, [14](#), [24](#)
extractClusters, [16](#)

factor.analysis, [9](#)
fitAncestralGraph, [43](#)
flip, [43](#)

ges, [26](#)
glmnet, [35](#), [36](#)
gplot, [17](#)
graph2dag, [18](#), [36](#)
graph2lavaan, [20](#)

igraph, [3](#), [13](#)
inference, [43](#)

lavaan, [39](#), [41](#), [42](#)
lavaan2graph, [21](#)
lavOptions, [41](#)

mergeNodes, [8](#), [22](#)
modelSearch, [23](#), [36](#)

orientEdges, [26](#)

p.adjust, [10](#), [12](#), [29](#), [32](#), [33](#), [37](#)
pairwiseMatrix, [27](#)

parents (ancestry), [5](#)
pathFinder, [28](#)
pcor.shrink, [41](#)
properties, [30](#)
protoclust, [48](#)

sachs, [31](#)
SEMace, [28](#), [29](#), [32](#)
SEMbap, [14](#), [33](#)
SEMdag, [14](#), [35](#)
SEMgsa, [37](#), [41](#)
SEMrun, [28](#), [39](#)
SEMrun, [9](#), [10](#), [40](#), [46](#)
Shipley.test, [44](#)
siblings (ancestry), [5](#)
summary.GGM, [45](#)
summary.RICF, [46](#)

weightGraph, [3](#), [19](#), [24](#), [47](#)