Cluster Analysis: Identifying Parkinson's Disease Subtypes

Jesse Mu

Wednesday, June 10

1 Preprocessing

1.1 Dataset Description

951 subjects, 145 metrics, collected 15-4-2012. From Pablo Martinez Martín. 170 subjects with missing values (brought down to 781); these were removed automatically, even if the missing values were not included in the selected features below. This will need to be changed later on, by keeping those removed that still have all selected features and perhaps with some compensation for missing values.

1.2 Selected Features

Combination of non-motor scale (NMS) symptoms and standard motor symptoms.

Name	Type	Format	Description
nms_d1	byte	%8.0g	cardiovascular
nms_d2	byte	%8.0g	sleep/fatigue
$\mathrm{nms}_{-}\mathrm{d}3$	byte	%8.0g	mood/cognition
nms_d4	byte	%8.0g	percep/hallucinations
$\mathrm{nms}_{ ext{-}}\mathrm{d}5$	byte	%8.0g	attention/memory
$\mathrm{nms_d6}$	byte	%8.0g	gastrointestinal
$\mathrm{nms}_{ ext{-}}\mathrm{d}7$	byte	%8.0g	urinary
nms_d8	byte	%8.0g	sexual function
$\mathrm{nms}_{-}\mathrm{d}9$	byte	%8.0g	miscellaneous
tremor	float	%9.0g	tremor
bradykin	float	%9.0g	bradykinesia ¹
rigidity	float	%9.0g	rigidity
axial	float	%9.0g	$ axial^2 $
pigd	float	%9.0g	postural instability and gait difficulty

Table 1: Selected Features and Details

Name	$\mid \mu \mid$	σ	min-max
nms_d1	1.76	3.32	0-24
nms_d2	8.71	8.76	0-48
$nms_{-}d3$	8.70	11.83	0-60
nms_d4	1.65	3.94	0-33
nms_d5	5.22	7.44	0-36
nms_d6	5.67	6.92	0-36
$\mathrm{nms}_{-}\mathrm{d}7$	8.02	9.09	0-36
nms_d8	3.57	5.97	0-24
nms_d9	6.99	7.74	0-48
tremor	2.59	2.63	0-12
bradykin	2.49	1.39	0-6
rigidity	2.34	1.36	0-6
axial	3.28	2.75	0-12
pigd	3.36	2.77	0-12

Table 2: Descriptive Statistics

1.3 Dimensionality Reduction: PCA

May not be useful? If we're trying to identify *clinically* relevant features, merging them may not be a good idea.

Figure 1 shows scree test elbow occurs around 2 or 3. Also, eigenvalues 1 and 2 > 1, while 3 is around .9

$\mathbf{2}$ k-means

2.1 Identifying optimal number of clusters

2.1.1 WSS Error Scree Test

Figure 2 shows no optimal elbow in scree test! Maybe 2-3?

2.1.2 Gap Statistic

Optimal cluster is the local maximum of the gap statistic, but it appears to be consistently increasing in Figure 3.

2.1.3 Average Silhouette Width

Figure 4 shows average silhouette width as being consistently under 0.25 for all clusters, implying the data is not well structured.

¹Impaired ability to adjust the body's position.

²Issues affecting the middle of the body.




Figure 1: Scree test: eigenvalues by factor

2.2 Cluster statistics

k	$\mid n \mid$	Within SS	sum(Within SS)
2	201/580	4248.585/4132.434	8381.019
3	420/231/130	2618.368/1973.82/3076.542	7668.73
4	61/372/145/203	1481.25/1845.389/2147.988/1609.555	7084.183

Table 3: Cluster statistics

2.3 Silhouette plots

Available in Figures 5, 6, and 7. Note: constructed with standardized z-score data.




Figure 2: Scree test: WSS error by cluster size

k	$\mathbb{C}\mathrm{P}^3$	CV Xerror ⁴	Root Feature	Root Error	Figure
2	0.0348	0.134	$axial \ge 0.44$	0.257	Figure 8
3	0.0100	0.194	bradykin < 0.0041	0.462	Figure 9
4	0.0100	0.248	bradykin < 0.0041	0.523	Figure 10

Table 4: k-kmeans decision trees statistics

2.4 Decision trees based on clusters

2.5 Interpretation of Clusters

2.5.1 Cluster summaries

Available in Figures 11, 12, and 13. Error bar is standard error.

2.5.2 Interpretation

k=2 seems too basic. Cluster is organized solely by severity - all symptoms, including motor and nonmotor, are higher in severity in cluster 1, and lower in cluster 2. Quite consistently, groups in cluster 1 are generally of slightly higher age and pd duration.

³Complexity Parameter

⁴10-fold cross validation




Figure 3: Gap statistic by cluster size

k=3 seems like a further development of k=2, where clusters are simply organized by linearly increasing severity.

k = 4 is where it gets interesting.

3 Affinity Propagation

3.1 Clustering

Package apcluster was used. Distance matrix was the negative euclidean squared distance (r=2).

AP with input preferences minimized (q = 0) resulted in 8 clusters. With the standard median input preferences (q = 0.5), algorithm failed to converge with default parameters. Even setting damping factor to 0.98, maximum iterations to 10000, and convergence iterations to 1000 failed to converge. Might need to try a longer run.

However, given that input preferences control how many clusters are found, I don't think it's very useful to have some dozen clusters running around.

3.1.1 Silhouette Plots

Silhouette plot in Figure 14 looks pretty weak, really. Tons of overlap between the clusters.




Figure 4: Average silhouette width by cluster size

3.2 Interpretation

Cluster sizes are available in Table 5
Boxplot summary of clusters available in Figure 15. **Discussion forthcoming.**

4 Biclustering

Used BCBimax clustering algorithm. Clusters seem quite sparse.


5 Subspace clustering

6 Bayesian Networks

Cluster	Size
1	54
2	68
3	25
4	259
5	102
6	68
7	185
8	20

Table 5: AP Cluster Sizes


Silhouette plot k = 4



Component 1
These two components explain 48.1 % of the point variability.

Figure 5: k-means cluster silhouette plot, k=2


Silhouette plot k = 4



Component 1
These two components explain 48.1 % of the point variability.

Figure 6: k-means cluster silhouette plot, k=3

Silhouette plot k = 4



Component 1
These two components explain 48.1 % of the point variability.

Figure 7: k-means cluster silhouette plot, k=4

UNSCALED Pruned Tree, 2 clusters




Figure 8: Decision Tree from k-means clustering, 2 clusters

UNSCALED Pruned Tree, 3 clusters




Figure 9: Decision Tree from k-means clustering, 3 clusters

UNSCALED Pruned Tree, 4 clusters




Figure 10: Decision Tree from k-means clustering, 4 clusters




Figure 11: Cluster Summaries, k=2




Figure 12: Cluster Summaries, k=3





Figure 13: Cluster Summaries, k=4

AP Silhouette Plot k = 8



Component 1
These two components explain 48.1 % of the point variability.

Figure 14: AP silhouette plot, k = 8




Figure 15: AP Boxplot Summaries




Figure 16: Biclustering N = 16




Figure 17: Bubbleplot N=16