

Introduction to Flow-based Generative Models

Pascal Mignon

pmignon@student.ethz.ch

13/04/2022





Agenda

- Recap: Generative Models
- Flow-based Generative Models
- RealNVP & Glow: illustrations of Flow-based models
- Related works
- Q&A

Recap: Generative Models

Recap: Generative models

Types of Generative Models

	Description	Architecture
Generative adversarial networks	Minimize the discriminator error loss	
Variational autoencoders	Maximize the Evidence Lower Bound (ELBO)	
Flow-based generative models		

Flow-based Generative Models


Flow-based Generative Models

Normalizing flows - overall idea


Inference

$$x \sim \hat{p}_X$$
$$z = f(x)$$

Data space \mathcal{X}





Latent space \mathcal{Z}




Generation

$$z \sim p_Z$$
$$x = f^{-1}(z)$$



Flow-based Generative Models

Normalizing flows - overall idea




Flow-based Generative Models

Normalizing flows - requirements

- ❑ **f must be reversible, ie. bijective**
- ❑ **f jacobian must be easily computable**

$$\mathbf{z}_K = f_K \circ \dots \circ f_2 \circ f_1(\mathbf{z}_0)$$

$$\ln p_K(\mathbf{z}_K) = \ln p_0(\mathbf{z}_0) - \sum_{k=1}^K \ln \left| \det \frac{\partial f_k}{\partial \mathbf{z}_{k-1}} \right|$$



Flow-based Generative Models


Normalizing flows - summary

Flow-based generative models

Description


Reversible - Using explicitly log-likelihood to train the generative model

Architecture



$$\mathbf{z}_K = f_K \circ \dots \circ f_2 \circ f_1(\mathbf{z}_0)$$
$$\ln p_K(\mathbf{z}_K) = \ln p_0(\mathbf{z}_0) - \sum_{k=1}^K \ln \left| \det \frac{\partial f_k}{\partial \mathbf{z}_{k-1}} \right|$$

$$\mathcal{L}(\mathcal{D}) = -\frac{1}{|\mathcal{D}|} \sum_{\mathbf{x} \in \mathcal{D}} \log p(\mathbf{x})$$



RealNVP & Glow: illustrations of Flow-based models

Illustration of Flow-based models

RealNVP, 2016

DENSITY ESTIMATION USING REAL NVP

Laurent Dinh*

Montreal Institute for Learning Algorithms
University of Montreal
Montreal, QC H3T1J4

Jascha Sohl-Dickstein
Google Brain

Samy Bengio
Google Brain

Illustration of Flow-based models

RealNVP, 2016, objective

Objective: create a reversible flow from input space x to latent space z

Constraints: intermediate functions must be reversible and the jacobian easily computable






Illustration of Flow-based models

RealNVP, 2016, proposed solution: coupling layers



(a) Forward propagation




(b) Inverse propagation

$$\begin{cases} y_{1:d} &= x_{1:d} \\ y_{d+1:D} &= x_{d+1:D} \odot \exp(s(x_{1:d})) + t(x_{1:d}) \end{cases}$$


$$\Leftrightarrow \begin{cases} x_{1:d} &= y_{1:d} \\ x_{d+1:D} &= (y_{d+1:D} - t(y_{1:d})) \odot \exp(-s(y_{1:d})), \end{cases}$$

Illustration of Flow-based models

RealNVP, 2016, proposed solution: coupling layers



(a) Forward propagation



(b) Inverse propagation


$$\frac{\partial y}{\partial x^T} = \begin{bmatrix} \mathbb{I}_d & 0 \\ \frac{\partial y_{d+1:D}}{\partial x_{1:d}^T} & \text{diag}(\exp[s(x_{1:d})]) \end{bmatrix}$$

$$\begin{cases} y_{1:d} &= x_{1:d} \\ y_{d+1:D} &= x_{d+1:D} \odot \exp(s(x_{1:d})) + t(x_{1:d}) \end{cases}$$


$$\Leftrightarrow \begin{cases} x_{1:d} &= y_{1:d} \\ x_{d+1:D} &= (y_{d+1:D} - t(y_{1:d})) \odot \exp(-s(y_{1:d})), \end{cases}$$

Illustration of Flow-based models


RealNVP, 2016, proposed solution: coupling layers with permutation



(a) Forward propagation




(b) Inverse propagation



(a) In this alternating pattern, units which remain identical in one transformation are modified in the next.

Illustration of Flow-based models

RealNVP, 2016, proposed solution: multi-scale architecture



(b) Multi-scale architecture (Dinh et al., 2016).

Illustration of Flow-based models

Glow, 2018

Glow: Generative Flow with Invertible 1×1 Convolutions

Diederik P. Kingma*, **Prafulla Dhariwal***
OpenAI, San Francisco

Illustration of Flow-based models

Glow, 2018, objective

Objective: create a reversible flow from input space x to latent space z

Constraints: intermediate functions must be reversible and the jacobian easily computable




Illustration of Flow-based models


Glow, 2018, Architecture

$$\mathbf{x} \xleftrightarrow{f_1} \mathbf{h}_1 \xleftrightarrow{f_2} \mathbf{h}_2 \cdots \xleftrightarrow{f_K} \mathbf{z}$$


$$\mathbf{z} = \mathbf{f}_\theta(\mathbf{x}) = \mathbf{g}_\theta^{-1}(\mathbf{x})$$

$$\mathbf{z} \sim p_\theta(\mathbf{z})$$

$$\mathcal{L}(\mathcal{D}) = \frac{1}{N} \sum_{i=1}^N -\log p_\theta(\mathbf{x}^{(i)})$$




(a) One step of our flow.



(b) Multi-scale architecture (Dinh et al., 2016).

Illustration of Flow-based models

Glow, 2018, Actnorm (activation normalization) layer




Description	Function	Reverse Function	Log-determinant
Actnorm. See Section 3.1.	$\forall i, j : \mathbf{y}_{i,j} = \mathbf{s} \odot \mathbf{x}_{i,j} + \mathbf{b}$	$\forall i, j : \mathbf{x}_{i,j} = (\mathbf{y}_{i,j} - \mathbf{b}) / \mathbf{s}$	$h \cdot w \cdot \text{sum}(\log \mathbf{s})$

- Affine transformation for batch normalization
- Parameters are chosen to have as output 0 mean and 1 standard deviation

Illustration of Flow-based models

Glow, 2018, 1x1 convolutional layer




Description	Function	Reverse Function	Log-determinant
Invertible 1×1 convolution. $\mathbf{W} : [c \times c]$. See Section 3.2.	$\forall i, j : \mathbf{y}_{i,j} = \mathbf{W} \mathbf{x}_{i,j}$	$\forall i, j : \mathbf{x}_{i,j} = \mathbf{W}^{-1} \mathbf{y}_{i,j}$	$h \cdot w \cdot \log \det(\mathbf{W}) $ or $h \cdot w \cdot \text{sum}(\log \mathbf{s})$ (see eq. (10))


- 1x1 convolution for permutation operation
- Weights are initialized as a rotation matrix
- Computation time can be optimized by choosing weights in its LU matrix decomposition

Illustration of Flow-based models


Glow, 2018, Affine coupling layer



Description	Function	Reverse Function	Log-determinant
Affine coupling layer. See Section 3.3 and (Dinh et al., 2014)	$\mathbf{x}_a, \mathbf{x}_b = \text{split}(\mathbf{x})$ $(\log \mathbf{s}, \mathbf{t}) = \text{NN}(\mathbf{x}_b)$ $\mathbf{s} = \exp(\log \mathbf{s})$ $\mathbf{y}_a = \mathbf{s} \odot \mathbf{x}_a + \mathbf{t}$ $\mathbf{y}_b = \mathbf{x}_b$ $\mathbf{y} = \text{concat}(\mathbf{y}_a, \mathbf{y}_b)$	$\mathbf{y}_a, \mathbf{y}_b = \text{split}(\mathbf{y})$ $(\log \mathbf{s}, \mathbf{t}) = \text{NN}(\mathbf{y}_b)$ $\mathbf{s} = \exp(\log \mathbf{s})$ $\mathbf{x}_a = (\mathbf{y}_a - \mathbf{t}) / \mathbf{s}$ $\mathbf{x}_b = \mathbf{y}_b$ $\mathbf{x} = \text{concat}(\mathbf{x}_a, \mathbf{x}_b)$	$\text{sum}(\log(\mathbf{s}))$



(a) Forward propagation



(b) Inverse propagation

Illustration of Flow-based models

RealNVP, 2016 vs. Glow, 2018, Comparative results

Table 2: Best results in bits per dimension of our model compared to RealNVP.

Model	CIFAR-10	ImageNet 32x32	ImageNet 64x64	LSUN (bedroom)	LSUN (tower)	LSUN (church outdoor)
RealNVP	3.49	4.28	3.98	2.72	2.81	3.08
Glow	3.35	4.09	3.81	2.38	2.46	2.67





Illustration of Flow-based models

RealNVP, 2016 vs. Glow, 2018, Comparative results

Table 2: Best results in bits per dimension of our model compared to RealNVP.

Model	CIFAR-10	ImageNet 32x32	ImageNet 64x64	LSUN (bedroom)	LSUN (tower)	LSUN (church outdoor)
RealNVP	3.49	4.28	3.98	2.72	2.81	3.08
Glow	3.35	4.09	3.81	2.38	2.46	2.67



(b) Affine coupling.

Conclusion

Illustration of Flow-based models

Strengths and weaknesses of flow-based models

Strengths

- **Reversible**, ie. direct transformation between input space and latent space
- Direct use of **log-likelihood**
- Easily **parallelizable**

Weaknesses

- Important **computation** time
- Not easy to **compute** log-likelihood

Illustration of Flow-based models

Glow, 2018 - Interesting experiments







Figure 6: Manipulation of attributes of a face. Each row is made by interpolating the latent code of an image along a vector corresponding to the attribute, with the middle image being the original image

Recap: Generative models

Types of Generative Models

	Description	Architecture
Generative adversarial networks	Minimize the discriminator error loss	
Variational autoencoders	Maximize the Evidence Lower Bound (ELBO)	
Flow-based generative models	Reversible - Using explicitly log-likelihood to train the generative model	

Related Works

Related works

Other related or relevant topics

- Other models with Normalizing Flows
 - [NICE 2014](#)
- Models based on Autoregressive Flows
 - [PixelRNN 2016](#)
- Divergence-based Generative Models
 - [Moser Flow: Divergence based generative models on manifolds 2021](#)

Q&A

Additional content

Change of variable formula

Change of Variables: Z and X be random variables which are related by a mapping $f : \mathbb{R}^n \rightarrow \mathbb{R}^n$ such that $X = f(Z)$ and $Z = f^{-1}(X)$. Then

$$p_X(\mathbb{x}) = p_Z(f^{-1}(\mathbb{x})) \left| \det \left(\frac{\partial f^{-1}(\mathbb{x})}{\partial \mathbb{x}} \right) \right|$$

Jacobian Matrix

$$\mathbf{J} = \begin{bmatrix} \frac{\partial f_1}{\partial x_1} & \cdots & \frac{\partial f_1}{\partial x_n} \\ \vdots & \ddots & \vdots \\ \frac{\partial f_m}{\partial x_1} & \cdots & \frac{\partial f_m}{\partial x_n} \end{bmatrix} \quad \mathbf{J}_{ij} = \frac{\partial f_i}{\partial x_j}$$

Illustration of Flow-based models

Glow, 2018 - Interesting experiments




Figure 9: Samples from shallow model on left vs deep model on right. Shallow model has $L = 4$ levels, while deep model has $L = 6$ levels

Illustration of Flow-based models

Glow, 2018 - Interesting experiments






Figure 8: Effect of change of temperature. From left to right, samples obtained at temperatures 0, 0.25, 0.6, 0.7, 0.8, 0.9, 1.0

Illustration of Flow-based models

RealNVP, 2016 vs. Glow, 2018, Improvements of 1x1 convolution



(a) Additive coupling.



(b) Affine coupling.