## **Bibliography**

- [1] API Recommended Practice 582, Welding Guidelines for the Chemical, Oil and Gas Industries
- [2] API Recommended Practice 651, Cathodic Protection of Aboveground Petroleum Storage Tanks
- [3] API Recommended Practice 652, Lining of Aboveground Petroleum Storage Tank Bottoms
- [4] API Publication 937, Evaluation of the Design Criteria for Storage Tanks with Frangible Roofs
- [5] API Publication 937-A, Study to Establish Relations for the Relative Strength of API 650 Cone Roof, Roof-to-Shell, and Shell-to-Bottom Joints
- [6] API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents
- [7] API Publication 2026, Safe Access/Egress Involving Floating Roofs of Storage Tanks in Petroleum Service
- [8] API Recommended Practice 2350, Overfill Protection for Storage Tanks in Petroleum Facilities
- [9] AISI T-192 <sup>29</sup>, Steel Plate Engineering Data, Volume 1 & 2 (Revised Edition 2011). Published jointly by the Steel Market Development Institute and Steel Plate Fabricators Association.
- [10] ASTM D3453, Flexible Cellular Materials—Urethane for Furniture and Automotive Cushioning, Bedding, and Similar Applications
- [11] PIP STF05501 30, Fixed Ladders and Cages Details
- [12] PIP STF05520, Pipe Railing for Walking and Working Surface Details
- [13] PIP STF05521, Details for Angle Railings for Walking and Working Surfaces
- [14] U.S. EPA <sup>31</sup>, 40 CFR Part 63, National Emission Standards for Hazardous Air Pollutants for Source Categories (HON)
- [15] Subpart F, National Emission Standards for Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry
- [16] Subpart G, National Emission Standards for Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry for Process Vents, Storage Vessels, Transfer Operators, and Waste Water
- [17] Subpart H, National Emission Standards for Organic Hazardous Air Pollutants for Equipment Leaks
- [18] U.S. EPA, 40 CFR Part 68, Chemical Accident Prevention Provisions Subpart G, Risk Management Plan (RMP)
- [19] U.S. EPA, 40 CFR Part 264, Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities (RCRA) Subpart J, Tank Systems

<sup>&</sup>lt;sup>29</sup> American Iron and Steel Institute, 1540 Connecticut Avenue, NW, Suite 705, Washington, DC 20036, www.steel.org.

<sup>&</sup>lt;sup>30</sup> Process Industry Practices, 3925 West Braker Lane (R4500), Austin, Texas 78759, www.pip.org.

<sup>&</sup>lt;sup>31</sup> U.S. Environmental Protection Agency, Ariel Rios Building, 1200 Pennsylvania Avenue, Washington, DC 20460, www.epa.gov.

Y-6 API STANDARD 650

- [20] U.S. OSHA <sup>32</sup>, 29 CFR 1910, Subpart D: Walking-Working Surfaces
- [21] U.S. OSHA, 29 CFR 1910.119, Process Safety Management of Highly Hazardous Chemicals
- [22] WRC, Bulletin 297 <sup>33</sup>, Local Stresses in Cylindrical Shells Due to External Loadings—Supplement to WRC Bulletin No. 107
- [23] Hershfield, D. M. 1961, "Rainfall Frequency Atlas of the United States for Durations from 30 Minutes to 24 Hours and Return Periods from 1 to 100 Years," Technical Paper No. 40, Weather Bureau, U.S. Department of Commerce, Washington, D.C., 115 pp.

<sup>&</sup>lt;sup>32</sup> U.S. Department of Labor, Occupational Safety and Health Administration, 200 Constitution Avenue, NW, Washington DC, 20210, www.osha.gov.

<sup>&</sup>lt;sup>33</sup> The Welding Research Council, 3 Park Avenue, 27th Floor, New York, New York 10016-5902, www.forengineers.org.