



Image Sensor	1920 × 1080 Resolution	250 Hz Native Frame Rate	N/A Latency
---------------------	---------------------------	-----------------------------	----------------

Global Shutter	Default Speed 0.25 ms	Minimum Speed 0.01 ms	Maximum Speed 1.8 ms at 500 fps
-----------------------	--------------------------	--------------------------	------------------------------------

Image Processing	On-board H.264 video compression	Compression Options Constant Bit Rate (CBR) Variable Bit Rate (VBR)
-------------------------	-------------------------------------	--

Connections	GigE data port	Ethernet camera sync	PoE power
--------------------	----------------	----------------------	-----------

Lens & Filter	Stock Lens None	Filter Switcher Included	Optional Lenses 75° × 47° FOV, 47° × 27° FOV
--------------------------	--------------------	-----------------------------	--

Size & Weight	Width 4.45 inches (11.3 cm)
--------------------------	---------------------------------------



Height 2.45 inches (6.22 cm)
--

Depth 1.78 inches (4.53 cm)

Weight 0.76 pounds (0.35 kg)
--

Camera Body	Aluminum & Polycarbonate	1/4"-20 Standard Tripod Mount (×2)
--------------------	-----------------------------	---------------------------------------

2 digit numeric LEDs status indicators	LED health and activity indicator
---	--------------------------------------