

Face Recognition Temperature with 8 Inch Screen

Product
Image



Product size

238*128*28 L*W*T (mm)

Aplication
Pictures






Product characteristics

3d digital filtering noise reduction, line-by-line scanning, the screen real fine;
 Smart Screen Protection Function, Prevent Burns;
 High stability, low energy saving: High Performance, low power DSP processor, stable operation;
 Support ID card, residence card, IC card card to open the door in a variety of ways;
 Support face recognition (live verification) , 3000 picture unit, unlimited number of wall machine;
 Support personalized fixed Password, dynamic password, visitor password and other password open way;
 Support Remote Cell Phone Door, call cell phone door, call room number door, call property management office door;
 Support Visual Intercom, voice intercom (using highly sensitive noise reduction chip) can support visitors to take pictures, support strangers to capture, blacklist comparison
 Large Screen Advertising, long-distance updating of advertising content, support for interactive advertising, even-screen advertising, support for property fees collection, support for multi-point, point-to-point mass notification, support for property warranty and other functions, support for external monitoring cameras, data Upload in real time

Product name	Specification parameter
Display screen	LCD SCREEN: 8.0 inch IPS LCD screen screen ratio: 10:16 Resolution:800*1280 Display Area:172×107 point distance: 0.13*0.13 contrast:800:1
Cameras	200 W,Binocular Wide Motion Camera,Led and infrared dual fill lamp
Temperature module	32 X 32 dot Matrix, Infrared induction

Motherboard scheme	CPU: 3288 memory: 2GB Built in storage: EMMC 8g operating system: Android6.0	
Interface		
Accessories	Manuals, warranty cards, certificates of conformity, adapters	
Product structure	Product architect	Hardware shell + lacquer process + aluminum alloy border
	Installation mode	Wall mounted type+Vertical machine
	Protective Glass	2mm toughened glass
	Weight	2kg
	Product size	238*128*28 (mm)
	Packing size	440*200*50 (mm)
Operating parameter	Brightness Control	
	Temperature	
	Working Environme	Working Temperature:-15C to + 65 c working humidity: 20% to95%
	Power supply	Dc12v wide voltage input
	Power	15W