

FINDING PARTITE HYPERGRAPHS EFFICIENTLY

FERRAN ESPUÑA

ABSTRACT. We provide a deterministic polynomial-time algorithm (for fixed k) that, for a given k -uniform hypergraph H with n vertices and edge density d , finds a complete k -partite subgraph of H with parts of size at least $c(d, k)(\log n)^{1/(k-1)}$. This generalizes work by Mubayi and Turán on bipartite graphs. The value we obtain for the part size matches the order of magnitude guaranteed by the non-constructive proof due to Erdős and is tight up to a constant factor.

1. INTRODUCTION

Hypergraph Turán problems concern how many edges a k -uniform hypergraph $H = (V, E)$ with n vertices can have without containing a specific subgraph G . The maximal such number is known as the *Turán number* $\text{ex}(n, G)$. It is known [5] that $\text{ex}(n, G)$ is sublinear in $\binom{n}{k}$ if and only if G is k -partite, i.e., if its vertex set can be partitioned into k disjoint sets such that each edge contains exactly one vertex from each part. Kővári, Sós, and Turán [6] (for $k = 2$) and Erdős [3] (for any $k \geq 2$) established that

$$(1) \quad \text{ex}(n, K(t, \cdot^k, t)) \leq \binom{n}{k} \cdot n^{-\frac{1}{t^{k-1}}},$$

where $K(t, \cdot^k, t)$ is the hypergraph consisting of k disjoint sets $V_1, \dots, V_k$ of size t and all hyperedges of the form $\{x_1, \dots, x_k\}$ with $x_i \in V_i$ for $i = 1, \dots, k$. This result implies the following.

Remark 1.1. *For all $k \geq 1$ and $0 < d < 1$, there is a constant $c(d, k)$ such that if H is a k -uniform hypergraph on n vertices with at least $d\binom{n}{k}$ edges, and if $t \leq c(d, k)(\log n)^{1/(k-1)}$, then H contains $K(t, \cdot^k, t)$ as a subgraph.*

Furthermore, the order of magnitude of t is tight up to a constant factor: For some constant $\hat{c}(d, k) > 0$, there are k -uniform hypergraphs with n vertices and at least $d\binom{n}{k}$ edges that do not contain $K(\hat{t}, \cdot^k, \hat{t})$ as a subgraph, as long as $\hat{t} \geq \hat{c}(d, k)(\log n)^{1/(k-1)}$. This was already noted by Erdős [3] and can be proved via the random alteration method [1].

Due to the fundamental role of Erdős' result, it is natural to ask whether a fast search algorithm for a complete k -partite subgraph of the size stated in Remark 1.1 exists. A brute-force search for a $K(t, \cdot^k, t)$ would involve checking all $\binom{n}{kt}$ vertex subsets, which is super-polynomial in the number of vertices n for $t = \Omega((\log n)^{1/(k-1)})$. For $k = 2$, Mubayi and Turán [7] developed a deterministic polynomial-time algorithm which reaches the stated order of magnitude for the subgraph part size. This work extends their approach to the general case of k -uniform hypergraphs, reaching analogous results for $k \geq 3$. More concretely, we prove the following.

Theorem 1.2. *There is a deterministic algorithm that, given a k -uniform hypergraph H with n vertices and $m = d\binom{n}{k}$ edges, finds a complete balanced k -partite subgraph $K(t, \cdot^k, t)$ in polynomial time, where*

$$t = t(n, d, k) = \left\lfloor \left(\frac{\log n}{\log(16/d)} \right)^{\frac{1}{k-1}} \right\rfloor.$$

This value of t matches the asymptotic order of magnitude from Remark 1.1. It is worth noting, however, that while our result is asymptotically tight regarding the dependence on n , the constant factor $\tilde{c}(d, k) = \log(16/d)^{-\frac{1}{k-1}}$ obtained by our algorithm is much smaller than that guaranteed by existence

proofs. For example, $\tilde{c}(d, k)$ remains bounded even as $d \rightarrow 1$, whereas the same is not true for the family of constants $c(d, k) = \log(1/d)^{-\frac{1}{k-1}}$ obtained directly from (1). We focus here on establishing polynomial-time constructibility rather than optimizing this constant to match the best known existential bounds.

2. THE ALGORITHM

We present a recursive algorithm, **FindPartite**, that finds a $K(t, \cdot^k, t)$ in a given k -uniform hypergraph H . The core idea is to reduce the uniformity of the host hypergraph H from k to $k-1$ in each recursive step. The algorithm takes a k -uniform hypergraph H with n vertices and m edges as input. It first defines the target part size t , a small set size w , and a threshold edge count s for the recursive call, based on the input hypergraph's parameters:

$$\begin{aligned} t &= t(n, d, k) = \left\lfloor \left(\frac{\log n}{\log(16/d)} \right)^{\frac{1}{k-1}} \right\rfloor, \\ w &= w(n, d, k) = \left\lceil \frac{4t}{d} \right\rceil, \text{ and} \\ s &= s(n, d, k) = \left\lceil \left(\frac{d}{4} \right)^t \binom{n}{k-1} \right\rceil, \end{aligned}$$

where $d = \frac{m}{\binom{n}{k}}$ is the edge density of H . The main steps are:

- (1) **Base Case** ($k = 1$): The edge set of a 1-uniform hypergraph is just a collection of singleton sets of vertices. Return the set of all vertices that are “edges”.
- (2) **Select High-Degree Vertices**: Choose a set $W \subset V$ of w vertices with the highest degrees in H .
- (3) **Find a Dense Link Graph**: Iterate through all subsets $T \subset W$ of size t . For each T , consider the set S of all subsets $y \subset V$ of size $k-1$ that form a hyperedge with *every* vertex in T .
- (4) **Recurse**: As we prove further along using the Kővári–Sós–Turán theorem, for at least one choice of T , the resulting set S is large ($|S| \geq s$). We form a new $(k-1)$ -uniform hypergraph $H' = (V, S)$ and make a recursive call: **FindPartite**(H' , $k-1$).
- (5) **Construct Solution**: The recursive call returns $k-1$ parts $V_1, \dots, V_{k-1}$ of size at least t . Every choice of one vertex from each of these parts forms an edge in H' . By construction, they form an edge of H with every vertex in T . Thus, $V_1, \dots, V_{k-1}, T$ span the desired $K(t, \cdot^k, t)$ subgraph in the original k -uniform hypergraph.

The pseudocode is given in Algorithm 1. In section 3, we formally prove that this algorithm is correct, in the sense that it returns a tuple $(V_1, \dots, V_k)$ of disjoint sets $V_i \subset V(H)$ of size at least t spanning a complete k -partite subgraph in H . In Section 4, we show that it runs in polynomial time in the number of vertices n of the input hypergraph H . This will conclude the proof of Theorem 1.2.

Algorithm 1 Finding a balanced k -partite k -uniform subgraph

```

1: function FINDPARTITE( $H, k$ )
2:   if  $k = 1$  then
3:     return ( $\{x: \{x\} \in E(H)\}$ )
4:   end if
5:    $n \leftarrow |V(H)|, m \leftarrow |E(H)|, d \leftarrow \frac{m}{\binom{n}{k}}$ 
6:    $t \leftarrow t(n, d, k), w \leftarrow w(n, d, k), s \leftarrow s(n, d, k)$ 
7:   assert ( $t \geq 2$ )
8:    $W \leftarrow$  a set of  $w$  vertices with highest degree in  $H$ 
9:   for all  $T \in \binom{W}{t}$  do
10:     $S \leftarrow \{y \in \binom{V}{k-1}: \forall x \in T, \{x\} \cup y \in E(H)\}$ 
11:    if  $|S| \geq s$  then
12:       $H' \leftarrow (V, S)$   $\triangleright H'$  is a  $(k-1)$ -uniform hypergraph
13:       $(V_1, \dots, V_{k-1}) \leftarrow \text{FINDPARTITE}(H', k-1)$ 
14:      return ( $V_1, \dots, V_{k-1}, T$ )
15:    end if
16:  end for
17: end function

```

3. PROOF OF CORRECTNESS

We now present the proof that all the steps in Algorithm 1 are well-defined and that it returns a tuple $(V_1, \dots, V_k)$ of disjoint sets $V_i \subset V(H)$ of size at least t spanning a complete k -partite subgraph in H . We assume $t \geq 2$ for our estimates to be easier. If $t < 2$, we may just return the vertices of any single edge in H .

It is not immediately clear that the set W defined in step 2 of the algorithm is well-defined, as for this it is necessary that $w \leq n$. To show this, we first observe that our assumption $t \geq 2$ implies that $1 \geq d \geq \frac{16}{\sqrt{n}}$. Suppose, by way of contradiction, that $w > n$. Then, we have

$$n \leq w - 1 \leq \frac{4t}{d} \leq \frac{4 \log n}{d \log(16/d)} \leq \frac{4\sqrt{n} \log n}{16 \log(16/d)}.$$

Taking the logarithms to be in base e , we note that $\log x \leq \sqrt{x}$ for all positive x , and that $\log(16/d) > 1$. Therefore, we get $n < \frac{n}{4}$, which is a contradiction.

Next, we prove that in step 3 of the algorithm we indeed find a set $T \in \binom{W}{t}$ such that the associated set $S \subset \binom{V}{k-1}$ has size at least s . That is, Algorithm 1 reaches line 13 at some point in the for loop. For this, consider the bipartite graph B with parts $\binom{V}{k-1}$ and W with edge set

$$\left\{ (x, y) \in \binom{V}{k-1} \times W \mid x \cup \{y\} \in E \right\}.$$

The edges of B correspond to the edges containing each vertex in W , so there are

$$z = \sum_{y \in W} d_H(y) \geq k \cdot m \cdot \frac{w}{n} = \frac{k \cdot w \cdot d \cdot \binom{n}{k}}{n} = w \cdot d \cdot \binom{n-1}{k-1}$$

of them, where the inequality follows from the fact that we have picked a set of w vertices with highest degree in H . The existence of a set $T \subset W$ as desired is equivalent to there being $T \subset W$ of size t and a set $S \subset \binom{V}{k-1}$ of size s such that the induced bipartite subgraph $B[S, T]$ is complete. To prove that this is the case, we use the following version [4] of the Kővári–Sós–Turán theorem [6].

Lemma 3.1. *Let u, w, s, t be positive integers with $u \geq s$, $w \geq t$, and let B be a bipartite graph with parts W and U such that $|U| = u, |W| = w$. If B has more than*

$$(s-1)^{1/t}(w-t+1)u^{1-1/t} + (t-1)u$$

edges, then there are $T \subset W$ of size t and $S \subset U$ of size s such that the induced bipartite subgraph $B[S, T]$ is complete.

We apply the lemma with $u = \binom{n}{k-1}$. It is clear from the definitions that our parameters satisfy the requirements $u \geq s$ and $w \geq t$. Suppose, by way of contradiction, that

$$w \cdot d \cdot \binom{n-1}{k-1} \leq z \leq (s-1)^{1/t} (w-t+1) \binom{n}{k-1}^{1-1/t} + (t-1) \binom{n}{k-1}.$$

Dividing by $\binom{n}{k-1}$ then shows that

$$\frac{1}{2} \cdot w \cdot d \leq \left(1 - \frac{k-1}{n}\right) \cdot w \cdot d = w \cdot d \cdot \frac{\binom{n-1}{k-1}}{\binom{n}{k-1}} < w \left(\frac{s-1}{\binom{n}{k-1}}\right)^{1/t} + (t-1),$$

where the first inequality follows from $n \geq 16^{2^{k-1}} > 2(k-1)$, which follows from $t \geq 2$ and $d \leq 1$. Finally, since $t \leq \frac{w \cdot d}{4}$ by the definition of w , we obtain

$$\left(\frac{d}{4}\right)^t \binom{n}{k-1} < s-1,$$

in contradiction to the definition of s . So far, we have shown that the sets defined in Algorithm 1 are well-defined and that the recursive call in line 13 is reached. We are now ready to prove that the algorithm returns a $K(t, \cdot, t)$ by examining what happens in the recursive call. More precisely, we show the following.

Theorem 3.2. *For $k \geq 2$, if $t \geq 2$, Algorithm 1 returns a tuple $(V_1, \dots, V_k)$ of disjoint sets $V_i \subset V(H)$ such that $|V_i| \geq t$ and $H[V_1, \dots, V_k]$ is complete.*

Proof. We proceed by induction on k . For $k = 2$, the recursive call returns the common neighborhood V_1 of the vertices in T , which is obviously disjoint from T , so it only remains to check that $|V_1| \geq t$. Now, since by construction $|V_1| = |S| \geq s$, it is enough that

$$s = \left\lceil \left(\frac{d}{4}\right)^t \cdot n \right\rceil \geq \left(\frac{d}{4}\right)^{\frac{\log n}{\log(16/d)}} \cdot n = \left(4 \cdot \frac{d}{16}\right)^{\frac{\log n}{\log(16/d)}} \cdot n = 4^{\frac{\log n}{\log(16/d)}} \cdot \frac{1}{n} \cdot n \geq 4^t > t.$$

For $k \geq 3$, we assume the inductive hypothesis holds for $k-1$. Let d' be the edge density of H' (which is the obtained $(k-1)$ -uniform hypergraph) and t' be $t(n, d', k-1)$. As long as $t' \geq 2$, the recursive call returns a tuple $(V_1, \dots, V_{k-1})$ of disjoint sets $V_i \subset V(H)$ such that $|V_i| \geq t'$ and $H'[V_1, \dots, V_{k-1}]$ is complete.

We claim that $t' \geq t$. This implies that $t' \geq 2$ so we get to apply the inductive hypothesis to H' . Furthermore, the sets V_i that we obtain when applying the algorithm to H' are of size at least $t' \geq t$. By construction of S , all the edges in H' are disjoint from T , hence the sets V_i are also disjoint from T . This means that the sets $V_1, \dots, V_{k-1}, T$ are disjoint. In addition, for all $(x_1, \dots, x_{k-1}, y) \in V_1 \times \dots \times V_{k-1} \times T$, we have that $\{x_1, \dots, x_{k-1}\} \in S$ so $\{x_1, \dots, x_{k-1}, y\} \in E(H)$. Equivalently, $H[V_1, \dots, V_{k-1}, T]$ is complete, finishing the proof.

Let us now prove the claim that $t' \geq t$. By the definition of s , we have $d' \geq \left(\frac{d}{4}\right)^t$. Therefore,

$$t' \geq \left\lceil \left(\frac{\log n}{\log \left(\frac{16}{(d/4)^t}\right)}\right)^{\frac{1}{k-2}} \right\rceil = \left\lfloor \left(\frac{\log n}{\log 16 + t \log(4/d)}\right)^{\frac{1}{k-2}} \right\rfloor.$$

Then, we substitute the definition of t , where removing the floor function maintains the inequality because the right side is decreasing in t :

$$t' \geq \left\lfloor \left(\frac{\log n}{\log 16 + \left(\frac{\log n}{\log(16/d)}\right)^{\frac{1}{k-1}} \log(4/d)}\right)^{\frac{1}{k-2}} \right\rfloor = \left\lfloor \left(\frac{(\log n)^{(1-\frac{1}{k-1})}}{\frac{\log 16}{(\log n)^{\frac{1}{k-1}}} + \frac{\log(4/d)}{\log(16/d)^{\frac{1}{k-1}}}}\right)^{\frac{1}{k-2}} \right\rfloor.$$

We claim that we can bound the denominator by showing that

$$(2) \quad \frac{\log 16}{(\log n)^{\frac{1}{k-1}}} + \frac{\log(4/d)}{\log(16/d)^{\frac{1}{k-1}}} \leq (\log(16/d))^{(1-\frac{1}{k-1})}.$$

Then, the expression simplifies to

$$t' \geq \left\lfloor \left(\frac{(\log n)^{(1-\frac{1}{k-1})}}{(\log(16/d))^{(1-\frac{1}{k-1})}} \right)^{\frac{1}{k-2}} \right\rfloor = \left\lfloor \left(\frac{\log n}{\log(16/d)} \right)^{\frac{1}{k-2}(1-\frac{1}{k-1})} \right\rfloor = \left\lfloor \left(\frac{\log n}{\log(16/d)} \right)^{\frac{1}{k-1}} \right\rfloor = t,$$

as desired. Let us prove Inequality (2). Suppose, by way of contradiction, that it does not hold. We can rewrite

$$(\log(16/d))^{(1-\frac{1}{k-1})} = \frac{\log(16/d)}{\log(16/d)^{\frac{1}{k-1}}}$$

and rearrange the inequality to obtain

$$\frac{\log 16}{(\log n)^{\frac{1}{k-1}}} > \frac{\log(16/d) - \log(4/d)}{\log(16/d)^{\frac{1}{k-1}}} = \frac{\log 4}{(\log(16/d))^{\frac{1}{k-1}}}.$$

This implies that

$$t \leq \left(\frac{\log n}{\log(16/d)} \right)^{\frac{1}{k-1}} < \frac{\log 16}{\log 4} = 2,$$

which contradicts the assumption that $t \geq 2$. $\square$

4. PROOF OF POLYNOMIAL COMPLEXITY

We now analyze the computational complexity of Algorithm 1 to show that it runs in time polynomial in n for any fixed uniformity k . We consider the input hypergraph H to be given as an adjacency k -dimensional tensor. If the hypergraph is provided sparsely (e.g., as a list of m edges), it can be preprocessed in polynomial time by reindexing the vertices and removing isolated ones. This reduces the effective number of vertices to n' such that $n' \leq k \cdot m$. Consequently, the tensor initialization time and space become $\mathcal{O}((km)^k)$, which remains polynomial in the sparse input size for fixed k . Since we will prove the algorithm is polynomial-time in this new size, the resulting algorithm is also polynomial in the sparse size.

We perform the analysis under the standard Word RAM model with word size $\Omega(\log n)$. This allows for basic arithmetic operations and array indexing on values up to n^k to be performed in $\mathcal{O}(1)$ time.

Let $T_k(n)$ denote the worst-case running time of the function **FindPartite** when called on a k -uniform hypergraph with n vertices. The algorithm's structure gives a recurrence relation for $T_k(n)$. We first analyze the cost of the operations within a single call for a fixed k , excluding the recursive step.

Querying whether a set of k vertices forms an edge in H can be done in constant time. Therefore, calculating the number of edges m can be done in $\mathcal{O}(n^k)$ time by iterating through all $\binom{n}{k}$ possible edges. The parameters t, w , and s can then be calculated in polylogarithmic time: If one wants to avoid the arithmetic on real numbers, the values can be obtained via binary search on equations obtained by rearranging the definitions of t, w , and s .

The set W of w vertices with highest degrees can be constructed in time $\mathcal{O}(n^k)$, for instance, by creating an array with the degree of each vertex (in time $\mathcal{O}(n \cdot n^{k-1}) = \mathcal{O}(n^k)$), sorting it in descending order (in time $\mathcal{O}(n \log n)$), and taking the first w elements.

The subsets of t elements of W can be iterated through in time $\mathcal{O}(\binom{w}{t})$ [8]. Similarly to the argument by Mubayi and Turán [7], we can bound this quantity by a polynomial in n . Indeed,

$$\binom{w}{t} \leq \left(\frac{ew}{t} \right)^t \leq \left(\frac{e(4t/d+1)}{t} \right)^t \leq \left(\frac{4e}{d} + \frac{e}{2} \right)^t \leq \left(\frac{4.5 \cdot e}{d} \right)^t < e^{t(2.6+\log(1/d))} = e^{2.6 \cdot t} e^{\log(1/d) \cdot t}.$$

For the first term, we use the fact that $t < (\log n)^{1/(k-1)} \leq \log n$ and so $e^{2.6 \cdot t} < e^{2.6 \cdot \log n} = n^{2.6}$. For the second term, we use that $t < ((\log n)/\log(1/d))^{1/(k-1)} \leq (\log n)/\log(1/d)$, so $e^{\log(1/d) \cdot t} < n$. All in all, we have

$$\binom{w}{t} < n^{2.6} n = n^{3.6}.$$

In each iteration of the loop, the set S can be constructed in the following way. We initialize a boolean adjacency tensor A of size n^{k-1} , with all entries set to **true**. We iterate through all $x \in \binom{[n]}{k-1}$ and $y \in T$ and set the entry corresponding to x to **false** if $x \cup \{y\}$ is not an edge in H . All in all, this takes

$\mathcal{O}(tn^{k-1}) = \mathcal{O}(n^k)$ steps, and then counting the number of `true` entries in the array takes $\mathcal{O}(n^{k-1})$ time. Therefore, the for loop (without the recursive call) takes $\mathcal{O}\left(\binom{w}{t}n^k\right) = \mathcal{O}(n^{k+3.6})$ time.

Finally, when the condition $|S| \geq s$ is satisfied, the recursive call to `FindPartite` is made. We can pass the array A to the recursive call directly, and the recursive call takes time $T_{k-1}(n)$. Putting everything together, we have the recurrence relation $T_k(n) = T_{k-1}(n) + \mathcal{O}(n^{k+3.6})$. This, together with the base case $T_1(n) = \mathcal{O}(n)$, gives us $T_k(n) = \mathcal{O}(n^{k+3.6})$. Similar analysis shows that if the more restrictive Turing Machine computational model is used, the algorithm runs in time $\mathcal{O}(n^{2k+3.6}p_k(\log(n)))$ where p_k is some polynomial depending on k .

5. CONCLUDING REMARKS AND FUTURE WORK

We have presented a deterministic, polynomial-time algorithm to find a large complete balanced k -partite subgraph in any sufficiently dense k -uniform hypergraph. This provides a constructive counterpart to a classical existence result by Erdős in extremal hypergraph theory.

Several avenues for future research remain open.

- **General Blow-ups:** Our algorithm finds a blow-up of a single edge, $K(t, \dots, t)$. Can this framework be adapted to find a t -blowup of an arbitrary fixed k -uniform hypergraph G when its Turán density is exceeded by a positive constant? For example, for $k = 2$, there are existence results for $t = \Omega(\log n)$ [2], but directly adapting Algorithm 1 would only yield $t = \mathcal{O}((\log n)^{1/(|V(G)|-1)})$.
- **Unbalanced k -Partite Graphs:** The algorithm could be modified to search for unbalanced complete partite graphs $K(t_1, \dots, t_k)$, where the part sizes may grow at different rates.
- **Optimality:** The bounds on t are asymptotically tight, but the constants can be improved significantly with a more refined analysis.

Acknowledgements. The ideas in this work stem from the author's master's thesis of the same name at Universitat Politècnica de Catalunya, under the supervision of Richard Lang. The author thanks him for suggesting the problem and for his guidance and support throughout the project.

REFERENCES

- [1] Noga Alon and Joel H. Spencer. *The probabilistic method*. John Wiley & Sons, 2016.
- [2] Béla Bollobás and Pál Erdős. On the structure of edge graphs. *Bull. London Math. Soc.*, 5:317–321, 1973.
- [3] Pál Erdős. On extremal problems of graphs and generalized graphs. *Israel J. Math.*, 2:183–190, 1964.
- [4] Carl Hyltén-Cavallius. On a combinatorial problem. *Colloq. Math.*, 6:59–65, 1958.
- [5] Peter Keevash. Hypergraph Turán problems. In *Surveys in combinatorics 2011*, volume 392 of *London Math. Soc. Lecture Note Ser.*, pages 83–139. Cambridge Univ. Press, Cambridge, 2011.
- [6] Thomas Kövari, Vera T. Sós, and Pál Turán. On a problem of K. Zarankiewicz. *Colloq. Math.*, 3:50–57, 1954.
- [7] Dhruv Mubayi and György Turán. Finding bipartite subgraphs efficiently. *Inform. Process. Lett.*, 110(5):174–177, 2010.
- [8] Edward M. Reingold, Jurg Nievergelt, and Narsingh Deo. *Combinatorial algorithms: theory and practice*. Prentice-Hall, Inc., Englewood Cliffs, NJ, 1977.