Video Transcript

Video 10: Web Sockets Streaming Exercise Solution (04:19)

So, if you remember, we needed to solve the problem of the web streaming exercise where we had a web socket server that was streaming data to the client and we needed to deal with reading chunks on the client so we could specify how big a chunk was. And the problem is that we decided to put a header in where we'd put the length of the message so that the end of the message wouldn't be guaranteed to be at the end of a chunk. So, we'd need to make sure that we're monitoring, what we might call, the full message that we've got so far, and we need to check its length.

So, for example, if this was 31 long, we know the header is 10 long, so the full message length would be 41. And so, this would be the 41 break. And we'd need to deal with this start of the next message, which might be something like 29 and maybe some blanks because that needs to be tagged on and make sure that it's the beginning of the next full message. So, I gave you some clues as to how to do that. Let's look at the code. So, this is the code I gave you, and the last thing we're doing is we're printing out the full message from zero to the message length plus the header.

Now, the full message contains maybe more than that, and that piece we need to put into the next message. So, let's call the next message and it's going to be full message, and we're going to go from the message length plus header. So, we're going to go from the end point there to the very end of that full message. Now, suppose this is actually the end of the message. Suppose this is the end of the message here. Will this cause a problem? No, no. So, what I'm saying is, even if 'next' contains nothing, that's not a problem.

Now, we want to put that as the start of the next message. So, now we just replace the code here. This, actually, let's put that with, that's 'next'. So, let me get rid, now, of all these comments so we can see the code. So, now this should be our solution. So, we're reinitializing full message. And in fact, we don't need 'next', that we could eliminate it, but I'm keeping it there just for clarity that this is the start of the next message. Now, we reinitialize full message and go back

© MIT xPRO® 2024. All rights reserved.

now to reading chunks.

So, let's save that and let's go to our Windows. Let's break into here and break into here. It's clear. Okay, and let's run, now, our server and let's run our solution. So, I changed your client, so we should be fine. That runs beautifully. So, this is our client and it mimics this beautifully and we get the end of the last message. Okay, so I hope you enjoyed that exercise.

© MIT xPRO® 2024. All rights reserved.