Algorithm Cheat Sheet · Which to Use

Find the first matching clue, then take the technique it points to. Italic phrases under each pill are the words to look for in the problem statement. Inspired by AlgoMonster's flowchart.

Graphs & trees

Tree structure?

Level order or min depth?

Yes → **BFS**
shortest unweighted path · level order

Count or build tree shapes?

Yes → **Divide & Conquer / Tree DP**
count distinct trees · subtree DP

No → **DFS**
tree paths · explore all branches

Directed acyclic graph?

Yes → **Topological Sort**
"course schedule" · prerequisites · DAG

Shortest path?

Weighted edges?

Yes → **Dijkstra's Algorithm**
shortest path · weighted edges

No → **BFS**
shortest unweighted path · level order

Connected components?

Yes → **Disjoint Set Union**
connected components · "merge accounts"

Tiny input?

Yes → **DFS / Backtracking**
enumerate paths · small graph

No → **BFS**
shortest unweighted path · level order

Sorted, search & k-th

Sorted in, monotonic out?

Range/rank queries + updates?

Yes → **Ordered Set / Fenwick / Segment Tree**
range sum + updates · order stats

No → **Binary Search**
sorted array · "minimize the max"

Top-k or k-th?

Yes → **Heap / Sorting**
kth largest · "top k" · running median

Linked lists

Linked list?

Fast/slow or offset pointers?

Yes → **Two pointers**
pair from ends · fast/slow · in-place

Merge several sorted lists?

Yes → **Heap / Divide & Conquer**
merge k sorted lists

No → **Linked-List Manipulation**
reverse / reorder a list

Lookups, intervals, partition, strings

Lookup, count, or group?

Yes → **Hash Table / Counting**
frequency · "first unique" · group by

Overlapping intervals?

Yes → **Sorting + Interval Scan**
merge intervals · "meeting rooms"

Partition in place?

Yes → **Two pointers / Partitioning**
move zeroes · Dutch flag · in-place

Match/split via dictionary?

Prefix/pattern search?

Yes → **Trie / String Matching / Rolling Hash**
prefix search · "starts with"

No → **Trie / DP / Memoization**
word break · dictionary split

Small constraints (n is tiny)

Brute force viable?

Yes → **Brute Force / Backtracking**
all permutations / subsets · n ≤ 12

Track a subset?

Yes → **Bitmask DP**
n ≤ 20 · "visit all" · subset state

No → **Dynamic Programming**
"number of ways" · max/min with choices

Subarrays & windows

Running sums?

Yes → **Prefix Sums**
subarray sum = k · negatives allowed · cumulative totals

Contiguous span?

Window invariant?

Yes → **Sliding Window**
longest/shortest substring · ≤ k distinct
exactly k → atMost(k)−atMost(k−1)

Nearest greater/smaller?

Yes → **Monotonic Stack**
next greater · "daily temperatures"

No → **Dynamic Programming**
"number of ways" · max/min with choices

Counting arrangements

Brute force viable?

Yes → **Brute Force / Backtracking**
all permutations / subsets · n ≤ 12

No → **Dynamic Programming**
"number of ways" · max/min with choices

Several sequences?

Monotonic property?

Yes → **Two pointers**
pair from ends · fast/slow · in-place

Overlapping subproblems?

Yes → **Dynamic Programming**
"number of ways" · max/min with choices

Locate indices?

Monotonic property?

Yes → **Two pointers**
pair from ends · fast/slow · in-place

Constant space?

Monotonic property?

Yes → **Two pointers**
pair from ends · fast/slow · in-place

Compute a max / min

Monotonic search space?

Yes → **Binary Search**
sorted array · "minimize the max"

Nearest greater/smaller?

Yes → **Monotonic Stack**
next greater · "daily temperatures"

Overlapping subproblems?

Yes → **Dynamic Programming**
"number of ways" · max/min with choices

No → **Greedy Algorithms**
intervals · "jump game" · local choice

Parsing, design, simulation, math (the tail)

Parsing symbols?

Count or optimise segments?

Yes → **Dynamic Programming**
"number of ways" · max/min with choices

No → **Stack**
valid parentheses · expression parse

Design a structure?

Yes → **Design + Supporting Structures**
"implement LRU / iterator"

Just follow the rules?

Yes → **Simulation / Basic DSA**
follow the rules step by step

Math or bit tricks?

Properties of numbers?

Yes → **Number Theory**
gcd / primes / modular arithmetic

No → **Math / Bit Manipulation**
XOR tricks · powers · "single number"

Otherwise

· **Specialized / Advanced Pattern**
rare / problem-specific trick

FAMILY ▢ graph/traversal ▢ search ▢ pointers/window ▢ heap/sort/interval ▢ dynamic prog. ▢ brute/backtrack ▢ stack ▢ other

Yes (green) take it · No (orange) alternative · purple = grouping question · · = fall-through default

Algorithm Cheat Sheet · How They Work

The mechanism behind each technique on the front — minimal Python-ish templates, not full implementations. Badge = typical time complexity.

BFS

O(V+E)

Explore level by level. Shortest path in an unweighted graph.

```
from collections import deque
q, seen = deque([s]), {s}
while q:
    u = q.popleft()
    for v in adj[u]:
        if v not in seen:
            seen.add(v); q.append(v)
```

DFS

O(V+E)

Go deep, then backtrack. Trees, paths, components, cycles.

```
def dfs(u):
    seen.add(u)
    for v in adj[u]:
        if v not in seen:
            dfs(v)
```

Topological Sort

O(V+E)

Order a DAG so every edge points forward (Kahn's algorithm).

```
indeg = [0]*n
for u in range(n):
    for v in adj[u]: indeg[v] += 1
q = deque(u for u in range(n) if indeg[u]==0)
order = []
while q:
    u = q.popleft(); order.append(u)
    for v in adj[u]:
        indeg[v] -= 1
        if indeg[v] == 0: q.append(v)
# len(order) < n  =>  graph has a cycle
```

Dijkstra

O(E log V)

Shortest path with non-negative weights, via a min-heap.

```
import heapq
dist = [INF]*n; dist[s] = 0
pq = [(0, s)]
while pq:
    d, u = heapq.heappop(pq)
    if d > dist[u]: continue
    for v, w in adj[u]:
        if d + w < dist[v]:
            dist[v] = d + w
            heapq.heappush(pq, (dist[v], v))
```

Union-Find (DSU)

~O(1) amort.

Merge sets, test connectivity, detect cycles. Path compression.

```
par = list(range(n))
def find(x):
    while par[x] != x:
        par[x] = par[par[x]]   # path-compress
        x = par[x]
    return x
def union(a, b):
    par[find(a)] = find(b)
```

Binary Search

O(log n)

Halve a sorted (or monotonic) space. Also "search on the answer".

```
lo, hi = 0, len(a)      # answer: hi = max+1
while lo < hi:
    mid = (lo + hi) // 2
    if ok(mid): hi = mid        # first True
    else:       lo = mid + 1
return lo
```

Two Pointers

O(n)

Walk a sorted array from both ends, or fast/slow on a list.

```
i, j = 0, len(a) - 1
while i < j:
    s = a[i] + a[j]
    if s == target: return (i, j)
    if s < target: i += 1
    else:          j -= 1
```

Sliding Window

O(n)

Grow right, shrink left to keep an invariant (e.g. ≤ k distinct).

```
left = 0; cnt = Counter()
for right, x in enumerate(a):
    cnt[x] += 1
    while len(cnt) > k:          # shrink
        cnt[a[left]] -= 1
        if cnt[a[left]] == 0: del cnt[a[left]]
        left += 1
    best = max(best, right - left + 1)
# exactly k  =  atMost(k) - atMost(k-1)
```

Heap / Top-k

O(n log k)

Keep the k best seen so far in a size-k min-heap.

```
import heapq
h = []                      # min-heap, size k
for x in a:
    heapq.heappush(h, x)
    if len(h) > k: heapq.heappop(h)
# h[0] is the k-th largest
```

Merge Intervals

O(n log n)

Sort by start, then fold each interval into the last if they touch.

```
a.sort()
out = [a[0]]
for s, e in a[1:]:
    if s <= out[-1][1]:
        out[-1][1] = max(out[-1][1], e)
    else:
        out.append([s, e])
```

Dynamic Programming

O(n·W)

Build answers from overlapping subproblems (0/1 knapsack shown).

```
dp = [0]*(W + 1)
for wt, val in items:
    for c in range(W, wt-1, -1):    # 0/1: down
        dp[c] = max(dp[c], dp[c-wt] + val)
return dp[W]
```

Backtracking

O(2ⁿ) / O(n!)

Choose, recurse, undo. Permutations & subsets when n is tiny.

```
def bt(start, path):
    res.append(path[:])       # record
    for i in range(start, n):
        path.append(a[i])
        bt(i + 1, path)       # i+1 => subsets
        path.pop()            # undo
```

Monotonic Stack

O(n)

Stack holds a sorted run; pop when the new value breaks it.

```
st = []; res = [-1]*n
for i, x in enumerate(a):
    while st and a[st[-1]] < x:   # next greater
        res[st.pop()] = x
    st.append(i)
```

Prefix Sums

O(n) build

Precompute cumulative totals for O(1) range-sum queries.

```
pre = [0]*(n + 1)
for i, x in enumerate(a):
    pre[i+1] = pre[i] + x
# sum(l..r) = pre[r+1] - pre[l]
# subarray==k: count pre[] in a hashmap
```

Trie

O(len) / op

Prefix tree for word lookups and "starts-with" queries.

```
def add(root, w):
    cur = root
    for c in w:
        cur = cur.setdefault(c, {})
    cur['$'] = True       # word ends here
```

FAMILY graph/traversal · search · pointers/window · heap/sort/interval · dynamic prog. · brute/backtrack · stack · other

Pseudocode — 0-indexed, adapt to your language · grey = comment