

Algorithm Cheat Sheet · Which to Use

Find the first matching clue, then take the technique it points to. Italic phrases under each pill are the words to look for in the problem statement. Inspired by AlgoMonster's flowchart.

CONSTRAINTS → COMPLEXITY $n \leq 12 \rightarrow O(n!)$ · $\leq 20 \rightarrow O(2^n)$ · $\leq 500 \rightarrow O(n^3)$ · $\leq 5000 \rightarrow O(n^2)$ · $\leq 10^6 \rightarrow O(n \log n)$ · $\leq 10^8 \rightarrow O(n)$ · $\geq 10^9 \rightarrow O(\log n)$ rough budget $\sim 10^8$ ops/s · Python $\sim 10^7$ · memory ~ 256 MB

Graphs & trees

Tree structure?

- Level order or min depth?
Yes **BFS**
shortest unweighted path · level order
- Count or build tree shapes?
Yes **Divide & Conquer / Tree DP**
count distinct trees · subtree DP
- No** **DFS**
tree paths · explore all branches

Directed acyclic graph?

- Yes** **Topological Sort**
"course schedule" · prerequisites · DAG

Shortest path?

- Weighted edges?
Yes **Dijkstra's Algorithm**
shortest path · weighted edges
- No** **BFS**
shortest unweighted path · level order

Connected components?

- Yes** **Disjoint Set Union**
connected components · "merge accounts"

Tiny input?

- Yes** **DFS / Backtracking**
enumerate paths · small graph
- No** **BFS**
shortest unweighted path · level order

Sorted, search & k-th

Sorted in, monotonic out?

- Range/rank queries + updates?
Yes **Ordered Set / Fenwick / Segment Tree**
range sum + updates · order stats
- No** **Binary Search**
sorted array · "minimize the max"
- Top-k or k-th?
Yes **Heap / Sorting**
kth largest · "top k" · running median

Linked lists

Linked list?

- Fast/slow or offset pointers?
Yes **Two pointers**
pair from ends · fast/slow · in-place
- Merge several sorted lists?
Yes **Heap / Divide & Conquer**
merge k sorted lists
- No** **Linked-List Manipulation**
reverse / reorder a list

Lookups, intervals, partition, strings

Lookup, count, or group?

- Yes** **Hash Table / Counting**
frequency · "first unique" · group by

Overlapping intervals?

- Yes** **Sorting + Interval Scan**
merge intervals · "meeting rooms"

Partition in place?

- Yes** **Two pointers / Partitioning**
move zeroes · Dutch flag · in-place

Match/split via dictionary?

- Prefix/pattern search?
Yes **Trie / String Matching / Rolling Hash**
prefix search · "starts with"
- No** **Trie / DP / Memoization**
word break · dictionary split

Small constraints (n is tiny)

Brute force viable?

- Yes** **Brute Force / Backtracking**
all permutations / subsets · $n \leq 12$

Track a subset?

- Yes** **Bitmask DP**
 $n \leq 20$ · "visit all" · subset state
- No** **Dynamic Programming**
"number of ways" · max/min with choices

Subarrays & windows

Running sums?

- Yes** **Prefix Sums**
subarray sum = k · negatives allowed · cumulative totals

Contiguous span?

- Window invariant?
Yes **Sliding Window**
*longest/shortest substring · $\leq k$ distinct
exactly k $\rightarrow$ atMost(k) - atMost(k-1)*

Nearest greater/smaller?

- Yes** **Monotonic Stack**
next greater · "daily temperatures"
- No** **Dynamic Programming**
"number of ways" · max/min with choices

Counting arrangements

Brute force viable?

- Yes** **Brute Force / Backtracking**
all permutations / subsets · $n \leq 12$
- No** **Dynamic Programming**
"number of ways" · max/min with choices

Several sequences?

- Monotonic property?
Yes **Two pointers**
pair from ends · fast/slow · in-place

Overlapping subproblems?

- Yes** **Dynamic Programming**
"number of ways" · max/min with choices

Locate indices?

- Monotonic property?
Yes **Two pointers**
pair from ends · fast/slow · in-place

Constant space?

- Monotonic property?
Yes **Two pointers**
pair from ends · fast/slow · in-place

Compute a max / min

Monotonic search space?

- Yes** **Binary Search**
sorted array · "minimize the max"

Nearest greater/smaller?

- Yes** **Monotonic Stack**
next greater · "daily temperatures"

Overlapping subproblems?

- Yes** **Dynamic Programming**
"number of ways" · max/min with choices
- No** **Greedy Algorithms**
intervals · "jump game" · local choice

Parsing, design, simulation, math (the tail)

Parsing symbols?

- Count or optimise segments?
Yes **Dynamic Programming**
"number of ways" · max/min with choices
- No** **Stack**
valid parentheses · expression parse

Design a structure?

- Yes** **Design + Supporting Structures**
"implement LRU / iterator"

Just follow the rules?

- Yes** **Simulation / Basic DSA**
follow the rules step by step

Math or bit tricks?

- Properties of numbers?
Yes **Number Theory**
gcd / primes / modular arithmetic
- No** **Math / Bit Manipulation**
XOR tricks · powers · "single number"

Otherwise

- Specialized / Advanced Pattern**
rare / problem-specific trick

Algorithm Cheat Sheet · How They Work

The mechanism behind each technique on the front — minimal Python-ish templates, not full implementations. Badge = typical time complexity.

BFS

O(V+E)

Explore level by level. Shortest path in an unweighted graph.

```
# adj[u] = node u's neighbour nodes (v)
from collections import deque
q, seen = deque([src]), {src}
while q:
    u = q.popleft()
    for v in adj[u]:
        if v not in seen:
            seen.add(v); q.append(v)
```

DFS

O(V+E)

Go deep, then backtrack. Trees, paths, components, cycles.

```
def dfs(u):
    seen.add(u)
    for v in adj[u]:
        if v not in seen:
            dfs(v)
```

Topological Sort

O(V+E)

Order a DAG so every edge points forward (Kahn's algorithm).

```
from collections import deque
indeg = [0] * n
for u in range(n):
    for v in adj[u]: indeg[v] += 1
q = deque(u for u in range(n) if indeg[u] == 0)
order = []
while q:
    u = q.popleft(); order.append(u)
    for v in adj[u]:
        indeg[v] -= 1
        if indeg[v] == 0: q.append(v)
# len(order) < n => graph has a cycle
```

Dijkstra

O(E log V)

Shortest path with non-negative weights, via a min-heap.

```
import heapq
dist = [float('inf')] * n; dist[src] = 0
pq = [(0, src)]
while pq:
    d, u = heapq.heappop(pq)
    if d > dist[u]: continue
    for v, w in adj[u]: # (neighbour, weight)
        if d + w < dist[v]:
            dist[v] = d + w
            heapq.heappush(pq, (dist[v], v))
```

Union-Find (DSU)

~O(1) amort.

Merge sets, test connectivity, detect cycles. Path compression.

```
parent = list(range(n))
def find(x):
    while parent[x] != x:
        parent[x] = parent[parent[x]] # compress
        x = parent[x]
    return x
def union(a, b):
    parent[find(a)] = find(b)
```

Binary Search

O(log n)

Halve a sorted (or monotonic) space. Also "search on the answer".

Example: first index $\geq x$; [1,3,3,5], $x=3 \rightarrow 1$

```
def lower_bound(arr, ok): # first True index
    lo, hi = 0, len(arr) # on answer: hi=max+1
    while lo < hi:
        mid = (lo + hi) // 2
        if ok(mid): hi = mid
        else: lo = mid + 1
    return lo
```

Two Pointers

O(n)

Walk a sorted array from both ends, or fast/slow on a list.

Example: pair summing to target; [2,7,11], $9 \rightarrow (0,1)$

```
def two_sum(arr, target): # arr is sorted
    i, j = 0, len(arr) - 1
    while i < j:
        s = arr[i] + arr[j]
        if s == target: return (i, j)
        if s < target: i += 1
        else: j -= 1
```

Sliding Window

O(n)

Grow right, shrink left to keep an invariant (e.g. $\leq k$ distinct).

Example: longest with $\leq k$ distinct; "eceba", $k=2 \rightarrow 3$

```
from collections import Counter
best, left = 0, 0; cnt = Counter()
for right, x in enumerate(arr):
    cnt[x] += 1
    while len(cnt) > k: # shrink
        cnt[arr[left]] -= 1
        if cnt[arr[left]] == 0: del cnt[arr[left]]
        left += 1
    best = max(best, right - left + 1)
# exactly k = atMost(k) - atMost(k-1)
```

Heap / Top-k

O(n log k)

Keep the k best seen so far in a size-k min-heap.

```
import heapq
heap = [] # min-heap, size k
for x in arr:
    heapq.heappush(heap, x)
    if len(heap) > k: heapq.heappop(heap)
# heap[0] is the k-th largest
```

Merge Intervals

O(n log n)

Sort by start, then fold each interval into the last if they touch.

Example: [[1,3],[2,6],[8,10]] $\rightarrow$ [[1,6],[8,10]]

```
intervals.sort()
merged = [intervals[0]]
for a, b in intervals[1:]:
    if a <= merged[-1][1]:
        merged[-1][1] = max(merged[-1][1], b)
    else:
        merged.append([a, b])
```

Dynamic Programming

O(coins*amt)

Build answers from overlapping subproblems.

Example: coins [1,2,5], amount 11 $\rightarrow$ 3

```
# dp[t] = running best (fewest coins to make t)
dp = [0] + [float('inf')] * amount
for coin in coins: # consider one more option
    # ascending/descending => can/cannot reuse
    for t in range(coin, amount + 1):
        # update every subproblem with choice
        dp[t] = min(dp[t], dp[t-coin] + 1)
# answer = dp[amount] (inf => impossible)
```

Memoization

O(states)

Recurse on subproblems, cache each result in a dict.

Example: nth Fibonacci; fib(6) $\rightarrow$ 8

```
memo = {}
def fib(num):
    if num <= 1: return num
    if num in memo: return memo[num]
    memo[num] = fib(num-1) + fib(num-2)
    return memo[num]
```

Backtracking

O(2ⁿ) / O(n!)

Choose, recurse, undo. Permutations & subsets when n is tiny.

Example: subsets of [1,2] $\rightarrow$ [], [1], [1,2], [2]

```
def backtrack(start, path):
    res.append(path[:]) # record
    for i in range(start, n):
        path.append(arr[i])
        backtrack(i + 1, path) # i+1 => subsets
    path.pop() # undo
```

Monotonic Stack

O(n)

Stack holds a sorted run; pop when the new value breaks it.

Example: next greater value to the right; [2,1,3] $\rightarrow$ [3,3,-1]

```
stack = []; res = [-1] * n
for i, x in enumerate(arr):
    while stack and arr[stack[-1]] < x:
        res[stack.pop()] = x
    stack.append(i)
```

Prefix Sums

O(n) build

Precompute cumulative totals for O(1) range-sum queries.

```
prefix = [0] * (n + 1)
for i, x in enumerate(arr):
    prefix[i+1] = prefix[i] + x
# sum(l..r) = prefix[r+1] - prefix[l]
# subarray=k: count prefix[] in a hashmap
```

Trie

O(len) / op

Prefix tree for word lookups and "starts-with" queries.

```
def insert(root, word):
    cur = root
    for c in word:
        cur = cur.setdefault(c, {})
    cur['$'] = True # word ends here
```