RECORD

ELECTRIC TOW TRACTORS



RANGE 2,5 kN



ELECTRIC TOW				SPECIFICATION VDI 2198			
TRACTOR							
Characteristics	1	Manufacturer		BALKANCAR RECORD		A G/777 0.5	
	2	Type				AC/ET 2,5	
	3	Power unit		Battery/diesel/gas		Battery	
	4	Type of control		Pedestrian/rider seated/stand-on		Rider seated	
	5	Tyres		L – pneumatic; SE – superelastic		L/L	
	6	Wheels (x–driven)		Number, front/rear		2/2 x	
	7	Overall dimensions	L	Length	mm	2780	
ns	8		В	Width	mm	1350	
sio	9		h _a	Height of hitch bar	mm	330	
Dimensions	10		h_3	Height of overhead guard	mm	2006	
l ii	11		h ₂	Height of seat	mm	950	
I	12	Turning radius	Wa	Outer radius	mm	2670	
	13			Travel with load/without load	km/h	9/15	
	14	Rated drawbar pull			kN	2,5	
	15	Climbing ability		With load/without load	%	6/15	
Weight	16	Weight		Including battery acc. to ISO 5053 – 87	kg	2500	
	17	Axle load		Front/rear	kg	900/1600	
	18	Tyres		Number, front/rear		2/2	
	19			Size, front		6,00-9	
	20			Size, rear		8,15-15	
sis	21	Wheelbase	Y		mm	1700	
Chassis	22	Track width	B_1/B_2	Front/rear	mm	1010/992	
\Box	23	Ground clearance $\frac{m_1}{m_2}$	m_1	Lowest point with load	mm	125	
	24		m_2	Center of wheelbase with load	mm	175	
	25	Service brake		Mech./hydr./pneum./combined		Hydraulic	
	26	Parking brake		Hand/foot		Hand	
Drive	27	Battery		Туре		Panzer	
	28			Voltage/rated capacity	V/Ah	80V/420Ah	
	29			Weight	kg	978	
	30	Electric motors		Manufacturer, type		"AMRE"- Itali	
	31			Drive motor performance at $S_2 - 60$ min	kW	9	
	32			Lift motor performance at S ₄ – 25%	kW	1,2	
	33	Drive control		Туре		Impulse regulator"PGDT"- England	
	34	Transmission		Туре		Mechanical	
	35	Noise level		Average value at operator's ear	dB(A)	58	

- * Tow tractors in accordance with BDS EN 1726-1
 * Dimensions and parameters as shown are for reference only.
 * Balkancar Rekord JSC reserves the right to introduce changes to the specifications and products without notice.



