## RECORD 4S

I.C. POWERED FORKLIFT TRUCKS




**RANGE 10,5t; 12,5t** 




RECORD 4S			SPECIFICATION VDI 2198					
	1	Manufacturer		BALKANCAR RECORD				
	2	Type				DV 1998.33.257 S	DV 1999.33.257 S	
stics	3	Load capacity	Q		kg	10000	12500	
Characteristics	4	Load center	C	Load center to fork face	mm	60		
ırac	5	Drive unit		Battery/diesel/LPG		Die	sel	
Ch	6	Type of operation		Pedestrian/rider seated/stand-on			Rider seated	
	7	Tyres		L – pneumatic; SE – superelastic		L/L (SE/SE)		
	8	Wheels (x–driven)		Number, front/rear		4x / 2		
	9		$h_3$	Lift height	mm	3300, 400	00, 4500	
	10	Lift	$h_2$	Free lift	mm	-		
	11		$h_5$	Extended free lift	mm		-	
	12	Fork carriage		According to DIN 15137		47		
	13	Fork dimensions	s/e/l	Thickness/width/length	mm	70x200x1200 <sup>1)</sup>		
	14	Tilt angle	α/β	Forward/backward	(°)	5°±1° /		
suc	15	Overall dimensions	$L_2$	Length	mm	4100		
ensic	16		В	Width	mm	2450		
Dimensions	17		$h_1$	Height, mast lowered	mm	3100, 3450, 3700		
ı	18		$h_4$	Height, mast extended	mm	4700, 5050, 5300		
	19		$h_6$	Height of overhead guard	mm	2420		
	20		h <sub>7</sub>	Height of seat	mm		1400	
	21	Turning radius	Wa	Outer radius	mm		4250	
	22	Load distance	X	Front axle center to fork face	mm		650	
	23	Aisle width	Ast <sub>4</sub>	For pallets 800x1200	mm	5600		
				For pallets 1000x1200		5800		
a	24			Travel with load/without load	km/h	8; 14; 24 / 9; 15; 25		
anc	25	Speed		Lifting with load/without load	m/s	-, .	0,4 / 0,45	
Performance	26			Lowering with load/without load	m/s	· · · · · · · · · · · · · · · · · · ·	0,4 / 0,4	
Perl	27	Rated drawbar pull		With load	kN	75		
	28	Climbing ability		With load/without load	%	35		
Ħ	29	Weight		Including battery acc. to ISO 5053 – 87	kg	12500	14800	
Weight	30	Axle load		With load front/rear	kg	20000 / 2500	24100 / 2700	
Ĺ	31			Without load front/rear	kg	6500 / 6000	7400 / 7400	
	32	Tyres		Number, front/rear		4 / 2		
	33			Size, front		9-20		
	34			Size, rear		300-15		
sis	35	Wheelbase	Y		mm	2750		
Chassis	36	Track width		Front/rear	mm		1900 / 1800	
ľ	37	Ground clearance	$m_1$	Lowest point with load	mm	250 350		
	38		$m_2$	Center of wheelbase with load	mm			
	39	Service brake		Mech./hydr./pneum./combined			Hydraulic Hand	
	40	Parking brake		Hand/foot				
	41	Battery		Type	****	Starter		
	42		<u> </u>	Voltage/rated capacity	V/Ah	12/135		
	43			Weight	kg	37 DELITZ DE 04 M 2012		
1	44	Internal combustion engine	<u> </u>	Manufacturer, type	1 777	DEUTZ BF 04 M 2012		
Drive	45			Engine performance to DIN 70020	kW	70		
Ω	46			Rated speed to DIN 70020	min <sup>-1</sup>	2200		
	47			Number of cylinders/displacement	cm <sup>3</sup>	4 / 4038		
	48	m · ·		Fuel consumption	l/h	6 (diesel)		
	49	Transmission		Type, speeds (forward/backward)	<u> </u>	Hydrodynamic "Clark" T12000, 3 / 3		
	50	Clutch coupling		Туре		Hydro transformer		
	51	Working pressure		For attachments	MPa	18		
	52	Noise level		Average value at operator' ear	dB(A)	85	5	

- Recommended fork dimensions
- Forklifts in accordance with BDS EN 1726-1
- Size  $h_4$  does not include a load backrest. When a backrest is fitted add  $+\,680$  mm.
- Other variants of specifications and characteristics are possible.

  Balkancar Rekord JSC reserves the right to introduce changes to the specifications and products without notice.
- The pictures and illustrations do not include all variants produced, additional equipment and accessories.
- Фотографии и иллюстрации не включают все варианты, дополнительное оборудование и аксесоары.







4004 Пловдив, БОЛГАРИЯ Кукленско шоссе 17 факс: +359 32 692 753 тел.: +359 32 695 050

www.balkancar-record.com