

ID · insole missing · S	.93	.94	.48	.47	.95	.93	.45	.86	.50	.32
ID · encoder dropout · S	.95	.95	.64	.47	.87	.86	.54	.95	.50	.48
ID · IMU bias · S	.50	.50	.53	.46	.50	.50	.48	.50	.50	.51
ID · packet loss · S	.88	.91	.50	.50	.50	.51	.49	.94	.48	.50
ID · stuck IMU · S	.96	.96	.48	.54	.66	.65	.53	.96	1.00	.49
ID · sensor delay · S	.88	.63	.44	.57	.61	.60	.52	.50	.95	.51
ID · burst packet loss · H	.74	.89	.50	.50	.50	.52	.50	.92	.05	.50
ID · partial dropout · H	.91	.91	.50	.50	.50	.51	.50	.94	1.00	.50
ID · delay jitter · H	.87	.64	.44	.57	.62	.60	.52	.50	.93	.51
HT · insole missing · S	.84	.85	.47	.42	.82	.80	.38	.84	.50	.29
HT · encoder dropout · S	.89	.89	.61	.40	.66	.64	.44	.98	.50	.49
HT · IMU bias · S	.50	.50	.53	.46	.51	.51	.48	.50	.50	.50
HT · packet loss · S	.79	.80	.50	.50	.50	.51	.49	.96	.46	.50
HT · stuck IMU · S	.84	.84	.48	.51	.48	.47	.51	1.00	1.00	.50
HT · sensor delay · S	.77	.56	.48	.52	.54	.54	.52	.50	.99	.50
HT · burst packet loss · H	.76	.78	.50	.50	.50	.51	.50	.92	.05	.50
HT · partial dropout · H	.81	.80	.50	.50	.50	.51	.50	.96	1.00	.50
HT · delay jitter · H	.77	.56	.48	.52	.55	.54	.50	.50	.96	.50
	All	Gate	Fault	Aleat.	Recon.	Forecast	Epist.	Stale	Coherence	Drift