

Question 21

Answer saved
Marked out of 1.00
Flag question

Consider the code:
<form action="target" method="post">
<input type="text" value="testing" name="bt"/>
<input type="submit" name="btn" value="search"/>
</form>

What value will be sent to the resource "target" after submitting?

- ☐ a. The text "testing" is sent
- ☒ b. Both "testing" and "search" are sent
- ☐ c. The text "search" is sent
- ☐ d. nothing is sent
- Clear my choice

Question 22

Answer saved
Marked out of 1.00
Flag question

consider the code:
<form action="/targetServlet">...</form>
Choose the right option.

- ☐ a. The browser will assume that "targetServlet" resides in the Lib folder
- ☒ b. The browser will assume the the path at the root location for specified host (http://host:port).
- ☐ c. The browser will assume that "targetServlet" resides in the same place the default page as index.jsp or index.html
- ☐ d. The browser will assume that "targetServlet" resides in the WEB_INF folder
- Clear my choice

Question 23

Answer saved
Marked out of 1.00
Flag question

Which mechanism does Struts 2 can be used some components in any projects or libraries?

- ☐ a. Using Action Context to contain information
- ☒ b. Using JavaBeans
- ☐ c. None of the others
- ☐ d. Using xml to configure
- Clear my choice

Question 24

Answer saved
Marked out of 1.00
Flag question

Consider the code in the file "web.xml":

```
<web-app>
....
<filter>
  <filter-name>myfilter</filter-name>
  <filter-class>vantn.filter.myfilter</filter-class>
</filter>
<filter-mapping>
  <filter-name>myfilter</filter-name>
  <url-pattern>/servlet1</url-pattern>
</filter-mapping>
....
</web-app>
```

Choose the right statement.

- [1] Intercept the requests and response that flow between a client and the servlet "servlet1".
- [2] Supports dynamic modification of requests between a client and the servlet "servlet1"
- [3] only apply the filter "myfilter" to all servlets in the web app exception the servlet "servlet1"
- [4] can not apply the filter "myfilter" by using "web.xml"

- ☐ a. 3
- ☐ b. 4
- ☐ c. 2
- ☒ d. 1
- Clear my choice

Question 25

Answer saved
Marked out of 1.00
Flag question

What memory scope is used to store data that exists until the web container is stopped?

- ☐ a. request scope
- ☒ b. application/context scope
- ☐ c. page scope
- ☐ d. session scope
- Clear my choice

Question 26

Answer saved
Marked out of 1.00
Flag question

Which symbol is used to get or call get method of object in EL?

- ☐ a. Double quote
- ☐ b. None of the others
- ☒ c. Dot Symbol
- ☐ d. Semi Colon Symbol
- Clear my choice

Question 27

Answer saved
Marked out of 1.00
Flag question

What statement is used to display data from the session scope in the page(.jsp)?

- ☒ a. \${sessionScope.name}
- ☐ b. All of the others
- ☐ c. <%= session.getAttribute(name) %>
- ☐ d. \${name}
- Clear my choice

Question 28

Consider the table structure:

Quiz navigation

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49											

Finish attempt ...

Time left 0:11:44

Answer saved
Marked out of
1.00
Flag
question

Accounts(accid: int primary key, fullname: varchar(20), role: int foreign key, email: varchar(20)).

Roles(roleid: int, description: varchar(50))

What query can be used to check the account id=1 that exists in the Accounts table?

- ☐ a. select * from Accounts where accid=1
- ☒ b. all of the others
- ☐ c. select accid from Accounts where accid=1
- ☐ d. select count(accid) from Accounts where accid=1

Clear my choice

Question 29

Answer saved
Marked out of
1.00
Flag
question

Which structure of war file does?

- ☐ a. WEB-INF directory, all directory putting outside WEB-INF directory that is shown in IDE tool, lib directory with jar files that are added, and/or META-INF directory
- ☐ b. None of the others
- ☐ c. WEB-INF directory, and META-INF directory
- ☒ d. WEB-INF directory, resources that browser can access depending permission putting outside WEB-INF directory, and/or META-INF directory

Clear my choice

Question 30

Answer saved
Marked out of
1.00
Flag
question

What java API is used in your code to access data that is stored in RDBMS?

- ☐ a. java.query.*
- ☐ b. javax.query.*
- ☐ c. java.sql.* and java.query.*
- ☒ d. java.sql.* and javax.sql.*

Clear my choice

Previous page

Next page



PREVIOUS ACTIVITY
supporting materials

NEXT ACTIVITY
Progress test 2



Jump to...

