

Question 1

Answer saved

Marked out of 1.00

Flag question

Consider the table structure:
Accounts(accd: int primary key, fullname: varchar(20), role: int foreign key, email: varchar(20)).
Roles(roleid: int, rolename: varchar(50))

What query can be used to get full name and role name of the account?

☐ a. select fullname, rolename from Accounts, Roles

☒ b. select fullname, rolename from Accounts, Roles where role=roleid

☐ c. select * from Accounts , Roles

☐ d. None of the others

Clear my choice

Question 2

Answer saved

Marked out of 1.00

Flag question

Consider the code in the file web.xml:

```
...
<context-param>
  <param-name>count</param-name>
  <param-value>5</param-value>
</context-param>
```

and in the servlet "testServlet.java"

```
public class testServlet extends HttpServlet{
  ...
  protected void processRequest(HttpServletRequest request, HttpServletResponse response) throws ServletException, IOException {
    //MISSING
  }
}
```

Choose the right option to get initial context parameter at [MISSING]

☒ a. ServletContext sc=getServletContext();
String result=sc.getInitParameter("count");

☐ b. ServletConfig scf=getServletConfig();
String result=scf.getInitParameter("count");

☐ c. ServletContext sc=getServletContext();
int result=sc.getInitParameter("count");

☐ d. ServletConfig scf=getServletConfig();
int result=scf.getInitParameter("count");

Clear my choice

Question 3

Answer saved

Marked out of 1.00

Flag question

Consider some statements:

[1] Dynamically access incoming requests from the user before the servlet processes the request
[2] Access the outgoing response from the web resources before it reaches the user
[3] Intercept the requests and response that flow between a client and a Servlet/JSP
[4] Was introduced as a Web component in java servlet specification version 2.3

What these statements are saying about?

☒ a. filter

☐ b. container

☐ c. back end services

☐ d. web server

Clear my choice

Question 4

Answer saved

Marked out of 1.00

Flag question

Consider some steps:

[1] Check available DB connection
[2] Create SQL String using DML
[3] Connect DB using method that you are built
[4] Create Statement/PreparedStatement/CallableStatement
[5] Execute Query to get ResultSet
[6] Process the ResultSet

Choose the right sequence to access the DB using JDBC API?

☐ a. 1,3,2,4,5,6

☐ b. 1,2,3,4,5,6

☐ c. 3,4,5,6,1,2

☒ d. 3,1,2,4,5,6

Clear my choice

Question 5

Answer saved

Marked out of 1.00

Flag question

What different points between Java Bean and Java class?

☐ a. Java Bean class must be implemented from Serializable

☐ b. Using <jspuseBean /> to locate or instantiate the Bean.

☐ c. Java Bean class must have a public no-argument constructor

☒ d. All of the others

Clear my choice

Question 6

Answer saved

Marked out of 1.00

Flag question

Which of following feature does indicate "Servlet should NOT use as dynamic page"?

☐ a. Getting auto refresh on receiving a request time

☐ b. Initialize only once at deploy time

☐ c. None of the others

☒ d. Low lever HTML format

Clear my choice

Question 7

What does the prefix in T1.D file means?

Quiz navigation

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49											

Finish attempt ...

Time left 0:12:08



Answer saved
Marked out of
1.00
Flag
question

- Which of the following is not correct when the prefix of tag is used?
- ☐ a. It is an address to access tag class
 - ☒ b. It is an alias name to avoid the conflict name of tag in this tid to others
 - ☐ c. It is a name that the users must be used and fill when they import taglib on JSP Page
 - ☐ d. None of the others
- [Clear my choice](#)

Question 8
Answer saved
Marked out of
1.00
Flag
question

Given tid fragment

```
<tag>
<name>test</name>
<tag-class>sample.custag.Test</tag-class>
<body-content>EMPTY</body-content>
<attribute>
  <name>a</name>
  <required>false</required>
  <rtexprvalue>true</rtexprvalue>
</attribute>
</tag>
```

Which following tag is NOT correct when it is applied above configuration? Assume that the prefix of tag is test in used.

- ☐ a. `<test>abc</test>`
- ☐ b. None of the others
- ☒ c. `<testtest a = "5"/>`
- ☐ d. `<testtest a = "${2 + 2}/>`

[Clear my choice](#)

Question 9
Answer saved
Marked out of
1.00
Flag
question

What is the meaning of param keyword in EL?

- ☐ a. None of the others
- ☒ b. param is a briefcase of request.getParameter
- ☐ c. param is a briefcase of Request Parameter
- ☐ d. param is a briefcase of Parameters of Context Scope, Config, and Request Scope

[Clear my choice](#)

Question 10
Answer saved
Marked out of
1.00
Flag
question

What attribute presents value that contains some target resource in the web application (e.g. Servlet or JSP)?

- ☐ a. multidata
- ☐ b. method
- ☐ c. encryption
- ☒ d. action

[Clear my choice](#)

[Next page](#)

« [PREVIOUS ACTIVITY](#)
supporting materials

[NEXT ACTIVITY](#) »
Progress test 2

Jump to...