

Question 31
Answer saved
Marked out of 1.00
Flag question

Consider the code in the file "index.jsp"

```
...
<form method="post">
  <input type="text" name="txt1" value="" placeholder="input email" />
  <input type="password" name="txt2" value="" placeholder="input password"/>
  <input type="submit" name="btn" value="submit" />
</form>
....
What statement is used to assign again the inputted value in the text control "txt1" after submitting?
```

☐ a. All of the others

☐ b. At the value property of the control "txt1", type: <%= request.getParameter("txt1") %>

☒ c. At the value property of the control "txt1", type: \${param.txt1}

☐ d. At the value property of the control "txt1", type: \${requestScope.txt1}

Clear my choice

Question 32
Answer saved
Marked out of 1.00
Flag question

Consider the code in the filter

```
public void doFilter(ServletRequest request, ServletResponse response,
    FilterChain chain) throws IOException, ServletException {
    try {
        chain.doFilter(request, response);
        request.setAttribute("id", "SE12345");
    } catch (Throwable t) {}
}
```

And the code in the servlet

```
...
String s= (String)request.getAttribute("id");
out.println("id: " +s);
....
```

Apply this filter to the servlet

What is displayed in the browser?

☐ a. the text "SE12345" is displayed in the browser.

☒ b. the empty string is displayed in the browser.

☐ c. the null value is displayed in the browser

☐ d. None of the others

Clear my choice

Question 33
Answer saved
Marked out of 1.00
Flag question

Which method does container generate code with scriptlets and expression?

☐ a. _jspForward

☐ b. service

☒ c. _jspService

☐ d. None of the others

Clear my choice

Question 34
Answer saved
Marked out of 1.00
Flag question

Consider the code:

```
....
String sql="select ORDERID,ORDERDATE,STATUS from ORDERS where STATUS=?";
PreparedStatement pst=cn.prepareStatement(sql);
//MISSING
ResultSet rs=pst.executeQuery();
....
What statement is used insert to [MISSING] to get orders that is processing?
```

☒ a. pst.setString(1,"processing");

☐ b. pst.getString("STATUS");

☐ c. pst.setInt(1,"processing");

☐ d. pst.setString("processing");

Clear my choice

Question 35
Answer saved
Marked out of 1.00
Flag question

Assume that all library files are imported and there is a data as user="testing" in the session scope .

Consider the code in the file "index.jsp"

```
...
<h1>welcome [MISSING]</h1>
....
What statement is used to display "testing" at [MISSING]?
[1] ${sessionScope.testing}
[2] ${sessionScope.user}
[3] ${session.getAttribute("testing")}
[4] ${"testing"}
```

☐ a. 4

☐ b. 3

☐ c. 1

☒ d. 2

Clear my choice

Question 36
Answer saved
Marked out of 1.00
Flag question

What method commonly used for passing user input/ sending information to the server. These request parameters are passed in the body of the request?

☐ a. GET

☐ b. SENT

☒ c. POST

☐ d. PASS

Clear my choice

Question 37
Answer saved

Which definition is used to map dynamic database connection?

Quiz navigation

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36
37	38	39	40	41	42	43	44	45	46	47	48
49											

Finish attempt ...

Time left 0:11:32

Marked out of 1.00
Flag question

☐ a. Resource

☒ b. Data-source

☐ c. Java Database Connection

☐ d. None of the others

Clear my choice

Question 38
Answer saved
Marked out of 1.00
Flag question

Which structure of Status Line in Response Message is?

☒ a. [HTTP Version] [Response Code] [Status]

☐ b. None of the others

☐ c. [HTTP Method] [Protocol Version] [Requested Resource forming URI]

☐ d. [HTTP Version] [Response Code] [Http Method]

Clear my choice

Question 39
Answer saved
Marked out of 1.00
Flag question

Assume that the web app is deployed and named "MyAPP", use the server name "localhost", port: 8080.
Consider the code in the filter
...
public void doFilter(ServletRequest request,ServletResponse response, FilterChain chain) throws ServletException, IOException {
 HttpServletRequest req = (HttpServletRequest)request;
 System.out.println("tried to access " + req.getRequestURL() +" on " + new Date() + ".");
 chain.doFilter(request,response);
}
and this filter is applied to the servlet1
What is the output when client send a request to the servlet1 on "Tue Mar 08 15:26:33 ICT 2022."?

☐ a. display the text: tried to access http://localhost:8080/MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.

☒ b. display the text: tried to access http://localhost:8080/MyApp on Tue Mar 08 15:26:33 ICT 2022.

☐ c. display the text: tried to access /MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.

☐ d. display the text: tried to access /servlet1 on Tue Mar 08 15:26:33 ICT 2022.

Clear my choice

Question 40
Answer saved
Marked out of 1.00
Flag question

Which following function in core library taglib of JSTL is used to make the urlrewriting technique?

☒ a. url and/or param

☐ b. import and/or param

☐ c. set and/or param

☐ d. None of the others

Clear my choice

Previous page

Next page

« PREVIOUS ACTIVITY
supporting materials

NEXT ACTIVITY
Progress test 2 »

Jump to...

FPT University HCM Campus
Contact: it.hcm@fpt.edu.vn
IT Support: 0914 291 596

[Get the mobile app](#)