Question 41
Answer saved
Marked out of 1.00
Flag question

What attribute presents value that contains some target resource in the web application (e.g. Servlet or JSP)?

- a. action
- b. method
- c. encryption
- d. multidata

Clear my choice

Question 42
Answer saved
Marked out of 1.00
Flag question

Which mechanism does forEach function of core taglib library of JSTL executes?

- a. None of the others
- b. Loop depends the container reading the size of collection
- c. Loop depends the while control structure when collection's item is existed
- d. Loop depends on event on tag when the collection's item is existed

Clear my choice

Question 43
Answer saved
Marked out of 1.00
Flag question

Which symbol is used to get or call get method of object in EL?

- a. Semi Colon Symbol
- b. None of the others
- c. Dot Symbol
- d. Double quote

Clear my choice

Question 44
Answer saved
Marked out of 1.00
Flag question

Assume that the web app is deployed and named "MyAPP", use the server name "localhost", port: 8080.
 Consider the code in the filter
...
public void doFilter(ServletRequest request,ServletResponse response, FilterChain chain) throws ServletException, IOException {
HttpServletRequest req = (HttpServletRequest)request;
System.out.println("tried to access " +   req.getRequestURL() +" on " + new Date() + ".");
 chain.doFilter(request,response);
}
and this filter is applied to the servlet1
What is the output when client send a request to the servlet1 on "Tue Mar 08 15:26:33 ICT 2022."?

- a. display the text: tried to access http://localhost:8080/MyApp on Tue Mar 08 15:26:33 ICT 2022.
- b. display the text: tried to access http://localhost:8080/MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.
- c. display the text: tried to access /servlet1 on Tue Mar 08 15:26:33 ICT 2022.
- d. display the text: tried to access /MyApp/servlet1 on Tue Mar 08 15:26:33 ICT 2022.

Clear my choice

Question 45
Answer saved
Marked out of 1.00
Flag question

What statement is used to display data from the session scope in the page(.jsp)?

- a. All of the others
- b. ${sessionScope.name}
- c. ${name}
- d. <%= session.getAttribute(name) %>

Clear my choice

Question 46
Answer saved
Marked out of 1.00
Flag question

choose the right option to insert data as: name="testing" to the request scope in the servlet.

- a. RequestScope.setAttribute("name","testing");
- b. Request.setAttribute("name","testing");
- c. this.setAttribute("name","testing");
- d. request.setAttribute("name","testing");

Clear my choice

Question 47
Answer saved
Marked out of 1.00
Flag question

Consider some steps:
[1] Check available DB connection
[2] Create SQL String using DML
[3] Connect DB using method that you are built
[4] Create Statement/PrepareStatement/CallableStatement
[5] Execute Query to get ResultSet

[6] Process the ResultSet

Choose the right sequence to access the DB using JDBC API?

- ○ a. 3,4,5,6,1,2
- ○ b. 1,2,3,4,5,6
- ○ c. 1,3,2,4,5,6
- ● d. 3,1,2,4,5,6

Clear my choice

How does output of Servlet Object present into browser?

- ○ a. The servlet's output should be put into Scope then Request Dispatcher will be forwarded to browser
- ● b. The servlet's output should be put into Response Object
- ○ c. The servlet's output is automatically sent to user's browser
- ○ d. None of the others

Clear my choice

Who initializes the Response Object?

- ○ a. None of the others
- ● b. Container
- ○ c. Servlet
- ○ d. Tomcat Server

Clear my choice

Previous page   Finish attempt …

Jump to… ⇅