

## ME1 Computing- Session 4: I/O Files and Conditional Flow

### Learning outcomes:

- Introduction of I/O Files
- Implement conditional flow
- Being able to select, as necessary, between counted loops and conditional flow

Please provide feedback at: <a href="https://www.menti.com">www.menti.com</a> with code 63 53 57
--

### Before you start

In your H drive create a folder `H:\ME1MCP\Session4` and work within it.

### Task A: I/O Files

1. Download the files `CIDs.txt` and `Marks.txt` from Blackboard. The first file stores CIDs numbers of some students, whilst the second file stores their corresponding marks. Write a script to compute the average mark and to find the maximum mark (do not use implicit functions such as `sum()` and `max()` ).

### Answer Question 1

### Task B: Searching values in a list

Using the same data imported from files in Task A:

- 1) Write a script to search and display the score of a student, specifying his/her CID from the keyboard.
- 2) Amend the script in Task A to display the list of students who achieved the maximum mark. Save the list into the file `Best.txt`.

### Answer Question 2

### Task C: Series expansion

1. The function  $y(x) = \frac{1}{1-x}$  can be represented by the series expansion:

$$y(x) = \frac{1}{1-x} = \sum_{i=0}^{N \rightarrow \infty} x^i = 1 + x + x^2 + x^3 + x^4 + \dots$$

in the interval  $-1 < x < 1$  only.

Write a script to evaluate the function  $y(x)$  in the range  $x = [-0.8 \ 0.8]$  with step  $0.01$ , for values of  $N = 2, 6, 10, 14$ .

Plot, on the same graph,  $y(x)$  vs  $x$  in the specified range  $x = [-0.8 \ 0.8]$ , for each value of  $N$ .

Evaluate the analytical value of  $y(x)$  in the same range of  $x$  and plot it, to compare the exact function with the truncated series.

### Answer Question 3

#### **Task D: Series expansions**

1. Given the series in Task C, write a script to calculate a finite approximation of such function at a given point  $x_p$ , i.e.  $y(x_p)$ .

Add terms of the series until the approximation reaches a given accuracy.

The accuracy is reached when  $|y_{n+1} - y_n| < 10^{-Q}$ .

Input the values of  $x_p$  and the accuracy  $Q$  from the keyboard.

Evaluate the exact value of  $y(x_p)$ , and display the error from the computed value. Observe the value of the error against  $10^{-Q}$ .

### Answer Question 4