Foxfab
POWER SOLUTIONS

PRODUCTION RELEASE FORM

GENERAL INFORMATION

Job No.:	J15302-02
Model No:	FFCC-C1-1200-V4-ALU-LZ-FUS(400A)
Catalog No:	FFCC-C1-1200-C4-G-ALU-LZ-FUS(400A)
Date:	7/11/2025
Job Name:	Garner Road -PO#2365-895801

ELECTRICAL RATING INFORMATION

Voltage:	600Y/347 VAC
Current:	1200A RMS
PH/W/Hz:	3PH/4W/60Hz
SCCR:	65kA RMS SYM.

SPECIFICATION/APPROVAL INFORMATION

ETL/CUL/UL SPEC:	ETL 1008
E File #:	4011005(ETL)
Drawing No:	FFCC-C1-1200-C4-G-ALU-LZ-FUS(400A)
Drawn By:	BB
Approved By:	BB
File Compliance Mech:	GC
File Compliance Elec:	KB

DETAILED REQUIREMENTS

Camlock Configuration

M/F	M
Colours	C4 - RD/BK/BU/WH/GN
Qty (PH)	3
Qty (GND)	1
Lug Config	LZ

Enclosure Information

Size	72 x 36 x 30 (Wall Mount)
Material	5052 Aluminum
Rating	Type 3R
Colour	ASA 61 GREY
Qty	1

OPTIONAL ACCESSORIES

			Specification
(AA)	☐	Camlock Snap Covers	
(AC)	☐	Heater with stat	
(AD)	☐	Additional Outlets (Specify if GFCI)	
(AE)	☐	Key Interlock	
(AF)	☐	Terminal Strip	
(AG)	☐	Phase Sequence Relay	
(AH)	☐	Power Meter	
(AI)	☐	Micro-Switch	
(AJ)	☐	Leg Stand Kit	
	☐	Tranformer required?	

EQUIPMENT SPECIFICATION

FFCC-X2 (T)	☐	Transfer switch	
FFCC-X2 (D)	☐	Disconnect Switch	
FFCC-X3	☐	Breaker(s)	
	☐	Other	

NOTES & COMMENTS

"LZ" ½ - 2 Hole Compression lugs Lugs Set (4 x 750 mcm mechanical lugs per phase)

Include Neutral Circuit (Camlocks Included)

FUS - 400A 3P Class J Fuses (Not a Typo)