

Some complexity results for identifying codes in graphs

Florent Foucaud (LaBRI, Bordeaux)
Adrian Kosowski (LaBRI-INRIA, Bordeaux)
George Mertzios (Durham University, UK)
Reza Naserasr (LRI-CNRS, Orsay)
Aline Parreau (LIFL, Lille)
Petru Valicov (LRI, Orsay)

Clermont-Ferrand

November 14th, 2012


JGA 2012

The test cover problem

Definition - TEST COVER (mentioned in Garey, Johnson, 1979)

INPUT: a set system (i.e. hypergraph) (X, \mathcal{S})

PROBLEM: find the minimum subset $\mathcal{T} \subseteq \mathcal{S}$ such that each element $x \in X$ belongs to a different set of sets in \mathcal{T} .




The test cover problem

Definition - TEST COVER (mentioned in Garey, Johnson, 1979)

INPUT: a set system (i.e. hypergraph) (X, \mathcal{S})

PROBLEM: find the minimum subset $\mathcal{T} \subseteq \mathcal{S}$ such that each element $x \in X$ belongs to a different set of sets in \mathcal{T} .



Remark

Equivalently: for any pair x, y of elements of X , there is a set in \mathcal{T} that contains **exactly** one of x, y , i.e. the symmetric difference of the sets of tests covering x, y is **nonempty**.

Theorem (Folklore)

Given a set system (X, \mathcal{S}) , a solution to TEST COVER has size at least $\log_2(|X|)$.

Proof: Must assign to each element of X , a distinct subset of \mathcal{T} .
Hence $|X| \leq 2^{|\mathcal{T}|}$. □

General bounds

Theorem (Folklore)

Given a set system (X, \mathcal{S}) , a solution to TEST COVER has size at least $\log_2(|X|)$.

Proof: Must assign to each element of X , a distinct subset of \mathcal{T} .
Hence $|X| \leq 2^{|\mathcal{T}|}$. □

Theorem (Bondy's theorem, 1972)

Given a set system (X, \mathcal{S}) , a minimal solution to TEST COVER has size at most $|X| - 1$.

Proof: nice and short graph-theoretic argument. □

Complexity results

Theorem (Garey, Johnson, 1979)

TEST COVER is NP-complete.

Theorem (Charon, Cohen, Hudry, Lobstein, 2008)

TEST COVER is NP-complete, even for set systems with a planar incidence graph.

Complexity results

Theorem (Garey, Johnson, 1979)

TEST COVER is NP-complete.

Theorem (Charon, Cohen, Hudry, Lobstein, 2008)

TEST COVER is NP-complete, even for set systems with a planar incidence graph.


Theorem (De Bontridder, Haldorsson, Haldorsson, Hurkens, Lenstra, Ravi, Stougie, 2003)

MIN TEST COVER is $O(\log(|X|))$ -approximable, but NP-hard to approximate within $o(\log(|X|))$.


Proof: Reductions from and to MIN SET COVER.




A special case: identifying the rooms of a building



A special case: identifying the rooms of a building




A special case: identifying the rooms of a building




Graph $G = (V, E)$. V : vertices (rooms), $E \subseteq V \times V$: edges (doors)

A special case: identifying the rooms of a building




Graph $G = (V, E)$. V : vertices (rooms), $E \subseteq V \times V$: edges (doors)

A special case: identifying the rooms of a building



Graph $G = (V, E)$. V : vertices (rooms), $E \subseteq V \times V$: edges (doors)

A special case: identifying the rooms of a building



Graph $G = (V, E)$. V : vertices (rooms), $E \subseteq V \times V$: edges (doors)

Identifying codes, a special case of test covers

G : undirected graph

$N[u]$: set of vertices v s.t. $d(u, v) \leq 1$

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Identifying codes, a special case of test covers

G : undirected graph

$N[u]$: set of vertices v s.t. $d(u, v) \leq 1$

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)

Identifying codes, a special case of test covers

G : undirected graph

$N[u]$: set of vertices v s.t. $d(u, v) \leq 1$

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)

Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)


Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,

$$N[u] \cap C \neq N[v] \cap C$$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$

(i.e. covering symmetric differences)



Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)



Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,

$$N[u] \cap C \neq N[v] \cap C$$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$

(i.e. covering symmetric differences)





Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G)$, $N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)



Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)



Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,

$$N[u] \cap C \neq N[v] \cap C$$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$

(i.e. covering symmetric differences)





Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)



Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)



Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,

$$N[u] \cap C \neq N[v] \cap C$$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$

(i.e. covering symmetric differences)



Examples



Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$

(i.e. covering symmetric differences)






Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)






Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)






Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)





Examples

Definition - Identifying code (Karpovsky, Chakrabarty, Levitin, 1998)

Subset C of $V(G)$ such that:

- C is a **dominating set** in G : $\forall u \in V(G), N[u] \cap C \neq \emptyset$, and
- C is a **separating code** in G : $\forall u \neq v$ of $V(G)$,
 $N[u] \cap C \neq N[v] \cap C$

Equivalently: $(N[u] \Delta N[v]) \cap C \neq \emptyset$
(i.e. covering symmetric differences)



Computational problems

Definition - IDCODE

INPUT: graph G , integer k

QUESTION: does G have an identifying code of size at most k ?

Theorem (Cohen, Honkala, Lobstein, Zémor, 1999)

IDCODE is NP-complete (reduction from 3SAT).

NP-completeness also holds for planar subcubic graphs, planar bipartite unit disk graphs, line graphs, etc.

Computational problems

Definition - MIN IDCODE

INPUT: graph G


PROBLEM: find a minimum-size identifying code of G

Theorem (Berger-Wolf, Laifenfeld, Trachtenberg, 2006)

MIN IDCODE is approximable within $O(\log(n))$, but NP-hard to approximate within $o(\log(n))$ (reduction from MIN SET COVER).


New and non-approximability reductions

Reduction: MIN TEST COVER to MIN IDCODE for bipartite graphs.



New and non-approximability reductions

Reduction: MIN TEST COVER to MIN IDCODE for bipartite graphs.




Theorem (F.)

- (X, S) has a test cover of size k if and only if $G(X, S)$ has an identifying code of size $k + 3\lceil \log_2(|S| + 1) \rceil + 2$. Constructive.
- If MIN IDCODE has an α -approximation algorithm, then MIN TEST COVER has a 4α -approximation algorithm.

New and non-approximability reductions

Reduction: MIN TEST COVER to MIN IDCODE for bipartite graphs.



Theorem (F.)

- (X, S) has a test cover of size k if and only if $G(X, S)$ has an identifying code of size $k + 3\lceil \log_2(|S| + 1) \rceil + 2$. Constructive.
- If MIN IDCODE has an α -approximation algorithm, then MIN TEST COVER has a 4α -approximation algorithm.


Proof: Build approximate id. code C with $|C| \leq \alpha OPT_{ID}$

$$\begin{aligned} \text{Build test cover } T: |T| &\leq \alpha OPT_{ID} - 3 \log_2(|S|) - 2 \\ &\leq \alpha(OPT_{TC} + 3 \log_2(|S|) + 2) - 3 \log_2(|S|) - 2 \\ &\leq \alpha OPT_{TC} + (\alpha - 1)3 \log_2(|S|) \\ &\leq 4\alpha OPT_{TC} \end{aligned}$$

□

New and non-approximability reductions

Reduction: MIN TEST COVER to MIN IDCODE for bipartite graphs.



Theorem (F.)


- (X, S) has a test cover of size k if and only if $G(X, S)$ has an identifying code of size $k + 3\lceil \log_2(|S| + 1) \rceil + 2$. Constructive.
- If MIN IDCODE has an α -approximation algorithm, then MIN TEST COVER has a 4α -approximation algorithm.

Corollary


It is NP-hard to approximate MIN IDCODE within $o(\log(n))$, even for bipartite graphs.

New non-approximability reductions

Similar reductions for split graphs and co-bipartite graphs.



split graphs



co-bipartite graphs


Theorem (F.)

It is NP-hard to approximate MIN IDCODE within $o(\log(n))$, even for split graphs and even for co-bipartite graphs.

Interval graphs

Definition - Interval graph

Intersection graph of intervals of the real line.



IDCODE for interval graphs

Theorem (F., Kosowski, Mertzios, Naserasr, Parreau, Valicov)

IDCODE is NP-complete for interval graphs. Reduction from 3-DIMENSIONAL MATCHING.

IDCODE for interval graphs

Theorem (F., Kosowski, Mertziros, Naserasr, Parreau, Valicov)

IDCODE is NP-complete for interval graphs. Reduction from 3-DIMENSIONAL MATCHING.

Definition - 3-DIMENSIONAL MATCHING

INPUT: three sets A, B, C with $|A| = |B| = |C|$, and a set T of triples of $A \times B \times C$.

QUESTION: is there a perfect 3-dimensional matching $M \subseteq T$, i.e. each element of $A \cup B \cup C$ belongs to exactly one triple of M ?

IDCODE for interval graphs

Theorem (F., Kosowski, Mertziros, Naserasr, Parreau, Valicov)

IDCODE is NP-complete for interval graphs. Reduction from 3-DIMENSIONAL MATCHING.

Definition - 3-DIMENSIONAL MATCHING

INPUT: three sets A, B, C with $|A| = |B| = |C|$, and a set T of triples of $A \times B \times C$.

QUESTION: is there a perfect 3-dimensional matching $M \subseteq T$, i.e. each element of $A \cup B \cup C$ belongs to exactly one triple of M ?

Theorem (Karp, 1972)

3-DIMENSIONAL MATCHING is NP-complete.


IDCODE for interval graphs - a P_5 as covering gadget

Main idea of the reduction: an interval can separate several pairs of intervals that are **far away** from each other (without affecting what lies in between).

IDCODE for interval graphs - a P_5 as covering gadget

Main idea of the reduction: an interval can separate several pairs of intervals that are **far away** from each other (without affecting what lies in between).


A small gadget to ensure that intervals are covered and separated:



IDCODE for interval graphs - transmitter gadget

Idea (“Transmitter gadget”): in order to separate $\{uv^1, uv^2\}$ and $\{vw^1, vw^2\}$, either:


1. take only v into the id. code, or
2. take both u, w — and separate the three pairs $\{x_1, x_2\}$, $\{y_1, y_2\}$, $\{z_1, z_2\}$ “for free”.




IDCODE for interval graphs - transmitter gadget

Idea (“Transmitter gadget”): in order to separate $\{uv^1, uv^2\}$ and $\{vw^1, vw^2\}$, either:

1. take only v into the id. code, or
2. take both u, w — and separate the three pairs $\{x_1, x_2\}$, $\{y_1, y_2\}$, $\{z_1, z_2\}$ “for free”.



IDCODE for interval graphs - the reduction



Idea: to separate pairs p, q, r, s we need the identifying vertices of some transmitter gadgets. Either take:

1. $Tr(p, q)$ and $Tr(r, s)$, but separate NO element pair a, b, c , or
2. $Tr(p, r, b)$, $Tr(q, r, c)$ and $Tr(s, a)$ and separate all three element pairs “for free”

IDCODE for unit interval graphs

Definition - Unit interval graph

Intersection graph of intervals of the real line all having unit length. Equivalent to *proper* interval graphs (no interval properly contains another).

IDCODE for unit interval graphs

Definition - Unit interval graph

Intersection graph of intervals of the real line all having unit length. Equivalent to *proper* interval graphs (no interval properly contains another).

Observation

Our reduction creates interval graphs that are far from proper/unit.

IDCODE for unit interval graphs

Definition - Unit interval graph

Intersection graph of intervals of the real line all having unit length. Equivalent to *proper* interval graphs (no interval properly contains another).

Observation

Our reduction creates interval graphs that are far from proper/unit.

Question

What is the complexity of IDCODE for *unit* interval graphs?


IDCODE for unit interval graphs

Definition - Ladder graph L_m

L_m is the grid graph $P_2 \square P_m$.

Definition - Cycle cover

Set \mathcal{S} of cycles of graph G s.t. $\bigcup_{S \in \mathcal{S}} E(S) = E(G)$.



IDCODE for unit interval graphs

Definition - LADDER CYCLE COVER

INPUT: An integer m and an integer k , and a set \mathcal{S} of cycles of L_m .

QUESTION: Is there a set $\mathcal{S}' \subseteq \mathcal{S}$ of size k which is a cycle cover of L_m ?

IDCODE for unit interval graphs

Definition - LADDER CYCLE COVER

INPUT: An integer m and an integer k , and a set \mathcal{S} of cycles of L_m .

QUESTION: Is there a set $\mathcal{S}' \subseteq \mathcal{S}$ of size k which is a cycle cover of L_m ?

Theorem (F., Kosowski, Mertzios, Naserasr, Parreau, Valicov)

IDCODE for unit interval graphs of order n can be reduced to LADDER CYCLE COVER for L_{n+1} and an input of n cycles.

Idea: Only separation of pairs of *consecutive* intervals is necessary, and each interval separates two such pairs.

IDCODE for unit interval graphs

Definition - LADDER CYCLE COVER

INPUT: An integer m and an integer k , and a set \mathcal{S} of cycles of L_m .

QUESTION: Is there a set $\mathcal{S}' \subseteq \mathcal{S}$ of size k which is a cycle cover of L_m ?

Theorem (F., Kosowski, Mertzios, Naserasr, Parreau, Valicov)


IDCODE for unit interval graphs of order n can be reduced to LADDER CYCLE COVER for L_{n+1} and an input of n cycles.

Idea: Only separation of pairs of *consecutive* intervals is necessary, and each interval separates two such pairs.


Question

What is the complexity of LADDER CYCLE COVER?

Complexity of IDCODE for various graph classes



Complexity of IDCODE for various graph classes



Complexity of IDCODE for various graph classes

