Feature selection

Fraida Fund

Contents

Feature selection and feature weighting . . . 2
Feature selection is hard! . . . 3
Optimization in two parts . . . 3
Search . . . 3
Search: exhaustive search . . . 3
Search: naive heuristic . . . 4
Search: sequential forward selection . . . 4
Search: sequential forward selection as a graph . . . 4
Search: sequential backward elimination as a graph . . . 5
Evaluation . . . 6
Evaluation of "goodness" . . . 6
Evaluation: univariate scoring . . . 6
Evaluation: multivariate scoring . . . 6
Evaluation: model-in-the-loop scoring . . . 6
Evaluation: "types" of methods . . . 6
Evaluation: aligning scoring function with prediction task . . . 7
Evaluation: scoring functions for filter methods (1) . . . 7
Evaluation: scoring functions for filter methods (2) . . . 7
Evaluation: wrapper methods . . . 8
An option for some models . . . 8
Recap . . . 8

Feature selection and feature weighting

Feature selection is actually two problems:

- best number of features
- best subset of features

These problems can be solved separately:

- find best subset of feature of every possible size
- then among those, select the best

or they can be solved together, for example:

- keep adding features until improvement due to another feature is less than some threshold t
- keep features whose "score" exceeds some threshold t
- etc.

For KNN, feature selection:

- reduces inference time
- addresses the "curse of dimensionality"
- makes the distance measure more useful, by considering only the features that are most relevant

For KNN, we can also do feature weighting (compute a weight for each feature, scale feature by that weight) as an alternative to (or in addition to) feature selection - this helps with the third item.

Feature selection is hard!

Computationally **hard** - even on small problems. In practice, we won't ever have a guarantee of finding the optimal subset.

Optimization in two parts

- **Search** the space of possible feature subsets
- **Evaluate** the goodness of a feature subset




Figure 1: Feature selection problem.

Search

Search: exhaustive search

Optimal search: consider every combination of features

- Too expensive to try all possibilities!

Search: naive heuristic

- evaluate d features, sort in order of "goodness"
- select top k features from the list (use CV to choose k?)

Problem: this approach considers each feature independently.

- Doesn't consider redundancy: if you have two copies of an informative features, they'll both score high (but you wouldn't necessarily want to include both in your model).
- Doesn't consider interaction: if you are going to use a model that can learn interactions "natively" (which KNN can!), this type of feature selection may exclude features that are not informative themselves, but whose combination is informative.




Figure 2: Example of features that are informative in combination (x_1, x_2), and features that are redundant (x_4, x_5).

Search: sequential forward selection

- Let S^{t-1} be the set of selected features at time $t-1$
- Score all combinations of current set + one more feature
- For the next time step S^t, add the feature that gave you the best performance.
- Repeat until termination criterion is satisfied.

This is not necessarily going to find the best feature subset! But, it is a lot faster than the exhaustive search, and is less likely to include redundant features than naive approach.

Search: sequential forward selection as a graph




Figure 3: Graph representation

Search: sequential backward elimination as a graph




Figure 4: Graph representation

"Backward" alternative: start with all features, and "prune" one at a time.

Compared to "forward" search, it is more likely to keep features that are useful in combination with another feature.




Figure 5: Feature selection search strategies.

Evaluation

Evaluation of "goodness"




Figure 6: Which feature should you choose?

- When x_1 is large, y tends to be 1; x_1 is small, y tends to be 0 (linear/monotonic relationship)
- When x_2 is "medium", y tends to be 0; x_2 is small or large, y tends to be 1 (not linear/monotonic)
- Whatever the value of x_3, either value of y is equally likely (not useful)
- For most values of x_4, it is not useful for predicting y, but when x_4 is 1, y tends to be 0.

Evaluation: univariate scoring

Pseudocode:

```
for j in range(X.shape[1]):
  score[j] = score_fn(X[:,j], y)
```

Note: You can also use the score for feature weighting (multiply the feature by the "score" so that high-scoring features have larger values): Compared to feature selection, feature weighting does not have the benefit of faster inference time, but it does have the advantage of not throwing out useful information.

Evaluation: multivariate scoring

Pseudocode:

```
for j, feat_set in enumerate(feat_sets):
  score[j] = score_fn(X[:,feat_set], y)
```

Evaluation: model-in-the-loop scoring

Pseudocode:

```
for j, feat_set in enumerate(feat_sets):
  score[j] = model.score( X[:,feat_set], y)
```

Evaluation: "types" of methods

- **Filter methods**: consider only the statistics of the training data, don't use the model.
- **Wrapper methods**: evaluate subsets of features on a model.

Filter methods are usually much faster - but won't necessarily find the features that are optimal *for your particular case*.

Evaluation: aligning scoring function with prediction task

Scoring functions from "least closely aligned with the prediction task" to "most closely aligned with the prediction task".

- using only statistics of `X` (e.g. reject features with very low variance) - doesn't tell you which features are most useful for predicting `y`!
- using statistics of `X, y` (e.g. reject features with small correlation with `y`) - doesn't tell you which features are most useful *for your model* for predicting `y`!
- using the score of the model on a validation set when trained on the feature(s)

When *would* it make sense to reject features with low variance? Consider a text classification task with indicator variables for each word in the vocabulary:

- `the` appears in all documents - not useful.
- `historiography` appears in a couple of documents - not useful.

Evaluation: scoring functions for filter methods (1)

- Need to choose "scoring" function that is a good fit for the model

Scoring function:

- Scoring function measures the relationship between `X` and `y`.
- For example: correlation coefficient, or F-statistic both of which measures linear relationship between `X` and `y`.

Problem: correlation coefficient scoring metric only captures linear relationship.

- If you expect the relationship to be linear, it's fine!
- If you are using a model (e.g. linear regression) that is only capable of learning linear relationships, it's fine! You don't want your feature selection method to give a high score to a column if the model won't be able to learn from it anyway.

Evaluation: scoring functions for filter methods (2)




Figure 7: F-test selects x_1 as the most informative feature, MI selects x_2.

Evaluation: wrapper methods

- Tuned to specific interaction of dataset + model!
- Usually much more expensive (especially considering model hyperparameter tuning...)




Figure 8: Using a wrapper method to evaluate different feature subsets, on the same/similar objective to the "real" final ML model.

An option for some models

- **Embedded methods**: use something built-in to training algorithm (e.g. LASSO regularization). (Not available for KNN!)

Recap

- **Important**: Don't use the test set for feature selection!
- Feature selection approach should "match" the data, model
- Computation is a concern - it won't be possible to optimize everything