

THE UNIVERSITY OF HONG KONG 香港大學 faculty of architecture 建築學院



Evolutionary computation with applications in 3D urban reconstruction 进化计算在城市三维重建中的应用

24 September 2019
Tianjin, China
Civil Aviation University of China



Fan Xue 薛帆

Assistant Professor Dept. of REC / iLab FoA, HKU, HKSAR, PRC



Outline



iLab



Evolutionary computation



Optimization-driven 3D reconstruction



Discussion



0.1 HKUrbanLab, HKU



iLab

◆ Faculty of Architecture, HKU 建筑学院

- 3 Departments: Arch., REC, DUPAD
- 2 Divisions: Landscape Arch., Arch. Conservation
- ♦ HKURBANlab 实验室集群
 - Newly branded research arm of FoA
 - 1 Academician (CAS), 12 full professors
 - 14 labs on
 - Urban planning;Property rights;
 - Chinese architecture; Rural;
 - Health; Sustainability;
 - Fabrication and materials;
 Conservation;
 - o iLab (data and information); Virtual Reality; ...





建築學院



www.arch.hku.hk




0.1 iLab: The urban big data hub



♦ iLab 实验室



- Urban big data hub
- multi-dimensional and multi-disciplinary urban big data collection, storage, analysis, and presentation to inform decisionmaking in urban development



- o Geographical Information Systems (GIS)
- Global Positioning Systems (GPS)
- Urban Remote Sensing (URS)
- Building Information Model (BIM)
- Internet of Things (IoT)
- virtual design and construction (VDC)
- integrated project delivery (IPD)









0.1 iLab



- **♦** Director
 - Prof. Wilson Lu
- Members
 - 1 Assistant Professor, 1 Postdoc Fellow
 - 3 Research Assistants, 6 PhD students
- **♦** Themes 方向
 - Urban big data / urban computing
 - o BIM, GIS, Digital Twin, Text mining, IoT, ...
 - Construction waste
 - Metrics, Behavioral analysis, policy
 - International construction
 - Corporate social responsibility



Lunch-time gathering




0.2 About myself



iLab

◆ A mixed background 背景

- BEng in Automation, CAUC
- MSc in Computer Science, CAUC
 - Advisor: Prof. W Fan
- PhD in System Engineering, HKPU
- PDF/RAP/AP in Construction IT
- ◆ Research interests 方向
 - Urban sensing and computing
 - Automation in construction
 - Applied operations research
 - Machine learning and data visualization



- ◆ Engineering■ ISE, CEM, EIE
- ♦ Computer Science■ AI, DFO, ML
- Economics
 - SCM



0.2 My research projects



iLab


◆ On-going 在研

- PI: HK RGC (17201717, 17200218), HKU-Tsinghua SPF (20300083), HKU (201811159177)
- Co-PI: Key R&D Guangdong (2019B010151001), HKU PTF (102009741)
- Co-I: NSFC (71671156), NSSFC (17ZDA062), HK SPPR (S2018.A8.010.18S), HK PPR (2018.A8.078.18D)



♦ Completed 完成

- PI: HKU (201702159013, 201711159016)
- Co-I: NSFC (60472123)
- ♦ Job vacancy Research Assistant (2~3 openings)
 - \$17,000/month, Transferable to PhD applicant (vision, performance)
 - New updates on my web page (QR code)







1.1 Fundamentals



- **♦** Function
 - A mapping f from a domain set to a range set
- Optimization problem
 - the selection of a *best* element (with regard to some criteria) from *some* set of available alternatives
 - Optimality ← Objective function
 - "Best value" in range $\min f: \mathbb{R}^n \mapsto \mathbb{R}$
 - \circ "Best element" in domain **arg min** f
- ♦ Fitness landscape
 - \blacksquare Appearance of f
 - Peaks/valleys contain the solutions
 - Extremum / extrema








1.1 Fundamentals




- iLab
- Optimality guaranteed methods
 - Linear programming
 - Linear super plane of fitness landscape
 - Gradient-based
 - Stationary points, where the first derivative is zero
 - Brach-and-bound/cut
 - Exhaustive
- ♦ Non-guaranteed methods
 - Monte Carlo
 - Quasi-gradient / Surrogate
 - Heuristics (Fixed rules)
 - Evolutionary / metaheuristics (rules of rules)

Expensive *f*

Inexpensive *f*, escape "local optima



First derivative and stationary points






1.2 Evolutionary computation



iLab

Evolutionary computation (EC)

- A.k.a. metaheuristics
- A set of optimization algorithms
 - Iteration, population
- Often a meta-model "M"
- ♦ A long History
 - From bio-inspiration
 - To meta-model
 - With many variants
 - see AC



Derivations of AC (Xue 2012)

Timeline of early EC (Xue 2012)




1.2 Evolutionary computation (cont.)






- \blacksquare For expensive f
- Escaping local optima
- Approximately a.k.a. derivative-free optimization (DFO)
- Examples
 - CMA: Covariance Matrix Adaptation
 - CMA-ES; Variants of CMA-ES
 - o CMA-VNS (Xue & Shen, 2017)
 - IDEA: Iterated Density Estimation EA
 - Nelder—Mead (downhill simplex)
 - NEWUOA: New Unconstrained Optimization w. quadratic Approxir
 - DIRECT: DIviding RECTangles



Nelder-Mead Source: Wikipedia.org



CMA-ES Source: otoro.net




1.3 Benchmark performance



iLab

- ♦ Black-Box Optimization Benchmark solving without explicit ∇
 - Surrogate methods
 - CMA-ES and its variants are competitive
 - Trust-region methods
 - o DIRECT, NEWUOA, etc.
 - Metaheuristics (GA, PSO, VNS, etc.)
 - Hyper-heuristics, data mining
 - ... and Monte Carlo




Comparison of algorithms for BBOB-2009 (Black-Box Optimization Benchmarking, higher is better) (Auger et al., 2010) *Image courtesy: Inria*



1.3 Benchmarking performance (cont.)



- iLab
- Symmetry detection in 3D point clouds (Xue et al. 2019a)
 - Among 7 algorithms
 - All with default parameters
 - DIRECT was the best
 - NSGA2 was the worst
- ♦ So, overall, we say
 - Quasi-derivative + evolutionary' > Quasi-derivative > evolutionary
 - Due to the characteristics of real world problems



1000

Number of iterations (k)

100

 10^{4}






2.1 3D urban reconstruction



- ♦ 3D Reconstruction
 - Capturing the shape and appearance of real objects to cyber space
- ♦ Abundant 2D/3D urban data from sensors






2.2 An indoor case (Xue et al. 2019b)



- ♦ Input: 3D point cloud
- ♦ Traditional methods
 - Non-semantic: Photogrammetry, 3D mesh
 - Semantic: Segment \rightarrow features \rightarrow class, parameters
- \diamond Modeling f for EC
 - Available 3D components from manufacturer/WWW
 - Best model = best fitting
 - Fitting parameters: 3D location (t_z, t_z, t_z) , 3D rotation (r_z)
 - o $x = (t_z, t_z, t_z, r_z)$, DoF(x) = 4
 - - \circ min f
 - o **s.t.** x in Boundary, C(x) ≤ 0









2.2.2 The overall flow



- **♦** Two inputs
- One output
- ♦ Four modules
 - Autodesk Revit
 - Component op. (Revit plugin) / C++ CLR
 - DFO algorithm (CMA-ES) / C++11
 - $\blacksquare f$ evaluation / C++11
 - **■** (See the message sequencing chart)



- †: In C++, supported by libcmaes (version 0.9.5, available at: https://github.com/beniz/libcmaes)
- 1: In C++, supported by PCL (version 1.8.1, with FLANN, available at: http://pointclouds.org)
- #: In C++-compatible CLR, supported by Autodesk Revit (version 2015 Educational, documents available at: http://www.revitapidocs.com)





2.2.3 f evaluation



iLab

 \diamondsuit *f* is still too expensive

 \blacksquare Computing m points against thousands of triangles

♦ An effective approximation

■ Component point cloud dense sampling (pre-iteration

■ Input cloud down sampling

 $O(m \log m)^{**}$

Iteration

• Transform component with x = O(n)

• Octree voxel down sampling $O(n \log n)^{**}$


o *nndist* for n' points $O(n' \log m')$

• Compute *f*

O(n')

Meta-model Evolution

 $f(X) = RMSE(BIM(X), P_{in})$ $\approx RMSE(P_X, P_{in})$ $\approx RMSE(P_X', P_{in}')$ $= \sqrt{\sum_{p \in P_{in}'} nndist^2(p, P_X')/m'}$ $\approx RMSE(P_{in}', P_X')$ $= \sqrt{\sum_{p \in P_X'} nndist^2(p, P_{in}')/||P_X'||}$





**: optional



2.2.3 Implementation with GUI










2.2.4 3D reconstruction as f descending





- **♦** T=6.448
 - **■** Manual = 330s
- ♦ Iter = 9,000
- ♦ Precision = 1.0
- ♦ Recall = 1.0



2.2.4 Result BIM





(a) A screenshot of the 3D view of the output asbuilt BIM

(b) A visual comparison between the input (grey points) and the output BIM



2.2.4 Demo video (another scene)









2.2.5 Parameter sensitivity analysis




- ♦ Two major parameters
 - Iterations per component (*trails*)
 - *Grid size* of octree voxelization
- **♦** Indicators
 - (a): correctness
 - **■** (b): *f*
 - (c): time consumption
 - (d): trade-off between (a) and (c)



(a) The number of correct components (higher (b) The objective function (lower is better) is better)



(c) The time cost (in log₁₀, lower is better)







2.3.1 Image-based reconstruction (Xue et al. 2018)



- Problem
 - To fit 3D object to 2D
- \diamondsuit f = dissimilarity
 - \blacksquare arg max f(x)=SSIM(t(x), m)
- ♦ Algorithm
 - CMA-ES
- **♦** Performance
 - Good
 - ~1 trails/s








2.3.2 Opt in algorithms (Xue et al. 2019c)



- Problem
 - Reconstructing repetitive objects
- \diamond Same f to 2.2
- **♦** Algorithm
 - → Multi-Modal Optimization (MMO)
 - NMMSO
- **Performance**
 - \blacksquare Recall \rightarrow + 10%
 - Precision \rightarrow + 10%
 - Time \rightarrow -35%







2.3.3 Topology reconstruction: Symmetry (Xue et al. 2019d)



- Problem
 - Detecting symmetry in point cloud
- f = distance
 - arg min $f = RMSE(C(x), C) \approx RMSE(C'(x), C')$
- Algorithm
 - CMA-ES
- **♦** Performance
 - Time = 98.6s
 - \blacksquare PCR = 93.7%








2.3.4 Clustering similar objects (Xue et al. 2019e)



iLab

Problem

- To cluster similar cloud patches
- \diamondsuit f = dissimilarity
 - \blacksquare min $f = RMSE(C_1(x), C_2)$
- **♦** Algorithm
 - CMA-ES
- Performance
 - ~0.6s for each pair



城市点云中的目标聚类





3.1 A recap



- ♦ "Any evidence-based decision making can be formulated as an optimization problem"
- ♦ Evolutionary computation
 - A long history
 - Still a thriving domain
 - Conferences: GECCO, IEEE CEC
 - Good to handle expensive, complex tests
 - E.g., 3D urban reconstruction
 - Especially recent algorithms





3.2 Modeling for EC



- \diamond To design f
 - Supporting functions
- ♦ To set up domain
- ♦ To validate range
- ♦ To apply EC
- ♦ To analyze parameter sensitivity



References



- il ab
- **Xue, F.**, Lu, W., Chen, K. (2018). Automatic generation of semantically rich as-built building information models using 2D images: A derivative-free optimization approach. *Computer-Aided Civil and Infrastructure Engineering*, *33*(11), 926-942.
- **Xue, F.**, Lu, W., Webster, C. J., & Chen, K. (2019a). A derivative-free optimization-based approach for detecting architectural symmetries from 3D point clouds. *ISPRS Journal of Photogrammetry and Remote Sensing*, 148, 32-40.
- **Xue, F.**, Lu, W., Chen, K., & Zetkulic, A. (2019b). From Semantic Segmentation to Semantic Registration: Derivative-Free Optimization—Based Approach for Automatic Generation of Semantically Rich As-Built Building Information Models from 3D Point Clouds. *Journal of Computing in Civil Engineering*, *33*(4), 04019024.
- **Xue, F.**, Lu, W., Chen, K., & Webster, C. J. (2019c). BIM reconstruction from 3D point clouds: A semantic registration approach based on multimodal optimization and architectural design knowledge, *Advanced Engineering Informatics*, 42, 100965.
- **Xue, F.**, Chen, K., & Lu, W. (2019d). Architectural symmetry detection from 3D urban point clouds: A derivative-free optimization (DFO) approach. In *Advances in Informatics and Computing in Civil and Construction Engineering* (pp. 513-519). Springer, Cham.
- **Xue, F.**, Chen, K., & Lu, W. (2019e). Understanding unstructured 3D point clouds for creating digital twin city: An unsupervised hierarchical clustering approach. *CIB World Building Congress* 2019.



THE UNIVERSITY OF HONG KONG 香港大學 faculty of architecture 建築學院



