

# Lecture 2 - Replicating Mian and Sufi

UCLA - Econ 221 - Fall 2018

*François Geerolf*

## Contents

<b>Introduction</b>	<b>1</b>
<b>1 Data</b>	<b>1</b>
1.1 Housing Supply elasticity . . . . .	1
1.2 Crosswalk . . . . .	2
1.3 House Prices . . . . .	2
1.4 Unemployment . . . . .	3
1.5 Employment . . . . .	4
1.6 Labor Force . . . . .	4
1.7 CBP . . . . .	5
1.8 Merge into Final Data . . . . .	6
<b>2 Regressions</b>	<b>6</b>
2.1 OLS . . . . .	6
2.2 Matching . . . . .	7
2.3 IV Regressions . . . . .	8

## Introduction

During this lecture, we do some “hands-on” data work based on the following academic articles:

Saiz, Albert. “The Geographic Determinants of Housing Supply.” The Quarterly Journal of Economics 125, no. 3 (August 1, 2010): 1253–96.

Mian, Atif, Kamalesh Rao, and Amir Sufi. “Household Balance Sheets, Consumption, and the Economic Slump.” The Quarterly Journal of Economics 128, no. 4 (November 1, 2013): 1687–1726.

Mian, Atif, and Amir Sufi. “What Explains the 2007–2009 Drop in Employment?” Econometrica 82, no. 6 (November 1, 2014): 2197–2223.

```
rm(list = ls())
pklist <- c("curl", "tidyverse", "foreign", "AER")
source("https://fgeerolf.github.io/code/load-packages.R")
```

## 1 Data

### 1.1 Housing Supply elasticity

```
curl_download("http://real.wharton.upenn.edu/~saiz/SUPPLYDATA.zip",
  destfile = "SUPPLYDATA.zip",
  quiet = FALSE)

# Unzip
unzip("SUPPLYDATA.zip")
```

```

unlink("SUPPLYDATA.zip")
unlink("readme.txt")
# Read in dta. Needs package foreign
data.Saiz2010 <- read.dta("HOUSING_SUPPLY.dta")
unlink("HOUSING_SUPPLY.dta")

```

## 1.2 Crosswalk

```

nber.crosswalk <- read.csv("http://www.nber.org/cbsa-msa-fips-ssa-county-crosswalk/cbsatocountycrosswalk.csv")

nber.crosswalk.extract <- nber.crosswalk %>%
  select(msa, cbsa) %>%
  head

```

## 1.3 House Prices

```

fhfa.data <- read.csv("https://www.fhfa.gov/DataTools/Downloads/Documents/HPI/HPI_master.csv")

fhfa.data.monthly <- fhfa.data %>%
  filter(frequency == "monthly") %>%
  mutate(date = yr + (period - 1)/12) %>%
  select(-yr, -period)

fhfa.data.quarterly <- fhfa.data %>%
  # Keep only quarterly
  filter(frequency == "quarterly",
         hpi_type == "traditional",
         hpi_flavor == "all-transactions") %>%
  # create new date variable collapsing year and quarter
  mutate(date = yr + (period - 1)/4) %>%
  # remove year and quarter
  select(-yr, -period) %>%
  # Keep only MSA geographies
  filter(level == "MSA") %>%
  select(place_name, place_id, date, index_nsa, index_sa)

fhfa.data.quarterly.extract <- fhfa.data.quarterly %>%
  filter(date %in% c(2006, 2009)) %>%
  rename(value = index_nsa) %>%
  select(-index_sa) %>%
  mutate(date = paste0("year", date)) %>%
  spread(date, value) %>%
  mutate(houseprice_d1ln = log(year2009) - log(year2006))

# Glance at data
fhfa.data.quarterly.extract %>%
  mutate(fips_msa = place_id %>% paste %>% as.numeric) %>%
  select(fips_msa, houseprice_d1ln) %>%

```

```
head
```

```
## fips_msa houseprice_d1ln
## 1 10180 0.12489273
## 2 10420 -0.05606812
## 3 10580 0.05390098
## 4 10500 0.06902736
## 5 10540 0.09718197
## 6 10740 0.08403987
```

## 1.4 Unemployment

```
bls.laus.current <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.1.CurrentS")
bls.laus.series <- read.delim("https://download.bls.gov/pub/time.series/la/la.series")
bls.la.area.type <- read.delim("https://download.bls.gov/pub/time.series/la/la.area_type")
bls.la.05.09 <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.0.CurrentU05-09")
bls.laus.area.code <- read.delim("https://download.bls.gov/pub/time.series/la/la.area")
```

```
bls.la.05.09.new <- bls.la.05.09 %>%
  filter(period != "M13") %>%
  mutate(month = period %>% substr(2, 3) %>% as.numeric,
         date = year + (month-1)/12) %>%
  select(-month, -year, -period, -footnote_codes) %>%
  left_join(bls.laus.series, by = "series_id") %>%
  filter(area_type_code == "B") %>%
  filter(date %in% c(2006, 2009),
         measure_code == 3) %>%
  mutate(date = paste0("year", date)) %>%
  select(area_code, date, value) %>%
  spread(date, value) %>%
  mutate(year2006 = year2006 %>% paste %>% as.numeric,
         year2009 = year2009 %>% paste %>% as.numeric,
         unemp_d1 = year2009 - year2006) %>%
  mutate(area_code = area_code %>% paste,
         fips_msa = area_code %>% substr(5, 9) %>% as.numeric)
```

```
## Warning: Column `series_id` joining factors with different levels, coercing
## to character vector
```

```
bls.la.05.09.new %>%
  select(fips_msa, unemp_d1) %>%
  head
```

```
## fips_msa unemp_d1
## 1 11500 4.8
## 2 12220 4.8
## 3 13820 4.5
## 4 19300 4.6
## 5 19460 5.6
## 6 20020 4.7
```

## 1.5 Employment

Link to data BLS LAUS: <https://download.bls.gov/pub/time.series/la>

Measures: <https://download.bls.gov/pub/time.series/la/la.measure>

```
bls.laus.current <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.1.CurrentS")
bls.laus.series <- read.delim("https://download.bls.gov/pub/time.series/la/la.series")
bls.la.area.type <- read.delim("https://download.bls.gov/pub/time.series/la/la.area_type")
bls.la.05.09 <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.0.CurrentU05-09")
bls.laus.area.code <- read.delim("https://download.bls.gov/pub/time.series/la/la.area")
```

```
bls.la.05.09.new.emp <- bls.la.05.09 %>%
  filter(period != "M13") %>%
  mutate(month = period %>% substr(2, 3) %>% as.numeric,
         date = year + (month-1)/12) %>%
  select(-month, -year, -period, -footnote_codes) %>%
  left_join(bls.laus.series, by = "series_id") %>%
  filter(area_type_code == "B") %>%
  filter(date %in% c(2006, 2009),
         measure_code == 5) %>%
  mutate(date = paste0("year", date)) %>%
  select(area_code, date, value) %>%
  spread(date, value) %>%
  mutate(year2006 = year2006 %>% paste %>% as.numeric,
         year2009 = year2009 %>% paste %>% as.numeric,
         emp_d1ln = log(year2009) - log(year2006)) %>%
  mutate(area_code = area_code %>% paste,
         fips_msa = area_code %>% substr(5, 9) %>% as.numeric)
```

```
## Warning: Column `series_id` joining factors with different levels, coercing
## to character vector
```

```
bls.la.05.09.new.emp %>%
  select(fips_msa, emp_d1ln) %>%
  head
```

```
##   fips_msa    emp_d1ln
## 1   11500 -0.035867730
## 2   12220 -0.034828067
## 3   13820 -0.048796762
## 4   19300  0.007244928
## 5   19460 -0.048428114
## 6   20020 -0.060530114
```

## 1.6 Labor Force

Link to data BLS LAUS: <https://download.bls.gov/pub/time.series/la>

Measures: <https://download.bls.gov/pub/time.series/la/la.measure>

```
bls.laus.current <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.1.CurrentS")
bls.laus.series <- read.delim("https://download.bls.gov/pub/time.series/la/la.series")
bls.la.area.type <- read.delim("https://download.bls.gov/pub/time.series/la/la.area_type")
bls.la.05.09 <- read.delim("https://download.bls.gov/pub/time.series/la/la.data.0.CurrentU05-09")
bls.laus.area.code <- read.delim("https://download.bls.gov/pub/time.series/la/la.area")
```

```

bls.la.05.09.new.lf <- bls.la.05.09 %>%
  filter(period != "M13") %>%
  mutate(month = period %>% substr(2, 3) %>% as.numeric,
         date = year + (month-1)/12) %>%
  select(-month, - year, -period, - footnote_codes) %>%
  left_join(bls.laus.series, by = "series_id") %>%
  filter(area_type_code == "B") %>%
  filter(date %in% c(2006, 2009),
         measure_code == 6) %>%
  mutate(date = paste0("year", date)) %>%
  select(area_code, date, value) %>%
  spread(date, value) %>%
  mutate(year2006 = year2006 %>% paste %>% as.numeric,
         year2009 = year2009 %>% paste %>% as.numeric,
         lf_d1ln = log(year2009) - log(year2006)) %>%
  mutate(area_code = area_code %>% paste,
         fips_msa = area_code %>% substr(5, 9) %>% as.numeric)

```

```

## Warning: Column `series_id` joining factors with different levels, coercing
## to character vector

```

```

bls.la.05.09.new.emp %>%
  select(fips_msa, emp_d1ln) %>%
  head

```

```

##   fips_msa    emp_d1ln
## 1   11500 -0.035867730
## 2   12220 -0.034828067
## 3   13820 -0.048796762
## 4   19300  0.007244928
## 5   19460 -0.048428114
## 6   20020 -0.060530114

```

## 1.7 CBP

```

curl_download("https://www2.census.gov/programs-surveys/cbp/datasets/2009/cbp09co.zip",
              destfile = "cbp09co.zip",
              quiet = FALSE)

```

```

unzip("cbp09co.zip")
unlink("cbp09co.zip")

```

```

cbp.2009 <- read.delim("cbp09co.txt", sep = ",")
unlink("cbp09co.txt")

```

```

curl_download("https://www2.census.gov/programs-surveys/cbp/datasets/2006/cbp06co.zip",
              destfile = "cbp06co.zip",
              quiet = FALSE)

```

```

unzip("cbp06co.zip")
unlink("cbp06co.zip")

```

```

cbp.2006 <- read.delim("cbp06co.txt", sep = ",")

```

```
unlink("cbp06co.txt")
```

## 1.8 Merge into Final Data

```
final <- bls.la.05.09.new %>%
  left_join(bls.la.05.09.new.emp, by = "fips_msa") %>%
  left_join(bls.la.05.09.new.lf, by = "fips_msa") %>%
  select(fips_msa, unemp_d1, emp_d1ln, lf_d1ln) %>%
  left_join(fhfa.data.quarterly.extract %>%
    mutate(fips_msa = place_id %>% paste %>% as.numeric) %>%
    select(fips_msa, houseprice_d1ln))

## Joining, by = "fips_msa"
```

## 2 Regressions

### 2.1 OLS

We run:

$$\Delta_{06-09}U_i = \Delta_{06-09}HP_i + \epsilon_i$$

```
final %>%
  lm(unemp_d1 ~ houseprice_d1ln, data = .) %>%
  summary

##
## Call:
## lm(formula = unemp_d1 ~ houseprice_d1ln, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.4302  -1.1529  -0.1800   0.9535  11.5579
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   3.27994    0.09661   33.95  <2e-16 ***
## houseprice_d1ln -6.61945    0.55298  -11.97  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.822 on 355 degrees of freedom
## (38 observations deleted due to missingness)
## Multiple R-squared:  0.2876, Adjusted R-squared:  0.2856
## F-statistic: 143.3 on 1 and 355 DF, p-value: < 2.2e-16

final %>%
  lm(emp_d1ln ~ houseprice_d1ln, data = .) %>%
  summary

##
## Call:
```

```
## lm(formula = emp_d1ln ~ houseprice_d1ln, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.273318 -0.023605  0.001109  0.026029  0.131301
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)   -0.001993   0.002330  -0.855   0.393
## houseprice_d1ln  0.069512   0.013336   5.212 3.17e-07 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.04393 on 355 degrees of freedom
## (38 observations deleted due to missingness)
## Multiple R-squared:  0.07109,    Adjusted R-squared:  0.06847
## F-statistic: 27.17 on 1 and 355 DF,  p-value: 3.172e-07
```

```
final %>%
  lm(lf_d1ln ~ houseprice_d1ln, data = .) %>%
  summary
```

```
##
## Call:
## lm(formula = lf_d1ln ~ houseprice_d1ln, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.140662 -0.021815 -0.000865  0.022033  0.134941
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    0.033499   0.001888  17.739 <2e-16 ***
## houseprice_d1ln -0.005143   0.010810  -0.476   0.635
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.03561 on 355 degrees of freedom
## (38 observations deleted due to missingness)
## Multiple R-squared:  0.0006372,    Adjusted R-squared:  -0.002178
## F-statistic: 0.2263 on 1 and 355 DF,  p-value: 0.6345
```

## 2.2 Matching

Final is fips\_msa = 10180 for Abilene, TX

Crosswalk is cbsa = fips\_msa

```
nber.crosswalk %>%
  select(fips_msa = cbsa, msa) %>%
  head
```

```
##   fips_msa  msa
## 1   33860 5240
## 2    NA 5160
```

```
## 3      NA      1
## 4    13820      1
## 5    13820 1000
## 6      NA      1
```

```
data.Saiz2010 %>%
  rename(msa = msanecma) %>%
  head
```

```
##   msa population                msaname      WRLURI
## 1  40    126441      Abilene, TX (MSA)  0.10083067
## 2  80    695781      Akron, OH (PMSA)  0.06756011
## 3 120    120855      Albany, GA (MSA) -0.49810675
## 4 160    876129 Albany-Schenectady-Troy, NY (MSA) -0.09178428
## 5 200    714554      Albuquerque, NM (MSA)  0.37347099
## 6 220    126443      Alexandria, LA (MSA) -1.67668915
##   FLAT_SHARE_50_15 S_LAND_50      lu11      lu91      lu92
## 1                99        100 0.008205139 5.833476e-05 0.0012621708
## 2                99        100 0.018677070 2.790428e-02 0.0079509728
## 3               100        100 0.013510201 1.063221e-01 0.0074655255
## 4                81        100 0.021399631 1.864739e-02 0.0032548599
## 5                89        100 0.003276727 2.593219e-03 0.0004627457
## 6               100        100 0.039517049 1.427566e-01 0.0097358040
##      unaval elasticity
## 1 0.01952564  3.094851
## 2 0.06453232  2.585493
## 3 0.12729786  3.392287
## 4 0.23330188  1.700388
## 5 0.11633269  2.112380
## 6 0.19200943  7.148086
```

## 2.3 IV Regressions

```
final %>%
  left_join(nber.crosswalk %>%
    select(fips_msa = cbsa, msa),
    by = "fips_msa") %>%
  left_join(data.Saiz2010 %>%
    select(msa = msanecma, elasticity)) %>%
  ivreg(unemp_d1 ~ houseprice_d1ln | elasticity, data = .) %>%
  summary
```

```
## Joining, by = "msa"
##
## Call:
## ivreg(formula = unemp_d1 ~ houseprice_d1ln | elasticity, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.5619  -0.8819  -0.1355   0.6864  11.5840
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
```



```
## (Intercept)      3.16272      0.06899  45.844   <2e-16 ***
## houseprice_d1ln -4.08364      1.94671  -2.098    0.0363 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.676 on 603 degrees of freedom
## Multiple R-Squared:  0.1815, Adjusted R-squared:  0.1801
## Wald test:    4.4 on 1 and 603 DF, p-value: 0.03635
```

```
final %>%
  left_join(nber.crosswalk %>%
    select(fips_msa = cbsa, msa),
    by = "fips_msa") %>%
  left_join(data.Saiz2010 %>%
    select(msa = msanecma, elasticity)) %>%
  lm(houseprice_d1ln ~ elasticity, data = .) %>%
  summary
```

```
## Joining, by = "msa"
##
## Call:
## lm(formula = houseprice_d1ln ~ elasticity, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.87417 -0.03136  0.02299  0.07690  0.21724
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -0.065042   0.012048  -5.398 9.68e-08 ***
## elasticity   0.027851   0.004256   6.543 1.29e-10 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1315 on 603 degrees of freedom
## (460 observations deleted due to missingness)
## Multiple R-squared:  0.0663, Adjusted R-squared:  0.06475
## F-statistic: 42.82 on 1 and 603 DF, p-value: 1.286e-10
```

```
final %>%
  left_join(nber.crosswalk %>%
    select(fips_msa = cbsa, msa),
    by = "fips_msa") %>%
  left_join(data.Saiz2010 %>%
    select(msa = msanecma, elasticity)) %>%
  select(elasticity) %>%
  summary
```

```
## Joining, by = "msa"
##
##      elasticity
## Min.      : 0.6728
## 1st Qu.: 1.6293
## Median : 2.4610
## Mean    : 2.5492
```

```
## 3rd Qu.: 3.1189
## Max.    :12.1480
## NA's    :446

final %>%
  left_join(nber.crosswalk %>%
    select(fips_msa = cbsa, msa),
    by = "fips_msa") %>%
  left_join(data.Saiz2010 %>%
    select(msa = msanecma, elasticity)) %>%
  lm(unemp_d1 ~ houseprice_d1ln, data = .) %>%
  summary

## Joining, by = "msa"

##
## Call:
## lm(formula = unemp_d1 ~ houseprice_d1ln, data = .)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -10.3229  -0.9963  -0.0805   0.8672  11.6555
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    3.18794    0.05298   60.17  <2e-16 ***
## houseprice_d1ln -6.77534    0.40804  -16.60  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 1.639 on 970 degrees of freedom
## (93 observations deleted due to missingness)
## Multiple R-squared:  0.2213, Adjusted R-squared:  0.2205
## F-statistic: 275.7 on 1 and 970 DF, p-value: < 2.2e-16
```