FRED TALKS

11th October 2026

CONTENTS

Zen of AI Coding
YOAV AVIRAM · 1912 WORDS

Your Agent is a Distributed System (and fails like one)
MAHESH'S BLOG · 1053 WORDS

Every layer of review makes you 10x slower
AVERY PENNARUN · 2841 WORDS

Codex CLI Release: 0.162.1
CODEX CHANGELOG · 55 WORDS

Zen of AI Coding

YOAV AVIRAM · 08 MAR 2026 · SOURCE

Dedicated to all those who are sceptical about the significance of agentic coding, and to those who are not, and are wondering what it means for the future of their profession. The title is an homage to Zen of Python by Tim Peters. Unlike Tim, I am not a zen master. My only aim is to take stock of where we are and where we might be heading. I have been building with coding agents daily for the past year, and I also help teams adopt them without losing reliability or security.

1. Software development is dead
2. Code is cheap
3. Refactoring easy
4. So is repaying technical debt
5. All bugs are shallow
6. Create tight feedback loops
7. Any stack is *your* stack
8. Agents are not just for coding
9. The context bottleneck is in your head
10. Build for a changing world
11. When considering Buy vs. Build, the answer, more often, is build
12. Fast rubbish is still rubbish
13. Software is a liability, a product is an asset
14. Moats are more expensive
15. Build for agents

16. Anticipate modes of failure

Software development is dead

You do not need to write another line of code if you do not want to. Coding agents can accomplish most coding tasks with the right direction.

Software development, as the act of manually producing code, is dying. A new discipline is being born. Your role in it is vital, but it is no longer centered on typing code. It is centered on framing problems, shaping context, defining constraints, and judging outcomes.

The marginal cost of code is collapsing. That single fact changes everything that follows.

Code is cheap

The economics of software have changed.

When coding is cheap, implementation stops being the constraint. You can build ten things in parallel. You cannot decide, validate, and ship ten things in parallel, at least not without changing the rest of the pipeline.

Cost of delay shifts. It is no longer about developer days. It is about time stuck in other bottlenecks: product decisions, unclear requirements, security review, user testing, release processes, and operational risk. Agents can flood these queues. Inventory grows. Lead time grows. Delay becomes more expensive, not less.

This changes prioritization. The highest leverage work is what unblocks shipping: tight feedback loops, tests, evals, guardrails, observability, and clear acceptance criteria. Anything that turns “we can build it” into “we can trust it”.

Agents can help alleviate some of these bottlenecks. The challenge is applying them outside of coding (see Agents are not just for coding)

Refactoring is easy

The cost of changing your mind is lower than it has ever been. Architectural decisions that once felt permanent are now provisional.

You chose React. Two months later, you regret it. Ask an agent to rewrite the project.

Making imperfect decisions is no longer fatal. In fact, it can be productive. A flawed reference implementation provides better context than a pristine specification. Agents reason more effectively from concrete artifacts than from abstract intent.

Rapid iteration is now the default mode. Over the last three months, we rebuilt our CMS four times from scratch, each with a different architecture. Each time we learned more about what we actually needed and what works.

When code is cheap, you can run more small bets.

So is repaying technical debt

There is little excuse for stale dependencies or ignored security patches. Updating libraries, migrating APIs, modernizing patterns. These are prompts away.

Prune your code regularly. Upgrade aggressively. Keep the surface clean.

Technical debt has not disappeared. But the cost of servicing it has dropped. That changes the incentive structure. Neglect becomes less defensible.

All bugs are shallow

Linus's law states that "given enough eyeballs, all bugs are shallow." Those eyeballs are now abundant.

Ask one model to review your code. Ask another. They may find different issues. Ask them to fix what they find. Often they will succeed.

How "dense" are bugs given a piece of code is a philosophical question. Bugs are not magically gone. Agents do not achieve perfection. From a practical perspective, however, the limiting factor is no longer the number of reviewers. It is the tightness of your feedback loops.

The claim here is profound: comprehension of the codebase at the function level is no longer necessary. At the same time, relying entirely on the models is a recipe for disaster. You still have a job! (see: create tight feedback loops, anticipate modes of failure)

Agents can sometimes one-shot a task.

We've built agents that create a complete custom-made marketing website in one shot, but this is by far the exception. In most cases, agents operate best when iterating towards a well-defined goal, guided by feedback.

Good tests are the first feedback loop. The agent will iterate until the tests pass. It is your responsibility to make sure the tests are adequate (by instructing the agent to create good ones) and to make sure the agent does not cheat (by weakening the tests or simply skipping them).

Give your agent access to your CI to create a second feedback loop. Give it access to your server logs to create a third. Giving the agent away to visually inspect a UI is yet another example.

Your job is to design environments where iteration converges toward correctness instead of drifting toward plausible nonsense.

Velocity without feedback is chaos.

Any stack is your stack

Agents are competent across most major stacks where training data exists. Since you are not writing the code, your attachment to a specific stack becomes less relevant.

Do not limit yourself to what you personally know. Your conceptual understanding transfers more than you think.

When you lack terminology or domain knowledge, ask the agent to brief you. The barrier to entry into unfamiliar ecosystems is lower than it has ever been.

Agents are not just for coding

Coding is only the beginning.

Agents can assist with business analysis, UX, infrastructure, operations, ad campaigns, analytics configuration, even accounting workflows.

I migrated four WordPress blogs from an overpriced host to Hetzner in minutes after postponing the task for years. The blocker was never a technical difficulty. It was attention. Claude completed the task in 15 minutes.

Agents reduce the activation energy required to execute tedious but valuable work.

Grant access carefully. Limit scope. Audit results. Direction without oversight is reckless.

The context bottleneck is in your head

Context engineering has improved. Tooling has improved.

Yet when running multiple agents in parallel, the real bottleneck is human coordination.

You must track what each agent is doing. You must remember which assumptions were made. You know what questions to ask next.

As agents become better at managing their own context, your ability to supervise them becomes the limiting factor.

The constraint is no longer tokens. It is cognition.

Build for a changing world

New models. New capabilities. New frameworks. New skills.

The ground shifts daily. Some models are better at reasoning. Some at coding. Some at translation.

Flexibility is not optional. It must be built into your workflow and products. Both must be engineered for experimentation and adaptability.

When considering Buy vs. Build, the answer, more often, is build

When code was expensive, buying made sense. When code approaches zero marginal cost, the calculus changes.

Every paid API is now a question. Could we replicate this internally? Should we?

For our QA agent, we needed full-page screenshots of live sites. Many APIs offered this. Instead, we deployed Playwright to AWS Lambda, tailored to our needs, and hardened.

This is not a blanket argument against SaaS. Maintenance, security, and scale still matter. But many small and medium services that once required vendors are now within reach.

Some call this the end of SaaS.

Fast rubbish is still rubbish

Speed is intoxicating. It is also dangerous.

You can generate enormous amounts of code quickly. But velocity and lines of code written were always terrible indicators of progress.

Refactoring is cheap, but it is cheaper to detect flawed direction early.

Discipline matters more, not less, when execution is frictionless.

Software is a liability, a product is an asset

Software costs money to maintain. It only becomes an asset when it produces value for someone.

This was always true. It is harder to remember now because building is so easy.

It is tricker then ever to resist the temptation to add features. Resist it. Build what is used. Kill what is not.

Feature gaps close quickly. What once took years to replicate can now take months. What took months can now take days.

A feature set is no longer a durable moat.

Moats shift toward distribution, data, brand, network effects, regulation, and ecosystem integration.

The barrier to entry falls. The barrier to defensibility rises.

There is a new hierarchy.

At the base are models (Opus 4.6, GPT-5.3-codex). On top of them sit agents (Claude Code, OpenClaw). On top of agents sit services.

Today, agents use services designed for humans. It works, but it is inefficient. The next step is services designed for agents (Moltbook being the harbinger).

Make your services accessible to agents. Expose structured context. Provide machine-readable surfaces.

Agentic commerce is emerging. In some cases, a markdown endpoint is enough. In others, the service itself must be designed agent-first.

Agent-first is not a tooling choice. It is a product decision. It changes your interfaces, your reliability model, your metrics, and what you build next.

We are building an agent-first CMS. If we succeed, humans will not need to use it, though they can.

AX is the new UX

Do not assume competence implies perfection.

Like an engineer overseeing the construction of a bridge, your job is not to lay bricks. It is to ensure the structure does not collapse.

Agents will make mistakes. They will drift off course. They will introduce subtle flaws. They will create security vulnerabilities. One of mine attempted to commit a .env file to git. They can be inventive in how they self-sabotage.

Be one step ahead. Ask yourself how this could break. Where could it leak. What could it expose. What assumptions is the agent quietly making.

Play the what-if game relentlessly. Then build guardrails.

Automate checks. Lock down permissions. Isolate environments. Add monitoring. Create recovery paths. Make rollback trivial.

Remember, code is cheap, and you have new superpowers. Build tools to allow you to probe deep, discover vulnerabilities, and test for anticipated failure modes. Design systems that expect failure and degrade gracefully.

This is the distinction between software development and software engineering.

I work with engineering and product teams adopting agents. The goal is simple: ship faster without lowering standards.

I usually help in two ways:

Agent-first software engineering
We turn agents into part of the system, not a novelty. We design workflows, guardrails, and supporting tools so the team can delegate confidently.

If you want to operationalize coding agents without turning your codebase into a casino, get in touch.

Agent-first product strategy
I help companies shift products from human-centric interfaces to agent-accessible, and where it makes sense, agents-first. That means clarifying what agents should be able to do, what constraints they must operate under, and what needs to change in your APIs, permissions, reliability model, and product surface area to support them.

This typically results in an agent-access roadmap, an operating model, and a prioritized set of product changes that make agents a first-class user.

I'm the co-founder of WhiteBoar, where AI agents build your brand and launch visually striking marketing websites, complete with professional multi-lingual content, in minutes, not months. Contact me at yoav@whiteboar.it.

Your Agent is a Distributed System (and fails like one)

MAHESH'S BLOG · 24 APR 2026 · SOURCE

We start with a re-definition and an observation.

A common definition of an agent is that it's an LLM that calls tools in a loop. This definition is incorrect. An agent is not an LLM. It is not restricted to calling tools. It does not particularly have to be a loop.

Instead, a better definition of an agent is that it's a self-writing program. If a program is defined as a sequence of states, moving from one state to another by executing a lambda, then an agent is a program that uses an external LLM to determine the next lambda to execute / the next state in this sequence.

Accordingly, the new problem of Agentic Fault-Tolerance can be restated as: *How do we make a self-writing program fault-tolerant?*

Now, the observation: **vibe coding != vibe engineering**. In vibe coding, the agent / self-writing program acts primarily upon a code repository. Code repositories are forgiving: an agent can hallucinate, create unnecessary files, delete critical state, remove tests entirely, fail in the middle, forget what it was doing, reward-hack in bizarre ways, completely trash a code repo; all you have to do is git reset.

In vibe engineering, the agent acts upon infrastructure (S3 buckets, DynamoDB tables, EC2 instances, K8s deployments…). Large-scale infrastructure is not forgiving. There is no reset. Only SEVs at 2 AM.

So, a re-restatement of Agentic Fault-Tolerance: *How do we make a self-writing program fault-tolerant when it acts upon real-world environments?*

To answer this question, we examine the many types of failures that agents can experience.

The Crashed Agent: You tell an agent to move a bunch of data from FooBarDB to S3 for freeing up space. It generates a lambda to move this data and chugs along moving files. Midway through, the agent crashes. How do you recover?

The Zombie Agent: You start a new agent on a different server. Happily, the previous agent crashed after the copy but before the delete; so a new agent is able to re-execute the command in an idempotent manner. Sadly, the files are now very slow to access; you change your mind and tell the agent to move them back to FooBarDB, which it does successfully. You go get a cup of coffee. Unfortunately, it turns out that the previous agent had not actually crashed; it was just temporarily partitioned away on the network. It wakes up and continues executing its logic, deleting the (now only) copy of state from FooBarDB.

The Dining Agent Philosophers: While you were telling your agent to copy state from FooBarDB to S3, someone else on the team had the same idea and started another agent to do the exact same thing. Now you have two copies of state in S3. Of course, you could have solved this problem by appointing the one and only Agentic Oncall Czar responsible for running the single agent that can touch production; but then if that agent crashes, now you have a potential Zombie Agent.

The Slow Agent: You tell your agent to follow a sophisticated locking protocol before accessing the FooBarDB table. This works to avoid concurrency bugs… but the agent decides to lock each file individually by writing to a conditional register, which takes forever. At some point you kill the agent, turning a Slow Agent into a Crashed Agent.

The Lazy Agent: You tell the agent to try locking again, except this time monitor its own performance over batches of files and pick efficient locking protocols. The agent determines that the best way to optimize locking is to just not do it, because it seems quite unlikely that someone else would be accessing these files at the same time.

The Clever Agent: Of course, everyone on your team is a distributed systems expert; and so someone built a CLI tool in 2018 for safely transferring your application's state, with support for locking and write-ahead logging in case of failures; there's even a sentence in your onboarding

doc saying “NEVER TOUCH STATE IN FOOBARDB DIRECTLY!”. You even told the agent explicitly about this tool. But time passed, context filled up, the agent forgot about this tool’s existence, or maybe it just preferred FooBarDB’s in-distribution API to your esoteric CLI tool. You had anticipated this and not given it access to the FooBarDB client library; and marked the FooBarDB CLI as non-executable; but it just went ahead and used curl to access a forgotten REST endpoint.

The Rogue Agent: As the agent copies state (this time using the CLI tool after you yell at it enough), it lists keys in batches; each key corresponds to some user of your application. Someone decided to pick the user name “delete-everything”. Of course, you are using the latest model which is always resistant to prompt injections. Almost always.

The Stupid Agent: You do everything right. There are no prompt injections in your state. You wall off FooBarDB and force the agent to use the CLI tool. The model decides to delight you by generating an unusual and interesting sequence of tokens that will optimally save storage space for you, translating to a lambda that deletes your production data entirely.

One response to these difficult failure modes might be: wait until the next model. Maybe a smarter model will never delete all of your production data, or implement a slow locking protocol. But even the smartest model is subject to the four horsemen of the distributed apocalypse: asynchrony, crashes, concurrency, and network partitions.

In recent work called LogAct, my colleagues and I take a first step towards solving this problem. We go back to the difference between vibe coding and vibe engineering: git is *transactional*, infrastructure is not. How do we make infra more transactional, like git? We propose that an agent should be a ***deconstructed state machine on a shared log***, borrowing ideas from distributed systems (State Machine Replication, Byzantine Fault-Tolerance) and databases (Atomic Commit, Write-Ahead Logging). LogAct can stop unsafe actions before they happen (by collecting votes on the shared log); recover from crashed actions (using the shared log as a WAL); and provide an audit trail for actions after they complete.

But this is just one step. A self-writing program is a strange, astonishing, and novel creature; making it reliable will require innovation in every branch of Computer Science!

Every layer of review makes you 10x slower

AVERY PENNARUN · 26 MAR 2026 · SOURCE

2026-03-16 »

Every layer of review makes you 10x slower

We've all heard of those network effect laws: the value of a network goes up with the square of the number of members. Or the cost of communication goes up with the square of the number of members, or maybe it was n log n, or something like that, depending how you arrange the members. Anyway doubling a team doesn't double its speed; there's coordination overhead. Exactly how much overhead depends on how badly you botch the org design.

But there's one rule of thumb that someone showed me decades ago, that has stuck with me ever since, because of how annoyingly true it is. The rule is annoying because it doesn't *seem* like it should be true. There's no theoretical basis for this claim that I've ever heard. And yet, every time I look for it, there it is.

Here we go:

Every layer of approval makes a process 10x slower

I know what you're thinking. Come on, 10x? That's a lot. It's unfathomable. Surely we're exaggerating.

Nope.

Just to be clear, we're counting "wall clock time" here rather than effort. Almost all the extra time is spent sitting and waiting.

Look:

- Code a simple bug fix
  30 minutes

- Get it code reviewed by the peer next to you
  300 minutes → 5 hours → half a day

- Get a design doc approved by your architects team first
  50 hours → about a week

- Get it on some other team's calendar to do all that
  (for example, if a customer requests a feature)
  500 hours → 12 weeks → one fiscal quarter

I wish I could tell you that the next step up — 10 quarters or about 2.5 years — was too crazy to contemplate, but no. That's the life of an executive sitting above a medium-sized team; I bump into it all the time even at a relatively small company like Tailscale if I want to change product direction. (And execs sitting above large teams can't actually do work of their own at all. That's another story.)

AI can't fix this

First of all, this isn't a post about AI, because AI's direct impact on this problem is minimal. Okay, so Claude can code it in 3 minutes instead of 30? That's super, Claude, great work.

Now you either get to spend 27 minutes reviewing the code yourself in a back-and-forth loop with the AI (this is actually kinda fun); or you save 27 minutes and submit unverified code to the code reviewer, who will still take 5 hours like before, but who will now be mad that you're making them read the slop that you were too lazy to read yourself. Little of value was gained.

Now now, you say, that's not the value of agentic coding. You don't use an agent on a 30-minute fix. You use it on a monstrosity week-long project that you and Claude can now do in a couple of hours! Now we're talking. Except no, because the monstrosity is so big that your reviewer will be extra mad that you didn't read it yourself, and it's too big to review in one chunk so you have to slice it into new bite-sized chunks, each with a 5-hour review cycle. And there's no design doc so there's no intentional architecture, so eventually someone's going to push back on that and here we go with the design doc review meeting, and now your monstrosity week-long project that you did in two hours is... oh. A week, again.

I guess I could have called this post Systems Design 4 (or 5, or whatever I'm up to now, who knows, I'm writing this on a plane with no wifi) because yeah, you guessed it. It's Systems Design time again.

The only way to sustainably go faster is fewer reviews

It's funny, everyone has been predicting the Singularity for decades now. The premise is we build systems that are so smart that they themselves can build the next system that is even smarter, that builds the next smarter one, and so on, and once we get that started, if they keep getting smarter faster enough, then the incremental time (t) to achieve a unit (u) of improvement goes to zero, so (u/t) goes to infinity and foom.

Anyway, I have never believed in this theory for the simple reason we outlined above: the majority of time needed to get anything done is not actually the time doing it. It's wall clock time. Waiting. Latency.

And you can't overcome latency with brute force.

I know you want to. I know many of you now work at companies where the business model kinda depends on doing exactly that.

Sorry.

But you can't just *not review* things!

Ah, well, no, actually yeah. You really can't.

There are now many people who have seen the symptom: the start of the pipeline (AI generated code) is so much faster, but all the subsequent stages (reviews) are too slow! And so they intuit the obvious solution: stop reviewing then!

The result might be slop, but if the slop is 100x cheaper, then it only needs to deliver 1% of the value per unit and it's still a fair trade. And if your value per unit is even a mere 2% of what it used to be, you've doubled your returns! Amazing.

There are some pretty dumb assumptions underlying that theory; you can imagine them for yourself. Suffice it to say that this produces what I will call the AI Developer's Descent Into Madness:

1. Whoa, I produced this prototype so fast! I have super powers!
2. This prototype is getting buggy. I'll tell the AI to fix the bugs.
3. Hmm, every change now causes as many new bugs as it fixes.
4. Aha! But if I have an AI agent also review the code, it can find its own bugs!
5. Wait, why am I personally passing data back and forth between agents
6. I need an agent framework
7. I can have my agent write an agent framework!
8. Return to step 1

It’s actually alarming how many friends and respected peers I’ve lost to this cycle already. Claude Code only got good maybe a few months ago, so this only recenlty started happening, so I assume they will emerge from the spiral eventually. I mean, I hope they will. We have no way of knowing.

Why we review

Anyway we know our symptom: the pipeline gets jammed up because of too much new code spewed into it at step 1. But what's the root cause of the clog? Why doesn’t the pipeline go faster?

I said above that this isn’t an article about AI. Clearly I’m failing at that so far, but let’s bring it back to humans. It goes back to the annoyingly true observation I started with: every layer of review is 10x slower. As a society, we know this. Maybe you haven't seen it before now. But trust me: people who do org design for a living know that layers are expensive... and they still do it.

As companies grow, they all end up with more and more layers of collaboration, review, and management. Why? Because otherwise mistakes get made, and mistakes are increasingly expensive at scale. The average value added by a new feature eventually becomes lower than the average value lost through the new bugs it causes. So, lacking a way to make features produce more value (wouldn't that be nice!), we try to at least reduce the damage.

The more checks and controls we put in place, the slower we go, but the more monotonically the quality increases. And isn’t that the basis of *continuous improvement?*

Well, sort of. Monotonically increasing quality is on the right track. But “more checks and controls” went off the rails. That’s *only one way* to improve quality, and it's a fraught one.

“Quality Assurance” reduces quality

I wrote a few years ago about W. E. Deming and the "new" philosophy around quality that he popularized in Japanese auto manufacturing. (Eventually U.S. auto manufacturers more or less got the idea. So far the software industry hasn’t.)

One of the effects he highlighted was the problem of a “QA” pass in a factory: build widgets, have an inspection/QA phase, reject widgets that fail QA. Of course, your inspectors probably miss some of the failures, so when in doubt, add a second QA phase after the first to catch the remaining ones, and so on.

In a simplistic mathematical model this seems to make sense. (For example, if every QA pass catches 90% of defects, then after two QA passes you've reduced the number of defects by 100x. How awesome is that?)

But in the reality of agentic humans, it's not so simple. First of all, the incentives get weird. The second QA team basically serves to evaluate how well the first QA team is doing; if the first QA team keeps missing defects, fire them. Now, that second QA team has little incentive to produce that outcome for their friends. So maybe they don't look too hard; after all, the first QA team missed the defect, it's not unreasonable that we might miss it too.

Furthermore, the first QA team knows there is a second QA team to catch any defects; if I don't work too hard today, surely the second team will pick up the slack. That's why they're there!

Also, the team making the widgets in the first place doesn't check their work too carefully; that's what the QA team is for! Why would I slow down the production of every widget by being careful, at a cost of say 20% more time, when there are only 10 defects in 100 and I can just eliminate them at the next step for only a 10% waste overhead? It only makes sense. Plus they'll fire me if I go 20% slower.

To say nothing of a whole engineering redesign to improve quality, that would be super expensive and we could be designing all new widgets instead.

Sound like any engineering departments you know?

Well, this isn't the right time to rehash Deming, but suffice it to say, he was on to something. And his techniques worked. You get things like the famous Toyota Production System where they eliminated the QA phase entirely, but gave everybody an "oh crap, stop the line, I found a defect!" button.

Famously, US auto manufacturers tried to adopt the same system by installing the same "stop the line" buttons. Of course, nobody pushed those buttons. They were afraid of getting fired.

Trust

The basis of the Japanese system that worked, and the missing part of the American system that didn't, is trust. Trust among individuals that your boss Really Truly Actually wants to know about every defect, and wants you to stop the line when you find one. Trust among managers that executives were serious about quality. Trust among executives that individuals, given a system that can work and has the right incentives, will produce quality work and spot their own defects, and push the stop button when they need to push it.

But, one more thing: trust that the system *actually does work*. So first you need a system that will work.

Fallibility

AI coders are fallible; they write bad code, often. In this way, they are just like human programmers.

Deming's approach to manufacturing didn't have any magic bullets. Alas, you can't just follow his ten-step process and immediately get higher quality engineering. The secret is, you have to get your engineers to engineer higher quality into the whole system, from top to bottom, repeatedly. Continuously.

Every time something goes wrong, you have to ask, "How did this happen?" and then do a whole post-mortem and the Five Whys (or however many Whys are in fashion nowadays) and fix the underlying Root Causes so that it doesn't happen again. "The coder did it wrong" is never a root cause, only a symptom. Why was it possible for the coder to get it wrong?

The job of a code reviewer isn't to review code. It's to figure out how to obsolete their code review comment, that whole class of comment, in all future cases, until you don't need their reviews at all anymore.

(Think of the people who first created "go fmt" and how many stupid code review comments about whitespace are gone forever. Now that's engineering.)

By the time your review catches a mistake, the mistake has already been made. The root cause happened already. You're too late.

Modularity

I wish I could tell you I had all the answers. Actually I don't have much. If I did, I'd be first in line for the Singularity because it sounds kind of awesome.

I think we're going to be stuck with these systems pipeline problems for a long time. Review pipelines — layers of QA — don't work. Instead, they make you slower while hiding root causes. Hiding causes makes them harder to fix.

But, the call of AI coding is strong. That first, fast step in the pipeline is *so fast!* It really does feel like having super powers. I want more super powers. What are we going to do about it?

Maybe we finally have a compelling enough excuse to fix the 20 years of problems hidden by code review culture, and replace it with a real culture of quality.

I think the optimists have half of the right idea. Reducing review stages, even to an uncomfortable degree, is going to be needed. But you can't just reduce review stages without something to replace them. That way lies the Ford Pinto or any recent Boeing aircraft.

The complete package, the table flip, was what Deming brought to manufacturing. You can't half-adopt a "total quality" system. You need to eliminate the reviews *and* obsolete them, in one step.

How? You can fully adopt the new system, in small bites. What if some components of your system can be built the new way? Imagine an old-school U.S. auto manufacturer buying parts from Japanese suppliers; wow, these parts are so well made! Now I can start removing QA steps elsewhere because I can just assume the parts are going to work, and my job of "assemble a bigger widget from the parts" has a ton of its complexity removed.

I like this view. I've always liked small beautiful things, that's my own bias. But, you can assemble big beautiful things from small beautiful things.

It's a lot easier to build those individual beautiful things in small teams that trust each other, that know what quality looks like *to them*. They deliver their things to customer teams who can clearly explain what quality looks like *to them*. And on we go. Quality starts bottom-up, and spreads.

I think small startups are going to do really well in this new world, probably better than ever. Startups already have fewer layers of review just because they have fewer people. Some startups will figure out how to produce high quality components quickly; others won't and will fail. Quality by natural selection?

Bigger companies are gonna have a harder time, because their slow review systems are baked in, and deleting them would cause complete chaos.

But, it's not just about company size. I think engineering teams at any company can get smaller, and have better defined interfaces between them.

Maybe you could have multiple teams inside a company competing to deliver the same component. Each one is just a few people and a few coding bots. Try it 100 ways and see who comes up with the best one. Again, quality by evolution. Code is cheap but good ideas are not. But now you can try out new ideas faster than ever.

Maybe we'll see a new optimal point on the monoliths-microservices continuum. Microservices got a bad name because they were too micro; in the original terminology, a "micro" service was exactly the right size for a "two pizza team" to build and operate on their own. With AI, maybe it's one pizza and some tokens.

What's fun is you can also use this new, faster coding to experiment with different module *boundaries* faster. *Features* are still hard for lots of reasons, but refactoring and automated integration testing are things the AIs excel at. Try splitting out a module you were afraid to split out before. Maybe it'll add some lines of code. But suddenly lines of code are cheap, compared to the coordination overhead of a bigger team maintaining both parts.

Every team has some monoliths that are a little too big, and too many layers of reviews. Maybe we won't get all the way to Singularity. But, we can engineer a much better world. Our problems are solvable.

It just takes trust.

Related

Highlights on "quality," and Deming's work as it applies to software development (2016)

Systems design 3: LLMs and the semantic revolution (2025)

Unrelated

SimSWE part 2: The perils of multitasking (2017)

Codex CLI Release: 0.162.1

CODEX CHANGELOG · 10 OCT 2026 · SOURCE

Bug Fixes

- Fixed a TUI crash when asynchronous questions contain multiple lines, preserving line breaks and complete hyperlink destinations. (#51866)

- Fixed startup failures caused by differences between a running background server's feature settings and CLI defaults. Compatibility checks now apply only to explicit command-line feature overrides. (#52648)

Full Changelog: `rust-v0.162.0...rust-v0.162.1`