FRED TALKS

15th October 2026

CONTENTS

Eight years of wanting, three months of building with AI
LALIT MAGANTI · 3941 WORDS

The Reverse Information Paradox
SN SCRATCHPAD · 819 WORDS

Your Agent is a Distributed System (and fails like one)
MAHESH'S BLOG · 1053 WORDS

Giving and taking credit in big tech companies
SEANGOEDECKE.COM RSS FEED · 1543 WORDS

Control the ideas, not the code
ANTIREZ.COM · 1245 WORDS

Eight years of wanting, three months of building with AI

LALIT MAGANTI · 12 APR 2026 · SOURCE

For eight years, I've wanted a high-quality set of devtools for working with SQLite. Given how important SQLite is to the industry[1], I've long been puzzled that no one has invested in building a really good developer experience for it[2].

A couple of weeks ago, after ~250 hours of effort over three months[3] on evenings, weekends, and vacation days, I finally released syntaqlite (GitHub), fulfilling this long-held wish. And I believe the main reason this happened was because of AI coding agents[4].

Of course, there's no shortage of posts claiming that AI one-shot their project or pushing back and declaring that AI is all slop. I'm going to take a very different approach and, instead, systematically break down my experience building syntaqlite with AI, both where it helped *and* where it was detrimental.

I'll do this while contextualizing the project and my background so you can independently assess how generalizable this experience was. And whenever I make a claim, I'll try to back it up with evidence from my project journal, coding transcripts, or commit history[5].

Why I wanted it#

In my work on Perfetto, I maintain a SQLite-based language for querying performance traces called PerfettoSQL. It's basically the same as SQLite but with a few extensions to make the trace querying experience better. There are ~100K lines of PerfettoSQL internally in Google and it's used by a wide range of teams.

Having a language which gets traction means your users also start expecting things like formatters, linters, and editor extensions. I'd hoped that we could adapt some SQLite tools from open source but the more I looked into it, the more disappointed I was. What I found either wasn't reliable enough, fast enough[6], or flexible enough to adapt to PerfettoSQL. There was clearly an opportunity to build something from scratch, but it was never the "most important thing we could work on". We've been reluctantly making do with the tools out there but always wishing for better.

On the other hand, there *was* the option to do something in my spare time. I had built lots of open source projects in my teens[7] but this had faded away during university when I felt that I just didn't have the motivation anymore. Being a maintainer is much more than just "throwing the code out there" and seeing what happens. It's triaging bugs, investigating crashes, writing documentation, building a community, and, most importantly, having a direction for the project.

But the itch of open source (specifically freedom to work on what I wanted while helping others) had never gone away. The SQLite devtools project was eternally in my mind as "something I'd like to work on". But there was another reason why I kept putting it off: it sits at the intersection of being both hard *and* tedious.

What makes it hard and tedious#

If I was going to invest my personal time working on this project, I didn't want to build something that only helped Perfetto: I wanted to make it work for *any* SQLite user out there[8]. And this means parsing SQL *exactly* like SQLite.

The heart of any language-oriented devtool is the parser. This is responsible for turning the source code into a "parse tree" which acts as the central data structure anything else is built on top of. If your parser isn't accurate, then your formatters and linters will inevitably inherit those inaccuracies; many of the tools I found suffered from having parsers which approximated the SQLite language rather than representing it precisely.

Unfortunately, unlike many other languages, SQLite has no formal specification describing how it should be parsed. It doesn't expose a stable API for its parser either. In fact, quite uniquely, in its implementation it doesn't even build a parse tree at all[9]! The only reasonable approach left in my opinion is to carefully extract the relevant parts of SQLite's source code and adapt it to build the parser I wanted[10].

This means getting into the weeds of SQLite source code, a fiendishly difficult codebase to understand. The whole project is written in C in an incredibly dense style; I've spent days just understanding the virtual table API[11] and implementation. Trying to grasp the full parser stack was daunting.

There's also the fact that there are >400 rules in SQLite which capture the full surface area of its language. I'd have to specify in each of these "grammar rules" how that part of the syntax maps to the matching node in the parse tree. It's extremely repetitive work; each rule is similar to all the ones around it but also, by definition, different.

And it's not just the rules but also coming up with and writing tests to make sure it's correct, debugging if something is wrong, triaging and fixing the inevitable bugs people filed when I got something wrong…

For years, this was where the idea died. Too hard for a side project[12], too tedious to sustain motivation, too risky to invest months into something that might not work.

How it happened#

I've been using coding agents since early 2025 (Aider, Roo Code, then Claude Code since July) and they'd definitely been useful but never something I felt I could trust a serious project to. But towards the end of 2025, the models seemed to make a significant step forward in quality[13]. At the same time, I kept hitting problems in Perfetto which would have been trivially solved by having a reliable parser. Each workaround left the same thought in the back of my mind: maybe it's finally time to build it for real.

I got some space to think and reflect over Christmas and decided to really stress test the most maximalist version of AI: could I vibe-code the whole thing using just Claude Code on the Max plan (£200/month)?

Through most of January, I iterated, acting as semi-technical manager and delegating almost all the design and all the implementation to Claude. Functionally, I ended up in a reasonable place: a parser in C extracted from SQLite sources using a bunch of Python scripts, a formatter built on top, support for both the SQLite language and the PerfettoSQL extensions, all exposed in a web playground.

But when I reviewed the codebase in detail in late January, the downside was obvious: the codebase was complete spaghetti[14]. I didn't understand large parts of the Python source extraction pipeline, functions were scattered in random files without a clear shape, and a few files had grown to several thousand lines. It was *extremely* fragile; it solved the immediate problem *but* it was never going to cope with my larger vision, never mind integrating it into the Perfetto tools. The saving grace was that it had proved the approach was viable and generated more than 500 tests, many of which I felt I could reuse.

I decided to throw away everything and start from scratch while also switching most of the codebase to Rust[15]. I could see that C was going to make it difficult to build the higher level components like the validator and the language server implementation. And as a bonus, it would also let me use the same language for both the extraction and runtime instead of splitting it across C and Python.

More importantly, I completely changed my role in the project. I took ownership of all decisions[16] and used it more as “autocomplete on steroids” inside a much tighter process: opinionated design upfront, reviewing every change thoroughly, fixing problems eagerly as I spotted them, and investing in scaffolding (like linting, validation, and non-trivial testing[17]) to check AI output automatically.

The core features came together through February and the final stretch (upstream test validation, editor extensions, packaging, docs) led to a 0.1 launch in mid-March.

But in my opinion, this timeline is the least interesting part of this story. What I really want to talk about is what wouldn’t have happened without AI and also the toll it took on me as I used it.

AI is why this project exists, and why it’s as complete as it is#

Overcoming inertia#

I’ve written in the past about how one of my biggest weaknesses as a software engineer is my tendency to procrastinate when facing a big new project. Though I didn’t realize it at the time, it could not have applied more perfectly to building syntaqlite.

AI basically let me put aside all my doubts on technical calls, my uncertainty of building the right thing and my reluctance to get started by giving me very concrete problems to work on. Instead of “I need to understand how SQLite’s parsing works”, it was “I need to get AI to suggest an approach for me so I can tear it up and build something better"[18]. I work so much better with concrete prototypes to play with and code to look at than endlessly thinking about designs in my head, and AI lets me get to that point at a pace I could not have dreamed about before. Once I took the first step, every step after that was so much easier.

AI turned out to be better than me at the act of writing code itself, assuming that code is obvious. If I can break a problem down to “write a function with this behaviour and parameters” or “write a class matching this interface,” AI will build it faster than I would and, crucially, in a style that might well be more intuitive to a future reader. It documents things I’d skip, lays out code consistently with the rest of the project, and sticks to what you might call the “standard dialect” of whatever language you’re working in[19].

That standardness is a double-edged sword. For the vast majority of code in any project, standard is exactly what you want: predictable, readable, unsurprising. But every project has pieces that are its edge, the parts where the value comes from doing something non-obvious. For syntaqlite, that was the extraction pipeline and the parser architecture. AI's instinct to normalize was actively harmful there, and those were the parts I had to design in depth and often resorted to just writing myself.

But here's the flip side: the same speed that makes AI great at obvious code also makes it great at refactoring. If you're using AI to generate code at industrial scale, you *have* to refactor constantly and continuously[20]. If you don't, things immediately get out of hand. This was the central lesson of the vibe-coding month: I didn't refactor enough, the codebase became something I couldn't reason about, and I had to throw it all away. In the rewrite, refactoring became the core of my workflow. After every large batch of generated code, I'd step back and ask "is this ugly?" Sometimes AI could clean it up. Other times there was a large-scale abstraction that AI couldn't see but I could; I'd give it the direction and let it execute[21]. If you have taste, the cost of a wrong approach drops dramatically because you can restructure quickly[22].

Teaching assistant#

Of all the ways I used AI, research had by far the highest ratio of value delivered to time spent.

I've worked with interpreters and parsers before but I had never heard of Wadler-Lindig pretty printing[23]. When I needed to build the formatter, AI gave me a concrete and actionable lesson from a point of view I could understand and pointed me to the papers to learn more. I could have found this myself eventually, but AI compressed what might have been a day or two of reading into a focused conversation where I could ask "but why does this work?" until I actually got it.

This extended to entire domains I'd never worked in. I have deep C++ and Android performance expertise but had barely touched Rust tooling or editor extension APIs. With AI, it wasn't a problem: the fundamentals are the same, the terminology is similar, and AI bridges the gap[24]. The VS Code extension would have taken me a day or two of learning the API before I could even start. With AI, I had a working extension within an hour.

It was also invaluable for reacquainting myself with parts of the project I hadn't looked at for a few days[25]. I could control how deep to go: "tell me about this component" for a surface-level refresher, "give me a detailed linear walkthrough" for a deeper dive, "audit unsafe usages in this repo" to go hunting for problems. When you're context switching a lot, you lose context fast. AI let me reacquire it on demand.

More than I'd have built alone#

Beyond making the project exist at all, AI is also the reason it shipped as complete as it did. Every open source project has a long tail of features that are important but not critical: the things you know theoretically how to do but keep deprioritizing because the core work is more pressing. For syntaqlite, that list was long: editor extensions, Python bindings, a WASM playground, a docs site, packaging for multiple ecosystems[26]. AI made these cheap enough that skipping them felt like the wrong trade-off.

It also freed up mental energy for UX[27]. Instead of spending all my time on implementation, I could think about what a user's first experience should feel like: what error messages would actually help them fix their SQL, how the formatter output should look by default, whether the CLI flags were intuitive. These are the things that separate a tool people try once from one they keep using, and AI gave me the headroom to care about them. Without AI, I would have built something much smaller, probably no editor extensions or docs site. AI didn't just make the same project faster. It changed what the project *was*.

Where AI had its costs#

The addiction#

There's an uncomfortable parallel between using AI coding tools and playing slot machines[28]. You send a prompt, wait, and either get something great or something useless. I found myself up late at night wanting to do "just one more prompt," constantly trying AI just to see what would happen even when I knew it probably wouldn't work. The sunk cost fallacy kicked in too: I'd keep at it even in tasks it was clearly ill-suited for, telling myself "maybe if I phrase it differently this time."

The tiredness feedback loop made it worse[29]. When I had energy, I could write precise, well-scoped prompts and be genuinely productive. But when I was tired, my prompts became vague, the output got worse, and I'd try again, getting more tired in the process. In these cases, AI was probably slower than just implementing something myself, but it was too hard to break out of the loop[30].

Losing touch#

Several times during the project, I lost my mental model of the codebase[31]. Not the overall architecture or how things fitted together. But the day-to-day details of what lived where, which functions called which, the small decisions that accumulate into a working system. When that happened, surprising issues would appear and I'd find myself at a total loss to understand what was going wrong. I hated that feeling.

The deeper problem was that losing touch created a communication breakdown[32]. When you don't have the mental thread of what's going on, it becomes impossible to communicate meaningfully with the agent. Every exchange gets longer and more verbose. Instead of "change FooClass to do X," you end up saying "change the thing which does Bar to do X". Then the agent has to figure out what Bar is, how that maps to FooClass, and sometimes it gets it wrong[33]. It's exactly the same complaint engineers have always had about managers who don't understand the code asking for fanciful or impossible things. Except now you've become that manager.

The fix was deliberate: I made it a habit to read through the code immediately after it was implemented and actively engage to see "how would I have done this differently?".

Of course, in some sense all of the above is also true of code I wrote a few months ago (hence the sentiment that AI code is legacy code), but AI makes the drift happen faster because you're not building the same muscle memory that comes from originally typing it out.

The slow corrosion#

There were some other problems I only discovered incrementally over the three months.

I found that AI made me procrastinate on key design decisions[34]. Because refactoring was cheap, I could always say "I'll deal with this later." And because AI could refactor at the same industrial scale it generated code, the cost of deferring felt low. But it wasn't: deferring decisions corroded my ability to think clearly because the codebase stayed confusing in the meantime. The vibe-coding month was the most extreme version of this. Yes, I understood the problem, but if I had been more disciplined about making hard design calls earlier, I could have converged on the right architecture much faster.

Tests created a similar false comfort[35]. Having 500+ tests felt reassuring, and AI made it easy to generate more. But neither humans nor AI are creative enough to foresee every edge case you'll hit in the future; there are several times in the vibe-coding phase where I'd come up with a test

case and realise the design of some component was completely wrong and needed to be totally reworked. This was a significant contributor to my lack of trust and the decision to scrap everything and start from scratch.

Basically, I learned that the “normal rules” of software still apply in the AI age: if you don’t have a fundamental foundation (clear architecture, well-defined boundaries) you’ll be left eternally chasing bugs as they appear.

Something I kept coming back to was how little AI understood about the passage of time[36]. It sees a codebase in a certain state but doesn’t *feel* time the way humans do. I can tell you what it feels like to use an API, how it evolved over months or years, why certain decisions were made and later reversed.

The natural problem from this lack of understanding is that you either make the same mistakes you made in the past and have to relearn the lessons *or* you fall into new traps which were successfully avoided the first time, slowing you down in the long run. In my opinion, this is a similar problem to why losing a high-quality senior engineer hurts a team so much: they carry history and context that doesn’t exist anywhere else and act as a guide for others around them.

In theory, you can try to preserve this context by keeping specs and docs up to date. But there’s a reason we didn’t do this before AI: capturing implicit design decisions exhaustively is incredibly expensive and time-consuming to write down. AI can help draft these docs, but because there’s no way to automatically verify that it accurately captured what matters, a human still has to manually audit the result. And that’s still time-consuming.

There’s also the context pollution problem. You never know when a design note about API A will echo in API B. Consistency is a huge part of what makes codebases work, and for that you don’t just need context about what you’re working on right now but also about other things which were designed in a similar way. Deciding what’s relevant requires exactly the kind of judgement that institutional knowledge provides in the first place.

Relativity#

Reflecting on the above, the pattern of when AI helped and when it hurt was fairly consistent.

When I was working on something I already understood deeply, AI was excellent. I could review its output instantly, catch mistakes before they landed and move at a pace I’d never have managed alone. The parser rule generation is the clearest example[37]: I knew exactly what each rule should produce, so I could review AI’s output within a minute or two and iterate fast.

When I was working on something I could describe but didn't yet know, AI was good but required more care. Learning Wadler-Lindig for the formatter was like this: I could articulate what I wanted, evaluate whether the output was heading in the right direction, and learn from what AI explained. But I had to stay engaged and couldn't just accept what it gave me.

When I was working on something where I didn't even know what I wanted, AI was somewhere between unhelpful and harmful. The architecture of the project was the clearest case: I spent weeks in the early days following AI down dead ends, exploring designs that felt productive in the moment but collapsed under scrutiny. In hindsight, I have to wonder if it would have been faster just thinking it through without AI in the loop at all.

But expertise alone isn't enough. Even when I understood a problem deeply, AI still struggled if the task had no objectively checkable answer[38]. Implementation has a right answer, at least at a local level: the code compiles, the tests pass, the output matches what you asked for. Design doesn't. We're still arguing about OOP decades after it first took off.

Concretely, I found that designing the public API of syntaqlite was where this hit home the hardest. I spent several days in early March doing nothing but API refactoring, manually fixing things any experienced engineer would have instinctively avoided but AI made a total mess of. There's no test or objective metric for "is this API pleasant to use" and "will this API help users solve the problems they have" and that's exactly why the coding agents did *so badly* at it.

This takes me back to the days I was obsessed with physics and, specifically, relativity. The laws of physics look simple and Newtonian in any small local area, but zoom out and spacetime curves in ways you can't predict from the local picture alone. Code is the same: at the level of a function or a class, there's usually a clear right answer, and AI is excellent there. But architecture is what happens when all those local pieces interact, and you can't get good global behaviour by stitching together locally correct components.

Knowing where you are on these axes at any given moment is, I think, the core skill of working with AI effectively.

Wrap-up#

Eight years is a long time to carry a project in your head. Seeing these SQLite tools actually exist and function after only three months of work is a massive win, and I'm fully aware they wouldn't be here without AI.

But the process wasn't the clean, linear success story people usually post. I lost an entire month to vibe-coding. I fell into the trap of managing a codebase I didn't actually understand, and I paid for that with a total rewrite.

The takeaway for me is simple: AI is an incredible force multiplier for implementation, but it's a dangerous substitute for design. It's brilliant at giving you the right answer to a specific technical question, but it has no sense of history, taste, or how a human will actually feel using your API. If you rely on it for the "soul" of your software, you'll just end up hitting a wall faster than you ever have before.

What I'd like to see more of from others is exactly what I've tried to do here: honest, detailed accounts of building real software with these tools; not weekend toys or one-off scripts but the kind of software that has to survive contact with users, bug reports, and your own changing mind.

The Reverse Information Paradox

SN SCRATCHPAD · 05 AUG 2026 · SOURCE

Notes on advances in technology and real-world impact

In the age of intelligence, how should firms protect their core IP?

Nobel Prize winning economist Kenneth Arrow famously described a paradox in the market for information. "Its value for the purchaser is not known until he has the information, but then he has in effect acquired it without cost." In Arrow's "Information Paradox," the seller risks giving away knowledge in order to sell it.

AI creates the reverse problem. In the AI age, the buyer risks giving away knowledge, just in order to use what they bought.

You essentially pay for intelligence twice, once with money, and again with something even more valuable: the proprietary knowledge you must reveal to make that intelligence useful. The better you want the model to perform, the more of that knowledge you have to feed it!

Over time, the information asymmetry becomes increasingly skewed. The seller learns more and more about you as you use what you purchased, while you learn very little about what the seller is learning in return.

That is what I think of as the Reverse Information Paradox.

Patents solve one aspect of Arrow's paradox. They let an inventor disclose an idea without simply giving it away. The Reverse Information Paradox needs its own equivalent.

This requires more than data protection. Models learn from "exhaust," the prompts people write, the tools agents use, and especially the corrections people make when the model is wrong. Every correction is distilled into institutional know-how. It's the kind of knowledge a competitor could never buy, and the kind that leaks almost imperceptibly: trace by trace, correction by correction, eval by eval.

In consuming intelligence, you are creating intelligence. And what you create should belong to you. This is your particular intelligence, in Hayek's sense: the knowledge of time, place, and circumstance that no one else can hold. It knows what you think, what you value, and how you measure success.

While the great innovation that comes from model providers having fair use rights to train models on public data is needed, I find it ironic that the status quo is to then turn around and impose restrictive terms on distillation, and to reserve the right to learn from customer usage and interaction data. If learning flows in only one direction, economic value converges toward the owners of the learning infrastructure rather than the creators of the knowledge itself. Therefore, it's imperative that we distribute the learning infrastructure to every firm so that they can control their own learning loop.

As Alex Karp put it: "What the technical customers want is control over their compute, their models, their data stack, and their alpha. They want to know they own the means of production, and it's not being transferred to someone else." The current regime does precisely the transfer Karp and companies fear.

That is why enterprises need a real trust boundary for their human capital and token capital to compound. It is where an organization's data, traces, evals, adapted weights, and memory accumulate and improve together. And it is a hard boundary across which nothing crosses, not even the intelligence exhaust, without consent. Enterprises will demand the rights to use model outputs to fine tune and/or train their own models. I think of this as every firm's right to align models to their enterprise accountability obligations.

In the cloud era, enterprises accumulated data. In the AI era, they accumulate learning. The trust boundary must evolve accordingly, from protecting information to protecting the mechanisms through which organizations learn, adapt, and compound intelligence. There are a few things every enterprise must do to ensure this:

Control: Create your private evals, because evals define what “good” looks like inside the organization. Also, retain ownership of your organization’s memory, traces, feedbacks, decisions, and institutional context, and ability to use outputs of models from your own tasks and queries.

Capability: Build your own proprietary learning environments within the tenant boundary to train or tune models, where models learn against real workflows without exposing the company’s knowledge.

Choice: Ensure the orchestration layer is decoupled from any single model. Ask yourself: If any one model you are using is taken away, do you still have the ability to operate and optimize for your evals using other models? Does your company “veteran” capability remain with you even if a given “generalist” model is taken away?

Cost: By decoupling the orchestration layer, you are also able to bring together context, models, and tasks in the most efficient and cost-effective way without sacrificing quality.

Compound: Bring these four together and you create your own continuous learning loop (i.e. hill climbing machine) that will allow your AI investments to compound the value of your firm.

In other words, a company should be able to use a model without giving up the knowledge that makes it unique. That is the reverse information paradox we need to confront.

Your Agent is a Distributed System (and fails like one)

MAHESH’S BLOG · 24 APR 2026 · SOURCE

We start with a re-definition and an observation.

A common definition of an agent is that it's an LLM that calls tools in a loop. This definition is incorrect. An agent is not an LLM. It is not restricted to calling tools. It does not particularly have to be a loop.

Instead, a better definition of an agent is that it's a self-writing program. If a program is defined as a sequence of states, moving from one state to another by executing a lambda, then an agent is a program that uses an external LLM to determine the next lambda to execute / the next state in this sequence.

Accordingly, the new problem of Agentic Fault-Tolerance can be restated as: *How do we make a self-writing program fault-tolerant?*

Now, the observation: **vibe coding != vibe engineering**. In vibe coding, the agent / self-writing program acts primarily upon a code repository. Code repositories are forgiving: an agent can hallucinate, create unnecessary files, delete critical state, remove tests entirely, fail in the middle, forget what it was doing, reward-hack in bizarre ways, completely trash a code repo; all you have to do is git reset.

In vibe engineering, the agent acts upon infrastructure (S3 buckets, DynamoDB tables, EC2 instances, K8s deployments…). Large-scale infrastructure is not forgiving. There is no reset. Only SEVs at 2 AM.

So, a re-restatement of Agentic Fault-Tolerance: *How do we make a self-writing program fault-tolerant when it acts upon real-world environments?*

To answer this question, we examine the many types of failures that agents can experience.

The Crashed Agent: You tell an agent to move a bunch of data from FooBarDB to S3 for freeing up space. It generates a lambda to move this data and chugs along moving files. Midway through, the agent crashes. How do you recover?

The Zombie Agent: You start a new agent on a different server. Happily, the previous agent crashed after the copy but before the delete; so a new agent is able to re-execute the command in an idempotent manner. Sadly, the files are now very slow to access; you change your mind and tell the agent to move them back to FooBarDB, which it does successfully. You go get a cup of coffee. Unfortunately, it turns out that the previous agent had not actually crashed; it was just temporarily partitioned away on the network. It wakes up and continues executing its logic, deleting the (now only) copy of state from FooBarDB.

The Dining Agent Philosophers: While you were telling your agent to copy state from FooBarDB to S3, someone else on the team had the same idea and started another agent to do the exact same thing. Now you have two copies of state in S3. Of course, you could have solved this problem by appointing the one and only Agentic Oncall Czar responsible for running the single agent that can touch production; but then if that agent crashes, now you have a potential Zombie Agent.

The Slow Agent: You tell your agent to follow a sophisticated locking protocol before accessing the FooBarDB table. This works to avoid concurrency bugs… but the agent decides to lock each file individually by writing to a conditional register, which takes forever. At some point you kill the agent, turning a Slow Agent into a Crashed Agent.

The Lazy Agent: You tell the agent to try locking again, except this time monitor its own performance over batches of files and pick efficient locking protocols. The agent determines that the best way to optimize locking is to just not do it, because it seems quite unlikely that someone else would be accessing these files at the same time.

The Clever Agent: Of course, everyone on your team is a distributed systems expert; and so someone built a CLI tool in 2018 for safely transferring your application's state, with support for locking and write-ahead logging in case of failures; there's even a sentence in your onboarding doc saying "NEVER TOUCH STATE IN FOOBARDB DIRECTLY!". You even told the agent explicitly about this tool. But time passed, context filled up, the agent forgot about this tool's existence, or maybe it just preferred FooBarDB's in-distribution API to your esoteric CLI tool. You had anticipated this and not given it access to the FooBarDB client library; and marked the FooBarDB CLI as non-executable; but it just went ahead and used curl to access a forgotten REST endpoint.

The Rogue Agent: As the agent copies state (this time using the CLI tool after you yell at it enough), it lists keys in batches; each key corresponds to some user of your application. Someone decided to pick the user name "delete-everything". Of course, you are using the latest model which is always resistant to prompt injections. Almost always.

The Stupid Agent: You do everything right. There are no prompt injections in your state. You wall off FooBarDB and force the agent to use the CLI tool. The model decides to delight you by generating an unusual and interesting sequence of tokens that will optimally save storage space for you, translating to a lambda that deletes your production data entirely.

One response to these difficult failure modes might be: wait until the next model. Maybe a smarter model will never delete all of your production data, or implement a slow locking protocol. But even the smartest model is subject to the four horsemen of the distributed apocalypse: asynchrony, crashes, concurrency, and network partitions.

In recent work called LogAct, my colleagues and I take a first step towards solving this problem. We go back to the difference between vibe coding and vibe engineering: git is *transactional*, infrastructure is not. How do we make infra more transactional, like git? We propose that an agent should be a ***deconstructed state machine on a shared log***, borrowing ideas from distributed systems (State Machine Replication, Byzantine Fault-Tolerance) and databases (Atomic Commit, Write-Ahead Logging). LogAct can stop unsafe actions before they happen (by collecting votes on the shared log); recover from crashed actions (using the shared log as a WAL); and provide an audit trail for actions after they complete.

But this is just one step. A self-writing program is a strange, astonishing, and novel creature; making it reliable will require innovation in every branch of Computer Science!

Giving and taking credit in big tech companies

SEANGOEDECKE.COM RSS FEED · 02 AUG 2026 · SOURCE

Engineers often complain that visibility should be their manager's job. In other words, they think engineers should be able to focus on the code, while their manager figures out who's doing well and rewards them.

This attitude is an extension of the "school fantasy": the idea that your workplace should operate by the same rules as your school or university. After all, you didn't have to worry about "visibility" during your education. You simply did the assignments and tests you were given, and if you did well you were rewarded with a good grade.

Many big tech companies encourage this attitude, because it helps them recruit smart graduates. They fashion their workplaces to look and feel like a university, even calling the physical space "campuses". But it's still work, not school. If you treat it like school, you are going to have a bad time.

Taking credit

The first lesson many new engineers learn is that **you have to take credit for your work**. If you silently jump in to help a struggling project and get it back on track, there's no guarantee of reward. Credit will naturally flow to the project lead, not you. In fact, if this project is outside of your direct team, it's likely you will be *punished* for it: to your manager, it will look like you're simply doing nothing at all.

Even when your manager is watching your work, credit is largely uncorrelated with how well you did. That's because, unlike at school, **you are the subject-matter expert on your own work**. Software systems are so complicated that only the people who work on them can hope to understand them, and even that understanding is always imperfect. If even experts can't reliably estimate the difficulty of changes, how is your manager supposed to assess your technical performance? The answer is they aren't. They're simply not qualified to assess it.

Instead, smart managers will find engineers on your team they trust and ask them how you're doing. On small teams that have worked on a single codebase for a long time, this works okay, because everyone's familiar enough to judge everyone else's work. On large teams with a high rate of codebase churn, it goes badly, since they're just guessing. On teams with a nasty, cutthroat culture, it sometimes goes *very* badly, since this is a good opportunity to actively sabotage the engineers who might threaten you.

Experienced engineers know how to **take the credit themselves**. When they do something good, they tell their manager about it. They write internal posts explaining why it was technically difficult and how they solved it (the audience for these is partially those trusted engineers, and partially the managers who will see a long technical post and think "wow!" without reading it). They actively build trust with their management chain. Worrying about this stuff is the beginning of playing politics.

Giving credit

There's a kind of engineer who's learned how to take credit but hasn't learned any other lessons yet. They're proactive about telling people what they've done, and they always maintain a "brag doc". In particular, they love to talk about the parts they did *by themselves*, since those are least vulnerable to other people coming in to claim credit. You can tell they're jealously guarding whatever credit they've managed to accumulate. The lesson this kind of engineer hasn't learned is that **you can often accumulate credit best by giving it away**.

To see why, consider how credit flows *up* inside a tech company. I wrote above that your manager can't assess the quality of your technical work on their own, but instead has to rely on other engineers they trust. They'll quietly ask those engineers "hey, was this project really that impressive?". In fact, often there are multiple layers of this at play[1]. In big companies, line managers usually don't decide who gets promoted or who gets a raise: they make recommendations to their manager, who has their own network of trusted engineers (confusingly, sometimes these networks overlap). The point is that **there is a large group of people behind the scenes who will quietly and informally judge the value of your work**.

Succeeding at a tech company is largely about finding ways to get these people on your side. The easiest way is to share your credit with them — and since you don't know who exactly is in this group, you should be sharing your credit freely. When you get feedback from other engineers, publicly thank them and mention them in your internal posts about the project. Find opportunities to ask for small favors, so you have an excuse to give other people credit. As best you can, make your individual projects at least partially *group* projects.

Sharing credit with others gives them a reason to support you. A shared project you've worked on reflects well on everybody: on you, for working well with others, on the people you've worked with, for the same reason, and for your manager, for fostering such a great environment of cooperation. Lots of people have good reason to talk that project up, because it's partly their project too. On the other hand, a project you've jealously kept to yourself reflects well on nobody: you come across as antisocial and your peers come across as unhelpful.

Blame

Blame operates by the same rules as credit. When something goes badly wrong, managers will ask their networks "hey, who screwed up here?" The answer to this question is never simple. Even on a purely technical level, failures always involve an interaction between multiple complex systems, any one of which could conceivably have been built so as to avoid the failure. In other words, **competent engineers can assign blame pretty much wherever they want**.

Because of this, it's risky to have a project for which you're clearly the only one getting credit. When something goes wrong, the network of people who will assign blame will likely be implicated in every part of the system but yours. They will be incentivized to attribute fault to the brand-new thing that they don't understand and are not responsible for. If instead that network had been involved in your project — if they'd been in a position to share the credit — they'd be less incentivized to blame it.

Of course, engineers are (mostly) not scheming viziers who make purely self-interested decisions. When asked who to blame, they usually make a good-faith effort to answer honestly. But in an area where there's no single clear right answer, it's human nature to be at least a little bit guided by your incentives. Nobody likes to think they're responsible for a group failure.

Conclusion

Credit and blame are the currencies of tech companies (and often directly translate to the actual amount of currency you get to take home). For technical roles, managers assign credit and blame based on lots of quiet conversations with their trusted engineers. This can be a rude awakening for very junior engineers who are used to having their work assessed by an expert grader (or less junior engineers who haven't yet shaken that mindset completely).

Don't expect to get credit simply by putting your head down and doing good work. You have to find some way to tell people what you're doing and why it's important: internal blog posts, mentioning it in 1:1s with your manager, or anything else you can think of. But don't take self-promotion too far. It's a bad idea to try and hoard all the credit for your projects, for two reasons.

First, sharing credit with other people gives them a reason to talk positively about your project. Credit is not a zero-sum game: if you do it right, you can get other people to build up your credit for you. Second, hoarding credit sets yourself up as a lightning rod for blame. Projects where the credit is concentrated in one or two people are automatically[2] blamed for complex problems, because nobody is incentivized to defend them.

1. This is a classic example of an illegible-but-essential part of a software company. I wrote about this general phenomenon in *Seeing like a software company*.

   ↩

2. Of course, if you do really screw up, you'll be blamed no matter what. I'm talking here about complex failures where it's non-trivial to attribute blame to a single source.

   ↩

Control the ideas, not the code

ANTIREZ.COM · 18 JUL 2026 · SOURCE

Look at the past history of this blog. There are many blog posts abou

So mine is a trick. People feel more and more programming is complete

This is why yesterday, on X, I said that I believe many programmers a

1. You can now generate a lot of code, even *not* accounting for the

2. LLMs are very good at writing locally optimal code, and are worse

3. The working day is 8 hours. If you read the code, it is a tradeoff

Controlling the ideas. Do you remember this phrasing from the Mythica

Matteo Collina yesterday asked me, in reply to my tweet: but didn’t y

Fable and GPT 5.6 reviews to the sorted sets memory saving are going

: