Machine Learning — Lecture 3

Linear Regression, Optimization, and Regularization

FCIS — For Course Use Only

Dr. Fayçal Hamdi

Faculty of Computer and Information Systems

Lecture 3 at a Glance

FCIS — Course Use Only

Linear Regression, Optimization, and Regularization

Course Learning Outcomes

CLO3: Construct and analyze machine learning models by applying algorithmic principles and internal computations.

CLO4: Apply supervised and unsupervised learning techniques to solve practical problems and interpret their outcomes.

Lecture purpose

- Introduce the first full supervised-learning model.
- Connect prediction, residuals, loss, and optimization.
- Derive how gradient descent updates model parameters.
- Explain how regularization controls model flexibility.
- Evaluate regression models using appropriate metrics.

FCIS — For Course Use Only

💡 Main idea: linear regression is simple, but it contains the complete learning pattern: **model → prediction → error → loss → optimization → evaluation**.

Learning Objectives

FCIS — Course Use Only

By the end of Lecture 3, you will be able to:

1. Formulate regression as a supervised-learning problem.
2. Represent simple and multiple linear regression mathematically.
3. Compute predictions, residuals, and squared errors.
4. Explain Mean Squared Error as an objective function.
5. Describe how gradient descent reduces loss.
6. Perform one manual parameter update for a simple linear model.
7. Distinguish batch, stochastic, and mini-batch gradient descent.
8. Explain overfitting through model flexibility and polynomial features.
9. Explain Ridge and Lasso regularization conceptually.
10. Evaluate regression models using MAE, MSE, RMSE, and R^2.

CIS — Course Slides Only

Lecture Roadmap

FCIS — Course Use Only

From a line to a learning algorithm

Stage	Main idea	Student output
1. Regression formulation	Predict a continuous quantity from input features.	Identify X, y, model output, and residuals.
2. Linear model	Represent prediction using weights and an intercept.	Compute $\hat{y} = w^\top x + b$.
3. Loss and optimization	Learn parameters by minimizing prediction error.	Compute MSE and one gradient update.
4. Model flexibility	More flexible models may fit training data too closely.	Explain underfitting/overfitting with polynomial features.
5. Regularization and evaluation	Penalize complexity and measure generalization.	Interpret Ridge/Lasso and regression metrics.

Course Use Only

Part I

FCIS — For Students Use Only

Regression as Supervised Learning

Regression predicts a **continuous numerical target** from one or more input features.

FCIS — For Course Use Only

What is a Regression Problem?

FCIS Internal Use Only

Predicting a numerical quantity

In supervised learning, we observe examples: $(x_i, y_i), \quad i = 1, \ldots, n$

For regression:

- x_i is the input feature vector;
- y_i is a real-valued target;
- the model predicts a number: $\hat{y}_i = f(x_i)$

Examples

Problem	Input features	Target
Predict apartment rent	area, district, rooms, age	monthly rent
Predict delivery time	distance, traffic, weather	minutes
Predict exam score	study hours, attendance, previous GPA	score
Predict customer spending	orders, visits, recency	spending amount

FCIS – For Course Use Only

💡 Regression is not about assigning a class. It is about estimating a numerical value.

The Learning Task

FCIS — Academic Use Only

Approximate an unknown relationship

The true relationship between features and target is usually unknown:

$$y = f(x) + \varepsilon$$

where:

- $f(x)$ is the systematic pattern;
- ε is noise, measurement error, or unobserved influence.

A model attempts to learn an approximation:

$$\hat{y} = \hat{f}(x)$$

FCIS — For Course Use Only

Goal

Find a model that predicts well on **new examples**, not only on the training data.

> A rent model should work for future apartments, not only for the apartments used during training.

Dataset Representation

FCIS — Private Use Only

Feature matrix and target vector

A regression dataset can be represented as:

$$X = \begin{bmatrix} x_{11} & x_{12} & \cdots & x_{1p} \\ x_{21} & x_{22} & \cdots & x_{2p} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \cdots & x_{np} \end{bmatrix}, \qquad y = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}.$$

Each row of X is one observation.

Each column of X is one feature.

FCIS — For Course Use Only

Prediction target

The model learns a function from features to target:

$$X \to y$$

Example Dataset

FCIS Lecture Use Only

Predicting final exam score

Student	Study Hours	Attendance (%)	Previous GPA	Final Score
A	3	60	2.1	55
B	6	75	2.8	68
C	9	88	3.2	81
D	12	95	3.6	90

Possible supervised-learning formulation

- Features: study hours, attendance, previous GPA
- Target: final score
- Task: regression
- Model output: predicted final score

FCIS – Student Course Use Only

💡 The target column should not be included as an input feature.

Residuals

FCIS — Private Use Only

How wrong is the prediction?

For each observation, the residual is:

$$e_i = y_i - \hat{y}_i$$

Interpretation:

Residual	Meaning
$e_i > 0$	model underpredicted
$e_i < 0$	model overpredicted
$e_i = 0$	exact prediction

FCIS - For Course Use Only

Why residuals matter

Residuals are the raw material for loss functions and diagnostic plots.

> If residuals show a systematic pattern, the model may be too simple or missing an important feature.

Part II

FCIS — For Private Use Only

Simple Linear Regression

Simple linear regression uses one feature to predict one continuous target using a straight line.

FCIS — For Course Use Only

Simple Linear Model

FCIS — Private Use Only

One feature, one target

Simple linear regression assumes: $\hat{y} = w_0 + w_1 x$

Where:

- w_0 is the intercept;
- w_1 is the slope;
- x is the input feature;
- $\hat{y}$ is the predicted target.

Interpretation

Parameter	Meaning
w_0	predicted value when $x = 0$
w_1	expected change in $\hat{y}$ for one-unit increase in x

> 💡 The model is linear in the parameters, not necessarily always sufficient for the data.

FCIS — For Course Use Only

Visual Interpretation

FCIS — For Educational Use Only

A line through data

Imagine predicting score from study hours.

Each data point represents one student:

$$(x_i, y_i)$$

The model line gives:

$$\hat{y}_i = w_0 + w_1 x_i$$

The vertical distance between the point and the line is the residual:

$$e_i = y_i - \hat{y}_i.$$

FCIS — For Course Use Only

> Training linear regression means finding a line whose residuals are small according to a chosen loss function.

Worked Prediction Example

FCIS — Internal Use Only

Compute $\hat{y}$ and residuals

Suppose the model is:

$$\hat{y} = 40 + 4x$$

where x is study hours.

For a student who studied $x = 6$ hours:

$$\hat{y} = 40 + 4(6) = 64$$

If the actual score is:

$$y = 68$$

then the residual is:

$$e = y - \hat{y} = 68 - 64 = 4$$

> The model underpredicted by 4 points.

FCIS — For Course Use Only

Multiple Linear Regression

FCIS — For Course Use Only

Many features, one target

With p features, the model becomes:

$$\hat{y} = w_0 + w_1 x_1 + w_2 x_2 + \cdots + w_p x_p$$

Vector form:

$$\hat{y} = w^\top x + b$$

Where:

- w is a vector of feature weights;
- b is the intercept;
- x is the feature vector.

FCIS — For Course Use Only

Example

$$\widehat{\text{score}} = 30 + 3(\text{hours}) + 0.2(\text{attendance}) + 5(\text{GPA})$$

Interpreting Coefficients

FCIS — For Course Use Only

What does a weight mean?

In a linear model: $\hat{y} = w_0 + w_1 x_1 + \cdots + w_p x_p$

the coefficient w_j is interpreted as the expected change in prediction when x_j increases by one unit, holding other features fixed.

Cautions

Issue	Why interpretation becomes difficult
Different feature scales	coefficients cannot be compared directly
Correlated features	effects are difficult to separate
Nonlinear relationships	linear coefficient may oversimplify
Interactions	effect of one feature may depend on another
Categorical encoding	interpretation depends on reference category

For Course Use Only

💡 Coefficient interpretation requires both mathematics and domain understanding.

Model Assumptions

FCIS — Private Use Only

What linear regression assumes approximately

Classical linear regression is most appropriate when:

- the relationship is approximately linear;
- residuals have mean near zero;
- residual variance is reasonably stable;
- observations are independent;
- features are measured appropriately;
- extreme outliers are not dominating the fit.

FCIS — For Course Use Only

In machine learning practice

We often focus less on formal statistical inference and more on predictive performance.

But assumptions still matter because they explain **when the model may fail**.

> A highly curved relationship may require feature transformations, polynomial terms, or a different model.

Part III

FCIS — For Private Use Only

Loss Functions

A loss function turns prediction errors into a numerical objective that the learning algorithm can minimize.

FCIS — For Course Use Only

Why We Need a Loss Function

FCIS — Course Use Only

Learning requires a criterion

Many possible lines can be drawn through data.

A loss function answers:

> Which line is better?

For regression, we often penalize prediction errors:

$$e_i = y_i - \hat{y}_i$$

FCIS — For Course Use Only

Common choices:

Loss idea	Formula
absolute error	$\lvert y_i - \hat{y}_i \rvert$
squared error	$(y_i - \hat{y}_i)^2$

💡 The chosen loss influences what the model considers a “good” fit.

Mean Squared Error

FCIS — Course Use Only

The standard regression objective

Mean Squared Error is:

$$MSE = \frac{1}{n}\sum_{i=1}^{n}(y_i - \hat{y}_i)^2$$

Why square the errors?

- negative and positive errors do not cancel;
- larger errors are penalized more strongly;
- the objective is smooth and convenient for optimization.

For Course Use Only

But

MSE can be sensitive to outliers because large errors are squared.

Worked Example: MSE

FCIS — Course Use Only

Three predictions

Observation	Actual y	Prediction $\hat{y}$	Error $y - \hat{y}$	Squared error
1	70	68	2	4
2	80	76	4	16
3	90	95	-5	25

Then:

$$MSE = \frac{4 + 16 + 25}{3} = 15$$

FCIS — For Course Use Only

Root Mean Squared Error:

$$RMSE = \sqrt{15} \approx 3.87$$

RMSE is in the same unit as the target, which often makes it easier to interpret.

Loss Surface

FCIS — For Educational Use Only

Parameters determine loss

For a simple model:

$$\hat{y} = w_0 + w_1 x$$

the loss depends on the parameters:

$$L(w_0, w_1) = \frac{1}{n} \sum_{i=1}^{n} (y_i - (w_0 + w_1 x_i))^2$$

Learning means finding parameters that reduce this loss.

For — For Course Use Only

> 💡 Optimization is the process of moving through parameter space toward lower loss.

Part IV

FCIS — Personal Use Only

Gradient Descent

Gradient descent is a general method for learning parameters by repeatedly moving in the direction that reduces the loss.

FCIS — For Course Use Only

Gradient Descent Intuition

FCIS — Course Use Only

Follow the slope downhill

Suppose the model has a parameter w and loss $L(w)$.

The derivative

$$\frac{dL}{dw}$$

tells us the slope of the loss with respect to w.

Gradient descent updates:

$$w \leftarrow w - \alpha \frac{dL}{dw}$$

FCIS — For Course Use Only

Where:

- α is the learning rate;
- the derivative points uphill;
- subtracting it moves downhill.

> If the derivative is positive, decrease w. If the derivative is negative, increase w.

Learning Rate

FCIS — For Course Use Only

Step size matters

The learning rate α controls how large each update is.

Learning rate	Possible behavior
Too small	very slow learning
Reasonable	gradual loss reduction
Too large	overshooting or divergence

FCIS — For Course Use Only

Update rule

$$w \leftarrow w - \alpha \nabla_w L$$

💡 Choosing a learning rate is a hyperparameter decision, not something learned directly from the training data.

Gradient for Simple Linear Regression

For Course Use Only

One data point

For one example: $\hat{y} = wx + b$

Use squared error: $L = (\hat{y} - y)^2$

Let the prediction error be: $r = \hat{y} - y$

Then: $\frac{\partial L}{\partial w} = 2rx$

and: $\frac{\partial L}{\partial b} = 2r$

Update:

$$w \leftarrow w - \alpha(2rx)$$

$$b \leftarrow b - \alpha(2r)$$

FCIS — For Course Use Only

Worked Gradient Update

FCIS — For Use Only

One example, one step

Suppose: $x = 3, \qquad y = 10$

and the current model parameters are: $w = 2, \qquad b = 1$

Prediction: $\hat{y} = wx + b = 2(3) + 1 = 7$

Prediction error: $r = \hat{y} - y = 7 - 10 = -3$

Gradients:

$$\frac{\partial L}{\partial w} = 2rx = 2(-3)(3) = -18$$

$$\frac{\partial L}{\partial b} = 2r = 2(-3) = -6$$

FCIS — For Course Use Only

With $\alpha = 0.1$:

$$w_{\text{new}} = 2 - 0.1(-18) = 3.8$$

$$b_{\text{new}} = 1 - 0.1(-6) = 1.6$$

Because the model underpredicted, both w and b increased.

Batch Gradient Descent

FCIS — Private Use Only

Use all training examples before updating

Batch Gradient Descent computes gradients using the entire training set:

$$\nabla L = \frac{1}{n} \sum_{i=1}^{n} \nabla L_i$$

Advantages

- stable direction;
- directly follows the full loss surface;
- good for small datasets.

Limitations

- expensive for very large datasets;
- one update requires scanning all examples;
- can be slow when n is large.

FCIS — For Course Use Only

💡 Batch gradient descent is conceptually clean but not always computationally efficient.

Stochastic Gradient Descent

FCIS — Personal Use Only

Update using one example at a time

Stochastic Gradient Descent updates parameters using one training example at a time.

Advantages

- fast updates;
- can handle large datasets;
- noisy updates may help escape shallow regions.

Limitations

- update direction is noisy;
- loss curve may fluctuate;
- learning rate scheduling becomes important.

FCIS — For Course Use Only

$$w \leftarrow w - \alpha \nabla L_i(w)$$

> SGD trades stability for speed and scalability.

Mini-Batch Gradient Descent

FCIS — Personal Course Use Only

A practical compromise

Mini-batch Gradient Descent uses a small subset of examples at each update.

If a mini-batch B has m examples:

$$\nabla L_B = \frac{1}{m} \sum_{i \in B} \nabla L_i.$$

Why common in practice?

- more stable than SGD;
- less expensive than full batch;
- efficient on modern hardware;
- works naturally with neural networks.

FCIS — For Course Use Only

💡 Mini-batch gradient descent is often the default training strategy for large-scale models.

Comparing Gradient Descent Variants

For Course Use Only

Stability vs. efficiency

Method	Data per update	Strength	Weakness
Batch GD	all examples	stable gradients	expensive for large data
SGD	one example	fast frequent updates	noisy trajectory
Mini-batch GD	small batch	practical compromise	still needs tuning

Conceptual comparison

Batch: stable but expensive

SGD: fast but noisy

Mini-batch: balanced

FCIS - For Course Use Only

When Optimization Fails

FCIS — Private Use Only

Common causes

Gradient descent may behave poorly when:

- the learning rate is too large;
- the learning rate is too small;
- features are on very different scales;
- the loss surface is ill-conditioned;
- the model is too flexible for the data;
- gradients vanish or explode in deep networks.

Practical response

- scale features;
- monitor training and validation loss;
- tune learning rate;
- use mini-batches;
- add regularization;
- stop training when validation performance worsens.

FCIS — For Course Use Only

💡 Optimization behavior is strongly connected to preprocessing and model complexity.

Part V

FCIS — For Private Use Only

Model Flexibility and Overfitting

A model that fits training data extremely well may still generalize poorly.

FCIS — For Course Use Only

Underfitting and Overfitting

FCIS Course Use Only

The central generalization problem

Situation	Training error	Validation/test error	Interpretation
Underfitting	high	high	model too simple or poor features
Good fit	low/moderate	low/moderate	captures useful pattern
Overfitting	very low	high	model fits noise/idiosyncrasies

Reminder

The objective is not to minimize training error at all costs.

The objective is to predict well on new data.

> 💡 Training performance alone cannot tell us whether a model generalizes.

FCIS Course Use Only

Polynomial Features

FCIS — Private Use Only

Increasing model flexibility

A linear model in x may be too simple for curved data.

We can add polynomial features:

$$x, \quad x^2, \quad x^3, \ldots$$

Then:

$$\hat{y} = w_0 + w_1 x + w_2 x^2 + w_3 x^3$$

The model is still linear in the parameters w_j, but it can represent nonlinear curves in the original input.

Risk

More polynomial terms can reduce training error but increase overfitting.

For Course Use Only

Flexibility Example

FCIS — Private Use Only

Three possible fits

Suppose the true relationship is curved.

Model	Behavior
Degree 1 polynomial	may underfit
Degree 2 or 3 polynomial	may capture the trend
Very high degree polynomial	may pass through nearly every point and overfit

> A very flexible curve may follow noise instead of the underlying pattern.

Key question

Which model gives the best validation performance?

Bias–Variance Intuition

FCIS — Course Use Only

A qualitative view

The expected prediction error can be understood through:

- bias;
- variance;
- irreducible noise.

High bias

The model is too simple and misses the pattern.

High variance

The model is too sensitive to the training data.

> 💡 Increasing flexibility often decreases bias but increases variance.

FCIS — For Course Use Only

Part VI

FCIS — For Class Use Only

Regularization

Regularization discourages unnecessarily complex models by adding a penalty to the loss.

FCIS — For Course Use Only

Why Regularize?

FCIS — Private Use Only

Control model complexity

The ordinary regression objective minimizes training error:

$$\text{Training Loss}$$

Regularization modifies the objective:

$$\text{Training Loss} + \lambda \times \text{Complexity Penalty}$$

FCIS - For Course Use Only

Where:

- λ controls the strength of regularization;
- larger λ means stronger penalty;
- λ is a hyperparameter.

> 💡 Regularization accepts a little more training error if it improves generalization.

Ridge Regression

FCIS — Private Use Only

Penalize large squared coefficients

Ridge regression adds an L_2 penalty:

$$L_{\text{ridge}} = MSE + \lambda \sum_{j=1}^{p} w_j^2$$

Effect

- shrinks coefficients toward zero;
- usually keeps all features;
- reduces sensitivity to noise and multicollinearity;
- often improves generalization.

> Ridge is useful when many features may contribute a little.

For Course Use Only

Lasso Regression

FCIS — For Course Use Only

Penalize absolute coefficient size

Lasso adds an L_1 penalty:

$$L_{\text{lasso}} = MSE + \lambda \sum_{j=1}^{p} |w_j|$$

Effect

- shrinks coefficients;
- can set some coefficients exactly to zero;
- performs a form of feature selection;
- useful when only a subset of features is expected to matter.

FCIS — For Course Use Only

💡 Lasso can simplify the model by removing some features from the prediction.

Ridge vs. Lasso

FCIS — For Course Use Only

Similar goal, different behavior

Aspect	Ridge	Lasso
Penalty	$\sum w_j^2$	$\sum \lvert w_j \rvert$
Coefficient effect	shrinks weights	can set weights to zero
Feature selection	usually no	yes, often
Useful when	many features contribute	few features matter
Stability	often stable with correlated features	may choose one of correlated features

Both methods require selecting λ, usually using validation or cross-validation.

Regularization Strength

FCIS — Course Use Only

What happens as λ changes?

λ	Expected behavior
0	ordinary linear regression
small	mild shrinkage
moderate	improved generalization possible
very large	coefficients strongly suppressed; underfitting risk

FCIS — For Course Use Only

Selection principle

Choose λ using validation performance, not training error alone.

> 💡 A stronger penalty is not always better. It must balance bias and variance.

Part VII

FCIS — Students Use Only

Regression Evaluation

A regression model should be evaluated using metrics that match the prediction goal and application context.

FCIS — For Course Use Only

MAE

FCIS — Personal Use Only

Mean Absolute Error

Mean Absolute Error is:

$$MAE = \frac{1}{n}\sum_{i=1}^{n}|y_i - \hat{y}_i|$$

Interpretation

MAE is the average absolute prediction error in target units.

Advantages

- easy to understand;
- less sensitive to outliers than MSE;
- directly interpretable.

Limitation

- not smooth at zero error, though this is usually not a practical problem for evaluation.

FCIS — For Course Use Only

MSE and RMSE

FCIS — Private Use Only

Penalizing larger errors

Mean Squared Error:

$$MSE = \frac{1}{n}\sum_{i=1}^{n}(y_i - \hat{y}_i)^2$$

Root Mean Squared Error:

$$RMSE = \sqrt{MSE}$$

FCIS — For Course Use Only

Interpretation

- MSE penalizes large errors strongly.
- RMSE returns to the original target unit.

If large errors are especially costly, RMSE may be more informative than MAE.

Coefficient of Determination

FCIS — Course Use Only

R^2

The coefficient of determination is:

$$R^2 = 1 - \frac{\sum_i (y_i - \hat{y}_i)^2}{\sum_i (y_i - \bar{y})^2}$$

Interpretation:

- $R^2 = 1$ means perfect prediction on the evaluated data.
- $R^2 = 0$ means no improvement over predicting the mean.
- $R^2 < 0$ means worse than predicting the mean.

> 💡 A high training R^2 does not guarantee good test performance.

Choosing a Regression Metric

FCIS — Private Use Only

The metric should match the application

Situation	Possible metric emphasis
Errors have linear cost	MAE
Large errors are especially bad	RMSE
Need variance-explained summary	R^2
Need easy unit interpretation	MAE or RMSE
Comparing across different targets	normalized or relative metrics

FCIS — For Course Use Only

Example

In medical dosage prediction, a few very large errors may be dangerous. RMSE or application-specific safety metrics may be important.

In rent estimation, MAE may be easy to explain:

> “The model is off by about 350 SAR on average.”

Evaluation Workflow

FCIS — Internal Use Only

Train, validate, test

A good workflow:

1. Fit preprocessing on the training set.
2. Train the model on training data.
3. Tune hyperparameters using validation data.
4. Compare models using validation performance.
5. Evaluate once on the test set.
6. Report the metric and interpret it in context.

FCIS — Course Use Only

> 💡 Evaluation is part of the modeling process, not an afterthought.

Part VIII

FCIS — Lecture Use Only

Worked Mini-Case

Let us connect the full regression pipeline using a small apartment-rent example.

FCIS — For Course Use Only

Mini-Case: Apartment Rent

FCIS — Course Use Only

Problem formulation

A real-estate website wants to estimate apartment rent.

Features

Feature	Type	Preprocessing
Area	numerical	scaling
Number of rooms	discrete numerical	scaling or keep as count
District	nominal categorical	one-hot encoding
Building age	numerical	scaling, possible nonlinear term
Furnished	binary	encode 0/1

FCIS — For Course Use Only

Target

$$y = \text{monthly rent}$$

> This is a supervised regression problem.

Mini-Case: Candidate Models

FCIS — Course Use Only

Different choices, different assumptions

Model	Assumption / behavior
Linear regression	rent changes linearly with features
Polynomial features + linear regression	allows curvature
Ridge regression	linear model with coefficient shrinkage
Lasso regression	linear model with possible feature selection

Evaluation plan

- Use validation data to select feature transformations and λ.
- Use test data only once for final evaluation.
- Report MAE and RMSE.
- Interpret whether the error is acceptable for users.

FCIS — For Course Use Only

Mini-Case: Reasoning Questions

FCIS — Course Use Only

What should students explain?

1. Why is `district` not directly numerical?
2. Why should area and building age possibly be scaled?
3. Why might building age have a nonlinear effect?
4. Why might Ridge help when many district indicators are used?
5. Why might MAE be easier to communicate to end users than MSE?
6. Why should the final test set not be used to choose λ?

ECIS — For Course Use Only

> A good model report explains both the numerical results and the reasoning behind preprocessing and modeling choices.

Part IX

FCIS — Personal Use Only

Activities and Common Mistakes

Linear regression is easy to implement, but easy to misuse.

FCIS — For Course Use Only

Activity: Compute Predictions

FCIS — For Course Use Only

Manual practice

Suppose:

$$\widehat{\text{score}} = 30 + 3(\text{hours}) + 0.2(\text{attendance}) + 5(\text{GPA})$$

For a student with:

$$\text{hours} = 8 \qquad \text{attendance} = 90 \qquad \text{GPA} = 3.0$$

compute the predicted score.

FCIS — For Course Use Only

Questions

1. What is $\hat{y}$?
2. If the actual score is 82, what is the residual?
3. Did the model overpredict or underpredict?

Manual practice

Suppose:

$$\widehat{\text{score}} = 30 + 3(\text{hours}) + 0.2(\text{attendance}) + 5(\text{GPA})$$

For a student with:

$$\text{hours} = 8 \qquad \text{attendance} = 90 \qquad \text{GPA} = 3.0$$

compute the predicted score.

FCIS — For Course Use Only

Questions

1. What is $\hat{y}$?
2. If the actual score is 82, what is the residual?
3. Did the model overpredict or underpredict?

$\hat{y} = 30 + 3(8) + 0.2(90) + 5(3) = 87$. Residual $= 82 - 87 = -5$, so the model overpredicted by 5.

Activity: Choose the Better Model

FCIS — Internal Use Only

Compare validation metrics

Two rent-prediction models were evaluated on validation data.

Model	MAE	RMSE	Interpretation
A	410	690	
B	460	540	

Questions

1. Which model has smaller average absolute error?
2. Which model has fewer very large errors?
3. Which one would you choose if large errors are very costly?
4. Why is there not always a single obvious answer?

FCIS — For Course Use Only

Compare validation metrics

Two rent-prediction models were evaluated on validation data.

Model	MAE	RMSE	Interpretation
A	410	690	
B	460	540	

Questions

1. Which model has smaller average absolute error?
2. Which model has fewer very large errors?
3. Which one would you choose if large errors are very costly?
4. Why is there not always a single obvious answer?

FCIS — For Course Use Only

> Model A has lower MAE, while Model B has lower RMSE. If large errors are especially costly, Model B may be preferable.

Activity: Detect Overfitting

FCIS — Private Use Only

Training vs. validation performance

Model	Training RMSE	Validation RMSE
Linear	18.5	20.1
Degree 3 polynomial	10.2	14.0
Degree 12 polynomial	1.1	38.7

Questions

1. Which model underfits?
2. Which model likely overfits?
3. Which model appears best by validation RMSE?
4. Why should we not choose the model with the lowest training error?

FCIS — For Course Use Only

Training vs. validation performance

Model	Training RMSE	Validation RMSE
Linear	18.5	20.1
Degree 3 polynomial	10.2	14.0
Degree 12 polynomial	1.1	38.7

Questions

1. Which model underfits?
2. Which model likely overfits?
3. Which model appears best by validation RMSE?
4. Why should we not choose the model with the lowest training error?

FCIS — For Course Use Only

> Degree 12 likely overfits. Degree 3 appears best by validation RMSE. The lowest training error is not the goal.

Common Mistakes

FCIS — Personal Use Only

Regression modeling errors

Mistake	Why it is a problem
Evaluating only training error	hides overfitting
Using target-derived features	leakage
Ignoring feature scale with regularization	penalty becomes hard to interpret
Choosing polynomial degree using test error repeatedly	test set becomes validation set
Interpreting coefficients without considering units	misleading comparisons
Removing outliers automatically	may remove important rare cases
Reporting MSE without units explanation	difficult for users to understand
Assuming linearity without checking residuals	may underfit nonlinear patterns

FCIS — For Course Use Only

Mini-Quiz

FCIS — For Course Use Only

Check your understanding

1. What is the difference between a prediction error and a loss?
2. Why does MSE penalize large errors more than MAE?
3. What does the learning rate control in gradient descent?
4. Why can polynomial features cause overfitting?
5. What is the main difference between Ridge and Lasso?
6. Why should λ be chosen using validation data?
7. Which metric is more interpretable in the original target unit: MSE or RMSE?
8. What does $R^2 < 0$ mean?

FCIS — For Course Use Only

Check your understanding

1. What is the difference between a prediction error and a loss?
2. Why does MSE penalize large errors more than MAE?
3. What does the learning rate control in gradient descent?
4. Why can polynomial features cause overfitting?
5. What is the main difference between Ridge and Lasso?
6. Why should λ be chosen using validation data?
7. Which metric is more interpretable in the original target unit: MSE or RMSE?
8. What does $R^2 < 0$ mean?

FCIS — For Course Use Only

Suggested answers: error is per prediction while loss aggregates errors; MSE squares errors; learning rate controls update size; high-degree polynomials can fit noise; Ridge shrinks, Lasso can zero coefficients; hyperparameters need validation; RMSE has original units; the model is worse than predicting the mean.

Lecture 3 Summary

FCIS — For Course Use Only

Key ideas to retain

Linear regression and optimization

- Regression predicts a continuous target.
- Linear regression uses:

$$\hat{y} = w^\top x + b.$$

- Residuals measure prediction errors.
- MSE is a common regression objective.
- Gradient descent updates parameters to reduce loss.
- Batch, stochastic, and mini-batch GD differ in how much data each update uses.

Generalization and evaluation

- More flexibility can reduce training error but increase overfitting.
- Polynomial features can represent nonlinear patterns.
- Ridge and Lasso add penalties to control complexity.
- MAE, MSE, RMSE, and R^2 describe regression performance differently.
- Model choice should be based on validation performance and application context.

FCIS — For Course use Only

End-of-Lecture Check

FCIS — Private Use Only

Five questions to test your understanding

1. How does a linear regression model make a prediction?
2. What does gradient descent change during training?
3. Why does scaling matter when regularization is used?
4. How can polynomial features produce both better fits and overfitting?
5. Which regression metric would you report to a non-technical stakeholder, and why?

For Course Use Only

Preparation for next lecture: Review the sigmoid function, probability interpretation, binary classification, and the difference between regression and classification.

Suggested Reading

FCIS — Private Use Only

Primary and supporting references

Primary reference

G. James, D. Witten, T. Hastie, and R. Tibshirani, *An Introduction to Statistical Learning with Applications in Python*, Springer, 2023.

- Review chapters/sections on linear regression, model flexibility, training/test error, and regularization.

Supporting references

A. Géron, *Hands-On Machine Learning with Scikit-Learn, Keras, and TensorFlow*, O'Reilly, 2022.

- Review linear models, gradient descent, polynomial regression, and regularized linear models.

K. P. Murphy, *Probabilistic Machine Learning: An Introduction*, MIT Press, 2022.

- Use selected sections for a deeper probabilistic view of regression, loss functions, and optimization.

For Course Use Only

💡 When reading, focus on how prediction, loss, optimization, and generalization form one connected learning process.