

How to Avoid Brute Force Attacks?


To protect your organization from brute force attack, enforce the use of strong passwords.

You can find some best practices for passwords below:

- Never use information that can be found online (like names of family members).
- Have as many characters as possible.
- Combine letters, numbers, and symbols.
- Minimum 8 characters.
- Each user account is different.
- Avoid common patterns.

Here are some ways you can protect users from brute-force attacks as administrators of an organization:

Lock Policy - After a certain number of failed login attempts, you can lock accounts and then unlock them as an administrator.



Progressive delays - You can lock accounts for a limited time after a certain number of failed login attempts.

Recaptcha - With tools such as Captcha-reCAPTCHA, you can make it mandatory for users to complete simple tasks in order to log on to a system.



☐ I'm not a robot


reCAPTCHA
[Privacy](#) - [Terms](#)

Strong Password Policy - You can force users to define long and complex passwords and force them to change their password periodically.



2FA - It is the method where a second verification is required from the user with an additional verification mechanism (SMS, mail, token, push notification, etc.) after entering the username and password.



4.1. Brute Force Attack Detection

Specific rules are usually defined on SIEM systems to detect brute force attacks. When defining these rules, we consider how many unsuccessful login attempts are made by the user within a certain period of time. While analyzing the relevant alarms, the logs of the trial protocol/application are examined and the necessary inferences are made. Examples of some brute force attacks are given below.

Source: Let's Defend.