

# Subsetting Data in R

# Overview

In this module, we will show you how to:

1. Look at your data in different ways
2. Create a data frame and a tibble
3. Create new variables/make rownames a column
4. Rename columns of a data frame
5. Subset rows of a data frame
6. Subset columns of a data frame
7. Add/remove new columns to a data frame
8. Order the columns of a data frame
9. Order the rows of a data frame

# Setup

We will largely focus on the `dplyr` package which is part of the `tidyverse`.



Some resources on how to use `dplyr`:

- <https://dplyr.tidyverse.org/>
- <https://cran.r-project.org/web/packages/dplyr/vignettes/dplyr.html>
- <https://www.opencasestudies.org/>

# Why dplyr?



**hadley** commented on May 26, 2016

Member ...

The d is for dataframes, the plyr is to evoke pliers. Pronounce however you like.



The `dp1yr` package is one of the most helpful packages for altering your data to get it into a form that is useful for creating visualizations, summarizing, or more deeply analyzing.

So you can imagine using pliers on your data.

## Loading in dplyr and tidyverse

See this website for a list of the packages included in the tidyverse:

<https://www.tidyverse.org/packages/>

```
library(tidyverse) # loads dplyr and other packages!
```

## Getting data to work with

Here we use one of the datasets that comes with base R called `mtcars`. We will now create a toy data frame named `df` using this data. This way we can alter `df` without worrying about changing `mtcars`.

```
df <- mtcars # df is a copy of mtcars  
head(df) # changing df does **not** change mtcars!
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

## Checking the data `dim()`

The `dim()`, `nrow()`, and `ncol()` functions are good options to check the dimensions of your data before moving forward.

```
dim(df) # rows, columns
```

```
[1] 32 11
```

```
nrow(df) # number of rows
```

```
[1] 32
```

```
ncol(df) # number of columns
```

```
[1] 11
```

## Checking the data: `glimpse()`

In addition to `head()` and `tail()`, the `glimpse()` function of the `dplyr` package is another great function to look at your data.

```
glimpse(df)
```

```
Rows: 32
```

```
Columns: 11
```

```
$ mpg   <dbl> 21.0, 21.0, 22.8, 21.4, 18.7, 18.1, 14.3, 24.4, 22.8, 19.2, 17.8,...  
$ cyl   <dbl> 6, 6, 4, 6, 8, 6, 8, 4, 4, 6, 6, 8, 8, 8, 8, 8, 8, 4, 4, 4, 4, 8,...  
$ disp  <dbl> 160.0, 160.0, 108.0, 258.0, 360.0, 225.0, 360.0, 146.7, 140.8, 16...  
$ hp    <dbl> 110, 110, 93, 110, 175, 105, 245, 62, 95, 123, 123, 180, 180, 180...  
$ drat  <dbl> 3.90, 3.90, 3.85, 3.08, 3.15, 2.76, 3.21, 3.69, 3.92, 3.92, 3.92,...  
$ wt    <dbl> 2.620, 2.875, 2.320, 3.215, 3.440, 3.460, 3.570, 3.190, 3.150, 3....  
$ qsec  <dbl> 16.46, 17.02, 18.61, 19.44, 17.02, 20.22, 15.84, 20.00, 22.90, 18...  
$ vs    <dbl> 0, 0, 1, 1, 0, 1, 0, 1, 1, 1, 1, 0, 0, 0, 0, 0, 0, 1, 1, 1, 1, 0,...  
$ am    <dbl> 1, 1, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0,...  
$ gear  <dbl> 4, 4, 4, 3, 3, 3, 3, 4, 4, 4, 4, 3, 3, 3, 3, 3, 3, 4, 4, 4, 3, 3,...  
$ carb  <dbl> 4, 4, 1, 1, 2, 1, 4, 2, 2, 4, 4, 3, 3, 3, 4, 4, 4, 1, 2, 1, 1, 2,...
```



## Checking your data: `slice_sample()`

What if you want to see the middle of your data? You can use the `slice_sample()` function of the `dplyr` package to see a random set of rows. You can specify the number of rows with the `n` argument or use a proportion with the `prop` argument.

```
slice_sample(df, n = 3)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2

```
slice_sample(df, prop = .2)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2

# Making data frames(base R) and tibbles (tidyverse)

# Creating data frames using base R data frame function

```
data.frame(df)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360.0	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225.0	105	2.76	3.460	20.22	1	0	3	1
Duster 360	14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Merc 280	19.2	6	167.6	123	3.92	3.440	18.30	1	0	4	4
Merc 280C	17.8	6	167.6	123	3.92	3.440	18.90	1	0	4	4
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Lincoln Continental	10.4	8	460.0	215	3.00	5.424	17.82	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2
AMC Javelin	15.2	8	304.0	150	3.15	3.435	17.30	0	0	3	2
Camaro Z28	13.3	8	350.0	245	3.73	3.840	15.41	0	0	3	4
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2

## Keep in mind...

Need to assign the output of the function to keep the result!

```
df_updated <- data.frame(df)
# this would overwrite the existing df object
df <- data.frame(df)
```

Or create a data frame when reading in the file

Or directly when reading in a csv with the `read.csv()` function (also base R)

```
# function comes from base R - no package loading required  
df_example_readr <- read.csv("documents/data_analysis/data_file.csv")
```

## tibble

We can create a **fancier** version of the previous data frame which can be really helpful.

## Creating a tibble

If we would like to create a `tibble` ("fancy" data frame), we can use the `tibble()` function.

```
tbl <- dplyr::tibble(df)
tbl
```

```
# A tibble: 32 × 11
   mpg   cyl  disp    hp  drat    wt   qsec    vs  am  gear  carb
  <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
1    21     6  160    110   3.9    2.62  16.5     0     1     4     4
2    21     6  160    110   3.9    2.88  17.0     0     1     4     4
3   22.8     4  108     93   3.85    2.32  18.6     1     1     4     1
4   21.4     6  258    110   3.08    3.22  19.4     1     0     3     1
5   18.7     8  360    175   3.15    3.44  17.0     0     0     3     2
6   18.1     6  225    105   2.76    3.46  20.2     1     0     3     1
7   14.3     8  360    245   3.21    3.57  15.8     0     0     3     4
8   24.4     4  147.     62   3.69    3.19   20      1     0     4     2
9   22.8     4  141.     95   3.92    3.15  22.9     1     0     4     2
10  19.2     6  168.    123   3.92    3.44  18.3     1     0     4     4
# ... with 22 more rows
```

Note don't necessarily need to use `head()` - tibbles conveniently print a portion of the data.

## tibbles from read\_csv()

Alternatively we can read data files using the tidyverse with the `read_csv()` function of the `readr` package from the `tidyverse` to make a tibble.

```
df_example_readr <- read_csv("documents/data_analysis/data_file.csv")
```

You may start to notice how the tidyverse package work well together!



# Summary of tibbles and data frames

## **Base R:**

Using `read.csv()` and `data.frame()` you can make data frames

## **Tidyverse (fancier version):**

Using `read_csv()` and `tibble()` you can make tibbles

We generally recommend using tibbles, but you can do a lot with tibbles too.

## Data frames vs tibbles

In the “tidy” data format, rownames are removed. For example, `df` has each car name as a row name. Here we use the `head()` function to see the first 2 rows of each. In this case we would want to make the rownames a new column first before making into a tibble.

```
head(df, 2)
```

		mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda	RX4	21	6	160	110	3.9	2.620	16.46	0	1	4	4
Mazda	RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4

```
head(tibble(df), 2)
```

```
# A tibble: 2 × 11
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	21	6	160	110	3.9	2.62	16.5	0	1	4	4
2	21	6	160	110	3.9	2.88	17.0	0	1	4	4

## rownames\_to\_column function

If you run into losing a variable contained in your row names, you can also use `rownames_to_column` to add it before turning it into a `tibble` to keep them:

```
head(rownames_to_column(df, var = "car"), 2)
```

	car	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
1	Mazda RX4	21	6	160	110	3.9	2.62	16.46	0	1	4	4
2	Mazda RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4

```
head(tibble(rownames_to_column(df, var = "car")), 2)
```

```
# A tibble: 2 × 12
```

	car	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
	<chr>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
1	Mazda RX4	21	6	160	110	3.9	2.62	16.5	0	1	4	4
2	Mazda RX4 W...	21	6	160	110	3.9	2.88	17.0	0	1	4	4

# Renaming Columns

# Renaming Columns of a data frame or tibble

To rename columns in `dplyr`, you can use the `rename` function.

For example, let's rename `mpg` to `MPG`. Notice the new name is listed **first**!

*# general format! not code!*

```
{data you are creating or changing} <- rename({data you are using},  
                                              {New Name} = {Old name})
```

```
df <- dplyr::rename(df, MPG = mpg)  
head(df)
```

	MPG	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

## Renaming All Columns of a data frame: dplyr

To rename all columns you use the `rename_all()`. In this case we will use `toupper()` to make all letters upper case. Could also use `tolower()` function.

```
df_upper <- dplyr::rename_all(df, toupper)
head(df_upper, 3)
```

	MPG	CYL	DISP	HP	DRAT	WT	QSEC	VS	AM	GEAR	CARB
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1

```
df <- dplyr::rename_all(df, tolower)
head(df, 3)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1

# Lab Part 1

[Website](#)

# Subsetting Columns



## Subset columns of a data frame:

We can grab the `carb` column using the `$` operator. This is the base R way to do this:

```
df$carb
```

```
[1] 4 4 1 1 2 1 4 2 2 4 4 3 3 3 4 4 4 1 2 1 1 2 2 4 2 1 2 2 4 6 8 2
```

## Subset columns of a data frame - **tidyverse** way:

To grab the `carb` column the `tidyverse` way we can use the `pull` function:

```
pull(df, carb)
```

```
[1] 4 4 1 1 2 1 4 2 2 4 4 3 3 3 4 4 4 1 2 1 1 2 2 4 2 1 2 2 4 6 8 2
```

## Subset columns of a data frame: dplyr

The `select` command from `dplyr` allows you to subset (gives a `tibble`!)

```
select(df, mpg)
```

	mpg
Mazda RX4	21.0
Mazda RX4 Wag	21.0
Datsun 710	22.8
Hornet 4 Drive	21.4
Hornet Sportabout	18.7
Valiant	18.1
Duster 360	14.3
Merc 240D	24.4
Merc 230	22.8
Merc 280	19.2
Merc 280C	17.8
Merc 450SE	16.4
Merc 450SL	17.3
Merc 450SLC	15.2
Cadillac Fleetwood	10.4
Lincoln Continental	10.4
Chrysler Imperial	14.7
Fiat 128	32.4
Honda Civic	30.4
Toyota Corolla	33.9
Toyota Corona	21.5
Dodge Challenger	15.5
AMC Javelin	15.2
Camaro Z28	13.3

## Subset columns of a data frame: dplyr

Note that if you want a single vector (not a `tibble`), use `pull` (or `$` if you were using base R):

```
pull(df, mpg)
```

```
[1] 21.0 21.0 22.8 21.4 18.7 18.1 14.3 24.4 22.8 19.2 17.8 16.4 17.3 15.2 10.4  
[16] 10.4 14.7 32.4 30.4 33.9 21.5 15.5 15.2 13.3 19.2 27.3 26.0 30.4 15.8 19.7  
[31] 15.0 21.4
```

*# pull with select works too!*

```
pull(select(df, mpg))
```

```
[1] 21.0 21.0 22.8 21.4 18.7 18.1 14.3 24.4 22.8 19.2 17.8 16.4 17.3 15.2 10.4  
[16] 10.4 14.7 32.4 30.4 33.9 21.5 15.5 15.2 13.3 19.2 27.3 26.0 30.4 15.8 19.7  
[31] 15.0 21.4
```

## Select columns of a data frame: dplyr

The `select` command from `dplyr` allows you to subset columns matching strings:

```
select(df, mpg, cyl)
```

	mpg	cyl
Mazda RX4	21.0	6
Mazda RX4 Wag	21.0	6
Datsun 710	22.8	4
Hornet 4 Drive	21.4	6
Hornet Sportabout	18.7	8
Valiant	18.1	6
Duster 360	14.3	8
Merc 240D	24.4	4
Merc 230	22.8	4
Merc 280	19.2	6
Merc 280C	17.8	6
Merc 450SE	16.4	8
Merc 450SL	17.3	8
Merc 450SLC	15.2	8
Cadillac Fleetwood	10.4	8
Lincoln Continental	10.4	8
Chrysler Imperial	14.7	8
Fiat 128	32.4	4
Honda Civic	30.4	4
Toyota Corolla	33.9	4
Toyota Corona	21.5	4
Dodge Challenger	15.5	8
AMC Javelin	15.2	8

## See the Select “helpers”

Here are a few:

```
one_of() # if they exist  
last_col()  
ends_with()  
contains() # like searching
```

Type `tidyselect::` in the console and see what RStudio suggests:

```
tidyselect::
```

# Lab Part 2

Website

# Subsetting Rows



## Subset rows of a data frame: dplyr

The command in `dplyr` for subsetting rows is `filter`.

```
filter(df, mpg > 20)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2

Note, no subsetting is necessary. R “knows” `mpg` refers to a column of `df`.

## Subset rows of a data frame: dplyr

You can have multiple logical conditions using the following:

- `==` : equals to
- `!=`: not equal to (`!` : not/negation)
- `>` / `<`: greater than / less than
- `>=` or `<=`: greater than or equal to / less than or equal to
- `&` : AND
- `|` : OR

## Subset rows of a data frame: dplyr

The `%in%` operator can be used find values from a pre-made list (using `c()`):

```
filter(df, mpg %in% c(20, 21, 22))
```

		mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda	RX4	21	6	160	110	3.9	2.620	16.46	0	1	4	4
Mazda	RX4 Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4

## Subset rows of a data frame: dplyr

You can filter by two conditions using & or commas:

```
filter(df, mpg > 20 & cyl == 4)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2

```
filter(df, mpg > 20, cyl == 4)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2

## Subset rows of a data frame: dplyr

If you want OR statements (meaning the data can meet either condition does not need to meet both), you need to use the pipe `|` between conditions:

```
filter(df, mpg > 20 | cyl == 4)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2

## **which()** function

Instead of removing rows like `filter`, `which()` simply shows where the values occur if they pass a specific condition. We will see that this can be helpful later when we want to select and filter in more complicated ways.

```
which(select(df,carb) == 4)
```

```
[1] 1 2 7 10 11 15 16 17 24 29
```

```
select(df,carb) == 4
```

	carb
Mazda RX4	TRUE
Mazda RX4 Wag	TRUE
Datsun 710	FALSE
Hornet 4 Drive	FALSE
Hornet Sportabout	FALSE
Valiant	FALSE
Duster 360	TRUE
Merc 240D	FALSE
Merc 230	FALSE
Merc 280	TRUE
Merc 280C	TRUE
Merc 450SE	FALSE
Merc 450SL	FALSE
Merc 450SLC	FALSE
Cadillac Fleetwood	TRUE
Lincoln Continental	TRUE
Chrysler Imperial	TRUE

# Lab Part 3

Website

## Combining **filter** and **select**

You can combine `filter` and `select` to subset the rows and columns, respectively, of a data frame:

```
select(filter(df, mpg > 20 & cyl == 4), cyl, hp)
```

	cyl	hp
Datsun 710	4	93
Merc 240D	4	62
Merc 230	4	95
Fiat 128	4	66
Honda Civic	4	52
Toyota Corolla	4	65
Toyota Corona	4	97
Fiat X1-9	4	66
Porsche 914-2	4	91
Lotus Europa	4	113
Volvo 142E	4	109

In **R**, the common way to perform multiple operations is to wrap functions around each other in a nested way such as above.



## Assigning Temporary Objects

One can also create temporary objects and reassign them:

```
df2 <- filter(df, mpg > 20 & cyl == 4)  
df2 <- select(df2, cyl, hp)
```

```
head(df2, 4)
```

		cyl	hp
Datsun	710	4	93
Merc	240D	4	62
Merc	230	4	95
Fiat	128	4	66

## Using the **pipe** (comes with **dplyr**):

Recently, the pipe `%>%` makes things such as this much more readable. It reads left side “pipes” into right side. RStudio **CMD/Ctrl + Shift + M** shortcut. Pipe `df` into `filter`, then pipe that into `select`:

```
df %>% filter(mpg > 20 & cyl == 4) %>% select(cyl, hp)
```

	cyl	hp
Datsun 710	4	93
Merc 240D	4	62
Merc 230	4	95
Fiat 128	4	66
Honda Civic	4	52
Toyota Corolla	4	65
Toyota Corona	4	97
Fiat X1-9	4	66
Porsche 914-2	4	91
Lotus Europa	4	113
Volvo 142E	4	109

# Adding/Removing Columns

## Adding new columns to a data frame: base R

You can add a new column, called `newcol` to `df`, using the `$` operator:

```
df$newcol <- df$wt/2.2  
head(df,3)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb	newcol
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4	1.190909
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4	1.306818
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1	1.054545

## Adding columns to a data frame: dplyr (tidyverse way)

The \$ method is very common.

The `mutate` function in `dplyr` allows you to add or modify columns of a data frame.

*# General format - Not the code!*

```
{data object to update} <- mutate({data to use},  
                                   {new variable name} = {new variable source})
```

```
df <- mutate(df, newcol = wt/2.2)
```

## Removing columns of a data frame: base R

You can remove a column by assigning to `NULL`:

```
df$newcol <- NULL
```

## Removing columns of a data frame: dplyr

The `NULL` method is still very common.

The `select` function can remove a column with minus (-):

```
select(df, - newcol)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1

**Or, you can simply select the columns you want to keep, ignoring the ones you want to remove.**

## Removing columns to a data frame: dplyr

You can use `c()` to list the columns to remove.

Remove `newcol` and `drat`:

```
select(df, -c("newcol", "drat"))
```

	mpg	cyl	disp	hp	wt	qsec	vs	am	gear	carb
Mazda RX4	21.0	6	160.0	110	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	2.875	17.02	0	1	4	4
Datsun 710	22.8	4	108.0	93	2.320	18.61	1	1	4	1
Hornet 4 Drive	21.4	6	258.0	110	3.215	19.44	1	0	3	1
Hornet Sportabout	18.7	8	360.0	175	3.440	17.02	0	0	3	2
Valiant	18.1	6	225.0	105	3.460	20.22	1	0	3	1
Duster 360	14.3	8	360.0	245	3.570	15.84	0	0	3	4
Merc 240D	24.4	4	146.7	62	3.190	20.00	1	0	4	2
Merc 230	22.8	4	140.8	95	3.150	22.90	1	0	4	2
Merc 280	19.2	6	167.6	123	3.440	18.30	1	0	4	4
Merc 280C	17.8	6	167.6	123	3.440	18.90	1	0	4	4
Merc 450SE	16.4	8	275.8	180	4.070	17.40	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.730	17.60	0	0	3	3
Merc 450SLC	15.2	8	275.8	180	3.780	18.00	0	0	3	3
Cadillac Fleetwood	10.4	8	472.0	205	5.250	17.98	0	0	3	4
Lincoln Continental	10.4	8	460.0	215	5.424	17.82	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	5.345	17.42	0	0	3	4
Fiat 128	32.4	4	78.7	66	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	1.615	18.52	1	1	4	2
Toyota Corolla	33.9	4	71.1	65	1.835	19.90	1	1	4	1
Toyota Corona	21.5	4	120.1	97	2.465	20.01	1	0	3	1
Dodge Challenger	15.5	8	318.0	150	3.520	16.87	0	0	3	2



Ordering columns

## Ordering the columns of a data frame: dplyr

The `select` function can reorder columns.

```
head(df)
select(df, cyl, mpg, wt, car) %>%
head()
```

## Ordering the columns of a data frame: dplyr

We can also use the `relocate()` function of `dplyr` to rearrange the columns.

For example, let say we just wanted `wt` to be first.

```
head(df)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb	newcol
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4	1.190909
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4	1.306818
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1	1.054545
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1	1.461364
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2	1.563636
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1	1.572727

```
df_carb <- relocate(.data = df, wt,  
                    .before = mpg)
```

```
df_carb
```

	wt	mpg	cyl	disp	hp	drat	qsec	vs	am	gear	carb	
Mazda RX4	2.620	21.0	6	160.0	110	3.90	16.46	0	1	4	4	
Mazda RX4 Wag	2.875	21.0	6	160.0	110	3.90	17.02	0	1	4	4	
Datsun 710	2.320	22.8	4	108.0	93	3.85	18.61	1	1	4	1	
Hornet 4 Drive	3.215	21.4	6	258.0	110	3.08	19.44	1	0	3	1	
Hornet Sportabout	3.440	18.7	8	360.0	175	3.15	17.02	0	0	3	2	
Valiant	3.460	18.1	6	225.0	105	2.76	20.22	1	0	3	1	
Duster 360	3.570	14.3	8	360.0	245	3.21	15.84	0	0	3	4	
Merc 240D	3.190	24.4	4	146.7	62	3.69	20.00	1	0	4	2	51/67
Merc 230	3.150	22.8	4	140.8	95	3.92	22.90	1	0	4	2	

Ordering rows

## Ordering the rows of a data frame: dplyr

The `arrange` function can reorder rows By default, `arrange` orders in ascending order:

```
arrange(df, mpg)
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Lincoln Continental	10.4	8	460.0	215	3.00	5.424	17.82	0	0	3	4
Camaro Z28	13.3	8	350.0	245	3.73	3.840	15.41	0	0	3	4
Duster 360	14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Maserati Bora	15.0	8	301.0	335	3.54	3.570	14.60	0	1	5	8
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
AMC Javelin	15.2	8	304.0	150	3.15	3.435	17.30	0	0	3	2
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2
Ford Pantera L	15.8	8	351.0	264	4.22	3.170	14.50	0	1	5	4
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Merc 280C	17.8	6	167.6	123	3.92	3.440	18.90	1	0	4	4
Valiant	18.1	6	225.0	105	2.76	3.460	20.22	1	0	3	1
Hornet Sportabout	18.7	8	360.0	175	3.15	3.440	17.02	0	0	3	2
Merc 280	19.2	6	167.6	123	3.92	3.440	18.30	1	0	4	4
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Ferrari Dino	19.7	6	145.0	175	3.62	2.770	15.50	0	1	5	6
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1

# Ordering the rows of a data frame: dplyr

Use the `desc` to arrange the rows in descending order:

```
arrange(df, desc(mpg))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Toyota Corolla	33.9	4	71.1	65	4.22	1.835	19.90	1	1	4	1
Fiat 128	32.4	4	78.7	66	4.08	2.200	19.47	1	1	4	1
Honda Civic	30.4	4	75.7	52	4.93	1.615	18.52	1	1	4	2
Lotus Europa	30.4	4	95.1	113	3.77	1.513	16.90	1	1	5	2
Fiat X1-9	27.3	4	79.0	66	4.08	1.935	18.90	1	1	4	1
Porsche 914-2	26.0	4	120.3	91	4.43	2.140	16.70	0	1	5	2
Merc 240D	24.4	4	146.7	62	3.69	3.190	20.00	1	0	4	2
Datsun 710	22.8	4	108.0	93	3.85	2.320	18.61	1	1	4	1
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Ferrari Dino	19.7	6	145.0	175	3.62	2.770	15.50	0	1	5	6
Merc 280	19.2	6	167.6	123	3.92	3.440	18.30	1	0	4	4
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Hornet Sportabout	18.7	8	360.0	175	3.15	3.440	17.02	0	0	3	2
Valiant	18.1	6	225.0	105	2.76	3.460	20.22	1	0	3	1
Merc 280C	17.8	6	167.6	123	3.92	3.440	18.90	1	0	4	4
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Ford Pantera L	15.8	8	351.0	264	4.22	3.170	14.50	0	1	5	4
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2

# Ordering the rows of a data frame: dplyr

Increasing and decreasing orderings:

```
arrange(df, mpg, desc(hp))
```

	mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb
Lincoln Continental	10.4	8	460.0	215	3.00	5.424	17.82	0	0	3	4
Cadillac Fleetwood	10.4	8	472.0	205	2.93	5.250	17.98	0	0	3	4
Camaro Z28	13.3	8	350.0	245	3.73	3.840	15.41	0	0	3	4
Duster 360	14.3	8	360.0	245	3.21	3.570	15.84	0	0	3	4
Chrysler Imperial	14.7	8	440.0	230	3.23	5.345	17.42	0	0	3	4
Maserati Bora	15.0	8	301.0	335	3.54	3.570	14.60	0	1	5	8
Merc 450SLC	15.2	8	275.8	180	3.07	3.780	18.00	0	0	3	3
AMC Javelin	15.2	8	304.0	150	3.15	3.435	17.30	0	0	3	2
Dodge Challenger	15.5	8	318.0	150	2.76	3.520	16.87	0	0	3	2
Ford Pantera L	15.8	8	351.0	264	4.22	3.170	14.50	0	1	5	4
Merc 450SE	16.4	8	275.8	180	3.07	4.070	17.40	0	0	3	3
Merc 450SL	17.3	8	275.8	180	3.07	3.730	17.60	0	0	3	3
Merc 280C	17.8	6	167.6	123	3.92	3.440	18.90	1	0	4	4
Valiant	18.1	6	225.0	105	2.76	3.460	20.22	1	0	3	1
Hornet Sportabout	18.7	8	360.0	175	3.15	3.440	17.02	0	0	3	2
Pontiac Firebird	19.2	8	400.0	175	3.08	3.845	17.05	0	0	3	2
Merc 280	19.2	6	167.6	123	3.92	3.440	18.30	1	0	4	4
Ferrari Dino	19.7	6	145.0	175	3.62	2.770	15.50	0	1	5	6
Mazda RX4	21.0	6	160.0	110	3.90	2.620	16.46	0	1	4	4
Mazda RX4 Wag	21.0	6	160.0	110	3.90	2.875	17.02	0	1	4	4
Hornet 4 Drive	21.4	6	258.0	110	3.08	3.215	19.44	1	0	3	1
Volvo 142E	21.4	4	121.0	109	4.11	2.780	18.60	1	1	4	2
Toyota Corona	21.5	4	120.1	97	3.70	2.465	20.01	1	0	3	1
Merc 230	22.8	4	140.8	95	3.92	3.150	22.90	1	0	4	2

# Lab Part 4

[Website](#)



**Extra Slides**

## Creating conditional variables

One frequently-used tool is creating variables with conditions.

A general function for creating new variables based on existing variables is the `ifelse()` function, which “returns a value depending on whether the element of test is **TRUE** or **FALSE**.”

```
ifelse(test, yes, no)
```

```
# test: an object which can be coerced  
#       to logical mode.
```

```
# yes: return values for true elements of test.
```

```
# no: return values for false elements of test.
```

## ifelse example

```
df$disp
```

```
[1] 160.0 160.0 108.0 258.0 360.0 225.0 360.0 146.7 140.8 167.6 167.6 275.8  
[13] 275.8 275.8 472.0 460.0 440.0 78.7 75.7 71.1 120.1 318.0 304.0 350.0  
[25] 400.0 79.0 120.3 95.1 351.0 145.0 301.0 121.0
```

Now with `ifelse()`

```
#ifelse(test, yes, no)  
ifelse(df$disp <= 200, "low", "high")
```

```
[1] "low" "low" "low" "high" "high" "high" "high" "low" "low" "low"  
[11] "low" "high" "high" "high" "high" "high" "high" "low" "low" "low"  
[21] "low" "high" "high" "high" "high" "low" "low" "low" "high" "low"  
[31] "high" "low"
```

## Adding columns to a data frame: dplyr

Combined with `ifelse(condition, TRUE, FALSE)`, it can give you:

```
df = mutate(df,  
             disp_cat = ifelse(displacement <= 200, "Low", "High")  
            )
```

```
head(df, 2)
```

			mpg	cyl	displacement	hp	drat	wt	qsec	vs	am	gear	carb	newcolumn
Mazda	RX4		21	6	160	110	3.9	2.620	16.46	0	1	4	4	1.190909
Mazda	RX4	Wag	21	6	160	110	3.9	2.875	17.02	0	1	4	4	1.306818
					displacement									
Mazda	RX4				Low									
Mazda	RX4	Wag			Low									

## Adding columns to a data frame: dplyr

Alternatively, `case_when` provides a clean syntax as well:

```
df = mutate(df,  
             disp_cat2 = case_when(  
               disp <= 200 ~ "Low",  
               disp > 200 ~ "High",  
             ))  
head(df$disp_cat2)  
  
[1] "Low"  "Low"  "Low"  "High" "High" "High"
```

## Renaming Columns of a data frame: base R

We can use the `colnames` function to extract and/or directly reassign column names of `df`:

```
colnames(df) # just prints
```

```
[1] "mpg"      "cyl"      "disp"     "hp"       "drat"     "wt"
[7] "qsec"     "vs"       "am"       "gear"     "carb"     "newcol"
[13] "disp_cat" "disp_cat2"
```

```
colnames(df)[1:3] = c("MPG", "CYL", "DISP") # reassigns
head(df)
```

	MPG	CYL	DISP	hp	drat	wt	qsec	vs	am	gear	carb	newcol
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4	1.190909
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4	1.306818
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1	1.054545
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1	1.461364
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2	1.563636
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1	1.572727
	disp_cat	disp_cat2										
Mazda RX4	Low	Low										
Mazda RX4 Wag	Low	Low										
Datsun 710	Low	Low										
Hornet 4 Drive	High	High										
Hornet Sportabout	High	High										
Valiant	High	High										

```
colnames(df)[1:3] = c("mpg", "cyl", "disp") #reset - just to keep consistent
```

## Renaming Columns of a data frame: base R

We can assign the column names, change the ones we want, and then re-assign the column names:

```
cn = colnames(df)
cn[ cn == "drat" ] = "DRAT"
colnames(df) = cn
head(df)
```

	mpg	cyl	disp	hp	DRAT	wt	qsec	vs	am	gear	carb	newcol
Mazda RX4	21.0	6	160	110	3.90	2.620	16.46	0	1	4	4	1.190909
Mazda RX4 Wag	21.0	6	160	110	3.90	2.875	17.02	0	1	4	4	1.306818
Datsun 710	22.8	4	108	93	3.85	2.320	18.61	1	1	4	1	1.054545
Hornet 4 Drive	21.4	6	258	110	3.08	3.215	19.44	1	0	3	1	1.461364
Hornet Sportabout	18.7	8	360	175	3.15	3.440	17.02	0	0	3	2	1.563636
Valiant	18.1	6	225	105	2.76	3.460	20.22	1	0	3	1	1.572727

	disp_cat	disp_cat2
Mazda RX4	Low	Low
Mazda RX4 Wag	Low	Low
Datsun 710	Low	Low
Hornet 4 Drive	High	High
Hornet Sportabout	High	High
Valiant	High	High

```
colnames(df)[ colnames(df) == "DRAT" ] = "drat" #reset
```

## Subset rows of a data frame with indices:

Let's select **rows** 1 and 3 from **df** using brackets:

```
df[ c(1, 3), ]
```

		mpg	cyl	disp	hp	drat	wt	qsec	vs	am	gear	carb	newcol	disp_cat
Mazda	RX4	21.0	6	160	110	3.90	2.62	16.46	0	1	4	4	1.190909	Low
Datsun	710	22.8	4	108	93	3.85	2.32	18.61	1	1	4	1	1.054545	Low
		disp_cat2												
Mazda	RX4													Low
Datsun	710													Low



## Subset columns of a data frame:

We can also subset a data frame using the bracket `[, ]` subsetting.

For data frames and matrices (2-dimensional objects), the brackets are `[rows, columns]` subsetting. We can grab the `x` column using the index of the column or the column name (`"carb"`)

```
df[, 11]
```

```
[1] 4 4 1 1 2 1 4 2 2 4 4 3 3 3 4 4 4 1 2 1 1 2 2 4 2 1 2 2 4 6 8 2
```

```
df[, "carb"]
```

```
[1] 4 4 1 1 2 1 4 2 2 4 4 3 3 3 4 4 4 1 2 1 1 2 2 4 2 1 2 2 4 6 8 2
```

## Biggest difference between **tbl** and data frame:

Mostly, **tbl** (tibbles) are the same as data frames, except they don't print all lines. When subsetting only one column using brackets, a data frame will return a vector, but a **tbl** will return a **tbl**

```
df[, 1]
```

```
[1] 21.0 21.0 22.8 21.4 18.7 18.1 14.3 24.4 22.8 19.2 17.8 16.4 17.3 15.2 10.4  
[16] 10.4 14.7 32.4 30.4 33.9 21.5 15.5 15.2 13.3 19.2 27.3 26.0 30.4 15.8 19.7  
[31] 15.0 21.4
```

```
tbl[, 1]
```

```
# A tibble: 32 × 1
```

```
  mpg  
<dbl>
```

```
1  21  
2  21  
3  22.8  
4  21.4  
5  18.7  
6  18.1  
7  14.3  
8  24.4  
9  22.8  
10 19.2
```

```
# ... with 22 more rows
```

```
tbl[, "mpg"]
```

## Subset columns of a data frame:

We can select multiple columns using multiple column names:

```
df[, c("mpg", "cyl")]
```

	mpg	cyl
Mazda RX4	21.0	6
Mazda RX4 Wag	21.0	6
Datsun 710	22.8	4
Hornet 4 Drive	21.4	6
Hornet Sportabout	18.7	8
Valiant	18.1	6
Duster 360	14.3	8
Merc 240D	24.4	4
Merc 230	22.8	4
Merc 280	19.2	6
Merc 280C	17.8	6
Merc 450SE	16.4	8
Merc 450SL	17.3	8
Merc 450SLC	15.2	8
Cadillac Fleetwood	10.4	8
Lincoln Continental	10.4	8
Chrysler Imperial	14.7	8
Fiat 128	32.4	4
Honda Civic	30.4	4
Toyota Corolla	33.9	4
Toyota Corona	21.5	4
Dodge Challenger	15.5	8
AMC Javelin	15.2	8
Camaro Z28	13.3	8