

## Lesson 09 Demo 06

### Analyzing Pod Logs

**Objective:** To analyze the logs of a pod hosting a container within a Kubernetes cluster to view the application or service's output

**Tools required:** kubeadm, kubectl, kubelet, and containerd

**Prerequisites:** A Kubernetes cluster should already be set up (refer to the steps provided in Lesson 02, Demo 01 for guidance).


Steps to be followed:

1. Configure and verify Nginx deployment

#### Step 1: Configure and verify Nginx deployment

1.1 Initiate the creation of a configuration file for the Nginx deployment:

**vi nginx.yaml**



```
labsuser@master:~$ vi nginx.yaml
labsuser@master:~$
```

1.2 Insert the following code into the **nginx.yaml** file:

```
apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    app: nginx
    name: nginx
spec:
  replicas: 1
  selector:
    matchLabels:
      app: nginx
  template:
    metadata:
      labels:
        app: nginx
    spec:
      containers:
      - image: nginx
        name: nginx
```

```
apiVersion: apps/v1
kind: Deployment
metadata:
  creationTimestamp: null
  labels:
    app: nginx
    name: nginx
spec:
  replicas: 1
  selector:
    matchLabels:
      app: nginx
  strategy: {}
  template:
    metadata:
      creationTimestamp: null
      labels:
        app: nginx
    spec:
      containers:
      - image: nginx
        name: nginx
        resources: {}
```

1.3 Create the Nginx deployment using the configuration file:

**kubectl create -f nginx.yaml**

```
labsuser@master:~$ kubectl create -f nginx.yaml
deployment.apps/nginx created
labsuser@master:~$
```

1.4 Use the following commands to verify deployments and pods:

**kubectl get deployments**

**kubectl get pods**

```
labsuser@master:~$ kubectl create -f nginx.yaml
deployment.apps/nginx created
labsuser@master:~$ kubectl get deployments
NAME      READY   UP-TO-DATE   AVAILABLE   AGE
admin     0/1     1            0           41h
nginx     1/1     1            1           90s
labsuser@master:~$ kubectl get pods
NAME                                READY   STATUS              RESTARTS   AGE
admin-56d684dff9-zjfhc             0/1     ImagePullBackOff    0           41h
counter                             1/1     Running             3 (14m ago) 21h
nginx-7854ff8877-mvrtr             1/1     Running             0           112s
pod-demo                           1/1     Running             7 (14m ago) 5d14h
labsuser@master:~$
```

1.5 Use the following command to view the logs of the Nginx pod:

**kubectl logs nginx-7854ff8877-mvrtr**

```

labsuser@master:~$ kubectl create -f nginx.yaml
deployment.apps/nginx created
labsuser@master:~$ kubectl get deployments
NAME      READY   UP-TO-DATE   AVAILABLE   AGE
admin     0/1     1            0           41h
nginx     1/1     1            1           90s
labsuser@master:~$ kubectl get pods
NAME                                READY   STATUS              RESTARTS   AGE
admin-56d684dff9-zjfhc             0/1     ImagePullBackOff    0           41h
counter                             1/1     Running             3 (14m ago) 21h
nginx-7854ff8877-mvrtr             1/1     Running             0           112s
pod-demo                           1/1     Running             7 (14m ago) 5d14h
labsuser@master:~$ kubectl logs nginx-7854ff8877-mvrtr
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Sourcing /docker-entrypoint.d/15-local-resolvers.envsh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/10/12 04:56:50 [notice] 1#1: using the "epoll" event method
2023/10/12 04:56:50 [notice] 1#1: nginx/1.25.2
2023/10/12 04:56:50 [notice] 1#1: built by gcc 12.2.0 (Debian 12.2.0-14)
2023/10/12 04:56:50 [notice] 1#1: OS: Linux 6.2.0-1013-aws
2023/10/12 04:56:50 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1024:524288
2023/10/12 04:56:50 [notice] 1#1: start worker processes
2023/10/12 04:56:50 [notice] 1#1: start worker process 29
2023/10/12 04:56:50 [notice] 1#1: start worker process 30
labsuser@master:~$

```

**Note:** Replace **nginx-7854ff8877-mvrtr** with the pod name from Step 1.4

By following these steps, you have successfully monitored the Nginx pod's logs following the creation of its deployment in Kubernetes.