

Lesson 04 Demo 09

Creating and Configuring the Metrics Server

Objective: To create and configure the metrics server in the Kubernetes cluster to identify the top nodes, pods, and containers

Tools required: kubeadm, kubectl, kubelet, and containerd

Prerequisites: A Kubernetes cluster should already be set up (refer to the steps provided in Lesson 02, Demo 01 for guidance).

Steps to be followed:

1. Create a deployment
2. Configure the metrics server
3. Verify the metrics server deployment

Step 1: Create a deployment

1.1 On the master node, enter the following command to create a YAML file:

nano deployment.yaml

```
labsuser@master:~$ nano deployment.yaml
labsuser@master:~$
```

This YAML will define the deployment.


1.2 Write the following code in the **deployment.yaml** file:

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: frontend
  labels:
    app: guestbook
    tier: frontend
spec:
  replicas: 3
  selector:
    matchLabels:
```

```

tier: frontend
template:
  metadata:
    labels:
      tier: frontend
  spec:
    containers:
      - name: php-redis
        image: gcr.io/google_samples/gb-frontend:v3

```




```

GNU nano 6.2 deployment.yaml *
apiVersion: apps/v1
kind: Deployment
metadata:
  name: frontend
  labels:
    app: guestbook
    tier: frontend
spec:
  replicas: 3
  selector:
    matchLabels:
      tier: frontend
  template:
    metadata:
      labels:
        tier: frontend
    spec:
      containers:
        - name: php-redis
          image: gcr.io/google_samples/gb-frontend:v3

```

1.3 Execute the following command to create a deployment:

kubectl create -f deployment.yaml



```

labsuser@master:~$ kubectl create -f deployment.yaml
deployment.apps/frontend created
labsuser@master:~$


```

1.4 Execute the following commands to get the status of the deployment:

kubectl get deployment frontend

kubectl get rs

kubectl get pods -l tier=frontend



```

labsuser@master:~$ kubectl get deployment frontend
NAME          READY   UP-TO-DATE   AVAILABLE   AGE
frontend      3/3     3             3           5m51s
labsuser@master:~$ kubectl get rs
NAME                                DESIRED   CURRENT   READY   AGE
frontend-5b85744f5d                 3         3         3       6m44s
labsuser@master:~$ kubectl get pods -l tier=frontend
NAME                                READY   STATUS    RESTARTS   AGE
frontend-5b85744f5d-bjkwz           1/1     Running   0           7m3s
frontend-5b85744f5d-q55bd           1/1     Running   0           7m3s
frontend-5b85744f5d-sbv1r           1/1     Running   0           7m3s
labsuser@master:~$

```

1.5 Describe the deployment using the following command: **kubectl describe deploy/frontend**

```
labsuser@master:~$ kubectl describe deploy/frontend
Name: frontend
Namespace: default
CreationTimestamp: Mon, 06 Nov 2023 18:41:20 +0000
Labels: app=guestbook
        tier=frontend
Annotations: deployment.kubernetes.io/revision: 1
Selector: tier=frontend
Replicas: 3 desired | 3 updated | 3 total | 3 available | 0 unavailable
StrategyType: RollingUpdate
MinReadySeconds: 0
RollingUpdateStrategy: 25% max unavailable, 25% max surge
Pod Template:
  Labels: tier=frontend
  Containers:
    php-redis:
      Image: gcr.io/google_samples/gb-frontend:v3
      Port: <none>
      Host Port: <none>
      Environment: <none>
      Mounts: <none>
      Volumes: <none>
  Conditions:
    Type           Status  Reason
    ----           -
    Available       True    MinimumReplicasAvailable
    Progressing     True    NewReplicaSetAvailable
OldReplicaSets: <none>
NewReplicaSet: frontend-5b85744f5d (3/3 replicas created)
Events:
  Type    Reason              Age   From                      Message
  ----    -
  Normal  ScalingReplicaSet   11m   deployment-controller     Scaled up replica set frontend-5b85744f5d to 3
labsuser@master:~$
```

Step 2: Configure the metrics server

2.1 Run the following command to create the metrics server: **kubectl apply -f <https://github.com/kubernetes-sigs/metrics-server/releases/latest/download/components.yaml>**

```
labsuser@master:~$ kubectl apply -f https://github.com/kubernetes-sigs/metrics-server/releases/latest/download/components.yaml
serviceaccount/metrics-server created
clusterrole.rbac.authorization.k8s.io/system:aggregated-metrics-reader created
clusterrole.rbac.authorization.k8s.io/system:metrics-server created
rolebinding.rbac.authorization.k8s.io/metrics-server-auth-reader created
clusterrolebinding.rbac.authorization.k8s.io/metrics-server:system:auth-delegator created
clusterrolebinding.rbac.authorization.k8s.io/system:metrics-server created
service/metrics-server created
deployment.apps/metrics-server created
apiservice.apiregistration.k8s.io/v1beta1.metrics.k8s.io created
labsuser@master:~$
```

2.2 Verify the status of the metrics server using the following command:
kubectl get pods -n kube-system

```
labsuser@master:~$ kubectl get pods -n kube-system
```

NAME	READY	STATUS	RESTARTS	AGE
calico-kube-controllers-7ddc4f45bc-hf2pb	1/1	Running	0	33m
calico-node-kb7rr	1/1	Running	0	32m
calico-node-n5cwx	1/1	Running	0	32m
calico-node-tvhrs	1/1	Running	0	33m
coredns-5dd5756b68-9gksj	1/1	Running	0	34m
coredns-5dd5756b68-p55fr	1/1	Running	0	34m
etcd-master.example.com	1/1	Running	0	34m
kube-apiserver-master.example.com	1/1	Running	0	34m
kube-controller-manager-master.example.com	1/1	Running	0	34m
kube-proxy-4qgn9	1/1	Running	0	32m
kube-proxy-6n2lj	1/1	Running	0	32m
kube-proxy-nsblp	1/1	Running	0	34m
kube-scheduler-master.example.com	1/1	Running	0	34m
metrics-server-fbb469ccc-5bhhl	0/1	Running	0	93s

```
labsuser@master:~$
```

Note: The metrics server is not in a ready state.

2.3 Run the following command to fetch a **k8s-metrics-server.patch.yaml** file:
wget -c
<https://gist.githubusercontent.com/initcron/1a2bd25353e1faa22a0ad41ad1c01b62/raw/008e23f9fbf4d7e2cf79df1dd008de2f1db62a10/k8s-metrics-server.patch.yaml>

```
labsuser@master:~$ wget -c https://gist.githubusercontent.com/initcron/1a2bd25353e1faa22a0ad41ad1c01b62/raw/008e23f9fbf4d7e2cf79df1dd008de2f1db62a10/k8s-metrics-server.patch.yaml
--2023-11-06 19:07:33-- https://gist.githubusercontent.com/initcron/1a2bd25353e1faa22a0ad41ad1c01b62/raw/008e23f9fbf4d7e2cf79df1dd008de2f1db62a10/k8s-metrics-server.patch.yaml
Resolving gist.githubusercontent.com (gist.githubusercontent.com)... 185.199.111.133, 185.199.108.133, 185.199.109.133, ...
Connecting to gist.githubusercontent.com (gist.githubusercontent.com)[185.199.111.133]:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 205 [text/plain]
Saving to: 'k8s-metrics-server.patch.yaml'

k8s-metrics-server.patch.yaml      100%[=====] 205 --.-KB/s  in 0s

2023-11-06 19:07:33 (8.00 MB/s) - 'k8s-metrics-server.patch.yaml' saved [205/205]

labsuser@master:~$
```

2.4 Run the following command to view the content of the **k8s-metrics-server.patch.yaml** file:
cat k8s-metrics-server.patch.yaml

```
labsuser@master:~$ cat k8s-metrics-server.patch.yaml
spec:
  template:
    spec:
      containers:
      - name: metrics-server
        command:
        - /metrics-server
        - --kubelet-insecure-tls
        - --kubelet-preferred-address-types=InternalIP
```

2.5 Run the following command to deploy the metrics server:

```
kubectl patch deploy metrics-server -p "$(cat k8s-metrics-server.patch.yaml)" -n kube-system
```

```
labsuser@master:~$ kubectl patch deploy metrics-server -p "$(cat k8s-metrics-server.patch.yaml)" -n kube-system
deployment.apps/metrics-server patched
labsuser@master:~$
```

Step 3: Verify the metrics server deployment

3.1 Execute the following command to verify the status of the metrics server:

```
kubectl get pods -n kube-system
```

```
labsuser@master:~$ kubectl get pods -n kube-system
```

NAME	READY	STATUS	RESTARTS	AGE
calico-kube-controllers-7ddc4f45bc-hf2pb	1/1	Running	0	51m
calico-node-kb7rr	1/1	Running	0	50m
calico-node-n5cwx	1/1	Running	0	50m
calico-node-tvhps	1/1	Running	0	51m
coredns-5dd5756b68-9gksj	1/1	Running	0	52m
coredns-5dd5756b68-p55fr	1/1	Running	0	52m
etcd-master.example.com	1/1	Running	0	52m
kube-apiserver-master.example.com	1/1	Running	0	52m
kube-controller-manager-master.example.com	1/1	Running	0	52m
kube-proxy-4qgn9	1/1	Running	0	50m
kube-proxy-6n2lj	1/1	Running	0	50m
kube-proxy-nsblp	1/1	Running	0	52m
kube-scheduler-master.example.com	1/1	Running	0	52m
metrics-server-678d4b775-7lmmwz	1/1	Running	0	5m26s

```
labsuser@master:~$
```

The metrics server is now running.

3.2 Execute the following commands to sort all nodes and identify those with top memory and CPU usage in the cluster:

kubectl top nodes

kubectl top nodes --sort-by cpu

kubectl top nodes --sort-by memory

kubectl top nodes master.example.com

```

labsuser@master:~$ kubectl top nodes
NAME                                CPU(cores)   CPU%   MEMORY(bytes)   MEMORY%
master.example.com                  673m         33%    2534Mi           67%
worker-node-1.example.com           225m         11%    2166Mi           28%
worker-node-2.example.com           232m         11%    2193Mi           28%
labsuser@master:~$ kubectl top nodes --sort-by cpu
NAME                                CPU(cores)   CPU%   MEMORY(bytes)   MEMORY%
master.example.com                  462m         23%    2538Mi           67%
worker-node-2.example.com           234m         11%    2209Mi           28%
worker-node-1.example.com           181m          9%    2172Mi           28%
labsuser@master:~$ kubectl top nodes --sort-by memory
NAME                                CPU(cores)   CPU%   MEMORY(bytes)   MEMORY%
master.example.com                  453m         22%    2538Mi           67%
worker-node-2.example.com           223m         11%    2194Mi           28%
worker-node-1.example.com           195m          9%    2175Mi           28%
labsuser@master:~$ kubectl top nodes master.example.com
NAME                                CPU(cores)   CPU%   MEMORY(bytes)   MEMORY%
master.example.com                  474m         23%    2540Mi           67%
labsuser@master:~$

```

By following these steps, you have successfully configured the metric server in the Kubernetes cluster to identify the top nodes, pods, and containers.