HIGH PERFORMANCE COMPUTING (HPC) HS26

Background for Mini-Challenge 2

Vision transformers, cluster execution, and performance measurement

This report supplies the background for autumn semester 2026 (HS26) and the ten experiments in the repository's `README.md`. It develops a small image classifier from tensor operations, then explains how to run and measure it. Examples are teaching building blocks, not measured results or a completed submission.

Prerequisites: basic Python, matrix multiplication, partial derivatives, and familiarity with a command-line shell. Read Chapters 1–3 before building the baseline; use Chapters 4–5 when running and interpreting experiments.

4 November 2026

References link to primary papers and official documentation. Online application programming interfaces (APIs) and cluster policies can change; record the versions and settings actually used.

Contents

1 PyTorch Introduction **1**

2 Scaled Dot-Product Attention **6**

3 Simple Vision Transformer **11**

4 Slurm introduction with simple examples **15**

5 Computation graphs and profiling **18**

References **23**

The examples use a central processing unit (CPU) locally and a graphics processing unit (GPU) on the cluster. NVIDIA's Compute Unified Device Architecture (CUDA) is the GPU computing platform used here. Scaled Dot-Product Attention (SDPA) is the attention operation developed in Chapter 2.

How the chapters support the experiments

Chapter	Experiments and questions supported
1	Dataset, optimization, validation, reproducibility, full training (1, 8–10).
2	Manual attention, gradients, vectorization, SDPA comparisons (1, 5–7).
3	Architecture, tensor shapes, correctness, compilation (1, 2, 6, 10).
4	CPU/GPU allocations, job scripts, output, resource accounting (3, 8, 10).
5	Graphs, timing, memory, profiler overhead, loading, synchronization (2–10).

The optional mixed-precision and multi-GPU goals extend this foundation; they do not change the required 32-bit floating-point (FP32), single-GPU comparisons. Each numbered chapter is limited to five pages. Front matter and references are separate.

Notation. $\mathbb{R}$ denotes the real numbers; $\mathbb{R}^{m\times n}$ is the space of matrices with m rows and n columns. A superscript T denotes transpose, and a colon in an index selects an entire axis. Token vectors are rows. exp and log are the natural exponential and logarithm. Symbols reused in another section are defined there again.

Chapter 1

PyTorch Introduction

Connection to the challenge. Build a trainable CPU baseline, move it to the allocated GPU, and keep the data, model, and optimization settings reproducible.

1.1 Tensors describe both data and computation

A tensor is an array with a shape, a data type, a device, and a memory layout. An image batch has shape (B, C, H, W): B is the batch size, C the number of channels, and H, W the image height and width in pixels. Tokens have shape (B, N, D), where N is the number of tokens per image and D the number of features per token (the embedding width). Labels have shape $(B,)$ with integer values in $\{0, \ldots, 364\}$. A dimension's meaning matters as much as its length. PyTorch's introductory tutorials provide the basic API vocabulary [1].

```
import torch
from torch import nn
import torch.nn.functional as F

torch.manual_seed(17)
torch.set_float32_matmul_precision("highest")
device = torch.device("cpu")  # use "cuda:0" inside a GPU allocation
x = torch.randn(8, 64, 128, device=device, dtype=torch.float32)
projection = nn.Linear(128, 128).to(device=device, dtype=torch.float32)
z = projection(x)             # (8, 64, 128)
assert z.device == x.device
```

Operation	Meaning and common mistake
`a * b`	Elementwise multiplication with broadcasting; not matrix multiplication.
`a @ b`	Matrix multiplication on the last two dimensions; preceding dimensions broadcast.
`x.transpose(-2,-1)`	Exchange two axes; generally changes strides without copying data.
`x.reshape(...)`	Change shape; may copy if the current strides cannot represent it.
`x.to(device)`	Return a tensor on the chosen device; use the returned value.

Broadcasting aligns dimensions from the right; dimensions must match or one must equal one. Thus a bias of shape $(D,)$ is shared by all BN tokens. Check shapes explicitly: accidental broadcasting can give plausible values while computing the wrong function. A transposed tensor can be non-contiguous; calling `view` on it may fail, while a later copy can affect performance.

1.2 Modules own parameters

An `nn.Module` defines `forward` and registers trainable parameters and child modules. Use `nn.Parameter` for a learned tensor. The `model.parameters()` iterator exposes parameters to an optimizer; `model.to(device)` moves registered state. Use `nn.ModuleList` for a collection of blocks so that their parameters are registered. A linear layer applies $z = xW^{\mathsf{T}} + b$: input row x has D_{in} features, output row z has D_{out} features, $W \in \mathbb{R}^{D_{\text{out}} \times D_{\text{in}}}$ is the stored weight matrix, and $b \in \mathbb{R}^{1 \times D_{\text{out}}}$ is the broadcast bias row. Below, mathematical weights multiply on the right and are stored transposed by PyTorch. In the code, `x` and `z` hold whole batches of rows; `nn` names the neural-network module namespace and `F` its functional interface.

1.3 Automatic differentiation and the objective

Let $\theta \in \mathbb{R}^{P_\theta}$ collect the classifier's P_θ trainable parameters. For sample index $b = 1, \ldots, B$, x_b is an input image, f_θ the classifier, $s_b = f_\theta(x_b) \in \mathbb{R}^{365}$ its logit vector, and $y_b \in \{0, \ldots, 364\}$ the target class. The scalar batch loss $\mathcal{L}(\theta)$ is mean cross-entropy, with class index c:

$$\mathcal{L}(\theta) = \frac{1}{B} \sum_{b=1}^{B} \left[-s_{b,y_b} + \log \left(\sum_{c=0}^{364} e^{s_{b,c}} \right) \right]. \tag{1.1}$$

Pass logits directly to `F.cross_entropy`; applying softmax first changes the intended input. PyTorch uses a numerically stable implementation. An epoch is a pass through the training set; a step is one batch update. Their lengths change differently when batch size changes.

Autograd applies the chain rule in reverse. Let $u = g(\theta) \in \mathbb{R}^m$ be an intermediate activation vector with m entries, where g maps parameters to activations and h maps activations to the scalar loss $\mathcal{L} = h(u)$. Then $\nabla_\theta \mathcal{L} = J_g(\theta)^\mathsf{T} \nabla_u h$. Here $J_g \in \mathbb{R}^{m \times P_\theta}$ is the Jacobian of g and ∇ denotes a gradient; the full Jacobian need not be formed. Model parameters are usually leaf tensors with `requires_grad=True`. Ordinary image inputs need not require gradients. Calling `backward()` accumulates into parameter `.grad` fields; gradients must therefore be cleared for independent updates [2].

```python
def train_step(model, optimizer, images, labels):
    optimizer.zero_grad(set_to_none=True)
    logits = model(images)
    loss = F.cross_entropy(logits, labels)
    loss.backward()
    optimizer.step()
    return loss.detach()  # metric without retaining the graph

# Construct the optimizer after placing the model on its device.
# model = TinyViT().to(device=device, dtype=torch.float32)  # Chapter 3
# optimizer = torch.optim.AdamW(model.parameters(), lr=3e-4)
# model.train()
# loss_on_device = train_step(model, optimizer, images, labels)
```

The challenge's training step comprises forward, loss, backward, and optimizer work; the example also clears gradients. `detach()` removes a tensor from the differentiation graph, but does not transfer it to the CPU. Saving the original loss tensor in a list can retain graph state and grow memory use. Use fresh forwards for subsequent steps; ordinary training does not need `retain_graph=True`.

1.4 What an optimizer changes

Stochastic gradient descent uses $\theta_{t+1} = \theta_t - \eta \nabla_\theta \mathcal{L}_t$, where t is the update index, θ_t the current parameters, $\mathcal{L}_t$ the current batch loss, and $\eta > 0$ the learning rate. AdamW is adaptive moment estimation (Adam) with decoupled weight decay. It maintains first and second moment estimates for each parameter and applies decoupled weight decay. Its state consumes memory and may be initialized lazily at the first update. Fix optimizer type, hyperparameters, and state across implementation comparisons [3].

`model.train()` and `model.eval()` set the model's training and evaluation modes; neither switches autograd off. Validation uses evaluation mode and a `torch.no_grad()` or `torch.inference_mode()` context. Return to training mode afterwards.

Check your understanding. Why does a forward-only timing omit much of a training step? Why do two consecutive calls to `backward()` on separate forwards still require clearing gradients?

1.5 Datasets, transformations, and loaders

A map-style dataset supplies a sample by index; a `DataLoader` selects indices, loads samples, and collates them into batches. The challenge uses Places365-Standard, with separate training and validation splits. The prepared shared copy must include the image layout and metadata expected by torchvision; `small=True` selects the 256×256 source images [4].

The following deterministic transformation resizes red, green, and blue (RGB) images to 128×128 for a compact example model. Its normalization constants are an explicit example choice, not statistics estimated from this dataset. Record and freeze the transformation. Never estimate preprocessing statistics using validation data.

```
import os
from torchvision import datasets, transforms
from torch.utils.data import DataLoader, Subset

transform = transforms.Compose([
    transforms.Resize((128, 128)),
    transforms.ToTensor(),             # RGB uint8 -> float in [0, 1]
    transforms.Normalize((0.485, 0.456, 0.406),
                         (0.229, 0.224, 0.225)),
])
root = os.environ["PLACES365_ROOT"]     # shared, prepared copy
train_data = datasets.Places365(root, split="train-standard",
    small=True, download=False, transform=transform)
val_data = datasets.Places365(root, split="val",
    small=True, download=False, transform=transform)

subset_rng = torch.Generator().manual_seed(17)
indices = torch.randperm(len(train_data), generator=subset_rng)[:512]
dev_data = Subset(train_data, indices.tolist())
torch.save(indices, "development_indices.pt")

workers = 0  # change only within the available CPU allocation
worker_options = ({"prefetch_factor": 2, "persistent_workers": True}
                  if workers > 0 else {})
train_loader = DataLoader(dev_data, batch_size=32, shuffle=True,
    num_workers=workers, pin_memory=(device.type == "cuda"),
    generator=torch.Generator().manual_seed(29), **worker_options)
val_loader = DataLoader(val_data, batch_size=32, shuffle=False,
    num_workers=workers, pin_memory=(device.type == "cuda"),
    **worker_options)
```

For the final experiment use `train_data`, not `dev_data`, and cover at least one complete training epoch. Keep a fixed validation subset for quick development if needed, but identify it explicitly. A tiny-subset overfitting check measures the ability to optimize; it is not held-out accuracy.

With zero workers, fetching occurs in the main process; positive worker counts create subprocesses. Let w be the number of workers and p the prefetch factor (batches prepared in advance per worker). For $w > 0$, up to roughly wp batches can be queued, in addition to batches being processed. More workers therefore change host memory demand as well as concurrency. Pinning uses page-locked host memory. It can assist transfers but does not by itself establish overlap [5].

Put script execution and loader creation under `if __name__ == "__main__":` when using multiprocessing. Seed Python, NumPy, and worker-side random transforms if used; the deterministic transform above avoids that additional source of variation.

1.6 Training, validation, and recoverable runs

Move both images and integer labels to the device before calling `train_step`. Keep metrics on the device until a logging boundary. For batch index k, let B_k be its image count and $\mathcal{L}_k$ its mean loss. Accumulate $B_k\mathcal{L}_k$ and divide by the total image count; averaging batch means gives a smaller final batch too much weight.

```
@torch.no_grad()
def validate(model, loader, device):
    model.eval()
    totals = torch.zeros(2, device=device)  # loss sum, correct count
    count = 0
    for images, labels in loader:
        images = images.to(device, non_blocking=True)
        labels = labels.to(device, non_blocking=True)
        logits = model(images)
        totals[0] += F.cross_entropy(logits, labels, reduction="sum")
        totals[1] += (logits.argmax(dim=1) == labels).sum()
        count += labels.numel()
    values = (totals / count).cpu().tolist()  # one final host read
    return {"loss": values[0], "accuracy": values[1]}
```

Call `model.train()` at the start of each training epoch. Validate on held-out images and never call the optimizer during validation. Record loss and accuracy against examples processed and against elapsed time, since the two plots answer different questions about learning and execution speed.

```
# Save after completing an epoch; config contains model/data/settings.
torch.save({"model": model.state_dict(),
            "optimizer": optimizer.state_dict(),
            "epoch": epoch, "config": config,
            "torch_rng": torch.get_rng_state()}, "checkpoint.pt")
```

For an exact resume also save CUDA, Python, NumPy, sampler/loader-generator, and scheduler states as applicable. Resuming halfway through an epoch requires tracking data position and worker randomness. A checkpoint of weights alone does not restore optimizer moments or the subsequent sample order. Use a separate initial checkpoint for controlled eager/compiled/SDPA comparisons.

1.7 Reproducibility is an experimental design choice

Record the seed, saved subset indices, transformations, package versions, CPU/GPU model, thread count, model configuration, optimizer, data order, and precision. A seed does not guarantee bitwise agreement across hardware or algorithms. Small FP32 differences are expected; document tolerances and compare learning over a common budget. For CPU experiments set `torch.set_num_threads(n)` before computation; n is the number of CPU threads used for numerical operations.

The required precision setting controls float32 matrix multiplication, not every backend independently. If adding convolutions, disable their TensorFloat-32 (TF32) mode using the controls supported by the installed PyTorch version. Do not enable autocast in required experiments. The linear patch embedding in Chapter 3 avoids a convolution-specific setting.

Use Weights & Biases (W&B) to associate configuration, Slurm job identifier (ID), metrics, and system samples with one run. For disconnected compute nodes use offline logging and synchronize later from a machine with access. Save raw measurements locally as comma-separated values (CSV) or JavaScript Object Notation (JSON) so the report notebook can regenerate plots without rerunning training. Network logging and scalar extraction belong outside short benchmark windows.

Check your understanding. Verify shapes, finite loss/gradients, parameter updates, and tiny-subset learning before profiling. Why do these checks not prove generalization?

Chapter 2

Scaled Dot-Product Attention

Connection to the challenge. Implement the manual baseline, explain every axis, and check that alternative attention implementations compute the same function and gradients.

2.1 One head: definitions before implementation

For one sample and one head, $Q \in \mathbb{R}^{N_q \times d_k}$ is the query matrix, $K \in \mathbb{R}^{N_k \times d_k}$ the key matrix, and $V \in \mathbb{R}^{N_k \times d_v}$ the value matrix. N_q counts query tokens; N_k counts key/value tokens. d_k is the query/key feature dimension and d_v the value feature dimension. Each row is one token: a query describes what it seeks, a key what it offers, and a value the information to mix. Define the score matrix S, attention-weight matrix A, and attention-output matrix O:

$$S = \frac{QK^\mathsf{T}}{\sqrt{d_k}} \in \mathbb{R}^{N_q \times N_k}, \qquad S_{ij} = \frac{1}{\sqrt{d_k}} \sum_{a=1}^{d_k} Q_{ia} K_{ja}, \tag{2.1}$$

$$A_{ij} = \frac{\exp(S_{ij} - m_i)}{\sum_{\ell=1}^{N_k} \exp(S_{i\ell} - m_i)}, \qquad m_i = \max_{1 \le \ell \le N_k} S_{i\ell}, \tag{2.2}$$

$$O = AV \in \mathbb{R}^{N_q \times d_v}, \qquad O_{ia} = \sum_{j=1}^{N_k} A_{ij} V_{ja}. \tag{2.3}$$

Both S and A have shape (N_q, N_k); m_i is the maximum score in row i. The output O has shape (N_q, d_v): one row per query and one column per value feature. Its row i is a weighted combination of value rows. i indexes queries, j and the summation index ℓ index keys, and a indexes features ($1, \dots, d_k$ in S_{ij}; $1, \dots, d_v$ in O_{ia}). Softmax acts *over keys for each query* (`dim=-1`); subtracting the row maximum m_i avoids overflow without changing the mathematical ratio:

$$\mathrm{Attention}(Q, K, V) = \mathrm{softmax}_{\mathrm{row}}\left(QK^\mathsf{T}/\sqrt{d_k}\right) V. \tag{2.4}$$

This is Scaled Dot-Product Attention (SDPA) [6]. For finite scores, $A_{ij} > 0$ and $\sum_j A_{ij} = 1$: each output row is a convex combination of value rows. A is generally neither symmetric nor column-normalized, even when $N_q = N_k$. Attention weights are not class probabilities.

2.2 Why divide by the square root?

For a heuristic at initialization, suppose the products $Q_{ia}K_{ja}$ are independent across a, with mean zero and variance one. Writing Var for variance gives

$$\mathrm{Var}\left(\sum_{a=1}^{d_k} Q_{ia} K_{ja}\right) = d_k, \qquad \mathrm{Var}(S_{ij}) = 1. \tag{2.5}$$

Scaling by $1/\sqrt{d_k}$ controls score magnitudes as head width grows. Large score differences make softmax nearly one-hot, often giving small derivatives. Independence is an explanatory assumption, not a guarantee after training. The scale uses the query/key feature dimension d_k.

2.3 Self-attention and multiple heads

Multi-head Attention (MHA) combines h attention heads. In a batch of B images, $X_b \in \mathbb{R}^{N\times D}$ is image b's matrix of N token rows, each with D features. Self-attention projects this same matrix into queries, keys, and values, using different learned maps. Assume h divides D; $d = D/h$ is each head's feature dimension. For head index $r \in \{1, \dots, h\}$ define

$$Q_b^{(r)} = X_b W_Q^{(r)} + \mathbf{1}_N (b_Q^{(r)})^\mathsf{T}, \tag{2.6}$$

$$K_b^{(r)} = X_b W_K^{(r)} + \mathbf{1}_N (b_K^{(r)})^\mathsf{T}, \tag{2.7}$$

$$V_b^{(r)} = X_b W_V^{(r)} + \mathbf{1}_N (b_V^{(r)})^\mathsf{T}. \tag{2.8}$$

For $\bullet \in \{Q, K, V\}$, $W_\bullet^{(r)} \in \mathbb{R}^{D\times d}$ is a projection weight matrix and $b_\bullet^{(r)} \in \mathbb{R}^d$ its bias vector. $\mathbf{1}_N$ is the column vector of N ones, which repeats each bias over tokens. Apply Equations (2.1)–(2.3) independently for each (b, r), now with $N_q = N_k = N$ and $d_k = d_v = d$. The head outputs $O_b^{(r)} \in \mathbb{R}^{N\times d}$ are concatenated *along features*, in head order, and projected:

$$\mathrm{MHA}(X_b) = [O_b^{(1)} \mid \cdots \mid O_b^{(h)}] W_O + \mathbf{1}_N b_O^\mathsf{T} \in \mathbb{R}^{N\times D}, \quad W_O \in \mathbb{R}^{D\times D},\ b_O \in \mathbb{R}^D. \tag{2.9}$$

Here W_O is the learned output-projection weight matrix, b_O its bias, and $\mathrm{MHA}(X_b)$ the final (N, D) output for image b. Concatenation $[\cdot \mid \cdot]$ joins head features. Heads need not acquire interpretable roles; the batch dimension vectorizes independent images without mixing them.

Object	Batched shape	Axis interpretation
Input X	(B, N, D)	Image, token, model feature
Combined projection	$(B, N, 3D)$	Contiguous Q, K, V feature groups
Q, K, V after splitting	(B, h, N, d)	Image, head, token, head feature
K^T in matmul	(B, h, d, N)	Only the last two axes exchanged
S, A	(B, h, N, N)	Image, head, query token, key token
O per head	(B, h, N, d)	Image, head, query token, value feature
Concatenated O	(B, N, D)	Head features adjacent for each token
Output	(B, N, D)	Same shape as input; new content

Concrete sizes. For $B = 8$, $N = 64$, $D = 128$, $h = 4$, we have $d = 32$, Q of shape $(8, 4, 64, 32)$, and A of shape $(8, 4, 64, 64)$. Softmax normalizes each of the $8 \cdot 4 \cdot 64$ rows of length 64. Mixing heads or images into that normalization would compute a different model.

Check your understanding. Given $D = 192$ and $h = 6$, what is the scale? Why must head outputs be transposed back to (B, N, h, d) before merging their last two axes?

2.4 A vectorized manual implementation

In this exercise skeleton, `x` is the input token tensor (B, N, D); `dim`, `heads`, and `head_dim` mean D, h, and d. The variables `q`, `k`, and `v` are batched query, key, and value tensors of shape (B, h, N, d); `s` and `a` are scores and weights of shape (B, h, N, N). The returned `o` is the final (B, N, D) output after merging heads and applying the output projection, whereas O above denotes one head's output. A combined projection orders all Q features, then K, then V. Imports are as in Chapter 1.

```
class ManualAttention(nn.Module):
    def __init__(self, dim, heads):
        super().__init__()
        if dim % heads != 0:
            raise ValueError("dim must be divisible by heads")
        self.heads = heads
        self.head_dim = dim // heads

    def forward(self, x):
        B, N, D = x.shape
        h, d = self.heads, self.head_dim
        q, k, v = ...          # each (B, h, N, d)
        s = ...
        a = ...
        o = ...                # (B, N, D)
        return o

torch.manual_seed(17)
attention = ManualAttention(dim=128, heads=4).float()
tokens = torch.randn(8, 64, 128, dtype=torch.float32)
result = attention(tokens)
assert result.shape == tokens.shape
```

There is no loop over samples, tokens, or heads. Batched matrix multiplication performs the independent products. `transpose(-2,-1)` swaps the token and feature dimensions of K; using a general reversal of all dimensions would also move the batch and head axes. `contiguous()` makes the post-transpose memory layout suitable for the final `view`; account for this copy when reading a trace.

Test small, distinguishable inputs. An all-zero score matrix must produce a uniform row distribution, so the result is the mean value row at every query. With $N = 1$ the head output must equal its only value row. Neither test proves a general implementation correct, but both expose axis and normalization errors cheaply. Also compare a tiny explicit-loop reference against the vectorized version for unequal tensor dimensions.

Do not alter semantics while optimizing. Keep the scaling, softmax axis, projections and biases, and head order fixed. Do not use `nn.MultiheadAttention`, SDPA, or compilation in the initial manual baseline. Autograd differentiates the basic operations; no custom CUDA code or backward implementation is needed.

Check your understanding. Why does attention mix across the N dimension while the linear projections act on the D dimension? Which intermediate grows quadratically with N?

2.5 Backward propagation and equivalence checks

The following derivation is for one sample and one head. For any tensor T, write $\bar{T} = \partial\mathcal{L}/\partial T$ for the gradient of the scalar loss $\mathcal{L}$, with the same shape as T. In particular, $\bar{O} \in \mathbb{R}^{N_q \times d_v}$ is the incoming output gradient. Since $O = AV$, the chain rule gives

$$\bar{V} = A^\mathsf{T}\bar{O}, \qquad \bar{A} = \bar{O}V^\mathsf{T}. \tag{2.10}$$

For row i, $J_i \in \mathbb{R}^{N_k \times N_k}$ is the softmax Jacobian (derivatives of the weight row with respect to its score row): $J_i = \operatorname{diag}(A_{i,:}) - A_{i,:}^\mathsf{T} A_{i,:}$. Here diag places the weight row on a diagonal matrix. Avoid forming J_i explicitly:

$$\bar{S}_{ij} = A_{ij}\left(\bar{A}_{ij} - \sum_{\ell=1}^{N_k} A_{i\ell}\bar{A}_{i\ell}\right). \tag{2.11}$$

Finally, from $S = QK^\mathsf{T}/\sqrt{d_k}$,

$$\bar{Q} = \frac{\bar{S}K}{\sqrt{d_k}}, \qquad \bar{K} = \frac{\bar{S}^\mathsf{T}Q}{\sqrt{d_k}}. \tag{2.12}$$

Shapes are respectively (N_k, d_v), (N_q, N_k), (N_q, N_k), (N_q, d_k), and (N_k, d_k) for $\bar{V}, \bar{A}, \bar{S}, \bar{Q}, \bar{K}$. Thus backward includes substantial matrix multiplication and uses forward information. A forward-only graph can help locate those dependencies, but does not show all training work.

For one self-attention head, omit sample/head superscripts: $Q = XW_Q + \mathbf{1}_N b_Q^\mathsf{T}$, with token matrix $X \in \mathbb{R}^{N \times D}$. The weight gradient is $\bar{W}_Q = X^\mathsf{T}\bar{Q} \in \mathbb{R}^{D \times d}$ and the bias gradient is $\bar{b}_Q = \bar{Q}^\mathsf{T}\mathbf{1}_N \in \mathbb{R}^d$; the analogous K and V contributions add to $\bar{X} = \bar{Q}W_Q^\mathsf{T} + \bar{K}W_K^\mathsf{T} + \bar{V}W_V^\mathsf{T}$. Here $\bar{X} \in \mathbb{R}^{N \times D}$ is the input-token gradient. Sum the appropriate sample/head contributions. Outputs alone do not establish backward correctness.

A comparison protocol. Clone the same weights into both modules, and use identical inputs. Let $Y \in \mathbb{R}^{B \times N \times D}$ be the full module output and R a fixed probe tensor of the same shape. The scalar inner product $\langle Y, R\rangle = \sum_{b,i,a} Y_{bia} R_{bia}$, summed over images, tokens, and features, makes R the incoming gradient. Compare outputs and vector–Jacobian products for inputs and parameters.

```
def output_and_grads(module, input_tokens, probe):
    x = input_tokens.detach().clone().requires_grad_(True)
    y = module(x)
    targets = (x, *tuple(module.parameters()))
    grads = torch.autograd.grad((y * probe).sum(), targets)
    return y.detach(), tuple(g.detach() for g in grads)

# Use identical parameter ordering/state in reference and candidate.
# Compare outputs, input gradients, and every parameter gradient:
# torch.testing.assert_close(actual, expected, rtol=1e-4, atol=1e-5)
```

The illustrative FP32 tolerances are a starting point, not a universal bound. Report maximum absolute error and relative error with a stated denominator floor, especially near zero. Repeat with several small random inputs and the actual comparison shapes. Also compare gradients of the full classification loss; do not update weights until both sides have been evaluated.

2.6 Cost, memory, and SDPA backends

For self-attention with $d = D/h$, count a multiply and add as two floating-point operations (FLOPs). Then the two head-level products together require approximately

$$\underbrace{2BhN^2d}_{QK^\top} + \underbrace{2BhN^2d}_{AV} = 4BN^2D \quad \text{FLOPs per forward pass.} \tag{2.13}$$

Softmax adds $\mathcal{O}(BhN^2)$ work; $\mathcal{O}$ denotes asymptotic growth, distinct from the output matrix O. The three input projections plus the output projection require approximately $8BND^2$ FLOPs, excluding biases. Projections can therefore dominate when N is small relative to D. These counts describe arithmetic, not elapsed time; memory traffic, launch overhead, and hardware occupancy also matter.

One FP32 score or probability tensor occupies $4BhN^2$ bytes. If both are materialized, they account for $8BhN^2$ bytes before other activations, gradients, parameters, and optimizer state. For $B = 32, h = 4, N = 64$, a single such tensor is 2 mebibytes (MiB), where $1\,\text{MiB} = 2^{20}$ bytes. Actual peak memory depends on tensor lifetimes and implementation; theoretical sizes are not a replacement for measurement. Keep N fixed in this challenge's experiments.

SDPA implements the same attention function through a backend-selected execution strategy [7, 8]. Replace only the score/softmax/value calculation in the manual module, keeping the surrounding projections:

```
# q, k, v already have shape (B, h, N, d).
out = F.scaled_dot_product_attention(q, k, v)

# Example: require the math backend instead of automatic selection.
from torch.nn.attention import SDPBackend, sdpa_kernel
with sdpa_kernel(backends=[SDPBackend.MATH]):
    out = F.scaled_dot_product_attention(q, k, v)
```

SDPA already applies the default $1/\sqrt{d}$ scaling: do not prescale Q as well. Current backend choices include `MATH`, `FLASH_ATTENTION`, `EFFICIENT_ATTENTION`, and `CUDNN_ATTENTION` where provided by the installed release [9]; cuDNN means CUDA Deep Neural Network library. Backend availability also depends on the device, dtype, strides, shape, and backward requirements.

Request one backend at a time and preserve its diagnostics. Verify the executed implementation in a native profiler trace. Automatic selection and math may use the same path; an enabled backend is not proof that it ran. If an FP32 backend is unsupported, report that result and retain FP32. Do not switch to 16-bit floating point (FP16) or 16-bit brain floating point (BF16, or bfloat16) to obtain a faster required comparison.

Fused algorithms can tile attention and avoid storing the full $N \times N$ matrix in device memory. FlashAttention's design reduces memory traffic while computing exact attention in real arithmetic [10]; finite-precision rounding can still differ. A fused graph may show fewer nodes without doing less mathematical work. Measure both attention forward/backward and complete training steps, since speeding up one component does not accelerate all work.

Chapter 3

Simple Vision Transformer

Connection to the challenge. Turn Places365 images into 365 class logits with a small, fixed architecture whose computation can be explained and profiled.

3.1 From pixels to a sequence of patch tokens

A Vision Transformer (ViT) applies attention to image patches [11]. Let $I \in \mathbb{R}^{B\times C\times H\times W}$ be the image batch: B images, C channels, height H, and width W. Use non-overlapping square patches of side length P pixels, where $P \mid H$ and $P \mid W$ mean that P divides both image dimensions. Then

$$G_H = H/P, \quad G_W = W/P, \quad N = G_H G_W, \quad F = CP^2. \tag{3.1}$$

G_H, G_W are the numbers of patch rows and columns, N the patch count, and F the pixel-value count per patch (unrelated to the Python alias `F`). Use zero-based spatial/feature indices: patch row $0 \le i < G_H$, patch column $0 \le j < G_W$, channel $0 \le c < C$, and within-patch row/column offsets u, v. For image index b, patch sequence index $n = iG_W + j$ gives

$$\xi_{b,n,(cP+u)P+v} = I_{b,c,iP+u,jP+v}, \quad 0 \le c < C, \quad 0 \le u, v < P. \tag{3.2}$$

The flattened-patch tensor is $\xi \in \mathbb{R}^{B\times N\times F}$. With embedding width D, let $E \in \mathbb{R}^{F\times D}$ be the shared projection weight matrix, $e \in \mathbb{R}^{D}$ its bias, and $\Pi \in \mathbb{R}^{N\times D}$ the learned position matrix. The initial token tensor $X^{(0)} \in \mathbb{R}^{B\times N\times D}$ is

$$X^{(0)}_{b,n,:} = \xi_{b,n,:}E + e^{\mathsf{T}} + \Pi_{n,:}. \tag{3.3}$$

Positions are shared across the batch. They encode the patch's place on the grid; the model cannot obtain that information merely from the sequence's storage order.




Figure 3.1: Patch embedding for one image. The drawn 4×4 grid is schematic; the example configuration uses 8×8 patches.

Without positional information, shared token operations and self-attention are permutation-equivariant: permuting the input tokens permutes the output tokens in the same way. Mean pooling then makes the classifier invariant to patch permutations. Learned positions break that unwanted ambiguity.

Example sizes. Resize to 128×128, choose $P = 16$, $C = 3$ and $D = 128$. There are $N = 64$ patches, each with $F = 768$ pixel values. The input $(B, 3, 128, 128)$ becomes $(B, 64, 768)$ and then $(B, 64, 128)$. A plain reshape directly from pixels to (B, N, F) is incorrect for the usual channel-first image layout; spatial axes must first be rearranged.

3.2 A compact encoder and classification head

Let L be the number of encoder blocks and $\ell = 1, \ldots, L$ the block index. Layer Normalization (LN), Multi-head Attention (MHA), and a Feed-Forward Network (FFN) with a Gaussian Error Linear Unit (GELU) activation form a pre-normalized residual block:

$$U^{(\ell)} = X^{(\ell-1)} + \mathrm{MHA}_\ell(\mathrm{LN}_{\ell,1}(X^{(\ell-1)})), \tag{3.4}$$

$$X^{(\ell)} = U^{(\ell)} + \mathrm{FFN}_\ell(\mathrm{LN}_{\ell,2}(U^{(\ell)})), \tag{3.5}$$

$$\mathrm{FFN}_\ell(T) = \mathrm{GELU}(TW_{1,\ell} + b_{1,\ell})W_{2,\ell} + b_{2,\ell}. \tag{3.6}$$

$X^{(\ell-1)}$ is the block input, $U^{(\ell)}$ the intermediate result after attention/residual addition, and $X^{(\ell)}$ the block output; each has shape (B, N, D). In the FFN, T denotes its input tensor of that shape and M its hidden feature width. $W_{1,\ell} \in \mathbb{R}^{D\times M}$ and $W_{2,\ell} \in \mathbb{R}^{M\times D}$ are projection weights; biases $b_{1,\ell} \in \mathbb{R}^M$ and $b_{2,\ell} \in \mathbb{R}^D$ broadcast over samples and tokens. Attention mixes tokens; the FFN transforms each token independently. Residual addition supplies a direct path for information and gradients.

LN operates over the D features of one token. For token row $t \in \mathbb{R}^D$ and feature index $a = 1, \ldots, D$,

$$\mathrm{LN}(t)_a = \gamma_a \frac{t_a - \mu}{\sqrt{\sigma^2 + \epsilon}} + \beta_a, \quad \mu = \frac{1}{D}\sum_{a=1}^{D} t_a, \quad \sigma^2 = \frac{1}{D}\sum_{a=1}^{D}(t_a - \mu)^2. \tag{3.7}$$

μ is the feature mean, σ^2 the feature variance, and $\epsilon = 10^{-5}$ a numerical-stability constant. The learned vectors $\gamma, \beta \in \mathbb{R}^D$ scale and shift each feature. Subscripts $(\ell, 1)$, $(\ell, 2)$, and final identify separately parameterized norms. After L blocks, normalize, average over tokens, and classify:

$$g_b = \frac{1}{N}\sum_{n=1}^{N} \mathrm{LN}_{\mathrm{final}}(X^{(L)})_{b,n,:}, \qquad s_b = g_b W_C + b_C^\intercal \in \mathbb{R}^{365}. \tag{3.8}$$

Here $g_b \in \mathbb{R}^D$ is image b's pooled feature row, $W_C \in \mathbb{R}^{D\times 365}$ the classifier weight matrix, $b_C \in \mathbb{R}^{365}$ its bias, and s_b the 365 class logits. The subscript C labels the classifier here. Pooling averages token index $n = 1, \ldots, N$ without adding a classification token.

Component	Example configuration	Parameters
Patch embedding	$768 \to 128$, with bias	98 432
Learned positions	64×128	8 192
One attention sublayer	$D = 128$, $h = 4$, $d = 32$, biases	66 048
One feed-forward sublayer	$128 \to 512 \to 128$, biases	131 712
Two norms per block	Two sets of $\gamma, \beta \in \mathbb{R}^{128}$	512
Two complete blocks	$L = 2$	396 544
Final norm	$D = 128$	256
Classifier	$128 \to 365$, with bias	47 085
Model total	Attention/FFN/norm rows above detail each block	**550 509**

This is one illustrative baseline, not a claim of optimal accuracy. Choose a feasible model once, document its parameter count and shapes, and keep it fixed for all required performance comparisons.

3.3 A minimal model built from the manual attention module

This code uses `ManualAttention` from Chapter 2. The model uses linear patch embeddings and mean pooling. The flattening order matches Equation (3.3).

```
class Block(nn.Module):
    def __init__(self, dim, heads, mlp_dim):
        super().__init__()
        self.norm1 = nn.LayerNorm(dim, eps=1e-5)
        self.attn = ManualAttention(dim, heads)
        self.norm2 = nn.LayerNorm(dim, eps=1e-5)
        self.ffn = nn.Sequential(nn.Linear(dim, mlp_dim),
                                 nn.GELU(), nn.Linear(mlp_dim, dim))

    def forward(self, x):
        x = x + self.attn(self.norm1(x))
        return x + self.ffn(self.norm2(x))

class TinyViT(nn.Module):
    def __init__(self, image_size=128, patch=16, dim=128,
                 heads=4, depth=2, mlp_dim=512, classes=365):
        super().__init__()
        if image_size % patch != 0:
            raise ValueError("image_size must be divisible by patch")
        self.image_size, self.patch = image_size, patch
        self.embed = nn.Linear(3 * patch * patch, dim)
        n = (image_size // patch) ** 2
        self.pos = nn.Parameter(torch.zeros(1, n, dim))
        nn.init.normal_(self.pos, std=0.02)
        self.blocks = nn.ModuleList(
            [Block(dim, heads, mlp_dim) for _ in range(depth)])
        self.norm = nn.LayerNorm(dim, eps=1e-5)
        self.head = nn.Linear(dim, classes)

    def forward(self, images):
        B, C, H, W = images.shape
        assert C == 3 and H == W == self.image_size
        p = self.patch
        x = images.reshape(B, C, H // p, p, W // p, p)
        x = x.permute(0, 2, 4, 1, 3, 5)
        x = x.reshape(B, (H // p) * (W // p), C * p * p)
        x = self.embed(x) + self.pos
        for block in self.blocks:
            x = block(x)
        return self.head(self.norm(x).mean(dim=1))

model = TinyViT().to(device=device, dtype=torch.float32)
optimizer = torch.optim.AdamW(model.parameters(), lr=3e-4)
assert sum(p.numel() for p in model.parameters()) == 550509
```

In the code, `image_size`, `patch`, `dim`, `heads`, and `depth` mean $H = W$, P, D, h, and L; `classes` is the class count. `mlp_dim` is the multilayer perceptron (MLP) hidden width M. Local variables `p` and `n` are patch side length P and patch count N; `x` holds successive representations. The loop visits the independently learned blocks in `ModuleList`.

3.4 From a smoke test to evidence of learning

Start on CPU with a tiny batch and check that the model returns $(B, 365)$ logits. Check patch ordering with an image containing numbered pixels: each flattened patch should contain exactly one spatial tile in the chosen channel order. A shape check alone would not detect a permutation error.

```
model.train()
images = torch.randn(2, 3, 128, 128, device=device)
labels = torch.tensor([0, 364], device=device, dtype=torch.long)
optimizer.zero_grad(set_to_none=True)
logits = model(images)
assert logits.shape == (2, 365)
loss = F.cross_entropy(logits, labels)
assert torch.isfinite(loss)
loss.backward()
assert all(p.grad is not None and torch.isfinite(p.grad).all()
           for p in model.parameters())
optimizer.step()
```

These assertions are diagnostic and can synchronize the GPU; remove them from performance measurement windows. Then overfit a few real training images with deterministic preprocessing. Loss should fall and training accuracy should rise with enough optimization. If not, check labels, normalization, device placement, gradient clearing, learning rate, and whether parameters update. Random labels and random images only check execution, not useful learning.

For 365 nearly uniform class probabilities, cross-entropy is near $\log(365) \approx 5.90$; this is a useful scale check, not a required initial loss. Uniform random guessing has expected accuracy $1/365 \approx 0.274\%$. An overfitted tiny training set can reach high training accuracy while held-out accuracy remains poor. Report these as different observations.

3.5 Relating architecture to performance experiments

The forward path contains patch rearrangement, projections, normalization, attention, feed-forward matrix multiplications, pooling, and classification. Backward propagates through all these operations; the optimizer then reads and writes parameter state. Attention may not be the largest cost for a small patch count. Locate the three largest measured CPU self-time operations on the graph instead of assuming which nodes dominate.

For compilation, first construct an eager reference and a separate candidate with identical weights. Apply `torch.compile(candidate)` to the model, leaving data loading and logging outside. Compilation may fuse operations or change dispatch overhead, and an initial call can include compilation work. Some inputs or control flow cause graph breaks; a new shape may cause recompilation [12]. Warm up forward *and backward* for each batch size, check output and gradient agreement, and profile the actual compiled path. Do not infer compiled execution from a TorchLens graph alone.

For the final comparison, train the manual eager, manual compiled, and fastest supported FP32 SDPA variants from the same initial checkpoint. Keep batch, data order, optimizer, transformations, and training budget fixed. Save each run's validation results, throughput windows, and configuration. A faster implementation is useful only if its computation and learning remain comparable within documented numerical differences.

Check your understanding. Explain why the classifier produces 365 logits, why positional parameters depend on N, and why changing the patch size would invalidate a controlled implementation comparison.

Chapter 4

Slurm introduction with simple examples

Connection to the challenge. Run experiments on allocated compute resources, reproduce the environment, and retrieve logs, checkpoints, and performance measurements.

4.1 Allocations, tasks, and steps

Slurm (Simple Linux Utility for Resource Management) schedules work on a shared cluster. An *allocation* reserves resources for a job; a *job step* launches processes within it. A *task* usually means a process, not a CPU thread. One-GPU training here uses one task with several allocated CPUs for the main process and data loading. Requesting eight tasks would not automatically make one training process eight times faster [13].

Request	Meaning for a one-node job
`-nodes=1`	One compute node.
`-ntasks=1`	One launched training process.
`-cpus-per-task=8`	Eight Slurm CPUs for that task; check local core/thread policy.
`-gres=gpu:rtx3080:1`	A generic resources (GRES) request for one GPU of the named type.
`-mem=24G`	Host random-access memory (RAM) per node, not GPU device memory.
`-time=00:10:00`	Ten-minute wall-time limit once running.
`-partition=p3080`	A site-defined group of eligible nodes.

`sbatch` queues a script and returns a job ID; submission does not mean execution has started. `salloc` obtains an allocation for interactive work, and `srun` starts a step (or requests resources when used directly). Run substantial computation on compute nodes, not the login node.

On Calculon, check the documentation here[1].

4.2 A short interactive GPU check

Calculon guide lists `p3080` and GPU type `rtx3080`; verify live availability and access before use [14, 15]. `nvidia-smi` is NVIDIA's System Management Interface for inspecting GPUs.

```
sinfo -o "%P %a %l %D %G"
srun --partition=p3080 --nodes=1 --ntasks=1 \
     --gres=gpu:rtx3080:1 --cpus-per-task=8 --mem=24G \
     --time=00:10:00 --pty bash
# Now on the allocated compute node:
source "$VENV_PATH/bin/activate"    # set VENV_PATH beforehand
hostname
nvidia-smi
python -c 'import torch; assert torch.cuda.is_available(); print(torch.cuda.get_device_name(0))'
exit                              # finish the interactive step
```

Slurm sets GPU visibility. In a one-GPU job, `cuda:0` normally means the first *visible* GPU, not necessarily physical GPU 0. Preserve `CUDA_VISIBLE_DEVICES`; do not overwrite it to select an unallocated GPU. Log both the device name and the device of a model parameter and input tensor. A CUDA-enabled installation alone does not move the computation to the GPU.

[1] https://fhnw-hpc.pages.fhnw.ch/docs/runjobs/

4.3 A batch script for repeatable training

Save the following example as `train.sbatch` when implementing the challenge. It assumes a prepared virtual environment and a written new training script `train.py` accepting the shown command-line interface (CLI). Adjust resource requests to the measured workload. `##SBATCH` directives must precede shell commands, and shell variables are not expanded inside them [16].

```
#!/bin/bash
#SBATCH --job-name=mc2-manual
#SBATCH --partition=p3080
#SBATCH --nodes=1
#SBATCH --ntasks=1
#SBATCH --gres=gpu:rtx3080:1
#SBATCH --cpus-per-task=8
#SBATCH --mem=24G
#SBATCH --time=02:00:00
#SBATCH --output=logs/%x-%j.out
#SBATCH --error=logs/%x-%j.err
set -euo pipefail
cd "$SLURM_SUBMIT_DIR"
: "${VENV_PATH:?Set VENV_PATH before submission}"
: "${PLACES365_ROOT:?Set the prepared shared dataset root}"
: "${RUN_ROOT:?Set your persistent output directory}"
source "$VENV_PATH/bin/activate"
export OMP_NUM_THREADS=2
export MKL_NUM_THREADS=2
export WANDB_MODE=offline
run_dir="${RUN_ROOT}/${SLURM_JOB_ID}"
mkdir -p "$run_dir"
hostname
date -Is
nvidia-smi
python -m pip freeze > "$run_dir/packages.txt"
srun python -u train.py --device cuda:0 --attention manual \
    --batch-size 32 --workers 4 --cpu-threads 2 --epochs 1 \
    --seed 17 --data-root "$PLACES365_ROOT" --output "$run_dir"
```

Here `PLACES365_ROOT` is the dataset root, `RUN_ROOT` the persistent output root, and `run_dir` this job's output directory. Slurm supplies `SLURM_SUBMIT_DIR` (submission directory) and `SLURM_JOB_ID` (job identifier); `%x` and `%j` expand to the job name and ID in log paths. Create `logs` before submission, since Slurm opens logs before the script runs. Set and export the three user paths:

```
export VENV_PATH PLACES365_ROOT RUN_ROOT
mkdir -p logs
sbatch train.sbatch
# Example response: Submitted batch job 123456
```

`OMP_NUM_THREADS` and `MKL_NUM_THREADS` bound thread counts for Open Multi-Processing (OpenMP) and Intel's Math Kernel Library (MKL). The program must enforce FP32/highest precision and the CLI settings. CPU threads and loader workers share the allocation: four worker processes plus two main-process numerical threads are a starting budget, not a guarantee against oversubscription by third-party libraries. Record actual thread settings and bound decoding-library threads where needed.

Use a pre-installed environment in batch jobs. Follow the cluster's software guide[2] for modules or containers; loading a CUDA toolkit does not install PyTorch. Keep checkpoints and raw measurements in persistent storage.

[2] https://fhnw-hpc.pages.fhnw.ch/docs/software/

4.4 Monitor, diagnose, and retrieve output

Use the job ID returned by `sbatch`, replacing the illustrative ID below.

```
squeue -u "$USER"                  # queued/running jobs
scontrol show job 123456           # allocation, state, pending reason
tail -f logs/mc2-manual-123456.out  # Ctrl-C stops tail, not the job
sacct -j 123456 --format=JobID,State,Elapsed,ExitCode,AllocCPUS,MaxRSS
scancel 123456                     # only to cancel this job
```

`sacct` includes job-step records; memory fields may be populated only for steps and depend on accounting configuration. `MaxRSS` is the maximum resident set size (RSS), a host-memory measure, not peak allocated CUDA memory [17]. `USER` is the shell's username variable. Slurm's reported completion should also be checked against the program's exit status, logs, saved metrics, and expected checkpoint.

Observation	What to inspect
Pending	Read the scheduler reason: unavailable resources, priority, or limits.
CUDA unavailable	Verify a GPU request, visible devices, the Python environment, and CUDA build.
CUDA out of memory	Inspect device peak memory and batch size; extra `-mem` does not enlarge GPU RAM.
Host out of memory	Inspect dataset replication, prefetch queues, worker count, and host RAM request.
Time limit	Check elapsed time and checkpoint progress; choose a feasible common training budget.
Missing output	Check the submit directory, log parent directory, job state, and stderr.

4.5 CPU jobs and storage conditions

An allocation without GPUs can be can be requested as before; activate the same suitable environment and run `train.py -device cpu` inside it.

```
srun --partition=performance --nodes=1 --ntasks=1 \
     --cpus-per-task=4 --mem=8G --time=00:10:00 --pty bash
# In the allocated shell, activate the environment and run the CPU test.
# Use matching thread counts and record the CPU model; exit when done.
```

For CPU-cluster monitoring, pass the matching cluster option to commands such as `squeue -M calc-cpu`. A local laptop CPU versus a cluster GPU comparison also changes CPU hardware, storage, and software; state those limitations.

For loading experiments, record the actual shared path, cache conditions, and whether a site-approved node-local scratch directory is used. Copy only the data needed for the test, respect quotas, and report staging time separately. Node-local data can disappear at job end; copy results to persistent storage before releasing the allocation. Repeated reads may be served from RAM, so a faster second pass does not by itself establish higher drive bandwidth.

Full runs should keep profiling disabled and log at a moderate interval. Store the job ID with configuration and W&B metadata. Offline runs can be synchronized later; retain local metric exports for the notebook regardless of service availability. Multi-GPU launchers, if attempted as an optional extension, must avoid multiplying Slurm tasks by launcher-created processes.

Chapter 5

Computation graphs and profiling

Connection to the challenge. Connect model operations to measured time, memory, kernels, and idle periods without confusing diagnostic traces with representative throughput.

5.1 A graph and a timeline answer different questions

A computation graph records dependencies: tensors are produced by operations and consumed by others. A forward visualization describes one executed path and its shapes. The autograd graph additionally carries backward dependencies; saved tensors or recomputation make those derivatives possible. Neither is a literal schedule of CPU instructions or GPU kernels.

Tool	Useful evidence and its boundary
Torchview	Forward module/operation structure and tensor shapes; Graphviz renders the diagram. It is not a device-time profiler [18].
TorchLens	Operation-level relationships, activations, and metadata. Record version, capture options, and activation retention. Interpret ordinary operation timings as instrumented host times; identify any supported native-profiler integration separately [19].
PyTorch Profiler	Host events, CUDA launches, device activity, shapes, and memory events. Correlate operations with kernels and the execution timeline [20].

```
import copy
from torchview import draw_graph
graph_model = copy.deepcopy(model).eval()
graph = draw_graph(graph_model, input_data=images, expand_nested=True)
graph.visual_graph.render("forward_graph", format="pdf")
```

Choose representative shapes and record that this graph uses evaluation mode. Capture separately from timing and use the training mode for training traces. An eager matrix multiplication may dispatch several operations; a compiled or fused kernel may implement several graph nodes. Views may need no kernel, whereas making a tensor contiguous can introduce a copy.




Figure 5.1: Schematic asynchronous execution on one GPU stream; t denotes elapsed time. Kernel labels A and B identify two operations, not mathematical variables. Host calls can finish before their kernels; synchronization waits for queued work.

5.2 Define the measured interval before timing it

Distinguish three scopes: (i) attention on prepared Q, K, V tensors, with forward/backward stated explicitly; (ii) a complete training step with inputs already on the device; and (iii) an end-to-end step including fetching, transformation, and transfer. State whether attention projections are included. Never transfer a speedup claim between these scopes without measuring it.

GPU calls usually enqueue work asynchronously [21]. For a representative wall-clock window, warm up first and synchronize at its boundaries. Here `images` and `labels` are already resident; neither loading nor host logging is measured.

```
import time
import statistics

def synchronize(device):
    if device.type == "cuda":
        torch.cuda.synchronize(device)

model.train()
for _ in range(10):  # illustrative; increase until stable
    train_step(model, optimizer, images, labels)
synchronize(device)
times = []
steps = 50
for repeat in range(3):
    synchronize(device)
    start = time.perf_counter()
    for _ in range(steps):
        train_step(model, optimizer, images, labels)
    synchronize(device)
    times.append(time.perf_counter() - start)
latencies = [t / steps for t in times]
rates = [steps * images.shape[0] / t for t in times]
print(statistics.mean(latencies), statistics.stdev(latencies))
print(statistics.mean(rates), statistics.stdev(rates))
```

This benchmark updates weights throughout. For implementation comparisons, restore identical model and optimizer states and use the same input sequence before each configuration. Warm-up must include optimizer state initialization and compiled backward work. Measure startup and compilation separately; fixed warm-up counts alone do not prove steady state.

Let n be the number of measured steps, B_k the image count at step index k, $m = \sum_{k=1}^{n} B_k$ the total image count, and T the window's elapsed time in seconds. Mean step time is T/n and throughput is m/T images/s. Repeat short benchmarks at least three times and report a central value, variability, steps, and images. Window-average step times do not measure individual-step variability; label the aggregation level. Full training runs need not be repeated three times, but should report variability across measurement windows.

CUDA events can time an interval on a stream: record a start event, enqueue work, record an end event, wait for it, then call `start.elapsed_time(end)` (milliseconds). Events may include device idle gaps between enqueues; they are not a sum of kernel durations. Work on other streams needs appropriate dependencies. Use wall-clock windows for input-pipeline throughput, and avoid synchronizing after every operation.

5.3 Capture short traces and read their timing fields

Warm up the workload before profiling. The example below captures a short end-to-end window with a profiler schedule; ensure at least six batches are available. For resident-input experiments omit fetching and transfer from the captured loop. Keep the training workload otherwise identical.

```
from torch.profiler import profile, ProfilerActivity, record_function
activities = [ProfilerActivity.CPU]
if device.type == "cuda":
    activities.append(ProfilerActivity.CUDA)
model.train()
iterator = iter(train_loader)
with profile(activities=activities, record_shapes=True,
             profile_memory=True, with_stack=False,
             schedule=torch.profiler.schedule(
                 wait=1, warmup=1, active=4, repeat=1)) as prof:
    for _ in range(6):
        with record_function("data_fetch"):
            images, labels = next(iterator)
        with record_function("host_to_device"):
            images = images.to(device, non_blocking=True)
            labels = labels.to(device, non_blocking=True)
        optimizer.zero_grad(set_to_none=True)
        with record_function("forward_and_loss"):
            loss = F.cross_entropy(model(images), labels)
        with record_function("backward"):
            loss.backward()
        with record_function("optimizer"):
            optimizer.step()
        prof.step()
prof.export_chrome_trace("trace.json")
print(prof.key_averages(group_by_input_shape=True).table(
    sort_by="self_cpu_time_total", row_limit=15))
```

Timing field	Interpretation
CPU self time	Time attributed to a host event excluding its nested child events.
CPU inclusive time	Host event duration including nested work; summing parents and children double-counts that time.
GPU/device time	Duration of correlated device activity; it is not the CPU time spent launching it. Field names can vary by profiler version.
Wall time	Elapsed time between measurement boundaries, including waits and overlap according to the chosen scope.

Open the exported trace in a compatible viewer such as Perfetto. Match expensive operations to shapes and modules, then inspect kernel launches, durations, copies, and idle gaps. Include backward and optimizer events. Aggregate call counts and input shapes, not just operator names. GPU activity on overlapping streams and nested CPU ranges cannot be added as disjoint wall time. A host transfer range can end before the corresponding copy completes.

5.4 Memory and the cost of observing execution

GPU *allocated* memory is used by live tensors tracked by PyTorch's allocator. *Reserved* memory includes allocator-managed cached blocks. Neither is identical to device-wide usage reported by a system monitor; contexts, libraries, and other processes can contribute to the latter. Freeing a tensor may reduce allocated memory without reducing reserved memory.

Reset peaks at a documented boundary after warm-up. The following reports the absolute peak for a window, including its already-live model and input tensors; it is not just incremental temporary memory [22].

```
# CUDA-only, after warm-up; choose the same boundary in every run.
optimizer.zero_grad(set_to_none=True)
torch.cuda.synchronize(device)
torch.cuda.reset_peak_memory_stats(device)
for _ in range(50):
    train_step(model, optimizer, images, labels)
torch.cuda.synchronize(device)
peak_allocated = torch.cuda.max_memory_allocated(device)
peak_reserved = torch.cuda.max_memory_reserved(device)
print(peak_allocated / 2**20, peak_reserved / 2**20)  # MiB
```

Parameter count alone underestimates training memory. FP32 parameters and gradients each require roughly $4P_\theta$ bytes for P_θ parameters; two FP32 Adam moment buffers add roughly $8P_\theta$ bytes. Activations, attention matrices, workspaces, and implementation-specific optimizer temporaries add further costs. Host-side loader queues consume different memory. Do not call `empty_cache()` between ordinary steps: doing so changes the allocator workload and is not representative training.

Profiler overhead experiment. Use the same fixed forward workload, weights, inputs, mode, grad-enabled state, and warm-up for four conditions: uninstrumented, basic native profiling, profiling with shapes/stacks, and TorchLens capture. Keep other options constant and record activation-retention settings. Measure synchronized external wall time; exclude rendering and file export, and state whether profiler entry/exit and result processing are included. Record available memory measures for the same boundary. Let T_0 be uninstrumented elapsed time and T_j the time with instrumentation mode j, measured in the same units. The dimensionless slowdown factor is ρ_j; the percentage increase is overhead_j:

$$\rho_j = T_j/T_0, \qquad \text{overhead}_j = 100\,(T_j/T_0 - 1)\%. \tag{5.1}$$

Shape/stack instrumentation and activation retention can add work and extend tensor lifetimes. Instrumentation can alter dispatch, synchronization, and memory behavior. Ordinary host operation times from TorchLens cannot establish a GPU speedup; document the timing source and use supported native device timings when available. Graph rendering has a different purpose and belongs outside the measured capture interval.

Batch size. A larger batch can raise step latency but improve images/s by doing more useful work per launch. Seek a throughput plateau or practical memory limit using up to four sizes, all with resident inputs. Use traces to test whether small batches leave launch gaps and whether large batches lengthen kernels. Sampled GPU utilization reports activity, not achieved floating-point operations per second (FLOP/s) or memory bandwidth efficiency; high utilization does not prove efficient execution.

5.5 Explain pipeline delays, synchronization, and speedups

For end-to-end experiments, time many steps from fetching inputs through completed updates. Compare with a matching resident-input reference. Label `next(loader)` waits, transfers, and model work, but remember that loader workers can prepare future batches while the GPU computes. Under ideal overlap, steady-state step time approaches the maximum of producer and consumer times; without overlap it approaches their sum. Real queues and dependencies require trace evidence.

Hold transformations, shuffle order, storage, pinning, and prefetch policy fixed while varying worker count. Include zero, small, moderate, and large counts within the CPU allocation. Pass multiprocessing-only options only when workers are positive; report total queued batches and separate worker startup from steady state. Extra workers can contend for CPUs, memory, metadata access, or storage bandwidth. Waiting for a batch does not identify which of file access, decoding, transformation, or queueing is responsible.

The main-process profiler does not automatically capture worker internals. An unchanged model graph under low and high worker counts is expected: file reads and queues lie outside the model. Compare TorchLens operation metadata with pipeline traces and throughput, identifying host versus device times. For storage comparisons, record shared versus local location or first versus repeated reads and cache conditions; do not infer disk input/output (I/O) solely from loader waiting time.

Accidental synchronization. `loss.item()` must provide a Python number, so a GPU result must become available on the host. The wait can include previously queued work. Compare no per-step extraction, extraction every step, and extraction at a larger interval, holding all model work fixed. Keep console and network output outside the comparison. Accumulate detached scalar tensors on device, then extract at logging boundaries; do not retain computation graphs. Inspect whether host/GPU overlap changes, rather than assuming extraction must always cause a large slowdown.

Limits to component speedups. In a simplified non-overlapping model, let $f \in [0, 1]$ be attention's fraction of baseline time and $s > 0$ its component speedup (baseline/new attention time). The complete-step speedup S is baseline/new step time, a dimensionless ratio:

$$S = \frac{1}{(1 - f) + f/s}. \tag{5.2}$$

For $f = 0.2$ and $s = 4$, $S \approx 1.18$. Real overlap can invalidate this decomposition; use it as a hypothesis and measure the full step. Fusion can reduce memory traffic and launches, while loading may still dominate training.

For compilation, ΔC is the additional one-time startup time relative to eager execution; t_e and t_c are the eager and compiled steady-state times per step, all in seconds. If $t_c < t_e$, the approximate number of steps needed to recover that startup cost is n_{break}:

$$n_{\text{break}} = \left\lceil \frac{\Delta C}{t_e - t_c} \right\rceil. \tag{5.3}$$

Here $\lceil \cdot \rceil$ rounds up to the nearest integer. This assumes fixed shapes, no further compilation, and comparable work. If $t_c \geq t_e$ and $\Delta C > 0$, there is no positive amortization benefit.

Check your understanding. For every plot, identify the scope, units, precision, workload, warm-up, repetitions, timing source, and uncertainty. Use unprofiled throughput to establish performance, short traces to explain it, and held-out learning curves to check that the faster execution remains useful.

References

[1] PyTorch Contributors. Learn the basics. PyTorch Tutorials, n.d.. URL https://docs.pytorch.org/tutorials/beginner/basics/intro.html. Accessed 4 November 2026.

[2] PyTorch Contributors. Automatic differentiation with torch.autograd. PyTorch Tutorials, n.d.. URL https://docs.pytorch.org/tutorials/beginner/basics/autogradqs_tutorial.html. Accessed 4 November 2026.

[3] PyTorch Contributors. Optimizing model parameters. PyTorch Tutorials, n.d.. URL https://docs.pytorch.org/tutorials/beginner/basics/optimization_tutorial.html. Accessed 4 November 2026.

[4] Torchvision Contributors. Places365 dataset. Torchvision Documentation, n.d. URL https://docs.pytorch.org/vision/stable/generated/torchvision.datasets.Places365.html. Accessed 4 November 2026.

[5] PyTorch Contributors. torch.utils.data: Datasets and data loading. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/data.html. Accessed 4 November 2026.

[6] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. URL https://arxiv.org/abs/1706.03762.

[7] PyTorch Contributors. torch.nn.functional.scaled_dot_product_attention. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/generated/torch.nn.functional.scaled_dot_product_attention.html. Accessed 4 November 2026.

[8] PyTorch Contributors. torch.nn.attention.sdpa_kernel. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/generated/torch.nn.attention.sdpa_kernel.html. Accessed 4 November 2026.

[9] PyTorch Contributors. torch.nn.attention.SDPBackend. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/generated/torch.nn.attention.SDPBackend.html. Accessed 4 November 2026.

[10] Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems*, volume 35, 2022. URL https://arxiv.org/abs/2205.14135.

[11] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021. URL https://arxiv.org/abs/2010.11929.

[12] PyTorch Contributors. Introduction to torch.compile. PyTorch Tutorials, n.d.. URL https://docs.pytorch.org/tutorials/intermediate/torch_compile_tutorial.html. Accessed 4 November 2026.

[13] SchedMD. Slurm quick start user guide, n.d.. URL https://slurm.schedmd.com/quickstart.html. Accessed 4 November 2026.

[14] FHNW Institute for Data Science. Calculon user guide: GPU jobs, n.d.. URL https://fhnw-hpc.pages.fhnw.ch/docs/runjobs/basics/gpu-jobs/. Accessed 4 November 2026.

[15] FHNW Institute for Data Science. Calculon user guide: Partitions and resource policies, n.d.. URL https://fhnw-hpc.pages.fhnw.ch/docs/runjobs/basics/partitions-qos/. Accessed 4 November 2026.

[16] SchedMD. Slurm workload manager: sbatch, n.d.. URL https://slurm.schedmd.com/sbatch.html. Accessed 4 November 2026.

[17] SchedMD. Slurm workload manager: sacct, n.d.. URL https://slurm.schedmd.com/sacct.html. Accessed 4 November 2026.

[18] Torchview Contributors. Torchview: Visualize PyTorch models. Official project repository, n.d. URL https://github.com/mert-kurttutan/torchview. Accessed 4 November 2026.

[19] TorchLens Contributors. TorchLens: Model graphs, activations, gradients, and metadata. Official project repository, n.d. URL https://github.com/johnmarktaylor91/torchlens. Accessed 4 November 2026.

[20] PyTorch Contributors. torch.profiler. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/profiler.html. Accessed 4 November 2026.

[21] PyTorch Contributors. CUDA semantics. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/notes/cuda.html. Accessed 4 November 2026.

[22] PyTorch Contributors. torch.cuda.memory.max_memory_allocated. PyTorch Documentation, n.d.. URL https://docs.pytorch.org/docs/stable/generated/torch.cuda.memory.max_memory_allocated.html. Accessed 4 November 2026.