

ZAP Scanning Report

Site: <http://localhost>

Generated on Sun, 24 Mar 2024 20:23:41

ZAP Version: 2.14.0

ZAP is supported by the [Crash Override Open Source Fellowship](#)

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	1
Low	1
Informational	0

Alerts

Name	Risk Level	Number of Instances
Cross-Domain Misconfiguration	Medium	4
X-Content-Type-Options Header Missing	Low	2

Alert Detail

Medium	Cross-Domain Misconfiguration
Description	Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server
URL	http://localhost/api/time-entries
Method	POST
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	http://localhost/api/time-entries/1
Method	PUT
Attack	
Evidence	Access-Control-Allow-Origin: *
Other	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from

Info	authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	http://localhost/api/time-entries/3
Method	PUT
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
URL	http://localhost/api/time-entries/6
Method	PUT
Attack	
Evidence	Access-Control-Allow-Origin: *
Other Info	The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.
Instances	4
Solution	Ensure that sensitive data is not available in an unauthenticated manner (using IP address white-listing, for instance). Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.
Reference	https://vulncat.fortify.com/en/detail?id=desc.config.dotnet.html5_overly_permissive_cors_policy
CWE Id	264
WASC Id	14
Plugin Id	10098

Low	X-Content-Type-Options Header Missing
Description	The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.
URL	http://localhost/api/time-entries
Method	POST
Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
URL	http://localhost/api/time-entries/6
Method	PUT

Attack	
Evidence	
Other Info	This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.
Instances	2
Solution	<p>Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages.</p> <p>If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application /web server to not perform MIME-sniffing.</p>
Reference	https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85) https://owasp.org/www-community/Security-Headers
CWE Id	693
WASC Id	15
Plugin Id	10021