

pyvar-run.sh — Quick Reference

Setup (once)

```
# 1. Install fswatch (auto-handoff dependency)
brew install fswatch

# 2. Make scripts executable
chmod +x ~/claude-docker/scripts/pyvar-run.sh
chmod +x ~/claude-docker/scripts/lib/*.sh

# 3. Create shared Docker network
docker network create pyvar_net
```

Phase reference

Phase	Mode on M4	Mode on Intel	Agent Teams
P1	sequential	sequential	off
P2	agent (4 teammates)	sequential	PRIMARY
P3	sequential	sequential	off
P4	sequential	sequential	off
P5	agent (8 teammates)	sequential	conditional
P6–P9	sequential	sequential	off

Daily workflow — most common commands

```
cd ~/claude-docker/scripts

# Start phase with auto-detected mode and hybrid handoff
./pyvar-run.sh p2

# Resume last session for a phase
./pyvar-run.sh p2 --resume

# Resume specific session
./pyvar-run.sh p2 --resume <session-id>

# Preview what would run (no execution)
./pyvar-run.sh p2 --dry-run

# List all saved sessions
./pyvar-run.sh sessions
```

Machine-specific resource overrides

```
# Force Intel profile (e.g. when on M4 but memory-constrained)
./pyvar-run.sh p2 --machine intel

# Force M4 profile
./pyvar-run.sh p2 --machine m4

# Resources auto-detected if --machine not set:
#   Intel i5 2.5GHz:  claude 1 CPU / 2 GB | worker 1.5 CPU / 4 GB
#   M4 4.4GHz:       claude 4 CPU / 5 GB | worker 4 CPU / 4 GB
```

Mode switching

```
# Force Agent Teams (M4 only – ignored on Intel)
./pyvar-run.sh p2 --mode agent

# Force sequential (any machine)
./pyvar-run.sh p2 --mode seq

# Switch mid-flight: commit all worktrees and switch to sequential
# (run from inside container or separate terminal)
./pyvar-run.sh p2 --mode seq --worktree credit-risk
```

Git worktrees (P2 Agent Teams)

```
# Step 1: create worktrees before starting Agent Teams session
./pyvar-run.sh p2 --setup-worktrees

# Step 2: run Agent Teams session (worktrees are auto-mounted)
./pyvar-run.sh p2 --mode agent

# Step 3: merge completed worktrees into main
./pyvar-run.sh p2 --teardown-worktrees

# Step 3 (dry-run): preview merge commands
./pyvar-run.sh p2 --teardown-worktrees --dry-run

# Run in a specific worktree (sequential fallback for one domain)
./pyvar-run.sh p2 --mode seq --worktree credit-risk --resume
```

Context exhaustion / auto-handoff

```
# Option A – fully automatic (new session starts immediately)
./pyvar-run.sh p2 --handoff auto

# Option C – hybrid (pauses, asks you to confirm)
./pyvar-run.sh p2 --handoff hybrid    # default

# Resume from a saved handoff file manually
./pyvar-run.sh p2 --handoff-file ~/.pyvar-sessions/handoff-p2-20260425T143000Z.md
```

The handoff watcher runs in the background whenever `pyvar-run.sh` starts. It watches for `CONTEXT_EXHAUSTED.md` in `/workspace/pyvar`. Claude Code writes this file automatically per the checkpoint instructions.

If `fswatch` is not installed, auto-handoff is disabled with a warning:

```
brew install fswatch
```

Full Option C stack (both containers)

```
# Start pyvar stack first
cd ~/projects/pyvar && docker compose up -d

# Then start Claude Code session
./pyvar-run.sh p3
# Claude can reach http://pyvar-api:8000 over pyvar_net
```

Backup and restore sessions

```
# Backup claude_home volume (preserves all sessions + plugins)
docker run --rm \
  -v claude-docker_claude_home:/data \
  -v $(pwd):/backup \
  alpine tar czf /backup/claude_home_$(date +%Y%m%d).tar.gz -C /data .

# Restore
docker run --rm \
  -v claude-docker_claude_home:/data \
  -v $(pwd):/backup \
  alpine sh -c "cd /data && tar xzf /backup/claude_home_YYYYMMDD.tar.gz"
```

Troubleshooting

Symptom	Cause	Fix
fswatch not found	not installed	brew install fswatch
Agent Teams not starting on M4	AT setting not applied	./pyvar-run.sh p2 --at-only
Worktree already exists	previous run not cleaned	git worktree list, then git worktree remove ../pyvar-worktrees/credit-risk
Context exhaustion not detected	Claude did not write CONTEXT_EXHAUSTED.md	Check session prompt includes checkpoint-instructions.md
Merge conflict on teardown	teammate modified same file	git mergetool in pyvar root
Plugin not found on Intel	marketplace not registered	./pyvar-run.sh p1 applies plugin config fresh