



CS 5541 – Computer Systems

"Based on lecture notes developed by Randal E. Bryant and David R. O'Hallaron in conjunction with their textbook "Computer Systems: A Programmer's Perspective"





Module 1

Representing Numbers


Part 7 — Extras

From: Computer Systems, Chapter 2

Instructor: James Yang
<https://cs.wmich.edu/~zjiang>
zjiang.yang@wmich.edu

Application of Boolean Algebra

- **Applied to Digital Systems by Claude Shannon**
 - 1937 MIT Master's Thesis
 - Reason about networks of relay switches
 - Encode closed switch as 1, open switch as 0



Connection when

$$A \& \sim B \mid \sim A \& B$$

$$= A \wedge B$$

Binary Number Property

Claim

$$1 + 1 + 2 + 4 + 8 + \dots + 2^{w-1} = 2^w$$

$$1 + \sum_{i=0}^{w-1} 2^i = 2^w$$

- **w = 0:**
 - $1 = 2^0$
- **Assume true for w-1:**
 - $\underbrace{1 + 1 + 2 + 4 + 8 + \dots + 2^{w-1}}_{= 2^w} + 2^w = 2^w + 2^w = 2^{w+1}$

Code Security Example

```
/* Kernel memory region holding user-accessible data */
#define KSIZE 1024
char kbuf[KSIZE];

/* Copy at most maxlen bytes from kernel region to user buffer */
int copy_from_kernel(void *user_dest, int maxlen) {
    /* Byte count len is minimum of buffer size and maxlen */
    int len = KSIZE < maxlen ? KSIZE : maxlen;
    memcpy(user_dest, kbuf, len);
    return len;
}
```

- Similar to code found in FreeBSD's implementation of `getpeername`
- There are legions of smart people trying to find vulnerabilities in programs

Typical Usage

```
/* Kernel memory region holding user-accessible data */
#define KSIZE 1024
char kbuf[KSIZE];

/* Copy at most maxlen bytes from kernel region to user buffer */
int copy_from_kernel(void *user_dest, int maxlen) {
    /* Byte count len is minimum of buffer size and maxlen */
    int len = KSIZE < maxlen ? KSIZE : maxlen;
    memcpy(user_dest, kbuf, len);
    return len;
}
```

```
#define MSIZE 528

void getstuff() {
    char mybuf[MSIZE];
    copy_from_kernel(mybuf, MSIZE);
    printf("%s\n", mybuf);
}
```

Malicious Usage

```
/* Declaration of library function memcpy */  
void *memcpy(void *dest, void *src, size_t n);
```

```
/* Kernel memory region holding user-accessible data */  
#define KSIZE 1024  
char kbuf[KSIZE];  
  
/* Copy at most maxlen bytes from kernel region to user buffer */  
int copy_from_kernel(void *user_dest, int maxlen) {  
    /* Byte count len is minimum of buffer size and maxlen */  
    int len = KSIZE < maxlen ? KSIZE : maxlen;  
    memcpy(user_dest, kbuf, len);  
    return len;  
}
```

```
#define MSIZE 528  
  
void getstuff() {  
    char mybuf[MSIZE];  
    copy_from_kernel(mybuf, -MSIZE);  
    . . .  
}
```

Mathematical Properties

- **Modular Addition Forms an *Abelian Group***

- **Closed** under addition

$$0 \leq \text{UAdd}_w(u, v) \leq 2^w - 1$$

- **Commutative**

$$\text{UAdd}_w(u, v) = \text{UAdd}_w(v, u)$$

- **Associative**

$$\text{UAdd}_w(t, \text{UAdd}_w(u, v)) = \text{UAdd}_w(\text{UAdd}_w(t, u), v)$$

- **0** is additive identity

$$\text{UAdd}_w(u, 0) = u$$

- Every element has additive **inverse**

- Let $\text{UComp}_w(u) = 2^w - u$

$$\text{UAdd}_w(u, \text{UComp}_w(u)) = 0$$

Mathematical Properties of TAdd

- **Isomorphic Group to unsigneds with UAdd**

- $TAdd_w(u, v) = U2T(UAdd_w(T2U(u), T2U(v)))$
 - Since both have identical bit patterns

- **Two's Complement Under TAdd Forms a Group**


- Closed, Commutative, Associative, 0 is additive identity
- Every element has additive inverse

$$TComp_w(u) = \begin{cases} -u & u \neq TMin_w \\ TMin_w & u = TMin_w \end{cases}$$

Characterizing TAdd

- Functionality**

- True sum requires $w+1$ bits
- Drop off MSB
- Treat remaining bits as 2's comp. integer



$$TAdd_w(u, v) = \begin{cases} u + v + 2^w & u + v < TMin_w \text{ (NegOver)} \\ u + v & TMin_w \leq u + v \leq TMax_w \\ u + v - 2^w & TMax_w < u + v \text{ (PosOver)} \end{cases}$$

Negation: Complement & Increment

- **Claim: Following Holds for 2's Complement**

$$\sim x + 1 == -x$$

- **Complement**

- Observation: $\sim x + x == 1111\dots111 == -1$

$$\begin{array}{r} x \quad 10011101 \\ + \quad \sim x \quad 01100010 \\ \hline -1 \quad 11111111 \end{array}$$

- **Complete Proof?**

Complement & Increment Examples

x = 15213

	Decimal	Hex	Binary
x	15213	3B 6D	00111011 01101101
~x	-15214	C4 92	11000100 10010010
~x+1	-15213	C4 93	11000100 10010011
y	-15213	C4 93	11000100 10010011


x = 0

	Decimal	Hex	Binary
0	0	00 00	00000000 00000000
~0	-1	FF FF	11111111 11111111
~0+1	0	00 00	00000000 00000000


Code Security Example #2

- **SUN XDR library**
 - Widely used library for transferring data between machines

```
void* copy_elements(void *ele_src[], int ele_cnt, size_t ele_size);
```



`malloc(ele_cnt * ele_size)`



XDR Code

```
void* copy_elements(void *ele_src[], int ele_cnt, size_t ele_size) {
    /*
     * Allocate buffer for ele_cnt objects, each of ele_size bytes
     * and copy from locations designated by ele_src
     */
    void *result = malloc(ele_cnt * ele_size);
    if (result == NULL)
        /* malloc failed */
        return NULL;
    void *next = result;
    int i;
    for (i = 0; i < ele_cnt; i++) {
        /* Copy object i to destination */
        memcpy(next, ele_src[i], ele_size);
        /* Move pointer to next memory region */
        next += ele_size;
    }
    return result;
}
```


XDR Vulnerability

```
malloc(ele_cnt * ele_size)
```

- **What if:**
 - `ele_cnt` = $2^{20} + 1$
 - `ele_size` = 4096 = 2^{12}
 - Allocation = ??
- **How can I make this function secure?**

Compiled Multiplication Code

C Function

```
long mul12(long x)
{
    return x*12;
}
```

Compiled Arithmetic Operations

```
leaq (%rax,%rax,2), %rax
salq $2, %rax
```

Explanation

```
t <- x+x*2
return t << 2;
```

- C compiler automatically generates shift/add code when multiplying by constant

Compiled Unsigned Division Code

C Function

```
unsigned long udiv8
(unsigned long x)
{
    return x/8;
}
```

Compiled Arithmetic Operations

```
shrq $3, %rax
```


Explanation

```
# Logical shift
return x >> 3;
```

- Uses logical shift for unsigned
- For Java Users
 - Logical shift written as >>>

Signed Power-of-2 Divide with Shift

- **Quotient of Signed by Power of 2**
 - $x \gg k$ gives $\lfloor x / 2^k \rfloor$
 - Uses arithmetic shift
 - Rounds wrong direction when $u < 0$




	Division	Computed	Hex	Binary
y	-15213	-15213	C4 93	11000100 10010011
$y \gg 1$	-7606.5	-7607	E2 49	11100010 01001001
$y \gg 4$	-950.8125	-951	FC 49	11111100 01001001
$y \gg 8$	-59.4257813	-60	FF C4	11111111 11000100

Correct Power-of-2 Divide

- **Quotient of Negative Number by Power of 2**

- Want $\lceil x / 2^k \rceil$ (Round Toward 0)
- Compute as $\lfloor (x+2^k-1) / 2^k \rfloor$
 - In C: $(x + (1 \ll k) - 1) \gg k$
 - Biases dividend toward 0


Case 1: No rounding



Biasing has no effect

Correct Power-of-2 Divide (Cont.)

Case 2: Rounding



Biasing adds 1 to final result

Compiled Signed Division Code

C Function

```
long idiv8(long x)
{
    return x/8;
}
```

Compiled Arithmetic Operations

```
    testq %rax, %rax
    js    L4
L3:
    sarq $3, %rax
    ret
L4:
    addq $7, %rax
    jmp  L3
```

Explanation

```
if x < 0
    x += 7;
# Arithmetic shift
return x >> 3;
```

- **Uses arithmetic shift for int**
- **For Java Users**
 - Arith. shift written as >>

Arithmetic: Basic Rules

- **Unsigned ints, 2's complement ints are isomorphic rings:
isomorphism = casting**
- **Left shift**
 - Unsigned/signed: multiplication by 2^k
 - Always logical shift
- **Right shift**
 - Unsigned: logical shift, div (division + round to zero) by 2^k
 - Signed: arithmetic shift
 - Positive numbers: div (division + round to zero) by 2^k
 - Negative numbers: div (division + round away from zero) by 2^k

Properties of Unsigned Arithmetic

- **Unsigned Multiplication with Addition Forms Commutative Ring**

- Addition is commutative group

- Closed under multiplication

$$0 \leq \text{UMult}_w(u, v) \leq 2^w - 1$$

- Multiplication Commutative

$$\text{UMult}_w(u, v) = \text{UMult}_w(v, u)$$

- Multiplication is Associative

$$\text{UMult}_w(t, \text{UMult}_w(u, v)) = \text{UMult}_w(\text{UMult}_w(t, u), v)$$

- 1 is multiplicative identity

$$\text{UMult}_w(u, 1) = u$$

- Multiplication distributes over addition

$$\text{UMult}_w(t, \text{UAdd}_w(u, v)) = \text{UAdd}_w(\text{UMult}_w(t, u), \text{UMult}_w(t, v))$$

Properties of Two's Comp. Arithmetic

- **Isomorphic Algebras**

- Unsigned multiplication and addition
 - Truncating to w bits
- Two's complement multiplication and addition
 - Truncating to w bits

- **Both Form Rings**

- Isomorphic to ring of integers mod 2^w

- **Comparison to (Mathematical) Integer Arithmetic**

- Both are rings
- Integers obey ordering properties, e.g.,

$$u > 0 \quad \Rightarrow \quad u + v > v$$

$$u > 0, v > 0 \quad \Rightarrow \quad u \cdot v > 0$$

- These properties are not obeyed by two's comp. arithmetic

$$TMax + 1 == TMin$$

$$15213 * 30426 == -10030 \quad (16\text{-bit words})$$

Reading Byte-Reversed Listings

- **Disassembly**
 - Text representation of binary machine code
 - Generated by program that reads the machine code
- **Example Fragment**

Address	Instruction Code	Assembly Rendition
8048365:	5b	pop %ebx
8048366:	81 c3 ab 12 00 00	add \$0x12ab,%ebx
804836c:	83 bb 28 00 00 00 00	cmpl \$0x0,0x28(%ebx)

- **Deciphering Numbers**

- Value:
- Pad to 32 bits:
- Split into bytes:
- Reverse:

0x12ab

0x000012ab

00 00 12 ab

ab 12 00 00

Module 1 (Part 7)

Summary

- Bonus content

