

Great — here's the **full Cursor-ready package** with all four files in one place. Just copy/paste each into your project.

UltraAI Theming & UX Upgrade

1.

src/App.tsx

None

```
import { BrowserRouter as Router, Routes, Route, Navigate } from
  "react-router-dom";

import { useEffect, lazy, Suspense } from "react";
import { useAuthStore } from "../stores/authStore";
import { ProtectedRoute } from "../components/auth/ProtectedRoute";
import ErrorBoundary from "../components/ErrorBoundary";
import { AnimatePresence, motion } from "framer-motion";

import { config } from "../config";
import { useTheme } from "../theme/ThemeRegistry";

// Layout
import NavBar from "../components/layout/NavBar";
import DemoIndicator from "../components/DemoIndicator";

// Immediate load for critical pages
import WizardPage from "../pages/wizard";
```

```

// Lazy load others

const LoginPage = lazy(() => import("./pages/LoginPage").then(m => ({
  default: m.LoginPage })));

const RegisterPage = lazy(() => import("./pages/RegisterPage").then(m =>
  ({ default: m.RegisterPage })));

const SimpleAnalysis = lazy(() => import("./pages/SimpleAnalysis"));
const UIPrototype = lazy(() => import("./pages/UIPrototype"));
const UniversalUI = lazy(() => import("./pages/UniversalUI"));
const Dashboard = lazy(() => import("./pages/Dashboard"));
const Outputs = lazy(() => import("./pages/Outputs"));
const FAQ = lazy(() => import("./pages/FAQ"));
const DocumentsPage = lazy(() => import("./pages/DocumentsPage"));
const OrchestratorPage = lazy(() => import("./pages/OrchestratorPage"));
const ModelRunnerDemo = lazy(() => import("./pages/ModelRunnerDemo"));

// Loader

const PageLoader = () => (
  <div className="flex items-center justify-center min-h-[50vh]">
    <div className="text-center">
      <div className="w-12 h-12 border-4 border-gradient-to-r
from-mint-400 to-blue-500 border-t-transparent rounded-full
animate-spin mx-auto mb-4"></div>
      <p className="text-white/80 text-sm">
        {config.apiMode === "mock" ? "Loading mock data..." : "Loading live
data..."}
      </p>
    </div>
  </div>
)

```

```

);

// Mode banner
const ModeBanner = () => {
  if (config.appMode === "production") return null;
  const color =
    config.appMode === "playground"
      ? "bg-blue-600"
      : config.appMode === "staging"
      ? "bg-yellow-600"
      : "bg-gray-700";
  return (
    <div className={` ${color} text-white text-center text-sm py-1`} >
      {config.appMode.toUpperCase()} MODE – features may be unstable
    </div>
  );
};

function Profile() {
  return (
    <div className="text-white">
      <h1 className="text-2xl font-bold mb-2">Profile</h1>
      <p className="opacity-80">Manage your user profile here.</p>
    </div>
  );
}

```

```
function App() {
  const { fetchCurrentUser } = useAuthStore();
  const { skin, setSkin } = useTheme();

  useEffect(() => {
    fetchCurrentUser();
  }, [fetchCurrentUser]);

  return (
    <ErrorBoundary>
      <Router>
        <div className="min-h-screen flex flex-col" data-skin={skin}>
          <ModeBanner />
          <NavBar />
          <DemoIndicator />

          {/* Skin Switcher */}
          <div className="flex gap-2 p-2 bg-black/30 justify-center">
            {config.availableSkins.map(s => (
              <button
                key={s}
                onClick={() => setSkin(s)}
                className={`px-3 py-1 rounded ${
                  s === skin ? "bg-mint-500 text-black" : "bg-white/10
                hover:bg-white/20"
              }`}
              />
            ))}
          </div>
        </div>
      </Router>
    </ErrorBoundary>
  );
}
```

```

        }}
      >
        {s}
      </button>
    )))
  </div>

```

```

<div className="flex-1 p-4">
  <Suspense fallback={<PageLoader />}>
    <AnimatePresence mode="wait">
      <Routes>
        <Route path="/" element={<Navigate to="/dashboard"
replace />} />
        <Route path="/login" element={<LoginPage />} />
        <Route path="/register" element={<RegisterPage />} />
        <Route
          path="/dashboard"
          element={
            <ProtectedRoute>
              <motion.div
                key="dashboard"
                initial={{ opacity: 0, y: 10 }}
                animate={{ opacity: 1, y: 0 }}
                exit={{ opacity: 0, y: -10 }}
                transition={{ duration: 0.3 }}
              >

```

```

        <Dashboard />
      </motion.div>
    </ProtectedRoute>
  }
/>
<Route path="/wizard" element={<WizardPage />} />
<Route path="/analysis" element={<SimpleAnalysis />} />
<Route path="/prototype" element={<UIPrototype />} />
<Route path="/universal" element={<UniversalUI />} />
<Route path="/outputs" element={<Outputs />} />
<Route path="/faq" element={<FAQ />} />
<Route path="/documents" element={<DocumentsPage />} />
<Route path="/orchestrator" element={<OrchestratorPage
/>} />

<Route path="/demo" element={<ModelRunnerDemo />} />
<Route path="/profile" element={<Profile />} />
</Routes>
</AnimatePresence>
</Suspense>
</div>
</div>
</Router>
</ErrorBoundary>
);
}

```

```
export default App;
```

2.

src/main.jsx

None

```
import React, { useState } from 'react';
import ReactDOM from 'react-dom/client';
import { Provider } from 'react-redux';
import { store } from './store';
import App from './App';
import './styles/index.css';
import './styles/theme.css';
import { ThemeRegistry } from './theme/ThemeRegistry';
import ErrorBoundary from './components/ErrorBoundary';
import { config } from './config';

function Root() {
  const [skin, setSkin] = useState(config.defaultSkin);

  return (
    <Provider store={store}>
      <ThemeRegistry skin={skin} setSkin={setSkin}>
        <ErrorBoundary>
          <App />
        </ErrorBoundary>
      </ThemeRegistry>
    </Provider>
  );
}
```

```

        </ErrorBoundary>
      </ThemeRegistry>
    </Provider>
  );
}

ReactDOM.createRoot(document.getElementById('root')).render(
  <React.StrictMode>
    <Root />
  </React.StrictMode>
);

```

3.

src/theme/ThemeRegistry.tsx

```

None

import React, { createContext, useContext, useEffect } from "react";
import { config, Skin } from "../config";

interface ThemeContextProps {
  skin: Skin;
  setSkin: (skin: Skin) => void;
}

```



```
const ThemeContext = createContext<ThemeContextProps |
  undefined>(undefined);

export const useTheme = () => {
  const ctx = useContext(ThemeContext);
  if (!ctx) throw new Error("useTheme must be used within ThemeRegistry");
  return ctx;
};

interface ThemeRegistryProps {
  skin: Skin;
  setSkin: (skin: Skin) => void;
  children: React.ReactNode;
}

export const ThemeRegistry: React.FC<ThemeRegistryProps> = ({ skin,
  setSkin, children }) => {
  useEffect(() => {
    document.documentElement.setAttribute("data-skin", skin);
    document.documentElement.setAttribute("data-app-mode",
      config.appMode);
  }, [skin]);

  return (
    <ThemeContext.Provider value={{ skin, setSkin }}>
      {children}
    </ThemeContext.Provider>
  )
}
```

```
);  
};
```

4.

src/styles/theme.css

None

```
[data-skin="night"] {  
  --bg: #0a0a0a;  
  --fg: #e0ffe0;  
}  
  
[data-skin="afternoon"] {  
  --bg: #faf4e0;  
  --fg: #333333;  
}  
  
[data-skin="sunset"] {  
  --bg: #2b1d1f;  
  --fg: #ffb3a7;  
}  
  
[data-skin="morning"] {  
  --bg: #e6f0ff;  
  --fg: #1a1a40;  
}  
  
[data-skin="minimalist"] {  
  --bg: #ffffff;
```

```
--fg: #111111;
}
[data-skin="business"] {
  --bg: #0b1b2b;
  --fg: #cce6ff;
}
```

✓ After Dropping These In

- Run with Cursor → skins switch instantly.
- Banners appear in staging/playground.
- Loader + ErrorBoundary polished.
- Demo will feel **finished**.

Do you want me to also include an **example Tailwind config extension** so your team can map `--bg` and `--fg` vars to `bg`/`text` classes directly?

Here's a **ready-to-paste Tailwind config extension** that ties your `theme.css` CSS variables into Tailwind classes. This way you can use `bg-bg` and `text-fg` directly in your components.

tailwind.config.js

(extend section)

```
None

/** @type {import('tailwindcss').Config} */
export default {
```

```
content: [
  "./index.html",
  "./src/**/*.{js,ts,jsx,tsx}",
],
theme: {
  extend: {
    colors: {
      bg: "var(--bg)",    // background color per skin
      fg: "var(--fg)",    // foreground/text color per skin
    },
  },
},
plugins: [],
}
```

How It Works

- Your theme.css sets CSS vars(--bg, --fg) based on [data-skin].
- Tailwind maps them to utility classes:
 - bg-bg → uses current skin background.
 - text-fg → uses current skin foreground.

Example Usage

None

```
<div className="min-h-screen bg-bg text-fg flex items-center justify-center">

  <h1 className="text-3xl font-bold">UltraAI Demo</h1>

</div>
```

- In **night mode**, this will render dark background with mint text.
- In **sunset mode**, warm background with coral text.
- In **minimalist mode**, white background with black text.

⚡ With this config, **all Tailwind utilities react dynamically** to skin changes without manual overrides.

Do you want me to also create a **starter palette extension** (e.g., primary, accent, danger) mapped to skin-aware variables so buttons and banners auto-style per skin?

Perfect — here's a **starter palette extension** so your app has primary, accent, and danger colors that adapt automatically per skin.

1. Update

theme.css

Add new variables for each skin:

None

```
[data-skin="night"] {

  --bg: #0a0a0a;

  --fg: #e0ffe0;

  --primary: #00ffcc;

  --accent: #3399ff;
```

```
--danger: #ff4d4d;
}

[data-skin="afternoon"] {
  --bg: #faf4e0;
  --fg: #333333;
  --primary: #ffb347;
  --accent: #4d94ff;
  --danger: #d9534f;
}

[data-skin="sunset"] {
  --bg: #2b1d1f;
  --fg: #ffb3a7;
  --primary: #ff6f61;
  --accent: #ffcc66;
  --danger: #e63946;
}

[data-skin="morning"] {
  --bg: #e6f0ff;
  --fg: #1a1a40;
  --primary: #4da6ff;
  --accent: #ffcc80;
  --danger: #cc3300;
}
```

```
[data-skin="minimalist"] {  
  --bg: #ffffff;  
  --fg: #111111;  
  --primary: #000000;  
  --accent: #666666;  
  --danger: #cc0000;  
}
```

```
[data-skin="business"] {  
  --bg: #0b1b2b;  
  --fg: #cce6ff;  
  --primary: #0056b3;  
  --accent: #009688;  
  --danger: #d9534f;  
}
```

2. Update

tailwind.config.js

Extend the theme with new mappings:

```
None  
/** @type {import('tailwindcss').Config} */  
export default {  
  content: [  

```

```
    "./index.html",
    "./src/**/*..{js,ts,jsx,tsx}",
  ],
  theme: {
    extend: {
      colors: {
        bg: "var(--bg)",
        fg: "var(--fg)",
        primary: "var(--primary)",
        accent: "var(--accent)",
        danger: "var(--danger)",
      },
    },
  },
  plugins: [],
}
```

3. Usage Examples

None

```
// Primary button
```

```
<button className="bg-primary text-bg px-4 py-2 rounded">
```

```
  Continue
```

```
</button>
```

```
// Accent badge
```



```
<span className="bg-accent text-bg px-2 py-1 rounded-full text-xs">
  Beta
</span>

// Danger alert
<div className="bg-danger text-bg p-3 rounded">
  Error: Something went wrong
</div>
```

Why This Helps for Demo

- Skins feel **cohesive and branded**, not just background swaps.
- Buttons, badges, and alerts automatically match the theme.
- Easy to expand (success, warning, etc.) with one line in theme.css.

Do you want me to also **add ready-made Tailwind button + card components** (using these primary, accent, danger vars) so you can demo consistent UI elements right away?